



12. Radio Frequency Exposure

12.1 Applicable Standards

☐ §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																																	
☒ §1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$. TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION <table><tr><th colspan="3">RF Source Frequency</th><th colspan="3">Minimum Distance</th><th>Threshold ERP</th></tr><tr><th>f_L MHz</th><th></th><th>f_H MHz</th><th>$\lambda_L / 2\pi$</th><th></th><th>$\lambda_H / 2\pi$</th><th>W</th></tr><tr><td>0.3</td><td>–</td><td>1.34</td><td>159 m</td><td>–</td><td>35.6 m</td><td>$1,920 R^2$</td></tr><tr><td>1.34</td><td>–</td><td>30</td><td>35.6 m</td><td>–</td><td>1.6 m</td><td>$3,450 R^2/f^2$</td></tr><tr><td>30</td><td>–</td><td>300</td><td>1.6 m</td><td>–</td><td>159 mm</td><td>$3.83 R^2$</td></tr><tr><td>300</td><td>–</td><td>1,500</td><td>159 mm</td><td>–</td><td>31.8 mm</td><td>$0.0128 R^2f$</td></tr><tr><td>1,500</td><td>–</td><td>100,000</td><td>31.8 mm</td><td>–</td><td>0.5 mm</td><td>$19.2R^2$</td></tr></table> Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.	RF Source Frequency			Minimum Distance			Threshold ERP	f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W	0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$	1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$	30	–	300	1.6 m	–	159 mm	$3.83 R^2$	300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2f$	1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2R^2$
RF Source Frequency			Minimum Distance			Threshold ERP																																												
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W																																												
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$																																												
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$																																												
30	–	300	1.6 m	–	159 mm	$3.83 R^2$																																												
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2f$																																												
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2R^2$																																												
☐ § 1.1307(b)(3)(i)(B).	Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$ $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ Where $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ and $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ d = the separation distance (cm);																																																	

**12.1 EUT Specification**

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☐ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☐ WLAN: 5725MHz ~ 5850MHz ☒ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☐ Blanket 1 mW Blanket Exemption ☒ MPE-based Exemption ☐ SAR-based Exemption
Remark: The maximum conducted output power is <u>8.11dBm (6.471mW)</u> at <u>2480MHz</u> (with <u>3.00dBi antenna gain</u> .)	

12.2 Result

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p power (mW)	Limit (mW)
2402-2480	8.11	8.61	3.00	9.46	8.83	3060

No non-compliance noted.

-----THE END OF REPORT-----