

## Summary

Test	Frequency (MHz)	Nominal Power (dBm)	Nominal Bandwidth (MHz)	Result
Peak output power (Sweep)	2402.000	10.0	1.000000	PASS
Power Spectral Density	2402.000	10.0	1.000000	PASS
Peak Power Spectral Density	2402.000	10.0	1.000000	PASS
Peak output power (Sweep)	2442.000	10.0	1.000000	PASS
Peak Power Spectral Density	2442.000	10.0	1.000000	PASS
Power Spectral Density	2442.000	10.0	1.000000	PASS
Peak output power (Sweep)	2480.000	10.0	1.000000	PASS
Peak Power Spectral Density	2480.000	10.0	1.000000	PASS
Power Spectral Density	2480.000	10.0	1.000000	PASS

## Peak output power (Sweep) (2402 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(b), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Combined Uncertainty of absolute Level Measurement (K=2) < 1 dB

### Result

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2402.000000	3.3	30.0	PASS

### Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.39900 GHz	2.39900 GHz
Stop Frequency	2.40500 GHz	2.40500 GHz
Span	6.000 MHz	6.000 MHz
RBW	2.000 MHz	>= 1.000 MHz
VBW	10.000 MHz	>= 6.000 MHz
SweepPoints	101	~ 101
SweepTime	953.450 ns	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off

## Power Spectral Density (2402 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(a),(e), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Uncertainty (K=2) < 1.3 dB

### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2402.247500	-7.153	8.0	PASS

### Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40125 GHz	2.40125 GHz
Stop Frequency	2.40275 GHz	2.40275 GHz
Span	1.500 MHz	1.500 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	300	~ 300
SweepTime	1.500 s	1.500 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off

## Peak Power Spectral Density (2402 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(a),(e), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Uncertainty (K=2) < 1.3 dB

### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2401.747500	-2.734	8.0	PASS

### Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40125 GHz	2.40125 GHz
Stop Frequency	2.40275 GHz	2.40275 GHz
Span	1.500 MHz	1.500 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	300	~ 300
SweepTime	1.500 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off

---

**Peak output power (Sweep) (2442 MHz; Nominal (10 dBm); 1 MHz)**

Customized settings.

Test according to FCC title 47 part 15 §15.247(b), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Combined Uncertainty of absolute Level Measurement (K=2) < 1 dB

**Result**

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2442.000000	2.2	30.0	PASS

## Peak Power Spectral Density (2442 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(a),(e), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Uncertainty (K=2) < 1.3 dB

### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2442.000000	2442.247500	-3.771	8.0	PASS

## Power Spectral Density (2442 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(a),(e), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Uncertainty (K=2) < 1.3 dB

### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2442.000000	2441.747500	-8.104	8.0	PASS

---

**Peak output power (Sweep) (2480 MHz; Nominal (10 dBm); 1 MHz)**

Customized settings.

Test according to FCC title 47 part 15 §15.247(b), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Combined Uncertainty of absolute Level Measurement (K=2) < 1 dB

**Result**

DUT Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)	Result
2480.000000	1.9	30.0	PASS



## Peak Power Spectral Density (2480 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(a),(e), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Uncertainty (K=2) < 1.3 dB

### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.747500	-4.020	8.0	PASS

## Power Spectral Density (2480 MHz; Nominal (10 dBm); 1 MHz)

Customized settings.

Test according to FCC title 47 part 15 §15.247(a),(e), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Measurement uncertainty calculated in accordance with ETSI TR 100 028-1.  
Expanded Uncertainty (K=2) < 1.3 dB

### Result

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.747500	-8.435	8.0	PASS