



MET Laboratories, Inc. *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230-3432 • PHONE (410) 354-3300 • FAX (410) 354-3313

33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

3162 BELICK STREET • SANTA CLARA, CALIFORNIA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

June 14, 2010

Ubiquiti Networks
91 E. Tasman
San Jose, CA 95134

Dear Robert Pera,

Enclosed is the EMC Wireless test report for compliance testing of the Ubiquiti Networks, M2D as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Part 15, Subpart B, ICES-003, Issue 4 February 2004 for a Class A Digital Device and FCC Part 15 Subpart C, RSS-210, Issue 7, June 2007 for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
MET LABORATORIES, INC.

Jennifer Warnell
Documentation Department

Reference: (\Ubiquiti Networks\EMCS82082-FCC247 Rev. 1)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc.

Electromagnetic Compatibility Criteria Test Report

for the

**Ubiquiti Networks
M2D**

Tested under
the FCC Certification Rules
contained in
Title 47 of the CFR, Parts 15 Subpart B & ICES-003
for Class A Digital Devices
&
15.247 Subpart C & RSS-210, Issue 7, June 2007
for Intentional Radiators

MET Report: EMCS82082-FCC247 Rev. 1

June 14, 2010

Prepared For:

**Ubiquiti Networks
91 E. Tasman
San Jose, CA 95134**

Prepared By:
MET Laboratories, Inc.
3162 Belick St.
Santa Clara, CA 95054

Electromagnetic Compatibility Criteria Test Report

for the

Ubiquiti Networks M2D

Tested under
the FCC Certification Rules
contained in
Title 47 of the CFR, Parts 15 Subpart B & ICES-003
for Class A Digital Devices
&
15.247 Subpart C & RSS-210, Issue 7, June 2007
for Intentional Radiators



Minh Ly, Project Engineer
Electromagnetic Compatibility Lab



Jennifer Warnell
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Parts 15B, 15.247 and Industry Canada standards ICES-003, Issue 4 February 2004, RSS-210, Issue 7, June 2007 under normal use and maintenance.



Shawn McMillen,
Wireless Manager, Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
∅	May 5, 2010	Initial Issue.
1	June 14, 2010	Revised to reflect engineer corrections.

Table of Contents

I.	Executive Summary	1
	A. Purpose of Test	2
	B. Executive Summary	2
II.	Equipment Configuration	3
	A. Overview	4
	B. References	5
	C. Test Site	5
	D. Description of Test Sample	6
	E. Equipment Configuration	8
	F. Support Equipment	8
	G. Ports and Cabling Information	8
	H. Mode of Operation	9
	I. Modifications	9
	a) Modifications to EUT	9
	b) Modifications to Test Standard	9
	J. Disposition of EUT	9
III.	Electromagnetic Compatibility Criteria for Unintentional Radiators	10
	§ 15.107(a) Conducted Emissions Limits	11
	§ 15.109(a) Radiated Emissions Limits	15
IV.	Electromagnetic Compatibility Criteria for Intentional Radiators	20
	§ 15.203 Antenna Requirement	21
	§ 15.207(a) Conducted Emissions Limits	22
	§ 15.247(a) 6 dB and 99% Bandwidth	26
	§ 15.247(b) Peak Power Output and RF Exposure	36
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge	49
	RSS-GEN Receiver Spurious Emissions	69
	§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge	72
	§ 15.247(e) Peak Power Spectral Density	87
V.	Test Equipment	96
VI.	Certification & User's Manual Information	98
	A. Certification Information	99
	B. Label and User's Manual Information	103
VII.	ICES-003 Procedural & Labeling Requirements	105

List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing	2
Table 2. EUT Summary Table.....	4
Table 3. References	5
Table 4. Equipment Configuration	8
Table 5. Support Equipment.....	8
Table 6. Ports and Cabling Information	8
Table 7. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b) and 15.207(a)	11
Table 8. Conducted Emissions - Voltage, AC Power.....	12
Table 9. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b)	15
Table 10. Radiated Emissions Limits, Test Results, 30 MHz – 1 GHz, FCC Limits	16
Table 11. Radiated Emissions Limits, Test Results, Above 1 GHz, FCC Limits.....	17
Table 12. Radiated Emissions Limits, Test Results, ICES-003 Limits	18
Table 13. Antenna List	21
Table 14. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)	22
Table 15. Conducted Emissions, 15.207, Test Results.....	23
Table 16. Occupied Bandwidth, Test Results, Port J5	27
Table 17. Occupied Bandwidth, Test Results, Port J6	27
Table 18. Output Power Requirements from §15.247.....	36
Table 19. RF Output Power, Test Results	37
Table 20. Restricted Bands of Operation.....	49
Table 21. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)	50
Table 22. Radiated Harmonics, Low Channel, 802.11n 20MHz.....	51
Table 23. Radiated Harmonics, Mid Channel, 802.11n 20MHz	51
Table 24. Radiated Harmonics, High Channel, 802.11n 20MHz	51
Table 25. Radiated Harmonics, Mid Channel, 802.11n 40MHz	52
Table 26. Spurious Emission Limits for Receivers	69
Table 27. Spectral Density, Test Results, 802.11n 20MHz, Port J5	88
Table 28. Spectral Density, Test Results, 802.11n 40MHz, Port J5	88
Table 29. Spectral Density, Test Results, 802.11n 20MHz, Port J6.....	88
Table 30. Spectral Density, Test Results, 802.11n 40MHz, Port J6.....	88
Table 31. Spectral Density, Test Results, 802.11n 20MHz, Combined	89
Table 32. Spectral Density, Test Results, 802.11n 40MHz, Combined	89
Table 33. Test Equipment List	97

List of Plots

Plot 1. Conducted Emission, Phase Line Plot	12
Plot 2. Conducted Emission, Neutral Line Plot.....	13
Plot 3. Radiated Emissions, 30 MHz - 1 GHz, FCC Limits	16
Plot 4. Radiated Emissions, Above 1 GHz, FCC Limits	17
Plot 5. Radiated Emissions, ICES-003 Limits.....	18
Plot 6. Conducted Emissions, Phase Line	23
Plot 7. Conducted Emissions, Neutral Line.....	24
Plot 8. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 1	28
Plot 9. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 6.....	28
Plot 10. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 11	29
Plot 11. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 1	29
Plot 12. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 6.....	30
Plot 13. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 11	30
Plot 14. 6dB Occupied Bandwidth, 802.11n 40MHz, Port J5, Channel 6.....	31
Plot 15. 6dB Occupied Bandwidth, 802.11n 40MHz, Port J6, Channel 6.....	31
Plot 16. 99% Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 1	32
Plot 17. 99% Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 6	32
Plot 18. 99% Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 11	33
Plot 19. 99% Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 1	33
Plot 20. 99% Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 6	34
Plot 21. 99% Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 11	34
Plot 22. 99% Occupied Bandwidth, 802.11n 40MHz, Port J5, Channel 6	35
Plot 23. 99% Occupied Bandwidth, 802.11n 40MHz, Port J6, Channel 6	35
Plot 24. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 1 (2412MHz).....	38
Plot 25. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 2 (2417MHz).....	38
Plot 26. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 3 (2422MHz).....	39
Plot 27. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 4 (2427MHz).....	39
Plot 28. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 6 (2437MHz).....	40
Plot 29. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 8 (2447MHz).....	40
Plot 30. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 9 (2452MHz).....	41
Plot 31. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 10 (2457MHz).....	41
Plot 32. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 11 (2462MHz).....	42
Plot 33. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 1 (2412MHz).....	42
Plot 34. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 2 (2417MHz).....	43
Plot 35. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 3 (2422MHz).....	43
Plot 36. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 4 (2427MHz).....	44
Plot 37. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 6 (2437MHz).....	44
Plot 38. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 8 (2447MHz).....	45
Plot 39. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 9 (2452MHz).....	45
Plot 40. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 10 (2457MHz).....	46
Plot 41. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 11 (2462MHz).....	46
Plot 42. Conducted Output Power, 802.11n 40MHz, Port J5, Channel 6 (2437MHz).....	47
Plot 43. Conducted Output Power, 802.11n 40MHz, Port J6, Channel 6 (2437MHz).....	47
Plot 44. Radiated Emissions, Low Chanel	52
Plot 45. Radiated Emissions, Mid Chanel.....	53
Plot 46. Radiated Emissions, High Chanel.....	53
Plot 47. Radiated Spurious Emission, 802.11n 20MHz, Ch1, 1-18GHz.....	54
Plot 48. Radiated Spurious Emission, 802.11n 20MHz, Ch6, 1-18GHz.....	54
Plot 49. Radiated Spurious Emission, 802.11n 20MHz, Ch11, 1-18GHz.....	55
Plot 50. Radiated Spurious Emission, 802.11n 40MHz, Ch6, 1-18GHz.....	55
Plot 51. Radiated Restricted Band, Channel 1, 802.11n 20MHz, Peak.....	56

Plot 52. Radiated Restricted Band, Channel 1, 802.11n 20MHz, Average	56
Plot 53. Radiated Restricted Band, Channel 2, 802.11n 20MHz, Peak	57
Plot 54. Radiated Restricted Band, Channel 2, 802.11n 20MHz, Average	57
Plot 55. Radiated Restricted Band, Channel 3, 802.11n 20MHz, Peak	58
Plot 56. Radiated Restricted Band, Channel 3, 802.11n 20MHz, Average	58
Plot 57. Radiated Restricted Band, Channel 4, 802.11n 20MHz, Peak	59
Plot 58. Radiated Restricted Band, Channel 4, 802.11n 20MHz, Average	59
Plot 59. Radiated Restricted Band, Channel 6 - Low, 802.11n 20MHz, Peak	60
Plot 60. Radiated Restricted Band, Channel 6 - Low, 802.11n 20MHz, Average	60
Plot 61. Radiated Restricted Band, Channel 6 - High, 802.11n 20MHz, Peak	61
Plot 62. Radiated Restricted Band, Channel 6 - High, 802.11n 20MHz, Average	61
Plot 63. Radiated Restricted Band, Channel 8, 802.11n 20MHz, Peak	62
Plot 64. Radiated Restricted Band, Channel 8, 802.11n 20MHz, Average	62
Plot 65. Radiated Restricted Band, Channel 9, 802.11n 20MHz, Peak	63
Plot 66. Radiated Restricted Band, Channel 9, 802.11n 20MHz, Average	63
Plot 67. Radiated Restricted Band, Channel 10, 802.11n 20MHz, Peak	64
Plot 68. Radiated Restricted Band, Channel 10, 802.11n 20MHz, Average	64
Plot 69. Radiated Restricted Band, Channel 11, 802.11n 20MHz, Peak	65
Plot 70. Radiated Restricted Band, Channel 11, 802.11n 20MHz, Average	65
Plot 71. Radiated Restricted Band, Channel 6, 802.11n 40MHz, Peak	66
Plot 72. Radiated Restricted Band, Channel 6, 802.11n 40MHz, Average	66
Plot 73. Conducted Rx Spurious 30 MHz – 1 GHz, Port J5	70
Plot 74. Conducted Rx Spurious 1 GHz – 10 GHz, Port J5	70
Plot 75. Conducted Rx Spurious 30 MHz – 1 GHz, Port J6	71
Plot 76. Conducted Rx Spurious 1 GHz – 10 GHz, Port J6	71
Plot 77. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 1, 30MHz - 1GHz	73
Plot 78. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 1, 1G-18GHz	73
Plot 79. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 1, 18GHz - 26.5GHz	74
Plot 80. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 6, 30MHz - 1GHz	74
Plot 81. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 6, 1G-18GHz	75
Plot 82. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 6, 18GHz - 26.5GHz	75
Plot 83. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 11, 30MHz - 1GHz	76
Plot 84. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 11, 1G-18GHz	76
Plot 85. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 11, 18GHz - 26.5GHz	77
Plot 86. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 1, 30MHz - 1GHz	77
Plot 87. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 1, 1GHz - 18GHz	78
Plot 88. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 1, 18GHz - 26.5GHz	78
Plot 89. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 6, 30MHz - 1GHz	79
Plot 90. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 6, 1GHz - 18GHz	79
Plot 91. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 6, 18GHz - 26.5GHz	80
Plot 92. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 11, 30MHz - 1GHz	80
Plot 93. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 11, 1GHz - 18GHz	81
Plot 94. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 11, 18GHz - 26.5GHz	81
Plot 95. Conducted Spurious Emission, 802.11n 40MHz, Port J5, Channel 6, 30MHz - 1GHz	82
Plot 96. Conducted Spurious Emission, 802.11n 40MHz, Port J5, Channel 6, 1GHz - 18GHz	82
Plot 97. Conducted Spurious Emission, 802.11n 40MHz, Port J5, Channel 6, 18GHz-26.5GHz	83
Plot 98. Conducted Spurious Emission, 802.11n 40MHz, Port J6, Channel 6, 30MHz - 1GHz	83
Plot 99. Conducted Spurious Emission, 802.11n 40MHz, Port J6, Channel 6, 1GHz - 18GHz	84
Plot 100. Conducted Spurious Emission, 802.11n 40MHz, Port J6, Channel 6, 18GHz-26.5GHz	84
Plot 101. Lower Conducted Band Edge, 802.11n 20MHz	85
Plot 102. Upper Conducted Band Edge, 802.11n 20MHz	85
Plot 103. Lower Conducted Band Edge, 802.11n 40MHz	86
Plot 104. Upper Conducted Band Edge, 802.11n 40MHz	86

Plot 105. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 1.....	90
Plot 106. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 6.....	90
Plot 107. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 11.....	91
Plot 108. Spectral Power Density, 802.11n 20MHz, Port J6, Channel 1.....	91
Plot 109. Spectral Power Density, 802.11n 20MHz, Port J6, Channel 6.....	92
Plot 110. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 11.....	92
Plot 111. Spectral Power Density, 802.11n 40MHz, Port J5, Channel 6.....	93
Plot 112. Spectral Power Density, 802.11n 40MHz, Port J6, Channel 6.....	93
Plot 113. Spectral Power Density, 802.11n 20MHz, Combined Ports, Channel 1.....	94
Plot 114. Spectral Power Density, 802.11n 20MHz, Combined Ports, Channel 6.....	94
Plot 115. Spectral Power Density, 802.11n 20MHz, Combined Ports, Channel 11.....	95
Plot 116. Spectral Power Density, 802.11n 40MHz, Combined Ports, Channel 6.....	95

List of Figures

Figure 1. Block Diagram of Test Configuration.....	7
Figure 2. Block Diagram, Occupied Bandwidth Test Setup.....	26
Figure 3. Peak Power Output Test Setup.....	36
Figure 4. Block Diagram, Conducted Receiver Spurious Emissions Test Setup.....	69
Figure 5. Block Diagram, Conducted Spurious Emissions Test Setup.....	72
Figure 6. Block Diagram, Peak Power Spectral Density Test Setup.....	87

List of Photographs

Photograph 1. Ubiquiti Networks M2D.....	6
Photograph 2. Conducted Emissions, Test Setup.....	14
Photograph 3. Radiated Emission, Test Setup, FCC Limits.....	19
Photograph 4. Radiated Emission, Test Setup, IC Limits.....	19
Photograph 5. Conducted Emissions, 15.207, Test Setup.....	25
Photograph 6. Radiated Spurious Emissions, Test Setup @ 3m.....	67
Photograph 7. Radiated Emissions, Test Setup, 1 GHz – 10 GHz.....	67
Photograph 8. Radiated Restricted Band, Test Setup @ 1m.....	68

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dB μ A	Decibels above one microamp
dB μ V	Decibels above one microvolt
dB μ A/m	Decibels above one microamp per meter
dB μ V/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kilohertz
kPa	kilopascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
μ H	microhenry
μ	microfarad
μ s	microseconds
NEBS	Network Equipment-Building System
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

I. Executive Summary

A. Purpose of Test

An EMC evaluation was performed to determine compliance of the Ubiquiti Networks M2D, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the M2D. Ubiquiti Networks should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the M2D, has been **permanently** discontinued.

B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Ubiquiti Networks, purchase order number US090040. All tests were conducted using measurement procedure ANSI C63.4-2003.

FCC Reference 47 CFR Part 15.247:2005	IC Reference RSS-210 Issue 7: 2007	Description	Compliance
47 CFR Part 15.107 (a)	ICES-003 Issue 4 February 2004	Conducted Emission Limits for a Class A Digital Device	Compliant
47 CFR Part 15.109 (a)	ICES-003 Issue 4 February 2004	Radiated Emission Limits for a Class A Digital Device	Compliant
Title 47 of the CFR, Part 15 §15.203	N/A	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	RSS-210(7.2.2)	Conducted Emission Voltage	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(1)	RSS-210(A8.1)	Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	RSS-210(A8.4)	RF Output Power	Compliant
Title 47 of the CFR, Part 15 §15.209, §15.247(d)	RSS-210(A8.5)	Radiated Spurious Emissions	Compliant
Title 47 of the CFR, Part 15 §15.205	RSS-210(A8.5)	Emissions at Restricted Band	Compliant
Title 47 of the CFR, Part 15 §15.209, §15.247(d)	RSS-210(A8.5)	Conducted Spurious Emissions	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	RSS-210(A8.3)	Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	RSS-Gen(5.5)	Maximum Permissible Exposure	Compliant
N/A	RSS-Gen(4.8)	Receiver Spurious Emissions	Compliant

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing

II. Equipment Configuration

A. Overview

MET Laboratories, Inc. was contracted by Ubiquiti Networks to perform testing on the M2D, under Ubiquiti Networks's purchase order number US090040.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Ubiquiti Networks, M2D.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	M2D	
Model(s) Covered:	M2D	
EUT Specifications:	Primary Power: 120 VAC, 60 Hz	
	FCC ID: SWX-M2D IC: 6545A-M2D	
	Type of Modulations:	OFDM
	Equipment Code:	DTS
	Peak RF Output Power:	23.92 dBm (0.246W)
EUT Frequency Ranges:	2412 – 2462 MHz	
Analysis:	The results obtained relate only to the item(s) tested.	
Environmental Test Conditions:	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
Evaluated by:	Minh Ly	
Report Date(s):	June 14, 2010	

Table 2. EUT Summary Table

B. References

CFR 47, Part 15, Subpart C	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
RSS-210, Issue 7, June 2007	Low-power Licence-exempt Radiocommunications Devices (All Frequency Bands): Category I Equipment
CFR 47, Part 15, Subpart B	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
ICES-003, Issue 4 February 2004	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
ANSI C63.4:2003	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI/NCSL Z540-1-1994	Calibration Laboratories and Measuring and Test Equipment - General Requirements
ANSI/ISO/IEC 17025:2000	General Requirements for the Competence of Testing and Calibration Laboratories
ANSI C63.10-2009	American National Standard for Testing Unlicensed Wireless Devices

Table 3. References

C. Test Site

All testing was performed at MET Laboratories, Inc., 3162 Belick St., Santa Clara, CA 95054. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

D. Description of Test Sample

The Ubiquiti Networks M2D, Equipment Under Test (EUT), is an Outdoor PtP Wireless Bridge.



Photograph 1. Ubiquiti Networks M2D




Figure 1. Block Diagram of Test Configuration

E. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Name / Description	Model Number	Serial Number
A	M2D	M2D	00156D1AC0DB
B	Power Supply (POE)	UBI-POE-15-8	0908-0012285
C	18dBi Grid	NB-2G-18	MET01

Table 4. Equipment Configuration

F. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number
D	Laptop	Dell	Vostro 1510

Table 5. Support Equipment

G. Ports and Cabling Information

Ref. ID	Port name on EUT	Cable Description or reason for no cable	Qty.	Length (m)	Shielded (Y/N)	Termination Box ID & Port Name
1	A,EUT	CAT 5E	1	2	Y	B, POE
2	A,EUT	Direct plug in				C
3	B	CAT 5E	1	2	Y	D
4	B	Power Cable	1	.5	N	120VAC Power Supply

Table 6. Ports and Cabling Information

H. Mode of Operation

Use Atheros Radio Test Software.

I. Modifications

- a) **Modifications to EUT**
No modifications were made to the EUT.
- b) **Modifications to Test Standard**
No modifications were made to the test standard.

J. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Ubiquiti Networks upon completion of testing.

III. Electromagnetic Compatibility Criteria for Unintentional Radiators

Electromagnetic Compatibility Criteria

§ 15.107 Conducted Emissions Limits

Test Requirement(s): **15.107 (a)** Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 7. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

15.107 (b) For a Class A digital device that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 7. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals. The lower limit applies at the band edges.

15.207(a), Except as shown in paragraphs (b) and (c) of this section*, charging, AC adapters or battery eliminators the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the Table 7, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency range (MHz)	Class A Conducted Limits (dB μ V)		*Class B Conducted Limits (dB μ V)	
	Quasi-Peak	Average	Quasi-Peak	Average
* 0.15- 0.45	79	66	66 - 56	56 - 46
0.45 - 0.5	79	66	56	46
0.5 - 30	73	60	60	50

Note 1 — The lower limit shall apply at the transition frequencies.
 Note 2 — The limit decreases linearly with the logarithm if the frequency in the range 0.15 MHz to 0.5 MHz.
 * -- Limits per Subsection 15.207(a).

Table 7. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b) and 15.207(a)

Test Results: The EUT was compliant with the Class A requirement(s) of this section. Measured emissions were below applicable limits.


Test Engineer(s): Minh Ly

Test Date(s): 04/15/10

Conducted Emissions - Voltage, AC Power


Line	Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
120VAC Line	3.97	24.7	73	-48.3	Pass	13.32	60	-46.68	Pass
120VAC Line	5.66	43.55	73	-29.45	Pass	33.68	60	-26.32	Pass
120VAC Line	11.71	35.24	73	-37.76	Pass	29.51	60	-30.49	Pass
120VAC Neutral	0.408	46.1	79	-32.9	Pass	38.18	66	-27.82	Pass
120VAC Neutral	5.69	40.23	73	-32.77	Pass	31.13	60	-28.87	Pass
120VAC Neutral	12.2	30.69	73	-42.31	Pass	27.02	60	-32.98	Pass

Table 8. Conducted Emissions - Voltage, AC Power




Plot 1. Conducted Emission, Phase Line Plot

Conducted Emissions - Voltage, AC Power



Plot 2. Conducted Emission, Neutral Line Plot

Conducted Emission Limits Test Setup



Photograph 2. Conducted Emissions, Test Setup

Radiated Emission Limits

§ 15.109 Radiated Emissions Limits

Test Requirement(s): **15.109 (a)** Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the Class B limits expressed in Table 9.

15.109 (b) The field strength of radiated emissions from a Class A digital device, as determined at a distance of 10 meters, shall not exceed the Class A limits expressed in Table 9.

Frequency (MHz)	Field Strength (dB μ V/m)	
	§15.109 (b), Class A Limit (dB μ V) @ 10m	§15.109 (a), Class B Limit (dB μ V) @ 3m
30 - 88	39.00	40.00
88 - 216	43.50	43.50
216 - 960	46.40	46.00
Above 960	49.50	54.00

Table 9. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b)

Test Procedures: The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. The method of testing and test conditions of ANSI C63.4 were used. An antenna was located 3 m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. Unless otherwise specified, measurements were made using a quasi-peak detector with a 120 kHz bandwidth.

Test Results: The EUT was compliant with the Class A requirement(s) of this section. Measured emissions were below applicable limits.


Test Engineer(s): Minh Ly

Test Date(s): 02/13/10 & 04/18/10

Radiated Emissions Limits Test Results, Class A

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBuV)	ACF (dB/m)	Pre Amp Gain (dB)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
98.48	V	360	100	26.21	12.335	0	2.817	-10.46	30.902	43.5	-12.598
98.48	H	78	210	24.84	10.796	0	2.817	-10.46	27.993	43.5	-15.507
390	V	170	100	26.46	15.7	0	4.092	-10.46	35.792	46.4	-10.608
390	H	222	100	29.66	16.1	0	4.092	-10.46	39.392	46.4	-7.008
780	V	360	218	23.7	20.2	0	6.132	-10.46	39.572	46.4	-6.828
780	H	24	142	24.7	20.5	0	6.132	-10.46	40.872	46.4	-5.528

Table 10. Radiated Emissions Limits, Test Results, 30 MHz – 1 GHz, FCC Limits




Plot 3. Radiated Emissions, 30 MHz - 1 GHz, FCC Limits

Radiated Emissions Limits Test Results, Class A

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBuV)	ACF (dB/m)	Pre Amp Gain (dB)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1560	H	54	111	83.94	25.51	54.139	0	-10.46	44.851	49.5	-4.649
1949	H	57	100	71.91	27.878	54.653	0	-10.46	34.675	49.5	-14.825
1949	V	13	100	69.7	27.878	54.653	0	-10.46	32.465	49.5	-17.035
10000	V	0	100	51.38	39.3	55.46	0	-10.46	24.76	49.5	-24.74
10000	H	0	100	51.4	39.3	55.46	0	-10.46	24.78	49.5	-24.72

Table 11. Radiated Emissions Limits, Test Results, Above 1 GHz, FCC Limits




Plot 4. Radiated Emissions, Above 1 GHz, FCC Limits

Radiated Emissions Limits Test Results, Class A

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBuV)	ACF (dB/m)	Pre Amp Gain (dB)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
61.72	V	89	238	56.3	6.156	40	1.218	0	23.674	40	-16.326
390	V	173	100	59.47	15.8	40	3.261	0	38.531	47	-8.469
390	H	144	230	60.97	15	40	3.261	0	39.231	47	-7.769
584.96	H	65	131	46.73	18.199	40	4.072	0	29.001	47	-17.999
779.96	V	351	148	51.14	19.602	40	4.693	0	35.435	47	-11.565
779.96	H	275	100	56.72	20.001	40	4.693	0	41.414	47	-5.586

Table 12. Radiated Emissions Limits, Test Results, ICES-003 Limits




Plot 5. Radiated Emissions, ICES-003 Limits

Radiated Emission Limits Test Setup



Photograph 3. Radiated Emission, Test Setup, FCC Limits



Photograph 4. Radiated Emission, Test Setup, IC Limits

IV. Electromagnetic Compatibility Criteria for Intentional Radiators

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.203 Antenna Requirement

Test Requirement: § 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

Results: The EUT as tested meets the criteria of this rule by virtue of having professionally installed. The EUT as tested is compliant the criteria of §15.203.

Test Engineer(s): Minh Ly

Test Date(s): 04/15/10

Gain	Type	Model	Serial Number	Manufacturer
18 dBi	Grid	NB-2G-18	MET01	Ubiquiti Networks

Table 13. Antenna List

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.207 Conducted Emissions Limits

Test Requirement(s): § 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB μ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 - 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

Table 14. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)

Test Procedure: The EUT was placed on a 0.8 m-high wooden table inside a screen room. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50 Ω /50 μ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.4-2003 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to an EMC/field intensity meter. For the purpose of this testing, the transmitter was turned on. Scans were performed with the transmitter on.

Test Results: The EUT was compliant with this requirement. Measured emission were below applicable limits.


Test Engineer(s): Minh Ly

Test Date(s): 04/15/10

15.207 Conducted Emissions Test Results


Line	Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
120VAC Line	0.153	51.71	65.836	-14.126	Pass	32.4	55.836	-23.436	Pass
120VAC Line	0.396	47.05	57.959	-10.909	Pass	36.53	47.959	-11.429	Pass
120VAC Line	5.735	41.25	60	-18.75	Pass	32.29	50	-17.71	Pass
120VAC Neutral	0.155	43.51	65.728	-22.218	Pass	29.62	55.728	-26.108	Pass
120VAC Neutral	5.61	45.84	60	-14.16	Pass	34.91	50	-15.09	Pass
120VAC Neutral	3.972	25.16	56	-30.84	Pass	14.17	46	-31.83	Pass

Table 15. Conducted Emissions, 15.207, Test Results




Plot 6. Conducted Emissions, Phase Line

15.207 Conducted Emissions Test Results



Plot 7. Conducted Emissions, Neutral Line

15.207 Conducted Emissions Test Setup Photo



Photograph 5. Conducted Emissions, 15.207, Test Setup

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a) 6 dB and 99% Bandwidth

Test Requirements: § 15.247(a): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Procedure: The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately 1% of the total emission bandwidth, VBW > RBW. The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels.

Test Results The EUT was compliant with § 15.247 (a).

The 6 dB and 99% Bandwidth was determined from the plots on the following pages.

Test Engineer(s): Minh Ly

Test Date(s): 04/14/10




Figure 2. Block Diagram, Occupied Bandwidth Test Setup

Occupied Bandwidth Test Results


Occupied Bandwidth (Port J5)				
Mode	Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Measured 99% Bandwidth (MHz)
HT20	Low	2412	17.85	17.69
	Mid	2437	17.02	17.80
	High	2462	17.62	17.71
HT40	Mid	2437	36.27	35.94

Table 16. Occupied Bandwidth, Test Results, Port J5


Occupied Bandwidth (Port J6)				
Mode	Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Measured 99% Bandwidth (MHz)
HT20	Low	2412	16.97	17.77
	Mid	2437	17.57	17.79
	High	2462	17.73	17.77
HT40	Mid	2437	36.54	36.05

Table 17. Occupied Bandwidth, Test Results, Port J6

Occupied Bandwidth Test Results




Plot 8. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 1




Plot 9. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 6

Occupied Bandwidth Test Results




Plot 10. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 11




Plot 11. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 1

Occupied Bandwidth Test Results




Plot 12. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 6




Plot 13. 6dB Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 11

Occupied Bandwidth Test Results




Plot 14. 6dB Occupied Bandwidth, 802.11n 40MHz, Port J5, Channel 6




Plot 15. 6dB Occupied Bandwidth, 802.11n 40MHz, Port J6, Channel 6

Occupied Bandwidth Test Results




Plot 16. 99% Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 1




Plot 17. 99% Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 6

Occupied Bandwidth Test Results




Plot 18. 99% Occupied Bandwidth, 802.11n 20MHz, Port J5, Channel 11




Plot 19. 99% Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 1

Occupied Bandwidth Test Results




Plot 20. 99% Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 6




Plot 21. 99% Occupied Bandwidth, 802.11n 20MHz, Port J6, Channel 11

Occupied Bandwidth Test Results



Plot 22. 99% Occupied Bandwidth, 802.11n 40MHz, Port J5, Channel 6



Plot 23. 99% Occupied Bandwidth, 802.11n 40MHz, Port J6, Channel 6

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(b) Peak Power Output and RF Exposure

Test Requirements: §15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
902-928	1.000
2400-2483.5	1.000
5725- 5850	1.000

Table 18. Output Power Requirements from §15.247

§15.247(c): if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in the Table 18, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400 – 2483.5 MHz band and using a point to point application may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Fixed, point-to-point operation excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

Test Procedure: The transmitter was connected to a calibrated spectrum analyzer. The EUT was measured at the low, mid and high channels of each band at the maximum power level.

Test Results: The EUT was compliant with the Peak Power Output limits of §15.247(b).

Test Engineer(s): Minh Ly

Test Date(s): 04/14/10





Figure 3. Peak Power Output Test Setup

RF Power Output Test Results


Peak Conducted Output Power						
Mode/Antenna	Carrier Channel	Frequency (MHz)	Port J5 (dBm)	Port J6 (dBm)	Combined (dBm)	Combined (W)
802.11n 20MHz	1	2412	12.36	12.94	15.66	0.036
	2	2417	18.06	17.94	21.01	0.126
	3	2422	18.11	18.38	21.25	0.133
	4	2427	19.10	19.40	22.26	0.168
	6	2437	20.93	20.89	23.92	0.247
	8	2447	19.40	19.53	22.47	0.177
	9	2452	17.87	18.20	21.04	0.127
	10	2457	17.06	17.69	20.39	0.109
	11	2462	12.65	13.29	15.99	0.039
802.11n 40MHz	6	2437	13.85	14.02	16.94	0.049

Table 19. RF Output Power, Test Results

RF Output Power Test Results




Plot 24. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 1 (2412MHz)




Plot 25. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 2 (2417MHz)

RF Output Power Test Results




Plot 26. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 3 (2422MHz)




Plot 27. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 4 (2427MHz)

RF Output Power Test Results




Plot 28. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 6 (2437MHz)




Plot 29. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 8 (2447MHz)

RF Output Power Test Results




Plot 30. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 9 (2452MHz)




Plot 31. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 10 (2457MHz)

RF Output Power Test Results




Plot 32. Conducted Output Power, 802.11n 20MHz, Port J5, Channel 11 (2462MHz)




Plot 33. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 1 (2412MHz)

RF Output Power Test Results




Plot 34. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 2 (2417MHz)




Plot 35. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 3 (2422MHz)

RF Output Power Test Results




Plot 36. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 4 (2427MHz)




Plot 37. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 6 (2437MHz)

RF Output Power Test Results



Plot 38. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 8 (2447MHz)




Plot 39. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 9 (2452MHz)

RF Output Power Test Results




Plot 40. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 10 (2457MHz)




Plot 41. Conducted Output Power, 802.11n 20MHz, Port J6, Channel 11 (2462MHz)

RF Output Power Test Results



Plot 42. Conducted Output Power, 802.11n 40MHz, Port J5, Channel 6 (2437MHz)



Plot 43. Conducted Output Power, 802.11n 40MHz, Port J6, Channel 6 (2437MHz)

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(b) RF Exposure

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 2412-2462 MHz; highest conducted power = **23.92dBm** (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

EUT maximum antenna gain = **17dBi Grid**

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm²)
P = Power Input to antenna (246.60mW)
G = Antenna Gain (63.1 numeric)

$$R = (246.6 * 50.11 / 4 * 3.14 * 1.0)^{1/2} = (12359.47 / 12.56)^{1/2} = \mathbf{31.36cm}$$

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge

Test Requirements: §15.247(d); §15.205: Emissions outside the frequency band.

§15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

§15.205(a): Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358 36.	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	(²)

Table 20. Restricted Bands of Operation

¹ Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

² Above 38.6

Test Requirement(s): § 15.209 (a): Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 21.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dB μ V) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

Table 21. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)

Test Procedures: The transmitter was turned. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line. Only noise floor was measured above 18 GHz.

Test Results: The EUT was compliant with the Radiated Spurious Emission limits of § 15.247(d). Emissions from 390MHz and 780MHz peaks are from digital portion of the device and appear to be lower than 56.4 dB μ V/m measured at 3 meters. This is equivalent to 15.109(b) limit (46.4 dB μ V/m@10m) plus 10dB adjustment for measurement at 3 meters.

Test Engineer(s): Minh Ly

Test Date(s): 04/20/10

Radiated Spurious Emissions Requirements

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg.)	P. Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg.	Limit @ 3 m (dBuV/m)	Delta (dB)
4.824	V	43.57	34.92	33.95	5.06	47.66	Peak	74	-26.34
4.824	V	29.16	34.92	33.95	5.06	33.25	Avg.	54	-20.75
7.236	V	44.05	33.34	35.62	6.26	52.59	Peak	74	-21.41
7.236	V	30.06	33.34	35.62	6.26	38.60	Avg.	54	-15.40
9.648	V	44.88	35.66	36.61	7.29	53.12	Peak	74	-20.88
9.648	V	31.5	35.66	36.61	7.29	39.74	Avg.	54	-14.26

Table 22. Radiated Harmonics, Low Channel, 802.11n 20MHz

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg.)	P. Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg.	Limit @ 3 m (dBuV/m)	Delta (dB)
4.874	V	53.38	35.22	33.94	5.06	57.16	Peak	74	-16.84
4.874	V	40.39	35.22	33.94	5.06	44.17	Avg.	54	-9.83
7.311	V	42.57	33.59	35.64	6.33	50.95	Peak	74	-23.05
7.311	V	31.75	33.59	35.64	6.33	40.13	Avg.	54	-13.87
9.748	V	43.71	35.55	36.75	7.42	52.33	Peak	74	-21.67
9.748	V	30.48	35.55	36.75	7.42	39.10	Avg.	54	-14.90


Table 23. Radiated Harmonics, Mid Channel, 802.11n 20MHz

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg.)	P. Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg.	Limit @ 3 m (dBuV/m)	Delta (dB)
4.924	V	43.03	35.52	33.94	5.06	46.51	Peak	74	-27.49
4.924	V	29.99	35.52	33.94	5.06	33.47	Avg.	54	-20.53
7.386	V	43.87	34.66	35.65	6.38	51.25	Peak	74	-22.75
7.386	V	29.88	34.66	35.65	6.38	37.26	Avg.	54	-16.74
9.848	V	44.74	35.45	36.89	7.54	53.72	Peak	74	-20.28
9.848	V	30.88	35.45	36.89	7.54	39.86	Avg.	54	-14.14

Table 24. Radiated Harmonics, High Channel, 802.11n 20MHz


Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 3 m (Peak) / (Avg.)	P. Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	EUT Field Strength Final Amp. (dBuV/m)	Limit Detector Peak / Avg.	Limit @ 3 m (dBuV/m)	Delta (dB)
4.874	V	43.68	35.22	33.94	5.06	47.46	Peak	74	-26.54
4.874	V	30.30	35.22	33.94	5.06	34.08	Avg.	54	-19.92
7.311	V	45.72	33.59	35.64	6.33	54.10	Peak	74	-19.90
7.311	V	32.55	33.59	35.64	6.33	40.93	Avg.	54	-13.07
9.748	V	42.82	35.55	36.75	7.42	51.44	Peak	74	-22.56
9.748	V	30.25	35.55	36.75	7.42	38.87	Avg.	54	-15.13

Table 25. Radiated Harmonics, Mid Channel, 802.11n 40MHz




Plot 44. Radiated Emissions, Low Channel

Radiated Spurious Emissions Requirements




Plot 45. Radiated Emissions, Mid Channel




Plot 46. Radiated Emissions, High Channel

Radiated Spurious Emissions Test Results




Plot 47. Radiated Spurious Emission, 802.11n 20MHz, Ch1, 1-18GHz




Plot 48. Radiated Spurious Emission, 802.11n 20MHz, Ch6, 1-18GHz

Radiated Spurious Emissions Test Results




Plot 49. Radiated Spurious Emission, 802.11n 20MHz, Ch11, 1-18GHz




Plot 50. Radiated Spurious Emission, 802.11n 40MHz, Ch6, 1-18GHz

Radiated Band Edge Measurements

Test Procedures: The transmitter was turned. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line.




Plot 51. Radiated Restricted Band, Channel 1, 802.11n 20MHz, Peak




Plot 52. Radiated Restricted Band, Channel 1, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 53. Radiated Restricted Band, Channel 2, 802.11n 20MHz, Peak




Plot 54. Radiated Restricted Band, Channel 2, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 55. Radiated Restricted Band, Channel 3, 802.11n 20MHz, Peak




Plot 56. Radiated Restricted Band, Channel 3, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 57. Radiated Restricted Band, Channel 4, 802.11n 20MHz, Peak




Plot 58. Radiated Restricted Band, Channel 4, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 59. Radiated Restricted Band, Channel 6 - Low, 802.11n 20MHz, Peak




Plot 60. Radiated Restricted Band, Channel 6 - Low, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 61. Radiated Restricted Band, Channel 6 - High, 802.11n 20MHz, Peak




Plot 62. Radiated Restricted Band, Channel 6 - High, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 63. Radiated Restricted Band, Channel 8, 802.11n 20MHz, Peak




Plot 64. Radiated Restricted Band, Channel 8, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 65. Radiated Restricted Band, Channel 9, 802.11n 20MHz, Peak




Plot 66. Radiated Restricted Band, Channel 9, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 67. Radiated Restricted Band, Channel 10, 802.11n 20MHz, Peak




Plot 68. Radiated Restricted Band, Channel 10, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 69. Radiated Restricted Band, Channel 11, 802.11n 20MHz, Peak




Plot 70. Radiated Restricted Band, Channel 11, 802.11n 20MHz, Average

Radiated Band Edge Measurements




Plot 71. Radiated Restricted Band, Channel 6, 802.11n 40MHz, Peak




Plot 72. Radiated Restricted Band, Channel 6, 802.11n 40MHz, Average


Radiated Spurious Emissions Test Setup



Photograph 6. Radiated Spurious Emissions, Test Setup @ 3m



Photograph 7. Radiated Emissions, Test Setup, 1 GHz – 10 GHz



Photograph 8. Radiated Restricted Band, Test Setup @ 1m

Electromagnetic Compatibility Criteria for Intentional Radiators

RSS-GEN Receiver Spurious Emissions Requirements

Test Requirements: The following receiver spurious emission limits shall be complied with:

- (a) If a radiated measurement is made, all spurious emissions shall comply with the limits of Table 26.

Spurious Frequency (MHz)	Field Strength (microvolt/m at 3 metres)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 26. Spurious Emission Limits for Receivers

- (b) If a conducted measurement is made, no spurious output signals appearing at the antenna terminals shall exceed 2 nanowatts per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5 nanowatts above 1 GHz.

Test Procedures: The EUT was programmed for receive mode only. Conducted measurements were taken at the antenna port of the EUT. 100 kHz resolution bandwidth was used from 30 MHz - 1 GHz and 300 kHz resolution was used for measurements done above 1 GHz. All plots are corrected for cable loss.

Test Results: Equipment is compliant with the Receiver Spurious Emissions Requirements of RSS-GEN.

Test Engineer(s): Minh Ly

Test Date(s): 04/15/10






Figure 4. Block Diagram, Conducted Receiver Spurious Emissions Test Setup

Conducted Receiver Spurious Emissions




Plot 73. Conducted Rx Spurious 30 MHz – 1 GHz, Port J5




Plot 74. Conducted Rx Spurious 1 GHz – 10 GHz, Port J5

Conducted Receiver Spurious Emissions



Plot 75. Conducted Rx Spurious 30 MHz – 1 GHz, Port J6



Plot 76. Conducted Rx Spurious 1 GHz – 10 GHz, Port J6

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge

Test Requirement: **15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure: For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

Since the EUT had an integral antenna, conducted measurements could not be performed. Measurements needed to be taken radiated. An antenna was located 3 m away from the EUT and plots were taken. The EUT was rotated through all three orthogonal axes. The plots were corrected for both antenna correction factor and cable loss.

See following pages for detailed test results with RF Conducted Spurious Emissions. Due to frequency limitation on the combiner, we performed radiated test for spurious emission.

Test Results: The EUT was compliant with the Conducted Spurious Emission limits of **§15.247(d)**.

Test Engineer(s): Minh Ly

Test Date(s): 04/14/10






Figure 5. Block Diagram, Conducted Spurious Emissions Test Setup

Conducted Spurious Emissions Test Results




Plot 77. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 1, 30MHz - 1GHz




Plot 78. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 1, 1G-18GHz

Conducted Spurious Emissions Test Results




Plot 79. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 1, 18GHz - 26.5GHz




Plot 80. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 6, 30MHz - 1GHz

Conducted Spurious Emissions Test Results




Plot 81. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 6, 1G-18GHz




Plot 82. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 6, 18GHz - 26.5GHz

Conducted Spurious Emissions Test Results




Plot 83. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 11, 30MHz - 1GHz




Plot 84. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 11, 1G-18GHz

Conducted Spurious Emissions Test Results




Plot 85. Conducted Spurious Emission, 802.11n 20MHz, Port J5, Channel 11, 18GHz - 26.5GHz




Plot 86. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 1, 30MHz - 1GHz

Conducted Spurious Emissions Test Results




Plot 87. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 1, 1GHz - 18GHz




Plot 88. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 1, 18GHz - 26.5GHz

Conducted Spurious Emissions Test Results




Plot 89. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 6, 30MHz - 1GHz




Plot 90. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 6, 1GHz - 18GHz

Conducted Spurious Emissions Test Results




Plot 91. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 6, 18GHz - 26.5GHz




Plot 92. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 11, 30MHz - 1GHz

Conducted Spurious Emissions Test Results




Plot 93. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 11, 1GHz - 18GHz




Plot 94. Conducted Spurious Emission, 802.11n 20MHz, Port J6, Channel 11, 18GHz - 26.5GHz

Conducted Spurious Emissions Test Results




Plot 95. Conducted Spurious Emission, 802.11n 40MHz, Port J5, Channel 6, 30MHz - 1GHz




Plot 96. Conducted Spurious Emission, 802.11n 40MHz, Port J5, Channel 6, 1GHz - 18GHz

Conducted Spurious Emissions Test Results




Plot 97. Conducted Spurious Emission, 802.11n 40MHz, Port J5, Channel 6, 18GHz-26.5GHz




Plot 98. Conducted Spurious Emission, 802.11n 40MHz, Port J6, Channel 6, 30MHz - 1GHz

Conducted Spurious Emissions Test Results




Plot 99. Conducted Spurious Emission, 802.11n 40MHz, Port J6, Channel 6, 1GHz - 18GHz




Plot 100. Conducted Spurious Emission, 802.11n 40MHz, Port J6, Channel 6, 18GHz-26.5GHz


Conducted Band Edge Test Results




Plot 101. Lower Conducted Band Edge, 802.11n 20MHz



Plot 102. Upper Conducted Band Edge, 802.11n 20MHz



Plot 103. Lower Conducted Band Edge, 802.11n 40MHz



Plot 104. Upper Conducted Band Edge, 802.11n 40MHz

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(e) Peak Power Spectral Density

Test Requirements: §15.247(e): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure: The transmitter was connected directly to a Spectrum Analyzer through an attenuator. The power level was set to the maximum level. A RBW of 1 MHz and VBW of 3 MHz were used to determine the peak emissions within the band. The Spectrum analyzer was then set to a RBW of 3 kHz and VBW was set to 10 kHz. The SPAN of the analyzer was set to 1 MHz with a 333.3 second sweep. Measurements were carried out at the low, mid and high channels. For combined ports, both RF ports are combined using a combiner and the test procedures above is followed.

Test Results: The EUT was compliant with the peak power spectral density limits of § 15.247 (e).
The peak power spectral density was determined from plots on the following page(s).

Test Engineer: Minh Ly

Test Date: 04/14/10




Figure 6. Block Diagram, Peak Power Spectral Density Test Setup

Peak Power Spectral Density Test Results

802.11n 20MHz						
	Carrier Channel	Frequency (MHz)	Measured PSD (dBm)	Directional Antenna Gain Offset	Limit (dBm)	Margin (dB)
Port J5	Low	2412	-19.64	4	8	-23.64
	Mid	2437	-10.75	4	8	-14.75
	High	2462	-20.22	4	8	-24.22

Table 27. Spectral Density, Test Results, 802.11n 20MHz, Port J5

802.11n 40MHz						
	Carrier Channel	Frequency (MHz)	Measured PSD (dBm)	Directional Antenna Gain Offset (dB)	Limit (dBm)	Margin (dB)
Port J5	Mid	2437	-20.56	4	8	-24.56

Table 28. Spectral Density, Test Results, 802.11n 40MHz, Port J5

802.11n 20MHz						
	Carrier Channel	Frequency (MHz)	Measured PSD (dBm)	Directional Antenna Gain Offset	Limit (dBm)	Margin (dB)
Port J6	Low	2412	-19.56	4	8	-23.56
	Mid	2437	-12.13	4	8	-16.13
	High	2462	-19.04	4	8	-23.04

Table 29. Spectral Density, Test Results, 802.11n 20MHz, Port J6

802.11n 40MHz						
	Carrier Channel	Frequency (MHz)	Measured PSD (dBm)	Directional Antenna Gain Offset (dB)	Limit (dBm)	Margin (dB)
Port J6	Mid	2437	-19.83	4	8	-23.83

Table 30. Spectral Density, Test Results, 802.11n 40MHz, Port J6

Peak Power Spectral Density Test Results


802.11n 20MHz						
	Carrier Channel	Frequency (MHz)	Measured PSD (dBm)	Directional Antenna Gain Offset	Limit (dBm)	Margin (dB)
Combined	Low	2412	-16.85	4	8	-20.85
	Mid	2437	-6.51	4	8	-10.51
	High	2462	-15.07	4	8	-19.07

Table 31. Spectral Density, Test Results, 802.11n 20MHz, Combined


802.11n 40MHz						
	Carrier Channel	Frequency (MHz)	Measured PSD (dBm)	Directional Antenna Gain Offset (dB)	Limit (dBm)	Margin (dB)
Combined	Mid	2437	-17.20	4	8	-21.2

Table 32. Spectral Density, Test Results, 802.11n 40MHz, Combined

Peak Power Spectral Density




Plot 105. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 1




Plot 106. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 6

Peak Power Spectral Density




Plot 107. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 11




Plot 108. Spectral Power Density, 802.11n 20MHz, Port J6, Channel 1

Peak Power Spectral Density




Plot 109. Spectral Power Density, 802.11n 20MHz, Port J6, Channel 6




Plot 110. Spectral Power Density, 802.11n 20MHz, Port J5, Channel 11

Peak Power Spectral Density




Plot 111. Spectral Power Density, 802.11n 40MHz, Port J5, Channel 6




Plot 112. Spectral Power Density, 802.11n 40MHz, Port J6, Channel 6

Peak Power Spectral Density




Plot 113. Spectral Power Density, 802.11n 20MHz, Combined Ports, Channel 1




Plot 114. Spectral Power Density, 802.11n 20MHz, Combined Ports, Channel 6

Peak Power Spectral Density



Plot 115. Spectral Power Density, 802.11n 20MHz, Combined Ports, Channel 11



Plot 116. Spectral Power Density, 802.11n 40MHz, Combined Ports, Channel 6

IV. Test Equipment

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ANSI/NCSL Z540-1-1994 and ANSI/ISO/IEC 17025:2000.

MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1S2421	EMI RECEIVER	ROHDE&SCHWARZ	ESIB 7	05/27/2009	05/27/2010
1S2121	PRE-AMPLIFIER	HEWLETT PACKARD	8449B	SEE NOTE	
1S2501	EMI RECEIVER	Rohde & Schwarz	ESU40	4/27/2009	4/27/2010
1S2128	HARMONIC MIXER	HEWLETT PACKARD	11970A	11/22/2008	11/22/2010
1S2129	HARMONIC MIXER	HEWLETT PACKARD	11970K	11/22/2008	11/22/2010
1S2603	HORN ANTENNA	ETS-LINDGREN	3117	4/9/2009	4/9/2011
N/A	HIGH PASS FILTER	MICRO-TRONICS	HPM13146	SEE NOTE	
1S2607	ANALYZER, SPECTRUM 9 KHZ-40GHZ	AGILENT	E4407B	06/29/2009	06/29/2010
1S508	LISN	SOLAR ELECTRONICS	9252-50- R24-BNC	06/05/2009	06/05/2010
1S2512	TRANSIENT LIMITER	AGILENT	11947A	SEE NOTE	
1S2518	THERMO-HYGROMETER	FISHER SCIENTIFIC	11-661-7D	1/28/2010	1/28/2012
1S2482	CHAMBER, 5 METER	PANASHIELD	641431	10/16/2009	10/16/2010
1S2108	RECIEVER, EMI, RF FILTER SECTION	HP	85460A	11/10/2009	11/10/2010
1S2399	TURNTABLE CONTROLLER	SUNOL SCIENCE	SC99V	SEE NOTE	
1S2484	BILOG ANTENNA	TESEQ	CBL6112D	01/27/2009	01/27/2012

Table 33. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

V. Certification & User's Manual Information

Certification & User's Manual Information

A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

§ 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

§ 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
 - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
 - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing*;
 - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
 - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

§ 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.¹ *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

§ 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

¹ In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

Certification & User's Manual Information

§ 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
- (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
- (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
- (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
- (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

Certification & User's Manual Information

Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

§ 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

§ 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

§ 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

ICES-003 Procedural & Labeling Requirements

From the Industry Canada Electromagnetic Compatibility Advisory Bulletin entitled, "Implementation and Interpretation of the Interference-Causing Equipment Standard for Digital Apparatus, ICES-003" (EMCAB-3, Issue 2, July 1995):

"At present, CISPR 22: 2002 and ICES technical requirements are essentially equivalent. Therefore, if you have CISPR 22: 2002 approval by meeting CISPR Publication 22, the only additional requirements are: to attach a note to the report of the test results for compliance, indicating that these results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations; to maintain these records on file for the requisite five year period; and to provide the device with a notice of compliance in accordance with ICES-003."

Procedural Requirements:

According to Industry Canada's Interference Causing Equipment Standard for Digital Apparatus ICES-003 Issue 4, February 2004:

- Section 6.1: A record of the measurements and results, showing the date that the measurements were completed, shall be retained by the manufacturer or importer for a period of at least five years from the date shown in the record and made available for examination on the request of the Minister.
- Section 6.2: A written notice indicating compliance must accompany each unit of digital apparatus to the end user. The notice shall be in the form of a label that is affixed to the apparatus. Where because of insufficient space or other constraints it is not feasible to affix a label to the apparatus, the notice may be in the form of a statement in the user's manual.

Labeling Requirements:

The suggested text for the notice, in English and in French, is provided below, from the Annex of ICES-003:

This Class [²] digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe [¹] est conforme à la norme NMB-003 du Canada.

² Insert either A or B but not both as appropriate for the equipment requirements.

End of Report