



**MET Laboratories, Inc.** *Safety Certification - EMI - Telecom Environmental Simulation*

914 WEST PATAPSCO AVENUE ● BALTIMORE, MARYLAND 21230-3432 ● PHONE (410) 354-3300 ● FAX (410) 354-3313

33439 WESTERN AVENUE ● UNION CITY, CALIFORNIA 94587 ● PHONE (510) 489-6300 ● FAX (510) 489-6372

3162 BELICK STREET ● SANTA CLARA, CALIFORNIA 95054 ● PHONE (408) 748-3585 ● FAX (510) 489-6372

May 26, 2010

Ubiquiti Networks  
91 E. Tasman  
San Jose, CA 95134

Dear Robert Pera,

Enclosed is the EMC Wireless test report for compliance testing of the Ubiquiti Networks, M5L as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Part 15, Subpart B, ICES-003, Issue 4 February 2004 for a Class A Digital Device and FCC Part 15 Subpart C, RSS-210, Issue 7, June 2007 for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,  
MET LABORATORIES, INC.

Jennifer Sanchez  
Documentation Department

Reference: (\Ubiquiti Networks\EMCS82080B-FCC247 Rev. 1)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc.

## **Electromagnetic Compatibility Criteria Test Report**

for the

**Ubiquiti Networks  
M5L**

**Tested under**

the FCC Certification Rules  
contained in  
Title 47 of the CFR, Parts 15 Subpart B & ICES-003  
for Class A Digital Devices  
&  
15.247 Subpart C & RSS-210, Issue 7, June 2007  
for Intentional Radiators

**MET Report: EMCS82080B-FCC247 Rev. 1**

May 26, 2010

**Prepared For:**

**Ubiquiti Networks  
91 E. Tasman  
San Jose, CA 95134**

**Prepared By:  
MET Laboratories, Inc.**  
3162 Belick St.  
□ Santa Clara, CA 95054

## Electromagnetic Compatibility Criteria Test Report

for the

### Ubiquiti Networks M5L

**Tested under**

the FCC Certification Rules  
contained in

Title 47 of the CFR, Parts 15 Subpart B & ICES-003  
for Class A Digital Devices

&

15.247 Subpart C & RSS-210, Issue 7, June 2007  
for Intentional Radiators



Anderson Soungpanya, Project Engineer  
Electromagnetic Compatibility Lab



Jennifer Sanchez  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Parts 15B, 15.247 and Industry Canada standards ICES-003, Issue 4 February 2004, RSS-210, Issue 7, June 2007 under normal use and maintenance.



Shawn McMillen,  
Wireless Manager, Electromagnetic Compatibility Lab

## Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	May 5, 2010	Initial Issue.
1	May 26, 2010	Revised to reflect engineer corrections.

# Table of Contents

<b>I.</b>	<b>Executive Summary</b> .....	<b>1</b>
	A. Purpose of Test .....	2
	B. Executive Summary .....	2
<b>II.</b>	<b>Equipment Configuration</b> .....	<b>3</b>
	A. Overview .....	4
	B. References .....	5
	C. Test Site .....	5
	D. Description of Test Sample .....	5
	E. Equipment Configuration .....	7
	F. Support Equipment .....	7
	G. Ports and Cabling Information .....	7
	H. Mode of Operation .....	8
	I. Method of Monitoring EUT Operation .....	8
	J. Modifications .....	8
	a) Modifications to EUT .....	8
	b) Modifications to Test Standard .....	8
	K. Disposition of EUT .....	8
<b>III.</b>	<b>Electromagnetic Compatibility Criteria for Unintentional Radiators</b> .....	<b>9</b>
	§ 15.107(a) Conducted Emissions Limits .....	10
	§ 15.109(a) Radiated Emissions Limits .....	14
<b>IV.</b>	<b>Electromagnetic Compatibility Criteria for Intentional Radiators</b> .....	<b>21</b>
	§ 15.203 Antenna Requirement .....	22
	§ 15.207(a) Conducted Emissions Limits .....	23
	§ 15.247(a) 6 dB and 99% Bandwidth .....	27
	§ 15.247(b) Peak Power Output and RF Exposure .....	41
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge .....	51
	RSS-GEN Receiver Spurious Emissions .....	60
	§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge .....	63
	§ 15.247(e) Peak Power Spectral Density .....	80
<b>V.</b>	<b>Test Equipment</b> .....	<b>92</b>
<b>VI.</b>	<b>Certification &amp; User's Manual Information</b> .....	<b>94</b>
	A. Certification Information .....	95
	B. Label and User's Manual Information .....	99
<b>VII.</b>	<b>ICES-003 Procedural &amp; Labeling Requirements</b> .....	<b>101</b>

## List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing .....	2
Table 2. EUT Summary Table .....	4
Table 3. References .....	5
Table 4. Equipment Configuration .....	7
Table 5. Support Equipment .....	7
Table 6. Ports and Cabling Information .....	7
Table 7. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b) and 15.207(a) .....	10
Table 8. Conducted Emissions - Voltage, AC Power, Phase Line (120V/60Hz) .....	11
Table 9. Conducted Emissions - Voltage, AC Power, Neutral Line (120V/60Hz) .....	12
Table 10. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b) .....	14
Table 11. Radiated Emissions Limits, Test Results, 30MHz – 1GHz FCC Limits .....	15
Table 12. Radiated Emissions Limits, Test Results, above 1GHz FCC Limits .....	16
Table 13. Radiated Emissions Limits, Test Results, ICES-003 Limits .....	17
Table 14. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a) .....	23
Table 15. Conducted Emissions, 15.207, Phase Line, Test Results .....	24
Table 16. Conducted Emissions, 15.207, Neutral Line, Test Results .....	25
Table 17. Occupied Bandwidth Test Results – 802.11n 20MHz Mode (Port 1) .....	28
Table 18. Occupied Bandwidth Test Results – 802.11n 40MHz Mode (Port 1) .....	28
Table 19. Occupied Bandwidth Test Results – 802.11n 20MHz Mode (Port 2) .....	28
Table 20. Occupied Bandwidth Test Results – 802.11n 40MHz Mode (Port 2) .....	28
Table 21. Output Power Requirements from §15.247 .....	41
Table 22. RF Output Power Test Results – 802.11n 20MHz Mode (Port 1) .....	42
Table 23. RF Output Power Test Results – 802.11n 40MHz Mode (Port 1) .....	42
Table 24. RF Output Power Test Results – 802.11n 20MHz Mode (Port 2) .....	42
Table 25. RF Output Power Test Results – 802.11n 40MHz Mode (Port 2) .....	42
Table 26. RF Output Power Results – All Ports, 802.11n mode (20MHz) .....	43
Table 27. RF Output Power Results – All Ports, 802.11n mode (40MHz) .....	43
Table 28. Restricted Bands of Operation .....	51
Table 29. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a) .....	52
Table 30. Radiated Harmonic Emissions – 802.11n 20MHz Mode .....	53
Table 31. Radiated Harmonic Emissions – 802.11n 40MHz Mode .....	54
Table 32. Spurious Emission Limits for Receivers .....	60
Table 33. Spectral Density Test Results, 802.11n 20MHz Mode (Port 1) .....	81
Table 34. Spectral Density Test Results, 802.11n 40MHz Mode (Port 1) .....	81
Table 35. Spectral Density Test Results, 802.11n 20MHz Mode (Port 2) .....	81
Table 36. Spectral Density Test Results, 802.11n 40MHz Mode (Port 2) .....	81
Table 37. Peak Power Spectral Density Test Results, HT20, MIMO Mode .....	82
Table 38. Peak Power Spectral Density Test Results, HT40, MIMO Mode .....	82
Table 39. Test Equipment List .....	93

## List of Plots

Plot 1. Conducted Emission, Phase Line Plot .....	11
Plot 2. Conducted Emission, Neutral Line Plot .....	12
Plot 3. Radiated Emissions, 30MHz – 1GHz, FCC Limits .....	15
Plot 4. Radiated Emissions, above 1GHz, FCC Limits .....	16
Plot 5. Radiated Emissions, Pre-Scan, ICES-003 Limits .....	17
Plot 6. Conducted Emissions, Phase Line .....	24
Plot 7. Conducted Emissions, Neutral Line .....	25
Plot 8. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 1 (99%) .....	29
Plot 9. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 1 (100kHz RBW) .....	29
Plot 10. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 1 (99%) .....	30
Plot 11. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 1 (100kHz RBW) .....	30

Plot 12. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 1 (99%)	31
Plot 13. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 1 (100kHz RBW)	31
Plot 14. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 1 (99%)	32
Plot 15. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 1 (100kHz RBW)	32
Plot 16. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 1 (99%)	33
Plot 17. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 1 (100kHz RBW)	33
Plot 18. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 1 (99%)	34
Plot 19. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 1 (100kHz RBW)	34
Plot 20. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 2 (99%)	35
Plot 21. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 2 (100kHz)	35
Plot 22. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 2 (99%)	36
Plot 23. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 2 (100kHz)	36
Plot 24. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 2 (99%)	37
Plot 25. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 2 (100kHz)	37
Plot 26. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 2 (99%)	38
Plot 27. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 2 (100kHz)	38
Plot 28. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 2 (99%)	39
Plot 29. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 2 (100kHz)	39
Plot 30. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 2 (99%)	40
Plot 31. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 2 (100kHz)	40
Plot 32. Peak Output Power 5745MHz Low Channel 802.11n 20MHz Port 1	44
Plot 33. Peak Output Power 5785MHz Mid Channel 802.11n 20MHz Port 1	44
Plot 34. Peak Output Power 5825MHz High Channel 802.11n 20MHz Port 1	45
Plot 35. Peak Output Power 5745MHz Low Channel 802.11n 40MHz Port 1	45
Plot 36. Peak Output Power 5785MHz Mid Channel 802.11n 40MHz Port 1	46
Plot 37. Peak Output Power 5825MHz High Channel 802.11n 40MHz Port 1	46
Plot 38. Peak Output Power 5745MHz Low Channel 802.11n 20MHz Port 2	47
Plot 39. Peak Output Power 5785MHz Mid Channel 802.11n 20MHz Port 2	47
Plot 40. Peak Output Power 5825MHz High Channel 802.11n 20MHz Port 2	48
Plot 41. Peak Output Power 5745MHz Low Channel 802.11n 40MHz Port 2	48
Plot 42. Peak Output Power 5785MHz Mid Channel 802.11n 40MHz Port 2	49
Plot 43. Peak Output Power 5825MHz High Channel 802.11n 40MHz Port 2	49
Plot 44. Radiated Spurious Emissions, 802.11n 20MHz Mode Low Channel	55
Plot 45. Radiated Spurious Emissions, 802.11n 20MHz Mode Mid Channel	55
Plot 46. Radiated Spurious Emissions, 802.11n 20MHz Mode High Channel	56
Plot 47. Radiated Spurious Emissions, 802.11n 40MHz Mode Low Channel	56
Plot 48. Radiated Spurious Emissions, 802.11n 40MHz Mode Mid Channel	57
Plot 49. Radiated Spurious Emissions, 802.11n 40MHz Mode High Channel	57
Plot 50. Conducted Receiver Spurious Emission, 30MHz – 1GHz, Port 1	61
Plot 51. Conducted Receiver Spurious Emission, 1 GHz – 20 GHz, Port 1	61
Plot 52. Conducted Receiver Spurious Emission, 30MHz – 1GHz, Port 2	62
Plot 53. Conducted Receiver Spurious Emission, 1 GHz – 20 GHz, Port 2	62
Plot 54. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 1 (30MHz-1GHz)	64
Plot 55. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 1 (1-18GHz)	64
Plot 56. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 1 (18-40GHz)	64
Plot 57. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 1 (30MHz-1GHz)	65
Plot 58. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 1 (1-18GHz)	65
Plot 59. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 1 (18-40GHz)	65
Plot 60. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 1 (30MHz-1GHz)	66
Plot 61. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 1 (1-18GHz)	66
Plot 62. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 1 (18-40GHz)	66
Plot 63. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 1 (30MHz-1GHz)	67
Plot 64. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 1 (1-18GHz)	67
Plot 65. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 1 (18-40GHz)	67
Plot 66. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 1 (30MHz-1GHz)	68
Plot 67. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 1 (1-18GHz)	68
Plot 68. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 1 (18-40GHz)	68

Plot 69. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 1 (30MHz-1GHz)	69
Plot 70. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 1 (1-18GHz)	69
Plot 71. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 1 (18-40GHz)	69
Plot 72. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 2 (30MHz-1GHz)	70
Plot 73. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 2 (1-18GHz)	70
Plot 74. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 2 (18-40GHz)	70
Plot 75. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 2 (30MHz-1GHz)	71
Plot 76. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 2 (1-18GHz)	71
Plot 77. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 2 (18-40GHz)	71
Plot 78. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 2 (30MHz-1GHz)	72
Plot 79. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 2 (1-18GHz)	72
Plot 80. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 2 (18-40GHz)	72
Plot 81. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 2 (30MHz-1GHz)	73
Plot 82. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 2 (1-18GHz)	73
Plot 83. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 2 (18-40GHz)	73
Plot 84. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 2 (30MHz-1GHz)	74
Plot 85. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 2 (1-18GHz)	74
Plot 86. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 2 (18-40GHz)	74
Plot 87. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 2 (30MHz-1GHz)	75
Plot 88. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 2 (1-18GHz)	75
Plot 89. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 2 (18-40GHz)	75
Plot 90. Conducted Band Edge 5745MHz Low Channel 802.11n 20MHz Port 1	76
Plot 91. Conducted Band Edge 5825MHz High Channel 802.11n 20MHz Port 1	76
Plot 92. Conducted Band Edge 5745MHz Low Channel 802.11n 40MHz Port 1	77
Plot 93. Conducted Band Edge 5825MHz High Channel 802.11n 40MHz Port 1	77
Plot 94. Conducted Band Edge 5745MHz Low Channel 802.11n 20MHz Port 2	78
Plot 95. Conducted Band Edge 5825MHz High Channel 802.11n 20MHz Port 2	78
Plot 96. Conducted Band Edge 5745MHz Low Channel 802.11n 40MHz Port 2	79
Plot 97. Conducted Band Edge 5825MHz High Channel 802.11n 40MHz Port 2	79
Plot 98. Power Spectral Density 5745MHz Low Channel 802.11n 20MHz Port 1	83
Plot 99. Power Spectral Density 5785MHz Mid Channel 802.11n 20MHz Port 1	83
Plot 100. Power Spectral Density 5825MHz High Channel 802.11n 20MHz Port 1	84
Plot 101. Power Spectral Density 5745MHz Low Channel 802.11n 40MHz Port 1	84
Plot 102. Power Spectral Density 5785MHz Mid Channel 802.11n 40MHz Port 1	85
Plot 103. Power Spectral Density 5825MHz High Channel 802.11n 40MHz Port 1	85
Plot 104. Power Spectral Density 5745MHz Low Channel 802.11n 20MHz Port 2	86
Plot 105. Power Spectral Density 5785MHz Mid Channel 802.11n 20MHz Port 2	86
Plot 106. Power Spectral Density 5825MHz High Channel 802.11n 20MHz Port 2	87
Plot 107. Power Spectral Density 5745MHz Low Channel 802.11n 40MHz Port 2	87
Plot 108. Power Spectral Density 5785MHz Mid Channel 802.11n 40MHz Port 2	88
Plot 109. Power Spectral Density 5825MHz High Channel 802.11n 40MHz Port 2	88
Plot 110. Power Spectral Density 5745MHz Low Channel 802.11n 20MHz Combined	89
Plot 111. Power Spectral Density 5785MHz Mid Channel 802.11n 20MHz Combined	89
Plot 112. Power Spectral Density 5825MHz High Channel 802.11n 20MHz Combined	90
Plot 113. Power Spectral Density 5745MHz Low Channel 802.11n 40MHz Combined	90
Plot 114. Power Spectral Density 5785MHz Mid Channel 802.11n 40MHz Combined	91
Plot 115. Power Spectral Density 5825MHz High Channel 802.11n 40MHz Combined	91



## List of Figures

Figure 1. Block Diagram of Test Configuration.....	6
Figure 2. Block Diagram, Occupied Bandwidth Test Setup.....	27
Figure 3. Block Diagram, Peak Power Output Test Setup.....	41
Figure 4. Block Diagram, Conducted Receiver Spurious Test Setup.....	60
Figure 5. Block Diagram, Conducted Spurious Emissions Test Setup.....	63
Figure 6. Block Diagram, Peak Power Spectral Density Test Setup.....	80

## List of Photographs

Photograph 1. Conducted Emissions, Test Setup.....	13
Photograph 2. Radiated Emission, 30MHz – 1GHz Test Setup.....	18
Photograph 3. Radiated Emission, 30MHz – 1GHz Test Setup (Back View).....	19
Photograph 4. Radiated Emission, above 1GHz Test Setup.....	20
Photograph 5. Conducted Emissions, 15.207, Test Setup.....	26
Photograph 6. Radiated Spurious Emission, Test Setup, 3m Distance.....	58
Photograph 7. Radiated Spurious Emission, Test Setup, 1m Distance.....	59

## List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dB $\mu$ A	Decibels above one <b>microamp</b>
dB $\mu$ V	Decibels above one <b>microvolt</b>
dB $\mu$ A/m	Decibels above one <b>microamp per meter</b>
dB $\mu$ V/m	Decibels above one <b>microvolt per meter</b>
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kilohertz
kPa	kilopascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
$\mu$ H	microhenry
$\mu$	microfarad
$\mu$ s	microseconds
NEBS	Network Equipment-Building System
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

# I. Executive Summary

## A. Purpose of Test

An EMC evaluation was performed to determine compliance of the Ubiquiti Networks M5L, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the M5L. Ubiquiti Networks should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the M5L, has been **permanently** discontinued

## B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Ubiquiti Networks, purchase order number US090040. All tests were conducted using measurement procedure ANSI C63.4-2003.

FCC Reference	IC Reference	Description	Compliance
47 CFR Part 15.247:2005	RSS-210 Issue 7: 2007		
47 CFR Part 15.107 (a)	RSS-210 Issue 7: 2007	Conducted Emission Limits for a Class A Digital Device	Compliant
47 CFR Part 15.109 (a)	RSS-210 Issue 7: 2007	Radiated Emission Limits for a Class A Digital Device	Compliant
Title 47 of the CFR, Part 15 §15.203	N/A	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	RSS-210(7.2.2)	Conducted Emission Voltage	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(1)	RSS-210(A8.1)	Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	RSS-210(A8.4)	RF Output Power	Compliant
Title 47 of the CFR, Part 15 §15.209, §15.247(d)	RSS-210(A8.5)	Radiated Spurious Emissions	Compliant
Title 47 of the CFR, Part 15 §15.205	RSS-210(A8.5)	Emissions at Restricted Band	Compliant
Title 47 of the CFR, Part 15 §15.209, §15.247(d)	RSS-210(A8.5)	Conducted Spurious Emissions	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	RSS-210(A8.3)	Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	RSS-Gen(5.5)	Maximum Permissible Exposure	Compliant
N/A	RSS-Gen(4.8)	Receiver Spurious Emissions	Compliant

**Table 1. Executive Summary of EMC Part 15.247 Compliance Testing**

## II. Equipment Configuration

## A. Overview

MET Laboratories, Inc. was contracted by Ubiquiti Networks to perform testing on the M5L, under Ubiquiti Networks's purchase order number US090040.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Ubiquiti Networks, M5L.

The results obtained relate only to the item(s) tested.

<b>Model(s) Tested:</b>	M5L	
<b>Model(s) Covered:</b>	M5L	
<b>EUT Specifications:</b>	Primary Power: 15VDC POE	
	FCC ID: SWX-M5L IC: 6545A-M5L	
	Type of Modulations:	OFDM
	Equipment Code:	DTS
	Peak RF Output Power:	20.68 dBm
	EUT Frequency Ranges:	5745-5825MHz
<b>Analysis:</b>	The results obtained relate only to the item(s) tested.	
<b>Environmental Test Conditions:</b>	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
<b>Evaluated by:</b>	Anderson Soungpanya	
<b>Report Date(s):</b>	May 26, 2010	

**Table 2. EUT Summary Table**

## B. References

<b>CFR 47, Part 15, Subpart C</b>	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
<b>RSS-210, Issue 7, June 2007</b>	Low-power Licence-exempt Radiocommunications Devices (All Frequency Bands): Category I Equipment
<b>CFR 47, Part 15, Subpart B</b>	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
<b>ICES-003, Issue 4 February 2004</b>	Electromagnetic Compatibility: Criteria for Radio Frequency Devices
<b>ANSI C63.4:2003</b>	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
<b>ANSI C63.10-2009</b>	American National Standard for Testing Unlicensed Wireless Devices
<b>ANSI/NCSL Z540-1-1994</b>	Calibration Laboratories and Measuring and Test Equipment - General Requirements
<b>ANSI/ISO/IEC 17025:2000</b>	General Requirements for the Competence of Testing and Calibration Laboratories

**Table 3. References**

## C. Test Site

All testing was performed at MET Laboratories, Inc., 3162 Belick St., Santa Clara, CA 95054. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

## D. Description of Test Sample

The Ubiquiti Networks M5L, Equipment Under Test (EUT), is a 802.11n MIMO Radio.




Figure 1. Block Diagram of Test Configuration



## E. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Name / Description	Model Number	Part Number	Serial Number
A	M5L	M5L	M5L	00156DECFA08
B	POE	UB1-POE-15-8	NA	0908-0012288

Table 4. Equipment Configuration

## F. Support Equipment

Support equipment necessary for the operation and testing of the EUT is included in the following list.

Ref. ID	Name / Description	Manufacturer	Model Number
C	Laptop	Dell	Vostro 1510

Table 5. Support Equipment

## G. Ports and Cabling Information

Ref. ID	Port name on EUT	Cable Description or reason for no cable	Qty.	Length (m)	Shielded (Y/N)	Termination Box ID & Port Name
1	A, RJ45	CAT5	1	1	Y	B
2	B, LAN	CAT5	1	.1	Y	C
3	C, DC Input	Power Cord	1	.5	N	100-240V AC power

Table 6. Ports and Cabling Information

## **H. Mode of Operation**

The EUT operates in OFDM mode.

## **I. Method of Monitoring EUT Operation**

A Spectrum Analyzer and a Power Meter was use to monitor the EUT's transmitter channel and power output.

## **J. Modifications**

- a) **Modifications to EUT**  
No modifications were made to the EUT.
- b) **Modifications to Test Standard**  
No modifications were made to the test standard.

## **K. Disposition of EUT**

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Ubiquiti Networks upon completion of testing.

## **III. Electromagnetic Compatibility Criteria for Unintentional Radiators**

## Electromagnetic Compatibility Criteria

### § 15.107 Conducted Emissions Limits

**Test Requirement(s):** **15.107 (a)** Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 7. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

**15.107 (b)** For a Class A digital device that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in Table 7. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals. The lower limit applies at the band edges.

**15.207(a)**, Except as shown in paragraphs (b) and (c) of this section\*, charging, AC adapters or battery eliminators the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the Table 7, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency range (MHz)	Class A Conducted Limits (dB $\mu$ V)		*Class B Conducted Limits (dB $\mu$ V)	
	Quasi-Peak	Average	Quasi-Peak	Average
* 0.15- 0.45	79	66	66 - 56	56 - 46
0.45 - 0.5	79	66	56	46
0.5 - 30	73	60	60	50

Note 1 — The lower limit shall apply at the transition frequencies.  
 Note 2 — The limit decreases linearly with the logarithm if the frequency in the range 0.15 MHz to 0.5 MHz.  
 \* -- Limits per Subsection 15.207(a).

**Table 7. Conducted Limits for Radio Frequency Devices calculated from FCC Part 15 Subsections 15.107(a) (b) and 15.207(a)**

**Test Results:** The EUT was Compliant with the Class A requirement(s) of this section.


**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 01/13/10

**Conducted Emissions - Voltage, AC Power, Phase Line (120V/60Hz)**

Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
.181	42.05	79	-36.95	Pass	27.92	66	-38.08	Pass
.447	43.25	79	-35.75	Pass	35.31	66	-30.69	Pass
3.92	37.01	73	-35.99	Pass	15.23	60	-44.77	Pass

Table 8. Conducted Emissions - Voltage, AC Power, Phase Line (120V/60Hz)




Plot 1. Conducted Emission, Phase Line Plot

**Conducted Emissions - Voltage, AC Power, Neutral Line (120V/60Hz)**

Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
.150	39.91	79	-39.09	Pass	21.37	66	-44.63	Pass
.450	51.17	79	-27.83	Pass	46.33	66	-19.67	Pass
1.27	38.27	73	-34.73	Pass	30.25	60	-29.75	Pass

Table 9. Conducted Emissions - Voltage, AC Power, Neutral Line (120V/60Hz)



Plot 2. Conducted Emission, Neutral Line Plot

## Conducted Emission Limits Test Setup



Photograph 1. Conducted Emissions, Test Setup

## Radiated Emission Limits

### § 15.109 Radiated Emissions Limits

**Test Requirement(s):** **15.109 (a)** Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the Class B limits expressed in Table 10.

**15.109 (b)** The field strength of radiated emissions from a Class A digital device, as determined at a distance of 10 meters, shall not exceed the Class A limits expressed in Table 10.

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	
	§15.109 (b), Class A Limit (dB $\mu$ V) @ 10m	§15.109 (a), Class B Limit (dB $\mu$ V) @ 3m
30 - 88	39.00	40.00
88 - 216	43.50	43.50
216 - 960	46.40	46.00
Above 960	49.50	54.00

**Table 10. Radiated Emissions Limits calculated from FCC Part 15, §15.109 (a) (b)**

**Test Procedures:** The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. The method of testing and test conditions of ANSI C63.4 were used. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. Unless otherwise specified, measurements were made using a quasi-peak detector with a 120 kHz bandwidth.

**Test Results:** The EUT was Compliant with the Class A requirement(s) of this section.

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 01/13/10




### Radiated Emissions Limits Test Results, Class A

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBμV)	ACF (dB/m)	Pre Amp Gain (dB)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBμV)	Limit (dBμV)	Margin (dB)
101.89	V	184	100	32.29	12.7	0	2.87	-10.46	37.4	43.5	-6.1
112.85	V	166	100	22.95	13.185	0	2.986	-10.46	28.661	43.5	-14.839
139.27	V	260	100	15.85	12.458	0	3.266	-10.46	21.114	43.5	-22.386
45.24	V	342	100	28.08	9.404	0	1.684	-10.46	28.708	39	-10.292
55.99	V	360	100	29.75	7.199	0	1.937	-10.46	28.426	39	-10.574
800.02	H	215	100	20.17	20.9	0	6.23	-10.46	36.84	46.4	-9.56

**Table 11. Radiated Emissions Limits, Test Results, 30MHz – 1GHz FCC Limits**

Note 1: The EUT was tested at 3 m.




**Plot 3. Radiated Emissions, 30MHz – 1GHz, FCC Limits**

### Radiated Emissions Limits Test Results, Class A

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBμV)	ACF (dB/m)	Pre Amp Gain (dB)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBμV)	Limit (dBμV)	Margin (dB)
1600	H	202	100	93.37	28.832	75.758	9.31	-10.46	45.294	49.5	-4.206
1600	V	182	100	90.15	28.832	75.758	9.31	-10.46	42.074	49.5	-7.426

**Table 12. Radiated Emissions Limits, Test Results, above 1GHz FCC Limits**

Note 1: The EUT was tested at 3 m.




**Plot 4. Radiated Emissions, above 1GHz, FCC Limits**

### Radiated Emissions Limits Test Results, Class A

Frequency (MHz)	Antenna Polarity	EUT Azimuth (Degrees)	Antenna Height (cm)	Uncorrected Amplitude (dBμV)	ACF (dB/m)	Pre Amp Gain (dB)	CBL (dB)	DCF (dB)	Corrected Amplitude (dBμV)	Limit (dBμV)	Margin (dB)
101.89	V	184	100	32.29	12.7	0	2.87	-10.46	37.4	40	-2.6
112.85	V	166	100	22.95	13.185	0	2.986	-10.46	28.661	40	-11.339
139.27	V	260	100	15.85	12.458	0	3.266	-10.46	21.114	40	-18.886
45.24	V	342	100	28.08	9.404	0	1.684	-10.46	28.708	40	-11.292
55.99	V	360	100	29.75	7.199	0	1.937	-10.46	28.426	40	-11.574
800.02	H	215	100	20.17	20.9	0	6.23	-10.46	36.84	47	-10.16


**Table 13. Radiated Emissions Limits, Test Results, ICES-003 Limits**

Note 1: The EUT was tested at 3 m.



**Plot 5. Radiated Emissions, Pre-Scan, ICES-003 Limits**

## Radiated Emission Limits Test Setup



**Photograph 2. Radiated Emission, 30MHz – 1GHz Test Setup**

## Radiated Emission Limits Test Setup



**Photograph 3. Radiated Emission, 30MHz – 1GHz Test Setup (Back View)**

## Radiated Emission Limits Test Setup



**Photograph 4. Radiated Emission, above 1GHz Test Setup**

## **IV. Electromagnetic Compatibility Criteria for Intentional Radiators**

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.203 Antenna Requirement

**Test Requirement:** § 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

**Results:** The EUT as tested is Compliant the criteria of §15.203 by meeting criteria C .

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 01/05/10

Gain	Type	Manufacturer
13dBi	Integral	Ubiquiti Networks



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.207 Conducted Emissions Limits

**Test Requirement(s):** § 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50  $\Omega$  line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
* 0.15- 0.45	66 - 56	56 - 46
0.45 - 0.5	56	46
0.5 - 30	60	50

**Table 14. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)**

**Test Procedure:** The EUT was placed on a 0.8 m-high wooden table inside a screen room. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50  $\Omega$ /50  $\mu$ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with *ANSI C63.4-2003 "Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz"*. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50  $\Omega$ /50  $\mu$ H LISN as the input transducer to an EMC/field intensity meter. For the purpose of this testing, the transmitter was turned on. Scans were performed with the transmitter on.

**Test Results:** The EUT was compliant with this requirement.


**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 01/13/10

### 15.207 Conducted Emissions - Voltage, AC Power, Phase Line (120V/60Hz)

Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
3.93	38.67	56	-17.33	Pass	20.87	46	-25.13	Pass
.179	47.78	64.536	-16.756	Pass	29.85	54.536	-24.686	Pass
.483	40.97	56.296	-15.326	Pass	29.24	46.295	-17.055	Pass

Table 15. Conducted Emissions, 15.207, Phase Line, Test Results




Plot 6. Conducted Emissions, Phase Line

### 15.207 Conducted Emissions - Voltage, AC Power, Neutral Line (120V/60Hz)

Freq (MHz)	QP Amplitude	QP Limit	Delta	Pass	Average Amplitude	Average Limit	Delta	Pass
.430	50.43	57.277	-6.847	Pass	37.48	47.277	-9.797	Pass
.156	43.89	65.675	-21.785	Pass	32.44	55.675	-23.235	Pass
2.87	38.14	56	-17.86	Pass	28.63	46	-17.37	Pass

Table 16. Conducted Emissions, 15.207, Neutral Line, Test Results



Plot 7. Conducted Emissions, Neutral Line

## 15.207 Conducted Emissions Test Setup Photograph



**Photograph 5. Conducted Emissions, 15.207, Test Setup**

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(a) 6 dB and 99% Bandwidth

**Test Requirements:** § 15.247(a): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.


**Test Procedure:** The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately 1% of the total emission bandwidth, VBW > RBW. The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels.

**Test Results** The EUT was Compliant with § 15.247 (a).

The 6 dB and 99% Bandwidth was determined from the plots on the following pages.

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 12/23/09



**Figure 2. Block Diagram, Occupied Bandwidth Test Setup**

## Occupied Bandwidth Test Results

Occupied Bandwidth			
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Measured 99% Bandwidth (MHz)
Low	5745	17.61	17.76
Mid	5785	17.33	17.95
High	5825	17.33	17.74

Table 17. Occupied Bandwidth Test Results – 802.11n 20MHz Mode (Port 1)

Occupied Bandwidth			
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Measured 99% Bandwidth (MHz)
Low	5745	36.19	37.03
Mid	5785	36.48	37.03
High	5825	36.25	36.83

Table 18. Occupied Bandwidth Test Results – 802.11n 40MHz Mode (Port 1)


Occupied Bandwidth			
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Measured 99% Bandwidth (MHz)
Low	5745	17.29	17.88
Mid	5785	17.70	17.85
High	5825	17.70	17.85

Table 19. Occupied Bandwidth Test Results – 802.11n 20MHz Mode (Port 2)


Occupied Bandwidth			
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Measured 99% Bandwidth (MHz)
Low	5745	35.91	36.79
Mid	5785	35.60	36.51
High	5825	36.33	36.62

Table 20. Occupied Bandwidth Test Results – 802.11n 40MHz Mode (Port 2)

## Occupied Bandwidth Test Results – 802.11n 20MHz (Port 1)




Plot 8. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 1 (99%)




Plot 9. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 1 (100kHz RBW)

## Occupied Bandwidth Test Results – 802.11n 20MHz (Port 1)




Plot 10. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 1 (99%)




Plot 11. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 1 (100kHz RBW)



### Occupied Bandwidth Test Results – 802.11n 20MHz (Port 1)




Plot 12. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 1 (99%)




Plot 13. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 1 (100kHz RBW)

### Occupied Bandwidth Test Results – 802.11n 40MHz (Port 1)




Plot 14. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 1 (99%)




Plot 15. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 1 (100kHz RBW)

## Occupied Bandwidth Test Results – 802.11n 40MHz (Port 1)




Plot 16. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 1 (99%)




Plot 17. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 1 (100kHz RBW)

## Occupied Bandwidth Test Results – 802.11n 40MHz (Port 1)




Plot 18. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 1 (99%)




Plot 19. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 1 (100kHz RBW)

### Occupied Bandwidth Test Results – 802.11n 20MHz (Port 2)




Plot 20. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 2 (99%)




Plot 21. Occupied Bandwidth 5745MHz Low Channel 802.11n 20MHz Port 2 (100kHz)

### Occupied Bandwidth Test Results – 802.11n 20MHz (Port 2)




Plot 22. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 2 (99%)




Plot 23. Occupied Bandwidth 5785MHz Mid Channel 802.11n 20MHz Port 2 (100kHz)

## Occupied Bandwidth Test Results – 802.11n 20MHz (Port 2)




Plot 24. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 2 (99%)




Plot 25. Occupied Bandwidth 5825MHz High Channel 802.11n 20MHz Port 2 (100kHz)

## Occupied Bandwidth Test Results – 802.11n 40MHz (Port 2)




Plot 26. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 2 (99%)




Plot 27. Occupied Bandwidth 5745MHz Low Channel 802.11n 40MHz Port 2 (100kHz)



### Occupied Bandwidth Test Results – 802.11n 40MHz (Port 2)




Plot 28. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 2 (99%)




Plot 29. Occupied Bandwidth 5785MHz Mid Channel 802.11n 40MHz Port 2 (100kHz)

### Occupied Bandwidth Test Results – 802.11n 40MHz (Port 2)



Plot 30. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 2 (99%)



Plot 31. Occupied Bandwidth 5825MHz High Channel 802.11n 40MHz Port 2 (100kHz)

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(b) Peak Power Output and RF Exposure

**Test Requirements:** §15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
902-928	1.000
2400-2483.5	1.000
5725- 5850	1.000

**Table 21. Output Power Requirements from §15.247**

§15.247(c): if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in the Table 21, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.


Fixed, point-to-point operation excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

**Test Procedure:** The transmitter was connected to a calibrated spectrum analyzer. The EUT was measured at the low, mid and high channels of each band at the maximum power level.

**Test Results:** The EUT was Compliant with the Peak Power Output limits of §15.247(b).

**Test Engineer(s):** Anderson Sounpanya

**Test Date(s):** 01/20/10



**Figure 3. Block Diagram, Peak Power Output Test Setup**

## RF Output Power Test Results

Peak Conducted Output Power			
Carrier Channel	Frequency (MHz)	Measured Peak Output Power (dBm)	Measured Peak Output Power (Watts)
Low	5745	16.19	0.041
Mid	5785	15.28	0.033
High	5825	15.43	0.034

Table 22. RF Output Power Test Results – 802.11n 20MHz Mode (Port 1)

Peak Conducted Output Power			
Carrier Channel	Frequency (MHz)	Measured Peak Output Power (dBm)	Measured Peak Output Power (Watts)
Low	5745	16.91	0.049
Mid	5785	15.95	0.039
High	5825	15.63	0.036

Table 23. RF Output Power Test Results – 802.11n 40MHz Mode (Port 1)

Peak Conducted Output Power			
Carrier Channel	Frequency (MHz)	Measured Peak Output Power (dBm)	Measured Peak Output Power (Watts)
Low	5745	18.03	0.063
Mid	5785	18.32	0.067
High	5825	17.87	0.061

Table 24. RF Output Power Test Results – 802.11n 20MHz Mode (Port 2)

Peak Conducted Output Power			
Carrier Channel	Frequency (MHz)	Measured Peak Output Power (dBm)	Measured Peak Output Power (Watts)
Low	5745	18.38	0.068
Mid	5785	18.54	0.071
High	5825	18.13	0.065

Table 25. RF Output Power Test Results – 802.11n 40MHz Mode (Port 2)

## RF Output Power Test Results

802.11n mode					
Carrier Channel	Frequency (MHz)	Port 1 (dBm)	Port 2 (dBm)	Total (dBm)	Total (W)
Low	5745	16.19	18.03	20.21	0.105
Mid	5785	15.28	18.32	20.04	0.101
High	5825	15.43	17.87	19.82	0.096


**Table 26. RF Output Power Results – All Ports, 802.11n mode (20MHz)**

802.11n mode					
Carrier Channel	Frequency (MHz)	Port 1 (dBm)	Port 2 (dBm)	Total (dBm)	Total (W)
Low	5745	16.91	18.38	20.68	0.117
Mid	5785	15.95	18.54	20.41	0.110
High	5825	15.63	18.13	20.04	0.101


**Table 27. RF Output Power Results – All Ports, 802.11n mode (40MHz)**

**Note:** Total Output Power = Port 1 ( $10^{(\text{Output Power}/10)/1000}$ ) + Port 2 ( $10^{(\text{Output Power}/10)/1000}$ )

## RF Output Power Test Results




**Plot 32. Peak Output Power 5745MHz Low Channel 802.11n 20MHz Port 1**




**Plot 33. Peak Output Power 5785MHz Mid Channel 802.11n 20MHz Port 1**

## RF Output Power Test Results




Plot 34. Peak Output Power 5825MHz High Channel 802.11n 20MHz Port 1




Plot 35. Peak Output Power 5745MHz Low Channel 802.11n 40MHz Port 1

## RF Output Power Test Results



Plot 36. Peak Output Power 5785MHz Mid Channel 802.11n 40MHz Port 1




Plot 37. Peak Output Power 5825MHz High Channel 802.11n 40MHz Port 1



## RF Output Power Test Results



Plot 38. Peak Output Power 5745MHz Low Channel 802.11n 20MHz Port 2




Plot 39. Peak Output Power 5785MHz Mid Channel 802.11n 20MHz Port 2

## RF Output Power Test Results




Plot 40. Peak Output Power 5825MHz High Channel 802.11n 20MHz Port 2




Plot 41. Peak Output Power 5745MHz Low Channel 802.11n 40MHz Port 2

## RF Output Power Test Results



**Plot 42. Peak Output Power 5785MHz Mid Channel 802.11n 40MHz Port 2**



**Plot 43. Peak Output Power 5825MHz High Channel 802.11n 40MHz Port 2**

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(b) RF Exposure

**RF Exposure Requirements:** §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

**RF Radiation Exposure Limit:** §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit Calculation: EUT's operating frequencies @ 5745-5825 MHz; highest conducted power = 20.68dBm (peak) therefore, **Limit for Uncontrolled exposure: 1 mW/cm<sup>2</sup> or 10 W/m<sup>2</sup>**

EUT maximum antenna gain = **13dBi Integral**

Equation from page 18 of OET 65, Edition 97-01

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{PG / 4\pi S}$$

where, S = Power Density (1 mW/cm<sup>2</sup>)  
P = Power Input to antenna (116.95mW)  
G = Antenna Gain (19.95numeric)

$$S = (116.95 * 19.95 / 4 * 3.14 * 20.0^2) = (2333.458 / 5024) = \mathbf{0.464 \text{ mW/cm}^2 @ 20\text{cm separation}}$$

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Radiated Spurious Emissions Requirements and Band Edge

**Test Requirements:** §15.247(d); §15.205: Emissions outside the frequency band.

**§15.247(d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

**§15.205(a):** Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
<sup>1</sup> 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	( <sup>2</sup> )

**Table 28. Restricted Bands of Operation**

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

<sup>2</sup> Above 38.6

**Test Requirement(s):** § 15.209 (a): Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 29.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dBµV) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

**Table 29. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)**

**Test Procedures:** The transmitter was turned. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line. Only noise floor was measured above 18 GHz.

**Test Results:** The EUT was Compliant with the Radiated Spurious Emission limits of § 15.247(d).

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 01/11/10

### Harmonic Emissions Requirements – Radiated

Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 1 m	P. Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	Distance Correction Factor 1m to 3m (dBμV/m)	EUT Field Strength Final Amp. (dBμV/m)	Limit Detector (Peak) / (Avg.)	Limit @ 3 m (dBμV/m)	Delta (dB)
11.49	V	45.06	34.86	38.14	7.72	-9.54	46.52	Peak	74	-27.48
11.49	V	31.33	34.86	38.14	7.72	-9.54	32.79	Avg.	54	-21.21
17.235	V	44.03	34.01	40.88	10.17	-9.54	51.54	Peak	74	-22.46
17.235	V	31.39	34.01	40.88	10.17	-9.54	38.90	Avg.	54	-15.10
<b>Low Channel 5745MHz</b>										
Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 1 m	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	Distance Correction Factor 1m to 3m (dBμV/m)	EUT Field Strength Final Amp. (dBμV/m)	Limit Detector (Peak) / (Avg)	Limit @ 3 m (dBμV/m)	Delta (dB)
11.57	V	42.19	34.91	38.23	7.63	-9.54	43.60	Peak	74	-30.40
11.57	V	30.14	34.91	38.23	7.63	-9.54	31.55	Avg	54	-22.45
17.355	V	43.83	33.93	41.03	10.33	-9.54	51.72	Peak	74	-22.28
17.355	V	31.34	33.93	41.03	10.33	-9.54	39.23	Avg	54	-14.77
<b>Mid Channel 5785MHz</b>										
Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 1 m	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	Distance Correction Factor 1m to 3m (dBμV/m)	EUT Field Strength Final Amp. (dBμV/m)	Limit Detector (Peak) / (Avg)	Limit @ 3 m (dBμV/m)	Delta (dB)
11.65	V	44.78	34.96	38.32	7.43	-9.54	46.03	Peak	74	-27.97
11.65	V	31.53	34.96	38.32	7.43	-9.54	32.78	Avg	54	-21.22
17.475	V	43.63	33.89	41.14	10.53	-9.54	51.86	Peak	74	-22.14
17.475	V	31.25	33.89	41.14	10.53	-9.54	39.48	Avg	54	-14.52
<b>High Channel 5825MHz</b>										

**Table 30. Radiated Harmonic Emissions – 802.11n 20MHz Mode**

Note: All other emissions were measured at the noise floor of the spectrum analyzer.

### Harmonic Emissions Requirements – Radiated


Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 1 m	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	Distance Correction Factor 1m to 3m (dB $\mu$ V/m)	EUT Field Strength Final Amp. (dB $\mu$ V/m)	Limit Detector (Peak) / (Avg)	Limit @ 3 m (dB $\mu$ V/m)	Delta (dB)
11.49	V	42.96	34.86	38.14	7.72	-9.54	44.42	Peak	74	-29.58
11.49	V	30.84	34.86	38.14	7.72	-9.54	32.30	Avg	54	-21.70
17.235	V	43.82	34.01	40.88	10.17	-9.54	51.33	Peak	74	-22.67
17.235	V	31.03	34.01	40.88	10.17	-9.54	38.54	Avg	54	-15.46
<b>Low Channel 5745MHz</b>										
Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 1 m	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	Distance Correction Factor 1m to 3m (dB $\mu$ V/m)	EUT Field Strength Final Amp. (dB $\mu$ V/m)	Limit Detector (Peak) / (Avg)	Limit @ 3 m (dB $\mu$ V/m)	Delta (dB)
11.57	V	43.71	34.91	38.23	7.63	-9.54	45.12	Peak	74	-28.88
11.57	V	31.09	34.91	38.23	7.63	-9.54	32.50	Avg	54	-21.50
17.355	V	44.32	33.93	41.03	10.33	-9.54	52.21	Peak	74	-21.79
17.355	V	31.04	33.93	41.03	10.33	-9.54	38.93	Avg	54	-15.07
<b>Mid Channel 5785MHz</b>										
Freq. (GHz)	Antenna Polarity (H/V)	Raw Amp. @ 1 m	P.Amp (dB)	Ant. Cor. Factor (dB/m)	Cable Loss (dB)	Distance Correction Factor 1m to 3m (dB $\mu$ V/m)	EUT Field Strength Final Amp. (dB $\mu$ V/m)	Limit Detector (Peak) / (Avg)	Limit @ 3 m (dB $\mu$ V/m)	Delta (dB)
11.65	V	44.13	34.96	38.32	7.43	-9.54	45.38	Peak	74	-28.62
11.65	V	31.27	34.96	38.32	7.43	-9.54	32.52	Avg	54	-21.48
17.475	V	44.95	33.89	41.14	10.53	-9.54	53.18	Peak	74	-20.82
17.475	V	31.27	33.89	41.14	10.53	-9.54	39.50	Avg	54	-14.50
<b>High Channel 5825MHz</b>										

**Table 31. Radiated Harmonic Emissions – 802.11n 40MHz Mode**


Note: All other emissions were measured at the noise floor of the spectrum analyzer.



## Radiated Spurious Emissions Test Results




Plot 44. Radiated Spurious Emissions, 802.11n 20MHz Mode Low Channel




Plot 45. Radiated Spurious Emissions, 802.11n 20MHz Mode Mid Channel

## Radiated Spurious Emissions Test Results




Plot 46. Radiated Spurious Emissions, 802.11n 20MHz Mode High Channel




Plot 47. Radiated Spurious Emissions, 802.11n 40MHz Mode Low Channel

## Radiated Spurious Emissions Test Results



Plot 48. Radiated Spurious Emissions, 802.11n 40MHz Mode Mid Channel



Plot 49. Radiated Spurious Emissions, 802.11n 40MHz Mode High Channel

## Radiated Spurious Emissions Test Setup Photograph



**Photograph 6. Radiated Spurious Emission, Test Setup, 3m Distance**



**Photograph 7. Radiated Spurious Emission, Test Setup, 1m Distance**

## Electromagnetic Compatibility Criteria for Intentional Radiators

### RSS-GEN Receiver Spurious Emissions Requirements

**Test Requirements:** The following receiver spurious emission limits shall be complied with:

- (a) If a radiated measurement is made, all spurious emissions shall comply with the limits of Table 32.

Spurious Frequency (MHz)	Field Strength (microvolt/m at 3 metres)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

**Table 32. Spurious Emission Limits for Receivers**


- (b) If a conducted measurement is made, no spurious output signals appearing at the antenna terminals shall exceed 2 nanowatts per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5 nanowatts above 1 GHz.

**Test Procedures:** The EUT was programmed for receive mode only. Conducted measurements were taken at the antenna ports of the EUT. 100 kHz resolution bandwidth was used from 30 MHz - 1 GHz and 300 kHz resolution was used for measurements done above 1 GHz. All plots are corrected for cable loss.

**Test Results:** Equipment complies with the Receiver Spurious Emissions Requirements of RSS-GEN.


**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 01/05/10




**Figure 4. Block Diagram, Conducted Receiver Spurious Test Setup**

## Conducted Receiver Spurious Emissions Test Results – Port 1




Plot 50. Conducted Receiver Spurious Emission, 30MHz – 1GHz, Port 1




Plot 51. Conducted Receiver Spurious Emission, 1 GHz – 20 GHz, Port 1

## Conducted Receiver Spurious Emissions Test Results – Port 2



Plot 52. Conducted Receiver Spurious Emission, 30MHz – 1GHz, Port 2



Plot 53. Conducted Receiver Spurious Emission, 1 GHz – 20 GHz, Port 2



## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge

**Test Requirement:** **15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

**Test Procedure:** For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10<sup>th</sup> harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

A conducted version of the EUT was provided with an MMCX connector at the antenna ports. The spectrum analyzer was set to a 100 kHz resolution bandwidth and 300 kHz video bandwidth. Measurements were taken at antenna ports 1 and 2. Plots are corrected for external attenuation and cable loss.

See following pages for detailed test results with RF Conducted Spurious Emissions.

**Test Results:** The EUT was Compliant with the Conducted Spurious Emission limits of §15.247(d).

**Test Engineer(s):** Anderson Soungpanya

**Test Date(s):** 12/23/09






Figure 5. Block Diagram, Conducted Spurious Emissions Test Setup


## RF Conducted Spurious Emissions Test Results – 802.11n 20MHz Mode



Plot 54. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 1 (30MHz-1GHz)




Plot 55. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 1 (1-18GHz)




Plot 56. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 1 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 20MHz Mode



**Plot 57. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 1 (30MHz-1GHz)**




**Plot 58. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 1 (1-18GHz)**




**Plot 59. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 1 (18-40GHz)**


## RF Conducted Spurious Emissions Test Results – 802.11n 20MHz Mode



**Plot 60. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 1 (30MHz-1GHz)**




**Plot 61. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 1 (1-18GHz)**




**Plot 62. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 1 (18-40GHz)**


## RF Conducted Spurious Emissions Test Results – 802.11n 40MHz Mode (Port 1)



Plot 63. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 1 (30MHz-1GHz)




Plot 64. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 1 (1-18GHz)




Plot 65. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 1 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 40MHz Mode (Port 1)



Plot 66. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 1 (30MHz-1GHz)




Plot 67. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 1 (1-18GHz)




Plot 68. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 1 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 40MHz Mode (Port 1)



Plot 69. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 1 (30MHz-1GHz)




Plot 70. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 1 (1-18GHz)




Plot 71. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 1 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 20MHz Mode (Port 2)



Plot 72. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 2 (30MHz-1GHz)




Plot 73. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 2 (1-18GHz)




Plot 74. Conducted Spurious 5745MHz Low Channel 802.11n 20MHz Port 2 (18-40GHz)




## RF Conducted Spurious Emissions Test Results – 802.11n 20MHz Mode (Port 2)



Plot 75. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 2 (30MHz-1GHz)




Plot 76. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 2 (1-18GHz)




Plot 77. Conducted Spurious 5785MHz Mid Channel 802.11n 20MHz Port 2 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 20MHz Mode (Port 2)



Plot 78. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 2 (30MHz-1GHz)




Plot 79. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 2 (1-18GHz)




Plot 80. Conducted Spurious 5825MHz High Channel 802.11n 20MHz Port 2 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 40MHz Mode (Port 2)



Plot 81. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 2 (30MHz-1GHz)




Plot 82. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 2 (1-18GHz)




Plot 83. Conducted Spurious 5745MHz Low Channel 802.11n 40MHz Port 2 (18-40GHz)


## RF Conducted Spurious Emissions Test Results – 802.11n 40MHz Mode (Port 2)



**Plot 84. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 2 (30MHz-1GHz)**




**Plot 85. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 2 (1-18GHz)**




**Plot 86. Conducted Spurious 5785MHz Mid Channel 802.11n 40MHz Port 2 (18-40GHz)**


## RF Conducted Spurious Emissions Test Results – 802.11n 40MHz Mode (Port 2)



Plot 87. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 2 (30MHz-1GHz)




Plot 88. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 2 (1-18GHz)




Plot 89. Conducted Spurious 5825MHz High Channel 802.11n 40MHz Port 2 (18-40GHz)

**Conducted Band Edge Test Results – 802.11n 20MHz Mode (Port 1)**




**Plot 90. Conducted Band Edge 5745MHz Low Channel 802.11n 20MHz Port 1**




**Plot 91. Conducted Band Edge 5825MHz High Channel 802.11n 20MHz Port 1**

### Conducted Band Edge Test Results – 802.11n 40MHz Mode (Port 1)




Plot 92. Conducted Band Edge 5745MHz Low Channel 802.11n 40MHz Port 1




Plot 93. Conducted Band Edge 5825MHz High Channel 802.11n 40MHz Port 1

### Conducted Band Edge Test Results – 802.11n 20MHz Mode (Port 2)




Plot 94. Conducted Band Edge 5745MHz Low Channel 802.11n 20MHz Port 2




Plot 95. Conducted Band Edge 5825MHz High Channel 802.11n 20MHz Port 2



### Conducted Band Edge Test Results – 802.11n 40MHz Mode (Port 2)



Plot 96. Conducted Band Edge 5745MHz Low Channel 802.11n 40MHz Port 2



Plot 97. Conducted Band Edge 5825MHz High Channel 802.11n 40MHz Port 2

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(e) Peak Power Spectral Density

**Test Requirements:** §15.247(e): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

**Test Procedure:** The transmitter was connected directly to a Spectrum Analyzer through an attenuator. The power level was set to the maximum level. A RBW of 1 MHz and VBW of 3 MHz were used to determine the peak emissions within the band. The Spectrum analyzer was then set to a RBW of 3 kHz and VBW was set to 10 kHz. The SPAN of the analyzer was set to 1 MHz with a 333.3 second sweep. Each port were measured individually then compared to the limit. Then both ports were measured simultaneously using a combiner. Measurements were carried out at the low, mid and high channels.

**Test Results:** The EUT was Compliant with the peak power spectral density limits of § 15.247 (e).

The peak power spectral density was determined from plots on the following page(s).

**Test Engineer:** Anderson Soungpanya

**Test Date:** 12/23/09




Figure 6. Block Diagram, Peak Power Spectral Density Test Setup, MIMO




Figure 7. Block Diagram, Peak Power Spectral Density Test Setup

## Peak Power Spectral Density Test Results

Peak Power Spectral Density				
Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-6.05	8	14.05
Mid	5785	-7.20	8	15.20
High	5825	-7.17	8	15.17

Table 33. Spectral Density Test Results, 802.11n 20MHz Mode (Port 1)

Peak Power Spectral Density				
Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-7.53	8	15.53
Mid	5785	-8.24	8	16.24
High	5825	-8.05	8	16.05

Table 34. Spectral Density Test Results, 802.11n 40MHz Mode (Port 1)

Peak Power Spectral Density				
Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-5.87	8	13.87
Mid	5785	-6.24	8	14.24
High	5825	-6.69	8	14.69

Table 35. Spectral Density Test Results, 802.11n 20MHz Mode (Port 2)

Peak Power Spectral Density				
Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-6.88	8	14.88
Mid	5785	-7.79	8	15.79
High	5825	-7.97	8	15.97

Table 36. Spectral Density Test Results, 802.11n 40MHz Mode (Port 2)

## Peak Power Spectral Density Test Results


HT20 MIMO Mode				
Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-3.04	8	11.04
Mid	5785	-3.19	8	11.19
High	5825	-3.77	8	11.77

Table 37. Peak Power Spectral Density Test Results, HT20, MIMO Mode (Combined Ports)


HT40 MIMO Mode				
Carrier Channel	Frequency (MHz)	Measured PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	5745	-2.45	8	10.45
Mid	5785	-4.22	8	12.22
High	5825	-3.33	8	11.33

Table 38. Peak Power Spectral Density Test Results, HT40, MIMO Mode (Combined Ports)

## Peak Power Spectral Density




Plot 98. Power Spectral Density 5745MHz Low Channel 802.11n 20MHz Port 1




Plot 99. Power Spectral Density 5785MHz Mid Channel 802.11n 20MHz Port 1

## Peak Power Spectral Density Test Results




Plot 100. Power Spectral Density 5825MHz High Channel 802.11n 20MHz Port 1




Plot 101. Power Spectral Density 5745MHz Low Channel 802.11n 40MHz Port 1

## Peak Power Spectral Density Test Results




Plot 102. Power Spectral Density 5785MHz Mid Channel 802.11n 40MHz Port 1




Plot 103. Power Spectral Density 5825MHz High Channel 802.11n 40MHz Port 1

## Peak Power Spectral Density Test Results




Plot 104. Power Spectral Density 5745MHz Low Channel 802.11n 20MHz Port 2




Plot 105. Power Spectral Density 5785MHz Mid Channel 802.11n 20MHz Port 2



## Peak Power Spectral Density Test Results




Plot 106. Power Spectral Density 5825MHz High Channel 802.11n 20MHz Port 2




Plot 107. Power Spectral Density 5745MHz Low Channel 802.11n 40MHz Port 2

## Peak Power Spectral Density Test Results




**Plot 108. Power Spectral Density 5785MHz Mid Channel 802.11n 40MHz Port 2**




**Plot 109. Power Spectral Density 5825MHz High Channel 802.11n 40MHz Port 2**

## Peak Power Spectral Density Test Results




Plot 110. Power Spectral Density 5745MHz Low Channel 802.11n 20MHz Combined




Plot 111. Power Spectral Density 5785MHz Mid Channel 802.11n 20MHz Combined

## Peak Power Spectral Density Test Results




Plot 112. Power Spectral Density 5825MHz High Channel 802.11n 20MHz Combined




Plot 113. Power Spectral Density 5745MHz Low Channel 802.11n 40MHz Combined

## Peak Power Spectral Density Test Results



Plot 114. Power Spectral Density 5785MHz Mid Channel 802.11n 40MHz Combined



Plot 115. Power Spectral Density 5825MHz High Channel 802.11n 40MHz Combined

## IV. Test Equipment

## Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ANSI/NCSL Z540-1-1994 and ANSI/ISO/IEC 17025:2000.

MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1S2421	EMI RECEIVER	ROHDE&SCHWARZ	ESIB 7	05/27/2009	05/27/2010
1S2121	PRE-AMPLIFIER	HEWLETT PACKARD	8449B	SEE NOTE	
1S2501	EMI RECEIVER	Rohde & Schwarz	ESU40	4/27/2009	4/27/2010
1S2198	HORN ANTENNA	EMCO	3115	09/03/2009	09/03/2010
1S2128	HARMONIC MIXER	HEWLETT PACKARD	11970A	11/22/2008	11/22/2010
1S2129	HARMONIC MIXER	HEWLETT PACKARD	11970K	11/22/2008	11/22/2010
1S2603	HORN ANTENNA	ETS-LINDGREN	3117	4/9/2009	4/9/2011
1S2202	HORN ANTENNA	EMCO	3116	4/10/2007	4/10/2010
N/A	HIGH PASS FILTER	MICRO-TRONICS	HPM13146	SEE NOTE	
1S2041	COUPLER, BI DIRECTIONAL COAXIAL	NARDA	N/A	SEE NOTE	
1S2483	ANALYZER, SPECTRUM	AGILENT	E4447A	1/12/2009	1/12/2010
1S2460	ANALYZER, SPECTRUM 9 KHZ-40GHZ	AGILENT	E4407B	04/14/2009	04/14/2010
1S508	LISN	SOLAR ELECTRONICS	9252-50-R24-BNC	06/05/2009	06/05/2010
1S2512	TRANSIENT LIMITER	AGILENT	11947A	SEE NOTE	
1S2518	THERMO-HYGROMETER	FISHER SCIENTIFIC	11-661-7D	1/21/2008	1/21/2010
1S2482	CHAMBER, 5 METER	PANASHIELD	641431	10/16/2009	10/16/2010
1S2108	RECIEVER, EMI, RF FILTER SECTION	HP	85460A	11/10/2009	11/10/2010
1S2399	TURNTABLE CONTROLLER	SUNOL SCIENCE	SC99V	SEE NOTE	
1S2485	BILOG ANTENNA	TESEQ	CBL6112D	03/20/2009	03/20/2010

**Table 39. Test Equipment List**

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

## **V. Certification & User's Manual Information**



## Certification & User's Manual Information

### A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

#### § 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

#### § 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
  - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
  - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing*;
  - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
  - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
  - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

## Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

### § 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.<sup>1</sup> *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

### § 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

---

<sup>1</sup> In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

## Certification & User's Manual Information

### § 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
- (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
- (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
- (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
- (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

## Certification & User's Manual Information

### Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

#### § 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

#### § 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

## Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

### § 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## ICES-003 Procedural & Labeling Requirements

From the Industry Canada Electromagnetic Compatibility Advisory Bulletin entitled, "Implementation and Interpretation of the Interference-Causing Equipment Standard for Digital Apparatus, ICES-003" (EMCAB-3, Issue 2, July 1995):

"At present, CISPR 22: 2002 and ICES technical requirements are essentially equivalent. Therefore, if you have CISPR 22: 2002 approval by meeting CISPR Publication 22, the only additional requirements are: to attach a note to the report of the test results for compliance, indicating that these results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations; to maintain these records on file for the requisite five year period; and to provide the device with a notice of compliance in accordance with ICES-003."

### Procedural Requirements:

According to Industry Canada's Interference Causing Equipment Standard for Digital Apparatus ICES-003 Issue 4, February 2004:

- Section 6.1: A record of the measurements and results, showing the date that the measurements were completed, shall be retained by the manufacturer or importer for a period of at least five years from the date shown in the record and made available for examination on the request of the Minister.
- Section 6.2: A written notice indicating compliance must accompany each unit of digital apparatus to the end user. The notice shall be in the form of a label that is affixed to the apparatus. Where because of insufficient space or other constraints it is not feasible to affix a label to the apparatus, the notice may be in the form of a statement in the user's manual.

### Labeling Requirements:

The suggested text for the notice, in English and in French, is provided below, from the Annex of ICES-003:

This Class [<sup>2</sup>] digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe [<sup>1</sup>] est conforme à la norme NMB-003 du Canada.

---

<sup>2</sup> Insert either A or B but not both as appropriate for the equipment requirements.

# End of Report