


# RF Exposure Evaluation Report

**APPLICANT** : Ubiquiti Network, Inc  
**EQUIPMENT** : Access Point  
**BRAND NAME** : UBIQUITI  
**MODEL NAME** : NBE-M2-13  
**FCC ID** : SWX-NBE2M13  
**STANDARD** : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)**



## Table of Contents

- 1. ADMINISTRATION DATA ..... 3**
  - 1.1. Testing Laboratory ..... 3
- 2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) ..... 3**
- 3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS ..... 3**
- 4. RF EXPOSURE LIMIT INTRODUCTION ..... 4**
- 5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION ..... 5**
  - 5.1. Standalone Power Density Calculation ..... 5

### Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA542937-01	Rev. 01	Initial issue of report	Aug. 03, 2015



1. Administration Data

1.1. Testing Laboratory

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Ubiquiti Network, Inc
Address	12F, No.105, Song Ren Rd., SinYi District, Taipei 110, Taiwan

Manufacturer	
Company Name	Ubiquiti Network, Inc
Address	12F, No.105, Song Ren Rd., SinYi District, Taipei 110, Taiwan

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Access Point
Brand Name	UBIQUITI
Model Name	NBE-M2-13
FCC ID	SWX-NBE2M13
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz
Mode	802.11g/n (HT5/HT8/HT10/HT20/HT30/HT40)
Antenna Type	Disc Antenna
EUT Stage	Production Unit

3. Maximum RF average output power among production units

Band / Mode		IEEE 802.11 Average Power (dBm)			
		5M / 10M	11g 8M	11g 20M	11g 30M
11g	Low	16.50	13.50	13.50	6.00
	Middle	16.00	12.50	16.00	4.00
	High	15.50	9.00	11.50	5.00

Band / Mode		IEEE 802.11 Average Power (dBm)				
		HT5 / HT10	HT8	HT20	HT30	HT40
11n	Low	17.00	13.50	13.50	4.00	10.50
	Middle	16.00	12.50	16.00	4.00	15.00
	High	15.50	11.00	11.50	4.00	8.50



### 4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



## **5. Radio Frequency Radiation Exposure Evaluation**

### **5.1. Standalone Power Density Calculation**

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2.4GHz WLAN	2412.0	13.00	17.00	30.000	1.000	1000.000	0.199	1.000

**Note:** For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.