



# **Compliance Testing, LLC**

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## **Test Report**

**Prepared for: Ubiquiti Networks, Inc**

**Model: PBE-5AC**

**Description: PowerBeam 5AC**

**FCC ID: SWX-PBE5AC**

**To**

**FCC Part 1.1310**

**Date of Issue: April 8, 2015**

**On the behalf of the applicant:**

**Ubiquiti Networks, Inc  
91 E. Tasman Drive  
San Jose, CA 95134**

**Attention of:**

**Michael Taylor, Compliance Manager  
Ph: (408) 942-3085  
E-mail: [compliance@ubnt.com](mailto:compliance@ubnt.com)**

**Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p14a0019**

**Greg Corbin  
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	April 8, 2015	Greg Corbin	Original Document



## ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

### **EUT Description**

**Model:** PBE-5AC

**Description:** PowerBeam 5AC

**Firmware:** N/A

**Software:** N/A

**Serial Number:** N/A

### **Additional Information:**

The EUT was tested conducted mode with RF connectors mounted on the EUT at the antenna input. When the test cable is plugged into the RF connector mounted to the EUT it disables the antenna connection.

The EUT is powered by POE (Power Over Ethernet).

The different data rates were evaluated and the worst case data rate was chosen for all the testing.



## Source Based Time Averaged Power Calculation

### Average Power calculations

Average Power = Peak Power \* duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output power (mW)	Duty Cycle	Average Power (mW)
5790	269.1	100	269.1

### MPE Evaluation

This is a **fixed/mobile** device used in uncontrolled /general population exposure environment.

#### Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

### Test Data

Test Frequency, MHz	5790
Power, Conducted, mW (P)	269.1
Antenna Gain Isotropic	6 dBi
Antenna Gain Numeric (G)	3.98
Antenna Type	Omni
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm <sup>2</sup>	Power mW (P)	Numeric Gain (G)	Distance (r <sup>2</sup> ) cm
0.213	269.1	3.98	20

Power Density (S) =0.213
Limit =(from above table) = 1.0

END OF TEST REPORT