



## Test Report

Prepared for: Ubiquiti Networks, Inc

Models: PBE-5AC-Gen2  
PBE-5AC-Omni-Gen2

Description: PowerBeam 5AC (G2)  
PowerBeam 5AC Omni (G2)

Serial Number: NA

FCC ID: SWX-PBE5ACG2  
IC: 6545A-PBE5ACG2

To

FCC Part 15.247

And

IC RSS-247

Date of Issue: March 8, 2017

On the behalf of the applicant:

Ubiquiti Networks, Inc  
2580 Orchard Parkway  
San Jose, CA 95131

Attention of:

Michael Taylor, Compliance Manager  
Ph: (408) 942-3085  
Email: [compliance@ubnt.com](mailto:compliance@ubnt.com)

Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1710009

**Poona Saber**  
**Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing.  
All results contained herein relate only to the sample tested.



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	February 8, 2017	Poona Saber	Original Document
2.0	March 7, 2017	Poona Saber	Corrected versions of KDB and Ansi standards on page 8, Note added on page 11 for measurements above 18 GHz, updated Annex A & Annex B



## Table of Contents

<b><u>Description</u></b>	<b><u>Page</u></b>
Standard Test Conditions Engineering Practices .....	6
Test Results Summary .....	8
Peak Output Power .....	9
Conducted Spurious Emission .....	10
Radiated Spurious Emissions .....	11
Occupied Bandwidth .....	12
Transmitter Power Spectral Density (PSD) .....	13
A/C Powerline Conducted Emission .....	14
Test Equipment Utilized .....	15

**ILAC / A2LA**

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

**The applicant has been cautioned as to the following**

15.21 - Information to User

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) - Special Accessories

Equipment marked to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer without an additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.



## Standard Test Conditions Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.10-2013 and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104°F) unless the particular equipment requirements specified testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Measurement results, unless otherwise noted, are worst-case measurements.

Environmental Conditions		
Temperature (°C)	Humidity (%)	Pressure (mbar)
23.3	32.5	973.5

### EUT Description

**Model:** PBE-5AC-Gen2, PBE-5AC-Omni-Gen2

**Description:** PowerBeam 5AC (G2), PowerBeam 5AC Omni (G2)

**Firmware:** AirOS 8.0.1

**Software:** AirOS 8.0.1

**Serial Number:** N/A

**Additional Information:** The EUT has shown compliance to 15.407 in the 5 GHz band. This report is adding the capability of 2.4 GHz for installation uses.

### EUT Operation during Tests

The EUT was controlled using documentation provided by the manufacturer. A TelNet communication was created and utilized to force the radio into required transmissions.



**Accessories:**

Qty	Description	Manufacturer	Model	S/N
1	POE Adapter	Ubiquiti Networks	NA	NA

**Cables:**

Qty	Description	Length (M)	Shielding Y/N	Shielded Hood Y/N	Ferrite Y/N
2	Ethernet Cables	<3m	Y	Y	N

**Modifications:** None

**15.203: Antenna Requirement:**

- The antenna is permanently attached to the EUT
- The antenna uses a unique coupling
- The EUT must be professionally installed
- The antenna requirement does not apply



## Test Results Summary

Specification	Test Name	Pass, Fail, N/A	Comments
15.247(b)	Peak Output Power	Pass	
15.247(b)	Conducted Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Radiated Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Emissions At Band Edges	Pass	
15.247(a)(2)	Occupied Bandwidth	Pass	
15.247(e)	Transmitter Power Spectral Density	Pass	
15.207	A/C Powerline Conducted Emissions	Pass	
RSS-Gen §7	Receiver Spurious Emission Limits	Pass	

References	Description
CFR47, Part 15, Subpart B	Unintentional Radiators
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63.10-2013	American National standard for testing Unlicensed Wireless Devices
ANSI C63.4-2014	Method and Measurements of Radio-Noise Emissions from low-Voltage Electrical and Electronic Equipment in the range 9kHz to 40GHz.
ISO/IEC 17025:2005	General requirements for the Competence of Testing and Calibrations Laboratories
KDB 558074 D01 v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating under §15.247





**Peak Output Power**

**Engineer:** Poona Saber

**Test Date:** 2/2/2017


**Test Procedure**

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

- RBW = 1-5% of the OBW, not to exceed 1MHz
- VBW  $\geq 3 \times$  RBW
- RMS Detector
- Number of points in sweep  $\geq 2 \times$  span / RBW
- Trace average at least 100 traces in power averaging mode
- Sweep = auto
- Span = 1.5 x EBW

The EUT was set to transmit on the lowest, middle and highest frequencies at the maximum power level. The RF output power was measured using the spectrum analyzer's channel power function

**Test Setup**



**Transmitter Peak Output Power**

Tuned Frequency (MHz)	Measured Value (dBm)	Specification Limit	Result
2412	15.73	1 W (30 dBm)	Pass
2442	15.13	1 W (30 dBm)	Pass
2462	13.61	1 W (30 dBm)	Pass



## Conducted Spurious Emission

**Engineer:** Poona Saber

**Test Date:** 2/3/2017

### Test Procedure

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

RBW = 100 kHz

VBW  $\geq$  3 x RBW

Peak Detector


Trace mode = max hold

Sweep = auto couple

Frequency Range = 30MHz – 10<sup>th</sup> Harmonic of the fundamental

The EUT was set to transmit on the lowest, middle and highest frequencies at the maximum power level. The trace was allowed to stabilize. All emission were investigated to insure they were attenuated from the peak fundamental by at least 20dB. If the average power levels were measured then the out-of-band emissions needed to be attenuated by 30dB. In addition emissions were investigated at the band edges to insure all out-of-band emissions were attenuated 20 or 30dB as necessary

### Test Setup



**See Annex A for test results**



### Radiated Spurious Emissions

**Engineer:** Poona Saber

**Test Date:** 2/7/2017


#### **Test Procedure Radiated Spurious Emissions: 30 – 1000 MHz**

The EUT was setup in a semi-anechoic test chamber set 3m from the receiving antenna. The output of the transmitter was connected to a non-radiating balance load. The EUT was set to transmit on the lowest, middle and highest frequencies at the maximum power level. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Emissions. The EUT was tested by rotating it 360° with the antennas in both the vertical and horizontal orientation and was raised from 1 to 4 meters to ensure the TX signal levels were maximized.

All emissions from 30 MHz to 1 GHz were examined.  
Measured Level includes antenna and receiver cable correction factors.  
Correction factors were input into the spectrum analyzer before recording “Measured Level”.

RBW = 100 KHz  
VBW = 300 KHz  
Detector – Quasi Peak


#### **Test Setup**



#### **Test Procedure for Radiated Spurious Emissions above 1 GHz**

The EUT was setup in a semi-anechoic test chamber set 3m from the receiving antenna. The output of the transmitter was connected to a non-radiating balance load. The EUT was set to transmit on the lowest, middle and highest frequencies at the maximum power level. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Emissions. The EUT was tested by rotating it 360° with the antennas in both the vertical and horizontal orientation and was raised from 1 to 4 meters to ensure the TX signal levels were maximized.

#### **Test Setup**



Note: In addition Radiated emissions in restricted bands, as defined in 15.205(a) were investigated to comply with radiated emission limit specified in 15.209.

Note: Emissions were investigated up to 26 GHz but only noise floor was measured above 18 GHz.

**See Annex B for test data**



**Occupied Bandwidth**

**Engineer:** Poona Saber

**Test Date:** 2/3/17


**Test Procedure**

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

- RBW = 100 kHz
- VBW  $\geq$  3 x RBW
- Peak Detector
- Trace mode = max hold
- Sweep = auto couple
- Span = 1.5 x EBW

The EUT was set to transmit at the lowest, middle and highest channels of the band at the maximum power levels. The maximum width of the emission that was determined by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that were attenuated by 6db and this value was used to determine the width of the carrier. Alternatively the spectrum analyzer's automatic bandwidth capability was used.

**Test Setup**



**6 dB Occupied Bandwidth Summary**

Frequency (MHz)	Measured Bandwidth (MHz)	Specification Limit (kHz)	Result
2412	17.76	$\geq$ 500	Pass
2442	17.86	$\geq$ 500	Pass
2462	17.8	$\geq$ 500	Pass

**99% Bandwidth Summary**

Frequency (MHz)	Measured Bandwidth (MHz)	Result
2412	21.4	Pass
2442	21.09	Pass
2462	21.34	Pass



## Transmitter Power Spectral Density (PSD)

**Engineer:** Poona Saber

**Test Date:** 2/3/17


### Test Procedure

The EUT was connected directly to a spectrum analyzer. The Spectrum Analyzer was set to the following:

DTS channel center frequency  
Span 1.5 x DTS bandwidth  
RBW = 3 kHz ≤ RBW ≤ 100 kHz  
VBW ≥ 3 x RBW  
Peak Detector  
Sweep time = auto couple  
Trace mode = max hold

The EUT was set to transmit at the lowest, middle and highest channels of the band at the maximum power levels. Once the trace has stabilize the peak marker was used to determine the peak power spectral density.

### Test Setup



### PSD Summary

Frequency (MHz)	Measured Data (dBm)	Specification Limit (dBm)	Result
2412	-11.73	8	Pass
2442	-8.93	8	Pass
2462	-10.98	8	Pass



**A/C Powerline Conducted Emission**

**Engineer:** Poona Saber


**Test Date:** 2/8/17

**Test Procedure**

The EUT power cable was connected to a LISN and the monitored output of the LISN was connected to a transient limiter, which then connected directly to a spectrum analyzer. The conducted emissions from 150 kHz to 30 MHz were measured and compared to the specification limits.

Testing was taken from a previous project using the same radio.

**Test Setup**



**See Annex C for test results**



## Test Equipment Utilized

Description	Manufacturer	Model #	CT Asset #	Last Cal Date	Cal Due Date
Horn Antenna, Amplified	ARA	DRG-118/A	i00271	06/16/16	06/16/18
Humidity / Temp Meter	Newport	IBTHX-W-5	i00282	5/26/16	5/26/17
Spectrum Analyzer	Agilent	E4407B	i00331	10/19/16	10/19/17
Bi-Log Antenna	Schaffner	CBL 6111D	i00349	8/3/16	8/3/17
EMI Analyzer	Agilent	E7405A	i00379	2/11/16	2/11/17
3 Meter Semi-Anechoic Chamber	Panashield	3 Meter Semi-Anechoic Chamber	i00428	8/15/16	8/15/18

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT