


RF Exposure Evaluation Report

APPLICANT : Ubiquiti Networks, Inc.
EQUIPMENT : Solar Gateway
BRAND NAME : UBIQUITI
MODEL NAME : SM-SG
FCC ID : SWX-SMSG
STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

| | |
|--|----------|
| 1. ADMINISTRATION DATA | 4 |
| 1.1. Testing Laboratory | 4 |
| 2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) | 5 |
| 3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS | 5 |
| 4. RF EXPOSURE LIMIT INTRODUCTION | 6 |
| 5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION | 7 |
| 5.1. Power Density Calculation..... | 7 |

**Revision History**

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|-------------------------|---------------|
| FA5O2404 | Rev. 01 | Initial issue of report | Jan. 20, 2016 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

**1. Administration Data****1.1. Testing Laboratory**

| Testing Laboratory | |
|--------------------|--|
| Test Site | SPORTON INTERNATIONAL INC. |
| Test Site Location | No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978 |

| Applicant | |
|--------------|---|
| Company Name | Ubiquiti Networks, Inc. |
| Address | 12F, No.105, Song Ren Rd.,SinYi District, Taipei 110,Taiwan |

| Manufacturer | |
|--------------|---|
| Company Name | Ubiquiti Networks, Inc. |
| Address | 12F, No.105, Song Ren Rd.,SinYi District, Taipei 110,Taiwan |

**2. Description of Equipment Under Test (EUT)**

| Product Feature & Specification | |
|---|--------------------------------|
| EUT Type | Solar Gateway |
| Brand Name | UBIQUITI |
| Model Name | SM-SG |
| FCC ID | SWX-SMSG |
| Wireless Technology and Frequency Range | Bluetooth: 2402 MHz ~ 2480 MHz |
| Mode | • Bluetooth v4.1-LE |
| Antenna Type | PIFA Antenna |
| EUT Stage | Identical Prototype |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF average output power among production units

| Mode / Band | Average Power (dBm) |
|-------------|---------------------|
| | BT4.1-LE (GFSK) |
| Bluetooth | 3 |



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0-30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | f/300 | 6 |
| 1500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | f/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Power Density Calculation

| Band | Frequency (MHz) | Antenna Gain (dBi) | Maximum Power (dBm) | Maximum EIRP (dBm) | Maximum EIRP (W) | Average EIRP (mW) | Power Density at 20cm (mW/cm ²) | Limit (mW/cm ²) | Power Density / Limit |
|-----------|-----------------|--------------------|---------------------|--------------------|------------------|-------------------|---|-----------------------------|-----------------------|
| Bluetooth | 2402.0 | 5.0 | 3.0 | 8.000 | 0.006 | 6.310 | 0.001 | 1.000 | 0.001256 |

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.