



# **NLOS Series Mobile Antennas** 900 to 928 MHz Operation

#### **Features**

- 900MHz Omni Directional Mobile Antennas
- Available in 5.5 and 7dBi gain models
- Stainless Steel Construction
- Magnetic Mounts, Trunk Lid mounts and Surface Mounts available

## **Applications**

- 900 MHz ISM Band Applications
   Non Line of Sight Applications
- 900MHz Mobile Applications
- Point to Multi-point Systems



5.5dBi Mobile

## **Description**

The NLOS Series Omnidirectional Mobile Antenna systems offered by Pacific Wireless are constructed of Stainless Steel for long service life. Available mounts include small and large magnetic mounts as well as trunk lid mounts. The antennas are vertically polarized. They come with a UHF Male connector as standard to mate with various mounts. The mounts come with 10 ft. of RG-58/U cable with N Female Connectors. Alternate connector configurations are available by request.

## **Specifications**


7dBi Mobile


| Parameter                            | Min | _ Typ _ | Max | Units |
|--------------------------------------|-----|---------|-----|-------|
| Frequency Range                      | 900 |         | 928 | MHz   |
| Input Return Loss (S <sub>11</sub> ) |     | -14     |     | dB    |
| VSWR                                 |     | 1.5:1   |     |       |
| Impedance                            |     | 50      |     | OHM   |
| Input Power                          |     |         | 100 | W     |
| Operating Temperature                | -45 |         | +70 | Deg C |

| 900 - 928 MHZ | MA9-5             | MA9-7             | MM-90                  | MM-110                 | MM-TM                     | MM-SM-LP                  | MM-SM-B                   |  |  |  |
|---------------|-------------------|-------------------|------------------------|------------------------|---------------------------|---------------------------|---------------------------|--|--|--|
| Gain          | 5.5dB             | 7dB               | Antenna Mounts         |                        |                           |                           |                           |  |  |  |
| Weight        | 3.9 Oz<br>(120 g) | 5.8 Oz<br>(180 g) | 1.5Lb<br>( 0.55Kg)     | 2.1Lb<br>(0.8Kg)       | 0.7Lb<br>(0.32Kg)         | 0.5Lb<br>(0.23Kg)         | 0.5Lb<br>(0.23Kg)         |  |  |  |
| Dimension     | 16 in<br>(40 cm)  | 20 in<br>(50 cm)  | 3.5"<br>(90mm) Dia     | 4.3"<br>(110mm) Dia    | 3"<br>(76mm)              | 1.5"x1.25"<br>(38 x 32mm) | 1.75" x 2"<br>(44 x 51mm) |  |  |  |
| Cable Length  |                   |                   | 10' (3.5M) RG-58/U     |                        |                           |                           |                           |  |  |  |
| Connector     | UHF Male          | UHF Male          | UHF in<br>N Female out | UHF in<br>N Female out | UHF in<br>N Female<br>out | UHF in<br>N Female out    | UHF in<br>N Female out    |  |  |  |

Page 2 PAWMA9

### **Antenna Patterns at 910Mhz**







MM-SM-LP
Thru Hole Low
Profile Surface
Mount for Mobile
Antennas



MM-SM-B Thru Hole Surface Mount for Mobile Antennas



MM-TM Stainless Steel Trunk Lid Mount for Mobile Antennas



MM-90 Magnetic Mount



MM-110
Large Magnetic Mount

#### **Notes:**

- All shipments F.O.B. Bluffdale, UT 84065
- All antennas carry a 2 Year Warranty

## **System Ordering:**

MA9-5
 MA9-7
 7dB NLOS Series 900MHz Mobile Antenna with UHF Connector
 MM-90
 3.5" Diameter Magnetic Mount, 10' RG-58/U cable with N Female Connector
 MM-110
 4.3" Diameter Magnetic Mount, 10' RG-58/U cable with N Female Connector
 MM-TM
 Trunk Lid Mount for Mobile Antennas, 10' RG-58/U cable with N Female Connector
 MM-SM-LP
 Low Profile ThruHole Surface Mount for Mobile Antennas, 10' RG-58/U cable with N Female Connector
 ThruHole Surface Mount for Mobile Antennas, 10' RG-58/U cable with N Female Connector

#### For further information contact:

