

§ 15.407(f)	Maximum Permissible Exposure				
Test Requirement(s):	<b>§15.407(f):</b> U-NII devices are subject to the radio frequency radiation exposure requirements specified in §1.1307(b), §2.1091 and §2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment.				
RF Exposure Requirements:	<b>§1.1307(b)(1) and §1.1307(b)(2):</b> Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.				
<b>RF Radiation Exposure Limit:</b>	<b>§1.1310:</b> As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.				
MDE Limit: EU	T's operating frequencies @ 5180 5240 MHz 5250 5320 MHz				

MPE Limit: EUT's operating frequencies @ 5180 - 5240 MHz, 5250 - 5320 MHz, 5500 - 5710 MHz, 5745 - 5825 MHz and 2400 - 2483.5 MHz; Limit for Uncontrolled exposure: 1 mW/cm<sup>2</sup> or 10 W/m<sup>2</sup>

Equation from page 18 of OET 65, Edition 97-01

 $S = PG / 4\pi R^2$  or  $R = \int (PG / 4\pi S)$ 

where,  $S = Power Density (mW/cm^2)$ 

P = Power Input to antenna (mW)

G = Antenna Gain (numeric value)

R = Distance (cm)

FCC											
Frequency (MHz)	Con. Pwr. (dBm)	Con. Pwr. (mW)	Ant. Gain (dBi)	Ant. Gain numeric	Pwr. Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Margin	Distance (cm)	Result		
2402*	13.35	21.63	5.0	3.16	0.014	1.0	-0.986	20	Pass		
2442*	24.22	246.24	4.0	2.51	0.123	1.0	-0.877	20	Pass		
5240*	27.16	520.00	5.9	3.89	0.403	1.0	-0.597	20	Pass		
5795	24.39	274.79	5.9	3.89	0.213	1.0	-0.787	20	Pass		
5310	23.99	250.61	5.9	3.89	0.194	0.920	0.726	20	Pass		
5710	23.96	248.89	5.9	3.89	0.193	0.967	0.774	20	Pass		
*Simultaneous Transmission (Worse case):				0.540	1.0	-0.460	20	Pass			

**Test Results**:

The safe distance for SWX-U6IWR where Power Density is less than the MPE Limit listed above was found to be 20 cm.