

<u>UNII 1</u>

§ 15.407(f)	Maximum Permissible Exposure						
Test Requirement(s):	§15.407(f): U-NII devices are subject to the radio frequency radiation exposure requirements specified in §1.1307(b), §2.1091 and §2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment.						
RF Exposure Requirements:	§1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions this section shall be operated in a manner that ensures that the public is exposed to radio frequency energy levels in excess of the Commission guidelines.						
RF Radiation Exposure Limit:	§1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.						
MPE Limit: EUT's operating frequencies @ <u>5180 – 5240 MHz</u> , <u>5745 – 5825 MHz and</u> <u>2400 – 2483.5 MHz</u> ; Limit for Uncontrolled exposure: 1 mW/cm ² or 10 W/m ²							
Equation from page 18 of OET 65, Edition 97-01							
S – PG	$\sqrt{4\pi P^2}$ or $P = \sqrt{(PG \sqrt{4\pi S})}$						

 $S = PG / 4\pi R^2$ or $R = \int (PG / 4\pi S)$

where, $S = Power Density (mW/cm^2)$

P = Power Input to antenna (mW)

- G = Antenna Gain (numeric value)
- R = Distance (cm)

Test Results:

FCC											
Frequency (MHz)	Con. Pwr. (dBm)	Con. Pwr. (mW)	Ant. Gain (dBi)	Ant. Gain numeric	Pwr. Density (mW/cm ²)	Limit (mW/cm ²)	Margin	Distance (cm)	Result		
5240	28.6	724.44	6	3.98	0.577	1.0	-0.423	20	Pass		
2437	23.4	218.78	3	1.99	0.07	1.0	-0.93	20	Pass		

*There is no simultaneous transmission

The safe distance for SWX-U6MESH where Power Density is less than the MPE Limit listed above was found to be 20 cm.