



427 West 12800 South
Draper, UT 84020

Test Report Certification

FCC ID	SWX-U7PRO
ISED ID	6545A-U7PRO
Equipment Under Test	U7-Pro
Test Report Serial Number	TR8585_04
Date of Tests	29 August; 1, 12, 14 October 2023
Report Issue Date	12 December 2023

Test Specification	Applicant
47 CFR FCC Part 15, Subpart E	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.



NVLAP LAB CODE 600241-0

Certification of Engineering Report

This report has been prepared by Unified Compliance Laboratory (UCL) to document compliance of the device described below with the requirement of Federal Communication Commissions (FCC) Part 15, Subpart E. This report may be reproduced in full. Partial reproduction of this report may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested.

Applicant	Ubiquiti Inc.
Manufacturer	Ubiquiti Inc.
Brand Name	UBIQUITI
Model Number	U7-Pro
FCC ID	SWX-U7PRO
ISED ID	6545A-U7PRO

On this 12th day of December 2023, I individually and for Unified Compliance Laboratory certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge and are made in good faith.

Although NVLAP has accredited the Unified Compliance Laboratory testing facilities, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. federal government.

Unified Compliance Laboratory



Written By: Kimberly Rodriguez



Reviewed By: Richard L. Winter

Revision History		
Revision	Description	Date
01	Original Report Release	24 October 2023
02	Updated Section 5.1 for beamforming gain and Section 2.10 for channel puncturing and RU considerations.	7 December 2023
03	Added information on partial RU considerations into section 2.6	11 December 2023
04	Added CBP Test Equipment to Section 4, RE diagrams to Section 4.3, RU test Data to section 5.6, updated CBP test procedure to include 0dBi antenna gain in section 5.7	12 December 2023

Table of Contents

1	Client Information.....	5
1.1	Applicant.....	5
1.2	Manufacturer.....	5
2	Equipment Under Test (EUT).....	6
2.1	Identification of EUT.....	6
2.2	Description of EUT.....	6
2.3	EUT and Support Equipment.....	7
2.4	Interface Ports on EUT.....	7
2.5	Operating Environment.....	7
2.6	Operating Modes.....	8
2.7	EUT Exercise Software.....	8
2.8	Block Diagram of Test Configuration.....	8
2.9	Modification Incorporated/Special Accessories on EUT.....	8
2.10	Deviation, Opinions Additional Information or Interpretations from Test Standard.....	8
3	Test Specification, Method and Procedures.....	9
3.1	Test Specification.....	9
3.2	Methods & Procedures.....	9
3.3	FCC Part 15, Subpart E.....	9
3.4	Results.....	9
3.5	Test Location.....	10
4	Test Equipment.....	11
4.1	Conducted Emissions at Mains Ports.....	11
4.2	Direct Connect at the Antenna Port Tests.....	11
4.3	Radiated Emissions.....	12
4.4	Contention Base Protocol Tests.....	13
4.5	Equipment Calibration.....	14
4.6	Measurement Uncertainty.....	14
5	Test Results.....	15
5.1	§15.203 Antenna Requirements.....	15
5.2	Conducted Emissions at Mains Ports Data.....	16
5.3	§15.403(i) 26 dB Emissions Bandwidth.....	18
5.4	§15.407(a)(3) Maximum Average Output Power.....	19
5.5	§15.407(b)(7) Spurious Emissions.....	21
5.6	§15.407(a) Maximum Power Spectral Density.....	25
5.7	§15.407(d) Contention Based Protocol.....	32

1 Client Information

1.1 Applicant

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

1.2 Manufacturer

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

2 Equipment Under Test (EUT)

2.1 Identification of EUT

Brand Name	UBIQUITI
Model Number	U7-PRO
Serial Number	9AZ 003
Dimensions (cm)	20.6 x 20.6 x 4.6

2.2 Description of EUT

The U7-Pro is WiFi 7 access point that represents the next generation of competitively priced, prosumer wireless technology for home and enterprise users. The U7-Pro provides high aggregate throughput speeds. The U7-Pro transmit in the 2.4 GHz, 5 GHz and 6 GHz frequency bands and uses integrated antennas. The U7-Pro is powered from an 802.3at power adapter.

This report covers the circuitry of the device subject to FCC Part 15, Subpart E. The circuitry of the device subject to FCC Part 15 Subpart B was found to be compliant and is covered under a separate Unified Compliance Laboratory test report.

The table below show the channels used within the different modulation bandwidths.

Band	Modulation Bandwidth	Frequency (MHz)	Maximum Power Setting
UNII-5	be (EHT20)	5995	TP10
		6195	TP10
		6415	TP10
	be (EHT40)	5965	TP12
		6205	TP13
		6405	TP13
	be (EHT80)	5985	TP16
		6225	TP16
		6385	TP16
	be (EHT160)	6205	TP19
		6185	TP19
		6325	TP19
	be (EHT320)	6265	TP21
	ax (HE20)	6115	TP10
6195		TP10	
6415		TP10	

ax (HE40)	6125	TP13
	6205	TP13
	6405	TP13
ax (HE80)	6145	TP16
	6225	TP16
	6385	TP16
ax (HE160)	6185	TP19
	6325	TP19

2.3 EUT and Support Equipment

The EUT and support equipment used during the test are listed below.

Brand Name Model Number Serial Number	Description	Name of Interface Ports / Interface Cables
BN: UBIQUITI MN: U7-Pro SN: 9AZ 003	WiFi Access Point	See Section 2.4
BN: UBIQUITI MN: U-POE-at SN: N/A	PoE Power Adapter	Unshielded Cat 5e cable/1 meters
BN: Dell MN: XPS 13 SN: N/A	Laptop Personal Computer	Unshielded Cat 5e cable/1 meters

Notes: (1) EUT

(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

2.4 Interface Ports on EUT

Name of Ports	No. of Ports Fitted to EUT	Cable Description/Length
AC Mains	1	3 conductor power cord/80 cm
POE (POE Injector)	1	Unshielded Cat 5e cable/8 meters
LAN (POE Injector)	1	Unshielded Cat 5e cable/1 meters

2.5 Operating Environment

Power Supply	120 Volts AC Mains to 48 Volts PoE
AC Mains Frequency	60 Hz

Temperature	24.7 – 26.4 °C
Humidity	30.4 – 35.9 %
Barometric Pressure	1017 mBar

2.6 Operating Modes

The U7-Pro was tested using test software in order to enable to constant transmission. The measurements within this report are corrected to reference a 100% duty cycle. All emission modes of 802.11ax were investigated. Partial Resource Units were investigated and found to comply to all requirements. center and edge allocations were measured and are included in the Annex for review. Per the manufacturer the U7-Pro does not support channel puncturing and considerations noted in KDB 987594 D02 per we not applicable.

2.7 EUT Exercise Software

EUT firmware version 1.0 was used to operate the transmitter using a constant transmit mode.

2.8 Block Diagram of Test Configuration




Diagram 1: Test Configuration Block Diagram

2.9 Modification Incorporated/Special Accessories on EUT

There were no modifications made to the EUT during testing to comply with the specification.

2.10 Deviation, Opinions Additional Information or Interpretations from Test Standard

None

3 Test Specification, Method and Procedures

3.1 Test Specification

Title	47 CFR FCC Part 15, Subpart E, Section 15.407 Limits and methods of measurement of radio interference characteristics of Unlicensed National Information Infrastructure Devices
Purpose of Test	The tests were performed to demonstrate initial compliance

3.2 Methods & Procedures

3.2.1 47 CFR FCC Part 15 Section 15.407

See test standard for details.

3.3 FCC Part 15, Subpart E

3.3.1 Summary of Tests

FCC Section	ISED Section	Environmental Phenomena	Frequency Range (MHZ)	Result
15.203	N/A	Antenna requirements	Structural Requirement	Compliant
15.207	RSS-Gen	Conducted Disturbance at Mains Port	0.15 to 30	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Bandwidth Requirement	5955 to 6415	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Peak Output Power ¹	5955 to 6415	Compliant
15.407(f)	RSS-247 §6.2.2, §6.2.3	Antenna Conducted Spurious Emissions ¹	0.009 to 40000	N/A
15.407(a)	RSS-247 §6.2.2, §6.2.3	Radiated Spurious Emissions	0.009 to 40000	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Peak Power Spectral Density ¹	5955 to 6415	Compliant
15.407(d)	RSS-247 §6.2.2, §6.2.3	Contention Based Protocol	5955 to 6415	Compliant

The testing was performed according to the procedures in ANSI C63.10-2013, KDB 789033, KDB 987594 and 47 CFR Part 15. Where applicable, KDB 662911 was followed to sum required measurements.

Note ¹: Various RU modes were considered for RF Power, PSD, and Spurious Emissions, and the "single client" RU mode is the worst case - the results herein are "single client" RU mode.

3.4 Results

In the configuration tested, the EUT complied with the requirements of the specification.

3.5 Test Location

Testing was performed at the Unified Compliance Laboratory 3-meter and 10-meter chamber located at 427 West 12800 South, Draper, UT 84020. Unified Compliance Laboratory is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Code 600241-0 which is effective until 30 June 2024. This site has also been registered with Innovations, Science and Economic Development (ISED) department as was accepted under Appendix B, Phase 1 procedures of the APEC Tel MRA for Canadian recognition. ISED No.: 25346, effective until 30 June 2024.

Unified Compliance Laboratory has been assigned Designation Number US5037 by the FCC and Conformity Assessment Number US0223 by ISED.

4 Test Equipment

4.1 Conducted Emissions at Mains Ports

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	AFJ	FFT3010	UCL-6754	2/22/2023	2/22/2024
LISN	AFJ	LS16C/10	UCL-6749	12/6/2021	12/6/2023
ISN	Teseq	ISN T800	UCL-2974	6/27/2022	6/27/2024
LISN	Com-Power	LIN-120C	UCL-2612	1/24/2023	1/24/2024
AC Power Source	Laplace Instruments	AC1000A	UCL-2857	N/A	N/A
Test Software	UCL	Revision 1	UCL-3107	N/A	N/A

Table 1: List of equipment used for Conducted Emissions Testing at Mains Port




Figure 1: Conducted Emissions Test

4.2 Direct Connect at the Antenna Port Tests

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	R&S	FSV40	UCL-2861	11/7/2022	11/7/2023
Signal Generator	R&S	SMB100A	UCL-2864	N/A	N/A
Vector Signal Generator	R&S	SMBV100A	UCL-2873	N/A	N/A
Switch Extension	R&S	OSP-B157WX	UCL-2867	2/22/2023	2/22/2024
Switch Extension	R&S	OSP-150W	UCL-2870	2/22/2023	2/22/2024

Table 2: List of equipment used for Direct Connect at the Antenna Port




Figure 2: Direct Connect at the Antenna Port Test

4.3 Radiated Emissions

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	Keysight	N9038A	UCL-2778	1/27/2023	1/27/2024
Pre-Amplifier 9 kHz – 1 GHz	Sonoma Instruments	310N	UCL-2889	10/7/2021	10/7/2023
Broadband Antenna	Scwarzbeck	VULB 9163	UCL-3062	9/13/2022	9/13/2024
Broadband Antenna	Scwarzbeck	VULB 9163	UCL-3071	6/08/2022	6/22/2024
Double Ridge Horn Antenna	Scwarzbeck	BBHA 9120D	UCL-3065	9/22/2022	9/22/2024
Log Periodic	Scwarzbeck	STLP 9129	UCL-3068	1/27/2023	1/27/2025
15 - 40 GHz Horn Antenna	Scwarzbeck	BBHA 9170	UCL-2487	6/09/2022	6/09/2024
1 – 18 GHz Amplifier	Com-Power	PAM 118A	UCL-3833	12/9/2022	12/9/2023
Test Software	UCL	Revision 1	UCL-3108	N/A	N/A

Table 3: List of equipment used for Radiated Emissions




Figure 3a: Radiated Emissions Test 30-1000MHz




Figure 4b: Radiated Emissions Test Above 1GHz

4.4 Contention Base Protocol Tests

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	Keysight	N9010B EXA	UCL-7069	4/25/2023	4/25/2024
Signal Generator	Keysight	MXG-B	UCL-6291	6/29/2023	6/29/2024
MIMO Test Set	Keysight	X8750A	UCL-7373	9/19/2023	9/19/2024

Table 4: List of equipment used for Direct Connect at the Antenna Port




Figure 1. CBP conducted test setup diagram. Source: KDB 987594 D02 V01r01

Figure 5: Contention Base Protocol Test

4.5 Equipment Calibration

All applicable equipment is calibrated using either an independent calibration laboratory or Unified Compliance Laboratory personnel at intervals defined in ANSI C63.4:2014 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to traceability is on file and is available for examination upon request.

4.6 Measurement Uncertainty

Test	Uncertainty (\pm dB)	Confidence (%)
Conducted Emissions	1.44	95
Radiated Emissions (9 kHz to 30 MHz)	2.50	95
Radiated Emissions (30 MHz to 1 GHz)	4.38	95
Radiated Emissions (1 GHz to 18 GHz)	4.37	95
Radiated Emissions (18 GHz to 40 GHz)	3.93	95
Direct Connect Tests	K Factor	Value
Emissions Bandwidth	2	2.0%
Output Power	2	1.0 dB
Peak Power Spectral Density	2	1.3 dB
Band Edge	2	0.8 dB
Transmitter Spurious Emissions	2	1.8 dB

5 Test Results

5.1 §15.203 Antenna Requirements

The EUT uses an integral antenna. Per the manufacturer, the Maximum gain of the antenna per chain is 5.8 dBi. This is an 802.11 device and utilizes CDD as described in KDB 662911 D01. The antenna is not user replaceable. For CDD transmissions, directional gain is calculated as follows.

$$\text{Array Gain} = 10 \log(\text{NANT}/\text{NSS}) \text{ dB}$$

NANT = number of transmit antennas and

NSS = number of spatial streams. NSS = 1 considered worst case.

For power measurements on IEEE 802.11 devices, Array Gain = 0 dB for $\text{NANT} \leq 4$;


For PSD measurements when $\text{Nss}=1$: Array Gain = $10 \log(\text{NANT}/\text{NSS})$ (dB) + Antenna Gain (dBi). Or $3.01 \text{ dB} + 5.8 \text{ dBi} = 8.81 \text{ dBi}$

Results

The EUT complied with the specification


5.2 Conducted Emissions at Mains Ports Data

5.2.1 Line



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBµV	dBµV	dBµV	dB	dBµV	dB	P/F
2	546,000kHz	12.23	0.00		QPeak	38.16	50.39	56.00	-5.61			
3	153,000kHz	12.26	0.00		QPeak	41.82	54.08	65.84	-11.76			
5	12.996	12.27	0.00		QPeak	33.02	45.29	60.00	-14.71			
1	549,000kHz	12.23	0.00		C_AVG	33.22	45.45			46.00	-0.55	
4	153,000kHz	12.26	0.00		C_AVG	25.61	37.87			55.84	-17.96	
6	12.981	12.27	0.00		C_AVG	26.77	39.04			50.00	-10.96	

5.2.2 Neutral



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBµV	dBµV	dBµV	dB	dBµV	dB	P/F
1	546,000kHz	12.18	0.00		QPeak	37.58	49.76	56.00	-6.24			
5	150,000kHz	12.21	0.00		QPeak	42.89	55.10	66.00	-10.90			
7	153,000kHz	12.21	0.00		QPeak	42.12	54.33	65.84	-11.50			
3	12.993	12.29	0.00		QPeak	31.97	44.26	60.00	-15.74			
2	549,000kHz	12.18	0.00		C_AVG	32.76	44.94			46.00	-1.06	
4	12.966	12.29	0.00		C_AVG	25.48	37.77			50.00	-12.23	
6	153,000kHz	12.21	0.00		C_AVG	26.39	38.60			55.84	-17.24	

Result

The EUT complied with the specification limit.

5.3 §15.403(i) 26 dB Emissions Bandwidth

All chains were measured under the guidance of KDB 789033 Section II.C. and KDB 66291 D01. Please see associated annex for details on instrument settings.

Nominal BW (MHz)	Frequency (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)
EHT 20	5955	19.20	22.90
EHT 20	6195	19.10	23.80
EHT 20	6415	19.10	22.30
EHT 40	5965	38.25	41.73
EHT 40	6205	38.25	42.48
EHT 40	6405	38.25	42.33
EHT 80	5985	78.00	88.00
EHT 80	6225	78.00	89.00
EHT 80	6385	77.50	88.00
EHT 160	6025	157.00	167.00
EHT 160	6185	158.00	170.00
EHT 160	6325	158.00	168.00
EHT 320	6265	317.50	337.24
HE 20	6115	19.10	23.00
HE 20	6195	19.20	22.10
HE 20	6415	19.20	22.60
HE 40	6125	38.00	44.13
HE 40	6205	38.25	42.33
HE 40	6405	38.25	42.48
HE 80	6145	77.50	89.00
HE 80	6225	77.50	85.50
HE 80	6385	78.00	88.50
HE 160	6185	157.00	170.00
HE 160	6325	157.00	172.00

Result

All chains were tested and the highest bandwidth per chain is reported above.

The 26 dB bandwidths are reported for information purposes. Please see Annex for all bandwidth measurements.

5.4 §15.407(a)(3) Maximum Average Output Power

All chains were measured and summed under the guidance of KDB 789033 Section II. E.2. and KDB 66291 D01. Please see associated annex for details on instrument settings.

The maximum average RF conducted output power measured for this device was 23.59 dBm or 228.56 mW. The limit is 30 dBm EIRP, or 1 watt EIRP. The antenna has a gain of 5.8 dBi.

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Conducted Output Power	EIRP	Measured PSD
EHT 20	5955	Mcs0_Nss4	10	12.14	17.94	-1.27
EHT 20	6195	Mcs0_Nss4	10	12.69	18.49	-0.87
EHT 20	6415	Mcs0_Nss4	10	12.87	18.67	-1.33
EHT 40	5965	Mcs0_Nss4	12	15.62	21.42	-1.72
EHT 40	6205	Mcs0_Nss4	13	15.74	21.54	-1.11
EHT 40	6405	Mcs0_Nss4	13	16.05	21.85	-1.27
EHT 80	5985	Mcs0_Nss4	16	18.38	24.18	-0.99
EHT 80	6225	Mcs0_Nss4	16	18.62	24.42	-1.16
EHT 80	6385	Mcs0_Nss4	16	18.71	24.51	-1.49
EHT 160	6025	Mcs0_Nss4	19	20.89	26.69	-1.24
EHT 160	6185	Mcs0_Nss4	19	21.12	26.92	-1.02
EHT 160	6325	Mcs0_Nss4	19	21.82	27.62	-1.37
EHT 320	6265	Mcs0_Nss4	21	23.59	29.39	-1.56
HE 20	6115	Mcs0_Nss4	10	12.07	17.87	-1.27
HE 20	6195	Mcs0_Nss4	10	12.65	18.45	-0.88
HE 20	6415	Mcs0_Nss4	10	12.78	18.58	-1.32
HE 40	6125	Mcs0_Nss4	13	14.88	20.68	-1.48
HE 40	6205	Mcs0_Nss4	13	15.68	21.48	-1.21
HE 40	6405	Mcs0_Nss4	13	15.97	21.77	-1.37
HE 80	6145	Mcs0_Nss4	16	17.81	23.61	-1.36
HE 80	6225	Mcs0_Nss4	16	18.57	24.37	-1.24
HE 80	6385	Mcs0_Nss4	16	18.68	24.48	-1.57
HE 160	6185	Mcs0_Nss4	19	21.05	26.85	-1.08
HE 160	6325	Mcs0_Nss4	19	21.63	27.43	-1.30

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Conducted Output Power	EIRP	Measured PSD
EHT 20	5955	Mcs0_Nss1	7	8.99	14.79	-3.88
EHT 20	6195	Mcs0_Nss1	7	9.21	15.01	-4.18
EHT 20	6415	Mcs0_Nss1	7	9.74	15.54	-4.37
EHT 40	5965	Mcs0_Nss1	9	11.42	17.22	-4.41
EHT 40	6205	Mcs0_Nss1	10	12.64	18.44	-4.06
EHT 40	6405	Mcs0_Nss1	10	12.92	18.72	-4.18
EHT 80	5985	Mcs0_Nss1	12	14.60	20.40	-4.37
EHT 80	6225	Mcs0_Nss1	13	15.41	21.21	-4.22
EHT 80	6385	Mcs0_Nss1	13	15.79	21.59	-4.32
EHT 160	6025	Mcs0_Nss1	16	18.09	23.89	-3.78
EHT 160	6185	Mcs0_Nss1	16	18.14	23.94	-3.89
EHT 160	6325	Mcs0_Nss1	16	18.95	24.75	-3.90
EHT 320	6265	Mcs0_Nss1	19	21.44	27.24	-3.72

Result

In the configuration tested, the maximum average RF output power was less than 1 watt EIRP; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots in attached Annex).

5.5 §15.407(b)(7) Spurious Emissions

5.5.1 Conducted Spurious Emissions

The frequency range from the lowest frequency generated or used in the device to the tenth harmonic of the highest fundamental frequency was investigated to measure any antenna-conducted emissions. The graphs show the measurement data from spurious emissions noted across the frequency range when transmitting at the lowest frequency, middle frequency and upper frequency. Shown below are plots with the EUT turned to the upper and lower channels with the antenna gain of 5.8 dBi accounted for. These demonstrate compliance with the provisions of this section at the band edges.

The emissions must be remaining below -27 dBm EIRP.

Result

Conducted spurious emissions were attenuated below the limit; therefore, the EUT complies with the specification.


5.5.2 Radiated Spurious Emissions in the Restricted Bands of § 15.205

The EUT uses various power settings based on the channel in use. In order to reduce test time, the radiated spurious emissions at the lowest, middle, and highest channel were measured at the maximum power of TP23.

Correction Factor = Antenna Factor + Cable Loss - Pre-Amplifier Gain, and is added to the Receiver reading.

Result


All emissions in the restricted bands of § 15.205 met the limits specified in § 15.209; therefore, the EUT complies with the specification. See Annex for Conducted Band edge plots.



QuasiPeak


Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin	Azimuth (°)	Height	Pol.	Correction (dB)
31.692 MHz	20.029	40	-19.971	69	2.759	Vertical	-8.569
32.681 MHz	32.403	40	-7.597	199	1	Vertical	-9.148
129.41 MHz	29.287	40	-10.713	341	1.138	Vertical	-14.232
31.369 MHz	20.912	40	-19.088	251	1.143	Horizontal	-8.51
32.273 MHz	29.759	40	-10.241	50	3.298	Horizontal	-8.831
243.82 MHz	27.376	47	-19.624	278	1.52	Horizontal	-15.915

Table 5: Radiated Emissions 30 – 1000 MHz



Frequency	SR #	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
7.3515 GHz	Peak	49.105	74	-24.895	177	2.398	Vertical	10.465
12.412 GHz	Peak	54.735	74	-19.265	31	1.638	Vertical	16.315
15.701 GHz	Peak	56.045	74	-17.955	31	1.996	Vertical	16.205
7.3515 GHz	AVG	32.27	54	-21.73	177	2.398	Vertical	10.465
12.412 GHz	AVG	36.987	54	-17.013	31	1.638	Vertical	16.315
15.701 GHz	AVG	37.389	54	-16.611	31	1.996	Vertical	16.205
12.387 GHz	Peak	56.916	74	-17.084	60	2.218	Horizontal	16.362
16.867 GHz	Peak	57.119	74	-16.881	7	2.897	Horizontal	18.552
12.387 GHz	AVG	39.941	54	-14.059	60	2.218	Horizontal	16.362
16.867 GHz	AVG	36.902	54	-17.098	7	2.897	Horizontal	18.552

Table 6: Transmitting on the Middle Frequency 6195 MHz



Frequency	SR #	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Pol.	RBW (Hz)	Correction (dB)
17.013 GHz	Peak	50.362	74	-23.638	259	Horizontal	1 M	-0.014
17.013 GHz	AVG	37.261	54	-16.739	259	Horizontal	1 M	-0.014

Table 7: Transmitting on the Middle Frequency 6195 MHz

5.6 §15.407(a) Maximum Power Spectral Density

The maximum average power spectral density conducted from the intentional radiator of the antenna shall not be greater than 5 dBm EIRP in any 1 MHz band during any time interval of continuous transmission. Results of this testing are summarized.

NSS=4 Test Results

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Conducted Output Power	Measured PSD
EHT 20	5955	Mcs0_Nss4	10	12.14	-1.27
EHT 20	6195	Mcs0_Nss4	10	12.69	-0.87
EHT 20	6415	Mcs0_Nss4	10	12.87	-1.33
EHT 40	5965	Mcs0_Nss4	12	15.62	-1.72
EHT 40	6205	Mcs0_Nss4	13	15.74	-1.11
EHT 40	6405	Mcs0_Nss4	13	16.05	-1.27
EHT 80	5985	Mcs0_Nss4	16	18.38	-0.99
EHT 80	6225	Mcs0_Nss4	16	18.62	-1.16
EHT 80	6385	Mcs0_Nss4	16	18.71	-1.49
EHT 160	6025	Mcs0_Nss4	19	20.89	-1.24
EHT 160	6185	Mcs0_Nss4	19	21.12	-1.02
EHT 160	6325	Mcs0_Nss4	19	21.82	-1.37
EHT 320	6265	Mcs0_Nss4	21	23.59	-1.56
HE 20	6115	Mcs0_Nss4	10	12.07	-1.27
HE 20	6195	Mcs0_Nss4	10	12.65	-0.88
HE 20	6415	Mcs0_Nss4	10	12.78	-1.32
HE 40	6125	Mcs0_Nss4	13	14.88	-1.48
HE 40	6205	Mcs0_Nss4	13	15.68	-1.21
HE 40	6405	Mcs0_Nss4	13	15.97	-1.37
HE 80	6145	Mcs0_Nss4	16	17.81	-1.36
HE 80	6225	Mcs0_Nss4	16	18.57	-1.24
HE 80	6385	Mcs0_Nss4	16	18.68	-1.57
HE 160	6185	Mcs0_Nss4	19	21.05	-1.08
HE 160	6325	Mcs0_Nss4	19	21.63	-1.30

NSS=1 Tet Results

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Conducted Output Power	Measured PSD
EHT 20	5955	Mcs0_Nss1	7	8.99	-3.88
EHT 20	6195	Mcs0_Nss1	7	9.21	-4.18
EHT 20	6415	Mcs0_Nss1	7	9.74	-4.37
EHT 40	5965	Mcs0_Nss1	9	11.42	-4.41
EHT 40	6205	Mcs0_Nss1	10	12.64	-4.06
EHT 40	6405	Mcs0_Nss1	10	12.92	-4.18
EHT 80	5985	Mcs0_Nss1	12	14.60	-4.37
EHT 80	6225	Mcs0_Nss1	13	15.41	-4.22
EHT 80	6385	Mcs0_Nss1	13	15.79	-4.32
EHT 160	6025	Mcs0_Nss1	16	18.09	-3.78
EHT 160	6185	Mcs0_Nss1	16	18.14	-3.89
EHT 160	6325	Mcs0_Nss1	16	18.95	-3.90
EHT 320	6265	Mcs0_Nss1	19	21.44	-3.72

Result

The maximum average power spectral density was less than the limit of 5 dBm EIRP; therefore, the EUT complies with the specification.

5.6.1 OFDMA RU Check

If EUT supports OFDMA multiple partial Resource Unit (RU) configurations were verified and the worst case mode was tested.




Figure 6: 6195 20MHz RU Vérification - Center




Figure 7: 6195 20MHz RU Vérification - Edge




Figure 8: 6195 20MHz RU Vérification - Center




Figure 9: 6195 20MHz RU Vérification - Edge




Figure 10: 6205 40MHz RU Vérification - Center




Figure 11: 6205 40MHz RU Vérification - Edge




Figure 12: 6225 80MHz RU Vérification - Center




Figure 13: 6225 80MHz RU Vérification - Edge




Figure 14: 6185 160MHz RU Vérification - Center




Figure 15: 6185 160MHz RU Vérification - Edge

5.7 §15.407(d) Contention Based Protocol


This product was tested and found to be compliant with the requirements of Contention-based Protocol as specified in FCC Part 15.407 and KDB 987594 D02.

Initially the test setup was connected directly to the signal source with all splitters (splitters terminated with a 50-ohm loads on unused ports) and cables in place to verify the AWGN signal is 10MHz wide at a signal level of less than or equal to -82dBm and for conducted measurements the threshold was adjusted for an antenna gain for 0dBi. The level at the signal generator required to achieve the required signal level at the DUT was recorded for use during testing.

The DUT was connected as shown in figure 4 above and set to transmit at a constant duty cycle at each frequency and bandwidth noted in the table below and verified to be communicating with the companion device as intended.


Starting at the levels established above, the AWGN signal was introduced to the DUT and increased to determine a threshold level at where the DUT will terminate with at least a 90% detection rate. The level at the DUT, which the 90% detection rate was achieved was recorded as the “Sensitivity Level” below.


Testing shall be repeated at each applicable channel and bandwidth as noted in Table 1 of KDB 987594 D02.



Plot 1: Level Details

Band	BW _{EUT}	F _{c1}	F _{c2}	Signal Power Level (dBm)	Detection Rate (%)	Margin (dB)
UNII-5 5.925 - 6.425GHz	20	6135	6135	-73	100	16.8
	160	6185	6110	-76	100	19.8
			6185	-75	100	18.8
			6260	-76	100	19.8
UNII-6 6.425 - 6.525GHz	20	6455	6455	-73	100	16.8
	160	6505	6430	-76	100	19.8
			6505	-72	100	15.8
			6580	-72	100	15.8
UN1I-7 6.525 - 6.875GHz	20	6695	6695	-72	100	15.8
	160	6665	6590	-68	100	11.8
			6665	-62	100	5.8
			6740	-72	100	15.8
UNII-8 6.875 - 7.125GHz	20	7015	7015	-76	100	19.8
	160	6985	6910	-70	100	13.8
			6985	-70	100	13.8
			7060	-73	100	16.8

Table 8: Trial Table

Plot 2: 20MHz Example Detection Trace



Plot 3: 160MHz Example Detection Trace

Result

The EUT complies with the specification.

-- End of Test Report --