



Radio Frequency Exposure

Applicant : Ubiquiti Inc.
Address : 685 Third Avenue, 27th Floor New York, New York
10017, USA
Equipment : UniFi Intercom
Model No. : UA-Intercom
Trade Name : UBIQUITI
FCC ID : SWX-UAINT

I HEREBY CERTIFY THAT :

The sample was received on Jul. 23, 2024 and the testing was completed on Aug. 12, 2024 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





CONTENTS

1.	Summary of Test Procedure and Test Results	4
1.1.	Applicable Standards	4
2.	Test Configuration of Equipment under Test	5
2.1.	Feature of Equipment under Test.....	5
2.2.	General Information of Test.....	5
2.3.	Measurement Uncertainty	6
3.	Test Equipment and Ancillaries Used for Tests	7
4.	Radio Frequency Exposure	9
4.1.	Applicable Standards	9
4.2.	EUT Specification.....	10
4.3.	Result	10



1. Summary of Test Procedure and Test Results

1.1. Applicable Standards

FCC Rules and Regulations Part 2.1091

FCC Rule	Description of Test	Result
2.1091	Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.

The difference is list below:

1. NFC chipset NXP 7161 changed to NXP 7160
2. eMCP size changed from 2GB to 3GB

note:

- 1) The new chip component is pin-for-pin compatible.
- 2) The new chip has the same basic function as the old chip, from an external perspective (internal circuitry may differ).
- 3) No change in radio parameters has occurred.
- 4) The same conditions apply when a small area (approximately the same area as the chip) of the PCB is replaced with an equivalent chip.



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

Operation Frequency Range	NFC: 13.553MHz~13.567MHz BLE: 2400-2483.5MHz
Center Frequency Range	NFC: 13.56MHz BLE: 2402MHz-2480MHz
Modulation Type	NFC: ASK BLE: GFSK
Modulation Technology	BLE:DTS
Data Rate	BLE: GFSK: 1Mbps
Antenna Type	NFC: Loop Antenna BLE: PIFA Antenna
Antenna Gain	NFC: 0dBi BLE: 4dBi

Note: For more details, please refer to the User's manual of the EUT.

2.2. General Information of Test

☒ Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
Frequency Range Investigated	Conducted: from 150kHz to 30 MHz Radiation: from 9 kHz to 40,000MHz	
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.	

NFC

Test Item	Test Site	Test Period	Environmental Conditions	Tested By
Frequency Stability	RFCON01-NK	2024/08/19	24.5°C / 52%	Pack Chen
Radiated Emissions	3M02-NK	2024/08/12	24.3°C / 47%	Park Chen
AC Power Line Conducted Emission	CON01-NK	2024/08/12	24.6°C / 59%	Leon Huang

BLE

Test Item	Test Site	Test Period	Environmental Conditions	Tested By
Radiated Emissions	3M02-NK	2024/08/12	24.3°C / 47%	Park Chen
AC Power Line Conducted Emission	CON02-NK	2024/08/12	24.6°C / 59%	Leon Huang



2.3. Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

NFC

Measurement Item	Uncertainty
AC Power Line Conducted Emission	$\pm 3.12\text{dB}$
Radiated Spurious Emission(9KHz~30MHz)	$\pm 3.5\text{dB}$
Radiated Spurious Emission(30MHz~1GHz)	$\pm 5.1\text{dB}$
20dB Bandwidth	$\pm 4.4\%$
Occupied Bandwidth	$\pm 4.5\%$
Frequency Stability	$\pm 0.23\text{KHz}$

BLE

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	$\pm 3.12\text{dB}$
Radiated Spurious Emission(9KHz~30MHz)	$\pm 3.5\text{dB}$
Radiated Spurious Emission(30MHz~1GHz)	$\pm 5.1\text{dB}$



3. Test Equipment and Ancillaries Used for Tests

NFC

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	369	2024/02/19	2025/02/18
Active Loop Antenna	Schwarzbeck	FMZB 1513	414	2024/01/16	2025/01/15
Horn Antenna	EMCO	3115	31589	2024/02/26	2025/02/25
Horn Antenna	EMCO	3116	31974	2023/10/16	2024/10/15
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	101329	2024/07/16	2025/07/15
Preamplifier	Agilent	8449B	3008A01954	2024/03/01	2025/02/28
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2023/10/13	2024/10/12
Preamplifier	EM Electronics corp.	EM330	60659	2024/02/17	2025/02/16
Cable-6m(9k~300M)	N/A	EMC5D-BM-BM-6	130606	2024/03/13	2025/03/12
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2024/02/23	2025/02/22
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2024/03/05	2025/03/04
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2024/03/05	2025/03/04
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2024/03/05	2025/03/04
Cable-1m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	804398/2	2023/10/12	2024/10/11
Cable-3m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	804619/2	2023/10/12	2024/10/11
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
Highpass Filter	WOKEN	WFIL-H3000-18000F-03	WR377WC2B1	2023/08/17	2024/08/16
Notch Filter	Warison	WFIL-N5925-7125F-04	WRQ4BFWC4M1	2024/03/11	2025/03/10
Hipass Filter	Warison	WFIL-H7500-18000F	WRQ4BFWC2J1	2024/03/11	2025/03/10

Test Item	Frequency Stability				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MY54200207	2024/04/24	2025/04/23
TEMP & HUMI CHAMBER	T-MACHINE	TMJ-9712	T-12-040111	2024/07/30	2025/07/29

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127516	2023/10/03	2024/10/02
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101934	2024/03/01	2025/02/28
Cable-6m(9k~300M)	N/A	EMC5D-BM-BM-6	130606	2024/03/13	2025/03/12
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



BLE

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	369	2024/02/19	2025/02/18
Active Loop Antenna	Schwarzbeck	FMZB 1513	414	2024/01/16	2025/01/15
Horn Antenna	EMCO	3115	31589	2024/02/26	2025/02/25
Horn Antenna	EMCO	3116	31974	2023/10/16	2024/10/15
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	101329	2024/07/16	2025/07/15
Preamplifier	Agilent	8449B	3008A01954	2024/03/01	2025/02/28
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2023/10/13	2024/10/12
Preamplifier	EM Electronics corp.	EM330	60659	2024/02/17	2025/02/16
Cable-6m(9k~300M)	N/A	EMC5D-BM-BM-6	130606	2024/03/13	2025/03/12
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2024/02/23	2025/02/22
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2024/03/05	2025/03/04
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2024/03/05	2025/03/04
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2024/03/05	2025/03/04
Cable-1m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	804398/2	2023/10/12	2024/10/11
Cable-3m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	804619/2	2023/10/12	2024/10/11
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
Highpass Filter	WOKEN	WFIL-H3000-18000F-03	WR377WC2B1	2023/08/17	2024/08/16
Notch Filter	Warison	WFIL-N5925-7125F-04	WRQ4BFWC4M1	2024/03/11	2025/03/10
Hipass Filter	Warison	WFIL-H7500-18000F	WRQ4BFWC2J1	2024/03/11	2025/03/10

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127516	2023/10/03	2024/10/02
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101934	2024/03/01	2025/02/28
Cable-6m(9k~300M)	N/A	EMC5D-BM-BM-6	130606	2024/03/13	2025/03/12
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



4. Radio Frequency Exposure

4.1. Applicable Standards

<input checked="" type="checkbox"/> §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																										
<input type="checkbox"/> §1.1307(b)(3)(i)(c)	<p>ERP is below a threshold calculated based on the distance , R between the person and t antenna / radiating structure, where $R > \lambda / 2 \pi$.</p> <p style="text-align: center;">TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th colspan="3">RF Source Frequency</th> <th colspan="2">Minimum Distance</th> <th>Threshold ERP</th> </tr> <tr> <th>f_L MHz</th> <th></th> <th>f_H MHz</th> <th>$\lambda_L / 2\pi$</th> <th></th> <th>$\lambda_H / 2\pi$</th> </tr> </thead> <tbody> <tr> <td>0.3</td> <td>–</td> <td>1.34</td> <td>159 m</td> <td>–</td> <td>35.6 m</td> </tr> <tr> <td>1.34</td> <td>–</td> <td>30</td> <td>35.6 m</td> <td>–</td> <td>1.6 m</td> </tr> <tr> <td>30</td> <td>–</td> <td>300</td> <td>1.6 m</td> <td>–</td> <td>159 mm</td> </tr> <tr> <td>300</td> <td>–</td> <td>1,500</td> <td>159 mm</td> <td>–</td> <td>31.8 mm</td> </tr> <tr> <td>1,500</td> <td>–</td> <td>100,000</td> <td>31.8 mm</td> <td>–</td> <td>0.5 mm</td> </tr> </tbody> </table> <p style="text-align: center;">Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.</p>	RF Source Frequency			Minimum Distance		Threshold ERP	f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	0.3	–	1.34	159 m	–	35.6 m	1.34	–	30	35.6 m	–	1.6 m	30	–	300	1.6 m	–	159 mm	300	–	1,500	159 mm	–	31.8 mm	1,500	–	100,000	31.8 mm	–	0.5 mm
RF Source Frequency			Minimum Distance		Threshold ERP																																						
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$																																						
0.3	–	1.34	159 m	–	35.6 m																																						
1.34	–	30	35.6 m	–	1.6 m																																						
30	–	300	1.6 m	–	159 mm																																						
300	–	1,500	159 mm	–	31.8 mm																																						
1,500	–	100,000	31.8 mm	–	0.5 mm																																						
<input checked="" type="checkbox"/> § 1.1307(b)(3)(i)(B).	<p>Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$</p> $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>Where</p> $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ <p>and</p> $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p style="text-align: center;">$d = \text{the separation distance (cm);}$</p>																																										



4.2. EUT Specification

Frequency band (Operating)	<input type="checkbox"/> WLAN: 2412MHz ~ 2462MHz <input type="checkbox"/> WLAN: 5150MHz ~ 5250MHz <input type="checkbox"/> WLAN: 5250MHz ~ 5350MHz <input type="checkbox"/> WLAN: 5470MHz ~ 5725MHz <input type="checkbox"/> WLAN: 5725MHz ~ 5850MHz <input checked="" type="checkbox"/> Bluetooth: 2402MHz ~ 2480MHz <input checked="" type="checkbox"/> NFC: 13.553MHz ~ 13.567MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption
Remark:	
The maximum conducted output power is 57.384 dBm (1.00mW) at 13.56MHz (with 0.00dBi antenna gain.)	

4.3. Result

Channel Frequency (MHz)	Fundamental Emission (dBm)	Antenna Gain (dBi)	Conducted Power (dBm)	Max. Tune up power (dBm)	Fundamental Emission (mW)	Limit (mW)
13.56	-37.85	0.00	-37.85	-37.35	0.00018413	1.00

Antenna Gain (dBi)	Antenna Gain (linear)	Distance (m)	Fundamental Emission (dBuV/m)	Fundamental Emission (V/m)	Fundamental Emission (W)	Fundamental Emission (dBm)
0	1	3	57.38	0.00073960528	0.00000016410	-37.85

No non-compliance noted.

-----THE END OF REPORT-----