

Test Engineer:	Osolemio Chang	Temperature:	21~25	°C
Test Date:	2016/7/31	Relative Humidity:	51~54	%

TEST RESULTS DATA
26dB and 99% OBW

Band II															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	52	5260	17.80	18.10	24.84	32.88	23.50		29.50		23.98		
11a	6Mbps	2	60	5300	17.85	18.00	27.00	33.84	23.52		29.52		23.98		
11a	6Mbps	2	64	5320	17.70	17.80	24.84	26.16	23.48		29.48		23.98		
HT20	MCS0	2	52	5260	19.00	19.60	27.72	38.40	23.79		29.79		23.98		
HT20	MCS0	2	60	5300	18.75	19.95	28.68	40.56	23.73		29.73		23.98		
HT20	MCS0	2	64	5320	18.80	18.80	25.44	26.88	23.74		29.74		23.98		
HT40	MCS0	2	54	5270	37.00	37.50	53.00	77.40	23.98		30.00		23.98		
HT40	MCS0	2	62	5310	36.80	36.70	47.20	46.20	23.98		30.00		23.98		
VHT20	MCS0	2	52	5260	18.90	19.35	27.60	41.04	23.76		29.76		23.98		
VHT20	MCS0	2	60	5300	19.15	19.45	31.92	40.20	23.82		29.82		23.98		
VHT20	MCS0	2	64	5320	18.65	18.80	25.20	29.04	23.71		29.71		23.98		
VHT40	MCS0	2	54	5270	36.80	37.70	53.00	78.00	23.98		30.00		23.98		
VHT40	MCS0	2	62	5310	36.70	36.60	45.60	45.60	23.98		30.00		23.98		
VHT80	MCS0	2	58	5290	75.72	75.72	89.60	87.36	23.98		30.00		23.98		

TEST RESULTS DATA
Average Power Table

FCC Band II															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	52	5260	0.25	0.25	18.34	19.23	21.82	23.98	4.00	26.99	Pass		
11a	6Mbps	2	60	5300	0.25	0.25	18.40	19.52	22.01	23.98	4.00	26.99	Pass		
11a	6Mbps	2	64	5320	0.25	0.25	17.06	17.93	20.53	23.98	4.00	26.99	Pass		
HT20	MCS0	2	52	5260	0.23	0.30	18.85	19.55	22.23	23.98	4.00	26.99	Pass		
HT20	MCS0	2	60	5300	0.23	0.30	18.67	19.78	22.27	23.98	4.00	26.99	Pass		
HT20	MCS0	2	64	5320	0.23	0.30	17.07	17.95	20.54	23.98	4.00	26.99	Pass		
HT40	MCS0	2	54	5270	0.43	0.44	18.90	19.67	22.31	23.98	4.00	26.99	Pass		
HT40	MCS0	2	62	5310	0.43	0.44	16.07	16.90	19.51	23.98	4.00	26.99	Pass		
VHT20	MCS0	2	52	5260	0.23	0.23	18.79	19.55	22.20	23.98	4.00	26.99	Pass		
VHT20	MCS0	2	60	5300	0.23	0.23	18.59	19.78	22.24	23.98	4.00	26.99	Pass		
VHT20	MCS0	2	64	5320	0.23	0.23	16.95	18.02	20.53	23.98	4.00	26.99	Pass		
VHT40	MCS0	2	54	5270	0.47	0.47	19.14	19.42	22.29	23.98	4.00	26.99	Pass		
VHT40	MCS0	2	62	5310	0.47	0.47	16.02	16.89	19.49	23.98	4.00	26.99	Pass		
VHT80	MCS0	2	58	5290	0.86	0.86	13.01	13.84	16.45	23.98	4.00	26.99	Pass		

TEST RESULTS DATA
Power Spectral Density

Band II														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	52	5260	0.25	0.25			9.75	9.99		7.01		Pass
11a	6Mbps	2	60	5300	0.25	0.25			9.75	9.99		7.01		Pass
11a	6Mbps	2	64	5320	0.25	0.25			8.43	9.99		7.01		Pass
HT20	MCS0	2	52	5260	0.23	0.30			9.71	9.99		7.01		Pass
HT20	MCS0	2	60	5300	0.23	0.30			9.79	9.99		7.01		Pass
HT20	MCS0	2	64	5320	0.23	0.30			8.18	9.99		7.01		Pass
HT40	MCS0	2	54	5270	0.43	0.44			6.63	9.99		7.01		Pass
HT40	MCS0	2	62	5310	0.43	0.44			4.12	9.99		7.01		Pass
VHT20	MCS0	2	52	5260	0.23	0.23			9.71	9.99		7.01		Pass
VHT20	MCS0	2	60	5300	0.23	0.23			9.69	9.99		7.01		Pass
VHT20	MCS0	2	64	5320	0.23	0.23			8.15	9.99		7.01		Pass
VHT40	MCS0	2	54	5270	0.47	0.47			6.80	9.99		7.01		Pass
VHT40	MCS0	2	62	5310	0.47	0.47			4.20	9.99		7.01		Pass
VHT80	MCS0	2	58	5290	0.86	0.86			-2.00	9.99		7.01		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band III															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	100	5500	17.65	17.65	24.48	24.48	23.47		29.47		23.98		
11a	6Mbps	2	116	5580	17.65	17.75	23.64	23.40	23.47		29.47		23.98		
11a	6Mbps	2	140	5700	17.60	17.65	23.76	23.52	23.46		29.46		23.98		
HT20	MCS0	2	100	5500	18.80	18.60	25.68	24.96	23.70		29.70		23.98		
HT20	MCS0	2	116	5580	18.70	18.65	25.32	24.72	23.71		29.71		23.98		
HT20	MCS0	2	140	5700	18.90	18.65	24.60	24.96	23.71		29.71		23.98		
HT40	MCS0	2	102	5510	36.80	36.90	46.40	45.80	23.98		30.00		23.98		
HT40	MCS0	2	110	5550	36.80	37.10	50.00	49.80	23.98		30.00		23.98		
HT40	MCS0	2	134	5670	36.80	36.80	46.40	47.00	23.98		30.00		23.98		
VHT20	MCS0	2	100	5500	18.55	18.65	25.20	25.80	23.68		29.68		23.98		
VHT20	MCS0	2	116	5580	18.55	18.60	24.72	25.32	23.68		29.68		23.98		
VHT20	MCS0	2	140	5700	18.80	18.80	25.32	25.32	23.74		29.74		23.98		
VHT40	MCS0	2	102	5510	36.80	36.80	46.40	46.00	23.98		30.00		23.98		
VHT40	MCS0	2	110	5550	36.90	37.10	51.60	51.60	23.98		30.00		23.98		
VHT40	MCS0	2	134	5670	36.80	36.80	46.60	46.40	23.98		30.00		23.98		
VHT80	MCS0	2	106	5530	75.96	75.84	90.56	88.64	23.98		30.00		23.98		
VHT80	MCS0	2	122	5610	75.96	75.96	88.64	88.32	23.98		30.00		23.98		

TEST RESULTS DATA
Average Power Table

FCC Band III															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	100	5500	0.25	0.25	15.36	16.03	18.72	23.98	4.00	26.99	Pass		
11a	6Mbps	2	116	5580	0.25	0.25	13.40	15.21	17.41	23.98	4.00	26.99	Pass		
11a	6Mbps	2	140	5700	0.25	0.25	14.52	16.49	18.63	23.98	4.00	26.99	Pass		
HT20	MCS0	2	100	5500	0.23	0.30	15.34	16.03	18.71	23.98	4.00	26.99	Pass		
HT20	MCS0	2	116	5580	0.23	0.30	12.60	14.85	16.88	23.98	4.00	26.99	Pass		
HT20	MCS0	2	140	5700	0.23	0.30	14.40	16.51	18.59	23.98	4.00	26.99	Pass		
HT40	MCS0	2	102	5510	0.43	0.44	14.79	15.72	18.29	23.98	4.00	26.99	Pass		
HT40	MCS0	2	110	5550	0.43	0.44	17.94	19.13	21.58	23.98	4.00	26.99	Pass		
HT40	MCS0	2	134	5670	0.43	0.44	16.68	18.22	20.53	23.98	4.00	26.99	Pass		
VHT20	MCS0	2	100	5500	0.23	0.23	15.40	15.87	18.65	23.98	4.00	26.99	Pass		
VHT20	MCS0	2	116	5580	0.23	0.23	12.65	14.71	16.81	23.98	4.00	26.99	Pass		
VHT20	MCS0	2	140	5700	0.23	0.23	14.30	16.46	18.53	23.98	4.00	26.99	Pass		
VHT40	MCS0	2	102	5510	0.47	0.47	14.95	15.52	18.25	23.98	4.00	26.99	Pass		
VHT40	MCS0	2	110	5550	0.47	0.47	17.92	19.02	21.52	23.98	4.00	26.99	Pass		
VHT40	MCS0	2	134	5670	0.47	0.47	16.64	18.22	20.51	23.98	4.00	26.99	Pass		
VHT80	MCS0	2	106	5530	0.86	0.86	8.23	9.52	11.93	23.98	4.00	26.99	Pass		
VHT80	MCS0	2	122	5610	0.86	0.86	15.17	16.57	18.93	23.98	4.00	26.99	Pass		

TEST RESULTS DATA
Power Spectral Density

Band III														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	100	5500	0.25	0.25			7.71	9.99	7.01			Pass
11a	6Mbps	2	116	5580	0.25	0.25			6.57	9.99	7.01			Pass
11a	6Mbps	2	140	5700	0.25	0.25			6.79	9.99	7.01			Pass
HT20	MCS0	2	100	5500	0.23	0.30			7.24	9.99	7.01			Pass
HT20	MCS0	2	116	5580	0.23	0.30			5.54	9.99	7.01			Pass
HT20	MCS0	2	140	5700	0.23	0.30			6.57	9.99	7.01			Pass
HT40	MCS0	2	102	5510	0.43	0.44			3.85	9.99	7.01			Pass
HT40	MCS0	2	110	5550	0.43	0.44			7.22	9.99	7.01			Pass
HT40	MCS0	2	134	5670	0.43	0.44			5.79	9.99	7.01			Pass
VHT20	MCS0	2	100	5500	0.23	0.23			7.35	9.99	7.01			Pass
VHT20	MCS0	2	116	5580	0.23	0.23			5.71	9.99	7.01			Pass
VHT20	MCS0	2	140	5700	0.23	0.23			6.51	9.99	7.01			Pass
VHT40	MCS0	2	102	5510	0.47	0.47			3.90	9.99	7.01			Pass
VHT40	MCS0	2	110	5550	0.47	0.47			7.24	9.99	7.01			Pass
VHT40	MCS0	2	134	5670	0.47	0.47			5.86	9.99	7.01			Pass
VHT80	MCS0	2	106	5530	0.86	0.86			-5.29	9.99	7.01			Pass
VHT80	MCS0	2	122	5610	0.86	0.86			1.68	9.99	7.01			Pass

TEST RESULTS DATA
26dB and 99% OBW

Straddle Channel															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		Emission Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	144	5720	17.80	17.80	24.60	29.04	-	-	-	-	-	-	
				NII-2C	13.9	14	17.24	20.36	22.43	28.43	23.37				
				NII-3	3.9	3.8	7.36	8.68	30.00	36.02	-				
HT20	MCS0	2	144	5720	18.90	19.30	28.56	38.40	-	-	-	-	-		
				NII-2C	14.5	14.8	18.8	24.92	22.61	28.61	23.74				
				NII-3	4.4	4.5	9.76	13.48	30.00	36.02	-				
HT40	MCS0	2	142	5710	37.00	37.50	53.80	71.60	-	-	-	-	-		
				NII-2C	33.7	34	41	52.6	23.98	30.00	23.98				
				NII-3	3.3	3.5	12.8	19	30.00	36.02	-				
VHT20	MCS0	2	144	5720	18.80	19.15	27.36	37.32	-	-	-	-	-		
				NII-2C	14.5	14.7	18.32	16.2	22.61	28.61	23.10				
				NII-3	4.3	4.45	9.04	21.12	30.00	36.02	-				
VHT40	MCS0	2	142	5710	37.00	37.80	52.60	70.80	-	-	-	-	-		
				NII-2C	33.6	34.2	42.2	55.4	23.98	30.00	23.98				
				NII-3	3.4	3.6	10.4	15.4	30.00	36.02	-				
VHT80	MCS0	2	138	5690	76.08	76.32	111.60	148.40	-	-	-	-	-		
				NII-2C	73.16	73.52	92.2	117.8	23.98	30.00	23.98				
				NII-3	2.92	2.8	19.4	30.6	30.00	36.02	-				

TEST RESULTS DATA
Average Power Table

FCC Straddle Channel														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	144	5720	0.25	0.25	17.16	18.36	20.81	-	4.00	-	-	-
				NII-2C	0.25	0.25	16.24	17.47	19.91	23.37	4.00	4.00	Pass	
				NII-3	0.25	0.25	9.97	11.06	13.56	-	4.00	4.00	Pass	
HT20	MCS0	2	144	5720	0.23	0.30	17.92	19.14	21.58	-	4.00	-	-	-
				NII-2C	0.23	0.30	16.82	18.14	20.54	23.74	4.00	4.00	Pass	
				NII-3	0.23	0.30	11.40	12.25	14.86	-	4.00	4.00	Pass	
HT40	MCS0	2	142	5710	0.43	0.44	17.91	19.31	21.68	-	4.00	-	-	-
				NII-2C	0.43	0.44	17.58	19.01	21.36	23.98	4.00	4.00	Pass	
				NII-3	0.43	0.44	6.51	7.57	10.08	-	4.00	4.00	Pass	
VHT20	MCS0	2	144	5720	0.23	0.23	17.84	19.12	21.54	-	4.00	-	-	-
				NII-2C	0.23	0.23	16.84	18.12	20.54	23.10	4.00	4.00	Pass	
				NII-3	0.23	0.23	10.98	12.23	14.66	-	4.00	4.00	Pass	
VHT40	MCS0	2	142	5710	0.47	0.47	17.98	19.21	21.65	-	4.00	-	-	-
				NII-2C	0.47	0.47	17.62	18.90	21.32	23.98	4.00	4.00	Pass	
				NII-3	0.47	0.47	7.02	7.60	10.33	-	4.00	4.00	Pass	
VHT80	MCS0	2	138	5690	0.86	0.86	18.39	18.34	21.37	-	4.00	-	-	-
				NII-2C	0.86	0.86	18.27	18.22	21.26	23.98	4.00	4.00	Pass	
				NII-3	0.86	0.86	2.78	2.58	5.69	-	4.00	4.00	Pass	

TEST RESULTS DATA
Power Spectral Density

Straddle Channel														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	144	NII-2C	0.25	0.25				9.12	9.99	7.01		Pass
				NII-3	0.25	0.25				9.12	28.99	7.01		Pass
HT20	MCS0	2	144	NII-2C	0.23	0.30				9.60	9.99	7.01		Pass
				NII-3	0.23	0.30				9.60	28.99	7.01		Pass
HT40	MCS0	2	142	NII-2C	0.43	0.44				6.83	9.99	7.01		Pass
				NII-3	0.43	0.44				6.83	28.99	7.01		Pass
VHT20	MCS0	2	144	NII-2C	0.23	0.23				9.53	9.99	7.01		Pass
				NII-3	0.23	0.23				9.53	28.99	7.01		Pass
VHT40	MCS0	2	142	NII-2C	0.47	0.47				6.80	9.99	7.01		Pass
				NII-3	0.47	0.47				6.80	28.99	7.01		Pass
VHT80	MCS0	2	138	NII-2C	0.86	0.86				4.34	9.99	7.01		Pass
				NII-3	0.86	0.86				4.34	28.99	7.01		Pass

TEST RESULTS DATA
Frequency Stability

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	64	5320	5320.000	0.000	0.00	20	108	
11a	6Mbps	1	64	5320	5320.000	0.000	0.00	20	132	
11a	6Mbps	1	64	5320	5319.975	-0.025	-4.70	20	120	
11a	6Mbps	1	64	5320	5320.000	0.000	0.00	-30	120	
11a	6Mbps	1	64	5320	5320.000	0.000	0.00	50	120	

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	100	5500	5500.000	0.000	0.00	20	108	
11a	6Mbps	1	100	5500	5500.000	0.000	0.00	20	132	
11a	6Mbps	1	100	5500	5500.000	0.000	0.00	20	120	
11a	6Mbps	1	100	5500	5500.000	0.000	0.00	-30	120	
11a	6Mbps	1	100	5500	5500.000	0.000	0.00	50	120	