



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Ubiquiti Networks, Inc

Model: UAP-AC-M

Description: UniFi® AC Access Point

Serial Number: N/A

FCC ID: SWX-UAPACM

To

FCC Part 1.1310

Date of Issue: August 30, 2017

On the behalf of the applicant:

Ubiquiti Networks, Inc
2580 Orchard Parkway
San Jose, CA 95131

Attention of:

Mark Feil
Ph: 801-898-1911
E-mail: mark.feil@ubnt.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1770021

Poona Saber
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	August 15, 2017	Poona Saber	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: UAP-AC-M

Description: UniFi® AC Access Point

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information: None

Source Based Time Averaged Power Calculation

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Average Power (mW)
2437	132.12
5825	107.15



MPE Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	2437
Power, Conducted, mW (P)	132.12
Antenna Gain Isotropic	9 dBi
Antenna Gain Numeric (G)	7.94
Antenna Type	Dual Band Array
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) =0.208
Limit =(from above table) = 1

Test Data

Test Frequency, MHz	5825
Power, Conducted, mW (P)	107.15
Antenna Gain Isotropic	15 dBi
Antenna Gain Numeric (G)	31.62
Antenna Type	Dual Band Array
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) =0.674
Limit =(from above table) = 1

END OF TEST REPORT