



UniFi Devices

Rooms make it easier to organize and manage multiple devices simultaneously. [Create a Room](#)

TYPE	NAME	STATUS	FIRMWARE STATUS	MODEL	ROOM	MODE
Unassigned Devices (50)						
Display		Online	Up to date	UC Display 13	-	Digital Signage Lobby Video
Display		Online	Up to date	UC Display 13	-	Digital Signage Lobby Video
Display		Online	Up to date	UC Display 13	-	Digital Signage-
Display		Online	Update available	UC Display 13	-	Digital Signage Lobby Video
Light		Offline	-	ULED PAC	-	-
Light		Pending Adoption	-	-	-	-
Light		Adopting	-	-	-	-
Light		Updating	1.0.1.112	ULED PAC	-	-
Light		Restarting	Update available	ULED PAC	-	-
Light		Managed by other Account	-	-	-	-
Light		Locating	Up to date	ULED PAC	-	On: 100
Light		Online	Up to date	ULED PAC	-	Off
Light		Online	Up to date	ULED PAC	-	On: 100
Light		Online	Up to date	ULED PAC	-	On: 100
Light Dimmer		Online	Up to date	UDIM AC	-	Control: 0 Lights(s)
Light Dimmer		Online	Up to date	UDIM AC	-	Control: 0 Lights(s)
Light Dimmer		Online	Up to date	UDIM AC	-	Control: 2 Lights
Light Dimmer		Online	Up to date	UDIM AC	-	Control: 2 Lights



# Connect Display 13"

PoE-powered, 13" Full HD touchscreen display designed for UniFi Connect.

The Connect Display 13" (UC Display13) is a PoE-powered, HD touchscreen display designed for UniFi Connect. The UC Display13 offers robust functionality with its two presentation modes: Digital Signage and Protect. In Digital Signage Mode, the UC Display13 showcases your custom, multimedia playlists in either landscape or portrait mode, and gives you the ability to schedule when they are presented. This display is ideal for businesses, hotels, convention centers, and other populated venues that need an intuitive, centrally managed content broadcasting solution to enhance the experience of clients and patrons. In Protect Mode, the UC Display13 provides the same intuitive camera management experience as the UniFi Protect application. With its included table mount and optional recessed or wall mounts (sold separately), the UC Display13 can be staged virtually anywhere within your space, and can be set up in minutes with the UniFi Connect web application or mobile app.



## Mechanical

Dimensions	Without table stand: 315.8 x 197.6 x 48.8 mm (12.4 x 7.8 x 1.9") With table stand: 315.8 x 235.9 x 125.5 mm (12.4 x 9.3 x 4.9")
Weight	Without table stand: 1.2 kg (2.65 lb) With table stand: 1.94 kg (4.28 lb)
Mounting	Table stand (included) Recessed mount (optional) Surface mount (optional)

## Hardware

Display size	337 mm (13.3") diagonal
Resolution	1920 x 1080 FHD (16:9)
Display luminance	340 nits (typical)
Touch screen technology	Capacitive multi-touch
Processor	Octa-core ARM® Cortex®-A53 at 2.2 GHz
Memory	Storage: 32 GB RAM: 2 GB
Power input	802.3at PoE+, 48VDC, 0.5A
Connectivity	(1) GbERJ45 port (1) USB-C port (for accessory UC-DisplayCam only)  Bluetooth® 4.2 Wi-Fi 2.4G b/g/n/ac, BW 20/40 MHz Wi-Fi 5G a/n/ac, BW 20/40/80 MHz
Button	Factory reset
Sensors	TOF (time of flight), NFC, G sensor (3-axis accelerometer)
NFC reading range	< 10 mm (< 0.4")
NFC standards	ISO 14443A, 14443B, 15693
NFC technology	NFC Tag 1, 2, 3, 4, 5 MIFARE Classic MIFARE Plus MIFARE Ultra light MIFARE DESFire EV1/EV2
Embedded front camera	5 MP
Microphone	Yes
Speaker	Yes
Operating temperature	0 to 40° C (32 to 104° F)

Operating humidity 20 - 90% noncondensing

Certifications FCC, IC

## Software

Application UniFi Connect

Minimum software requirements Web browser (Chrome™ recommended)

Mobile apps UniFi Connect iOS™ and Android™

### E-label Access

E-label and warning statements can be found in the device/controller GUI under Device > Overview > E-label info