

# FCC Test Report

**FCC ID** : SWX-UDM  
**Equipment** : UniFi Dream Machine  
**Brand Name** : UBIQUITI  
**Model Name** : UDM  
**Applicant** : Ubiquiti Networks, Inc.  
685 Third Avenue, 27th Floor New York,  
New York 10017 USA  
**Manufacturer** : Ubiquiti Networks, Inc.  
685 Third Avenue, 27th Floor New York,  
New York 10017 USA  
**Standard** : 47 CFR FCC Part 15.247

The product was received on Jul. 16, 2018, and testing was started from Jul. 18, 2018 and completed on Nov. 06, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



# Table of Contents

**HISTORY OF THIS TEST REPORT .....3**

**SUMMARY OF TEST RESULT .....4**

**1 GENERAL DESCRIPTION .....5**

1.1 Information.....5

1.2 Testing Applied Standards .....7

1.3 Testing Location Information .....7

1.4 Measurement Uncertainty .....7

**2 TEST CONFIGURATION OF EUT.....8**

2.1 Test Condition .....8

2.2 Test Channel Mode .....8

2.3 The Worst Case Measurement Configuration.....8

2.4 Support Equipment.....9

2.5 Test Setup Diagram .....10

**3 TRANSMITTER TEST RESULT .....11**

3.1 AC Power-line Conducted Emissions .....11

3.2 DTS Bandwidth.....12

3.3 Maximum Conducted Output Power .....13

3.4 Power Spectral Density .....15

3.5 Emissions in Non-restricted Frequency Bands .....16

3.6 Emissions in Restricted Frequency Bands.....17

**4 TEST EQUIPMENT AND CALIBRATION DATA.....20**

**APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS**

**APPENDIX B. TEST RESULTS OF DTS BANDWIDTH**

**APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER**

**APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY**

**APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS**

**APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS**

**APPENDIX G. TEST PHOTOS**

**PHOTOGRAPHS OF EUT V02**



### History of this test report

Report No.	Version	Description	Issued Date
FR870420-01AL	01	Initial issue of report	Nov. 09, 2018
FR870420-01AL	02	Update Photographs of EUT	Nov. 15, 2018



### Summary of Test Result

Report Clause	Ref. Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	FCC 15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	FCC 15.207
3.2	15.247(a)	DTS Bandwidth	PASS	≥500kHz
3.3	15.247(b)	Maximum Conducted Output Power	PASS	Power [dBm]:30
3.4	15.247(e)	Power Spectral Density	PASS	PSD [dBm/3kHz]:8
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	Non-Restricted Bands: >30 dBc
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	Restricted Bands: FCC 15.209

<b>Declaration of Conformity:</b>
The judgment of conformity in the report is based on the measurement results excluding the measurement uncertainty.
<b>Comments and explanations:</b>
None

Reviewed by: Sam Chen

Report Producer: Ann Hou

# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- ♦ Bluetooth LE uses a GFSK (1Mbps) modulation for DSSS.
- ♦ BWch is the nominal channel bandwidth.

### 1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	-	-	internal antenna	I-PEX
2	-	-	internal antenna	I-PEX
3	-	-	internal antenna	I-PEX
4	-	-	internal antenna	I-PEX
5	-	-	internal antenna	I-PEX

Ant.	2.4G		5G		BT	
	Port	Gain (dBi)	Port	Gain (dBi)	Port	Gain (dBi)
1	1	3	4	4.5	-	-
2	2	3	3	4.5	-	-
3	-	-	2	4.5	-	-
4	-	-	1	4.5	-	-
5	-	-	-	-	1	2

Note 1: The EUT has five antennas.

#### For 2.4GHz function:

For IEEE 802.11 b/g/n mode (2TX/2RX)

Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

#### For 5GHz function:

For IEEE 802.11 a/an/ac mode (4TX/4RX)

Ant. 1 (port 4), Ant. 2 (port 3), Ant. 3 (port 2) and Ant. 4 (port 1) could transmit/receive simultaneously.

#### For BT function:

For Bluetooth mode (1TX/1RX)

Ant. 5 (port 1) could transmit/receive simultaneously.



1.1.3 EUT Information

Operational Condition	
EUT Power Type	From AC mains
EUT Function	<input checked="" type="checkbox"/> Point-to-multipoint <input type="checkbox"/> Point-to-point
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device)	
Combined Equipment - Brand Name / Model No.:	...
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems)	
Host System - Brand Name / Model No.:	...
<input type="checkbox"/> Other:	

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
BT-LE(1Mbps)	0.625	2.041	405u	3k

## 1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2013
- ◆ KDB 558074 D01 v05

## 1.3 Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
AC Conduction	CO04-HY	Andy	24.8°C / 56.5%	06/Oct/2018
RF Conducted	TH06-HY	Tim	24.5°C / 52.3%	18/Jul/2018
Radiated	03CH02-HY	Jeff	23.9°C / 55%	06/Nov/2018

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.9 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%
Temperature	0.7 °C	Confidence levels of 95%
Humidity	4 %	Confidence levels of 95%

## 2 Test Configuration of EUT

### 2.1 Test Condition

RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	120V

### 2.2 Test Channel Mode




Test Software	Putty
---------------	-------

### 2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	AC mains mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains




The Worst Case Mode for Following Conformance Tests			
<b>Tests Item</b>	Emissions in Restricted Frequency Bands		
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
<b>Operating Mode &lt; 1GHz</b>	CTX		
1	AC mains mode		
<b>Operating Mode &gt; 1GHz</b>	CTX		
<b>Orthogonal Planes of EUT</b>	<b>X Plane</b>	<b>Y Plane</b>	<b>Z Plane</b>
			
<b>Worst Planes of EUT</b>		V	

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Simultaneous Transmission Analysis
<b>Operating Mode</b>	CTX
1	Bluetooth+WLAN 2.4GHz+WLAN 5GHz
Refer to Sporton Test Report No.: FA870420-01 for Co-location RF Exposure Evaluation.	

## 2.4 Support Equipment

Support Equipment - RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	DoC
2	Adapter for Notebook	DELL	HA65NM130	DoC
3	AC Power Line	N/A	N/A	N/A

## 2.5 Test Setup Diagram



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

Test Method
<ul style="list-style-type: none"> <li>Refer as ANSI C63.10-2013, clause 6.2 foray power-line conducted emissions.</li> </ul>

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

### 3.2 DTS Bandwidth

#### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
<b>Systems using digital modulation techniques:</b>
<ul style="list-style-type: none"> <li>▪ 6 dB bandwidth <math>\geq</math> 500 kHz.</li> </ul>


#### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.2.3 Test Procedures

Test Method
<ul style="list-style-type: none"> <li>▪ For the emission bandwidth shall be measured using one of the options below:</li> </ul>
<input checked="" type="checkbox"/> Refer as KDB 558074, clause 8.2 (11.9.2.2 of ANSI C63.10) DTS bandwidth measurement.
<input type="checkbox"/> Refer as RSS-Gen, clause 6.7 for for occupied bandwidth testing.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

#### 3.2.4 Test Setup



#### 3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

### 3.3 Maximum Conducted Output Power

#### 3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"> <li>▪ If <math>G_{TX} \leq 6</math> dBi, then <math>P_{Out} \leq 30</math> dBm (1 W)</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Point-to-multipoint systems (P2M): If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Point-to-point systems (P2P): If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)/3</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Smart antenna system (SAS):</li> </ul>
	<ul style="list-style-type: none"> <li>- Single beam: If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)/3</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>- Overlap beam: If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)/3</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>- Aggregate power on all beams: If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)/3 + 8</math> dB dBm</li> </ul>
<b>e.i.r.p. Power Limit:</b>	
	<ul style="list-style-type: none"> <li>▪ 2400-2483.5 MHz Band</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Point-to-multipoint systems (P2M): <math>P_{eirp} \leq 36</math> dBm (4 W)</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Point-to-point systems (P2P): <math>P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Smart antenna system (SAS)</li> </ul>
	<ul style="list-style-type: none"> <li>- Single beam: <math>P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>- Overlap beam: <math>P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})</math> dBm</li> </ul>
	<ul style="list-style-type: none"> <li>- Aggregate power on all beams: <math>P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])</math> dBm</li> </ul>
$P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi.	


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> <li>▪ Maximum Peak Conducted Output Power</li> </ul>	
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.1 (11.9.1.1 of ANSI C63.10) RBW ≥ EBW method.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.2 (11.9.1.2 of ANSI C63.10) integrated band power method.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.3 (11.9.1.3 of ANSI C63.10) peak power meter.
<ul style="list-style-type: none"> <li>▪ Maximum Average Conducted Output Power</li> </ul>	
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.2.2 (11.9.2.2 of ANSI C63.10) using a spectrum analyzer.
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.3.2.3 (11.9.2.3 of ANSI C63.10) using a power meter.
<ul style="list-style-type: none"> <li>▪ For conducted measurement.</li> </ul>	
<ul style="list-style-type: none"> <li>▪ If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.</li> </ul>	
<ul style="list-style-type: none"> <li>▪ If multiple transmit chains, EIRP calculation could be following as methods:  <math display="block">P_{total} = P_1 + P_2 + \dots + P_n</math>                     (calculated in linear unit [mW] and transfer to log unit [dBm])  <math display="block">EIRP_{total} = P_{total} + DG</math> </li> </ul>	

### 3.3.4 Test Setup



### 3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

### 3.4 Power Spectral Density

#### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<ul style="list-style-type: none"> <li>Power Spectral Density (PSD) ≤ 8 dBm/3kHz</li> </ul>


#### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures

Test Method
<ul style="list-style-type: none"> <li>Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).</li> </ul>
<input checked="" type="checkbox"/> Refer as KDB 558074, clause 8.4 (11.10 of ANSI C63.10) Method PKPSD.
<ul style="list-style-type: none"> <li>For conducted measurement.             <ul style="list-style-type: none"> <li>If The EUT supports multiple transmit chains using options given below:                 <ul style="list-style-type: none"> <li>Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.</li> </ul> </li> </ul> </li> </ul>

#### 3.4.4 Test Setup



#### 3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

### 3.5 Emissions in Non-restricted Frequency Bands

#### 3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30
<p>Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.</p> <p>Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.</p>	


#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> <li>Refer as KDB 558074, clause 8.5 (11.11 of ANSI C63.10) for non-restricted frequency bands.</li> </ul>

#### 3.5.4 Test Setup



#### 3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



### 3.6 Emissions in Restricted Frequency Bands

#### 3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


#### 3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.6.3 Test Procedures

Test Method	
	<ul style="list-style-type: none"> <li>▪ The average emission levels shall be measured in [duty cycle <math>\geq</math> 98 or duty factor].</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.</li> </ul>
	<ul style="list-style-type: none"> <li>▪ For the transmitter unwanted emissions shall be measured using following options below:</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Refer as KDB 558074, clause 8.6 (11.12 of ANSI C63.10) for restricted frequency bands.</li> </ul>
	<ul style="list-style-type: none"> <li>▪ For the transmitter band-edge emissions shall be measured using following options below:</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Refer as KDB 558074 clause 8.7.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Refer as KDB 558074, clause 8.7.2 (6.10.6 of ANSI C63.10) for marker-delta method for band-edge measurements.</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Refer as KDB 558074, clause 8.7.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).</li> </ul>

### 3.6.4 Test Setup





### 3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

### 3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F

## 4 Test Equipment and Calibration Data

### Instrument for AC Conduction

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR	102051	9KHz ~ 3.6GHz	03/May/2018	02/May/2019
LISN	R&S	ENV216	101295	9kHz ~ 30MHz	17/Nov/2017	16/Nov/2018
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	05/Oct/2018	04/Oct/2019
AC POWER	APC	AFC-11005G	F310050055	47Hz~63Hz 5~300V	NCR	NCR
Impuls Begrenzer Pulse Limiter	SCHWARZBECK	VTSD 9561-F	9561-F041	9 kHz ~ 30 MHz	12/Oct/2017	11/Oct/2018

### NCR : Non-Calibration Require

### Instrument for Radiated Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	27/Oct/2017	26/Oct/2018
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	17/Oct/2018	16/Oct/2019
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	1GHz ~ 18GHz 3m	27/Oct/2017	26/Oct/2018
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	1GHz ~ 18GHz 3m	17/Oct/2018	16/Oct/2019
Amplifier	Agilent	8447D	2944A11149	100kHz ~ 1.3GHz	27Jul/2018	02/Jul/2019
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	23/Apr/2018	19/Apr/2019
Microwave Preamplifier	Agilent	8449B	3008A02373	1GHz ~ 26.5GHz	28/Sep/2017	27/Sep/2018
Microwave System Preamplifier	KEYSIGHT	83017A	MY53270196	1GHz ~ 26.5GHz	05/Sep/2018	04/Sep/2019
Spectrum Analyzer	Rohde & Schwarz	FSP40	100593	9KHz - 40GHz	12/Dec/2017	11/Dec/2018
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100354	9kHz ~ 2.75GHz	08/Dec/2017	07/Dec/2018
RF Cable-R03m	Jye Bao	RG142	CB017	9kHz ~ 1GHz	19/Jan/2018	18/Jan/2019
RF Cable-high	SUHNER	SUCOFLEX104	MY34918/4	1GHz ~ 40GHz	19/Jan/2018	18/Jan/2019
Bilog Antenna	SCHAFFNER	CBL 6112D	2678	30MHz ~ 1GHz	07/Jul/2018	06/Jul/2019
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA 9170154	18GHz ~ 40GHz	06/Feb/2018	05/Feb/2019
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120D	BBHA 9120 D 1531	1GHz ~ 18GHz	18/Apr/ 2018	17/Apr/2019
Preamplifier	MITEQ	TTA1840-35-HG	1864481	18GHz ~ 40GHz	31/Aug/2017	30/Aug/2018
Preamplifier	MITEQ	TTA1840-35-HG	1864481	18GHz ~ 40GHz	24/Aug/2018	23/Aug/2019
Loop Antenna	TESEQ	HLA 6120	31244	9k-30MHz	29/Mar/2018	28/Mar/2019




Instrument for Conducted Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101013	10Hz~40GHz	05/Feb/2018	04/Feb/2019
Signal Generator	Anritsu	MG3694C	163401	10MHz ~ 40GHz	15/Jan/2018	14/Jan/2019
Pulse Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	27/Feb/2018	26/Feb/2019
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	27/Feb/2018	26/Feb/2019
CABLE 0.2m	HUBER	MY37960/4	RF Cable - 17	1 to 18GHz	17/Jan/2018	16/Jan/2019
CABLE 0.2m	HUBER	MY37960/4	RF Cable - 17	30 to 1000MHz	17/Jan/2018	16/Jan/2019
CABLE 0.5m	HUBER	MY37963/4	RF Cable - 22	1 to 18GHz	17/Jan/2018	16/Jan/2019



AC Power-line Conducted Emissions Result																																																																																																																																		
Operating Mode	1	Power Phase	Neutral																																																																																																																															
Operating Function	AC mains mode																																																																																																																																	
<div style="text-align: right;">Date: 2018-10-06</div>																																																																																																																																		
	<table border="1"> <thead> <tr> <th></th> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>Read Level</th> <th>LISN Factor</th> <th>Cable Loss</th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB</th> <th>dBuV</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th></th> </tr> </thead> <tbody> <tr><td>1</td><td>0.18</td><td>43.75</td><td>-10.58</td><td>54.33</td><td>34.12</td><td>9.62</td><td>0.01</td><td>Average</td></tr> <tr><td>2</td><td>0.18</td><td>55.07</td><td>-9.26</td><td>64.33</td><td>45.44</td><td>9.62</td><td>0.01</td><td>QP</td></tr> <tr><td>3</td><td>0.46</td><td>41.80</td><td>-4.87</td><td>46.67</td><td>32.11</td><td>9.61</td><td>0.08</td><td>Average</td></tr> <tr><td>4</td><td>0.46</td><td>48.06</td><td>-8.61</td><td>56.67</td><td>38.37</td><td>9.61</td><td>0.08</td><td>QP</td></tr> <tr><td>5</td><td>0.55</td><td>42.51</td><td>-3.49</td><td>46.00</td><td>32.83</td><td>9.61</td><td>0.07</td><td>Average</td></tr> <tr><td>6</td><td>0.55</td><td>47.35</td><td>-8.65</td><td>56.00</td><td>37.67</td><td>9.61</td><td>0.07</td><td>QP</td></tr> <tr><td>7</td><td>0.58</td><td>40.23</td><td>-5.77</td><td>46.00</td><td>30.56</td><td>9.61</td><td>0.06</td><td>Average</td></tr> <tr><td>8</td><td>0.58</td><td>48.31</td><td>-7.69</td><td>56.00</td><td>38.64</td><td>9.61</td><td>0.06</td><td>QP</td></tr> <tr><td>9 MAX</td><td>0.63</td><td>45.14</td><td>-0.86</td><td>46.00</td><td>35.48</td><td>9.61</td><td>0.05</td><td>Average</td></tr> <tr><td>10</td><td>0.63</td><td>52.32</td><td>-3.68</td><td>56.00</td><td>42.66</td><td>9.61</td><td>0.05</td><td>QP</td></tr> <tr><td>11</td><td>0.68</td><td>42.42</td><td>-3.58</td><td>46.00</td><td>32.76</td><td>9.62</td><td>0.04</td><td>Average</td></tr> <tr><td>12</td><td>0.68</td><td>47.82</td><td>-8.18</td><td>56.00</td><td>38.16</td><td>9.62</td><td>0.04</td><td>QP</td></tr> </tbody> </table>		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark		MHz	dBuV	dB	dBuV	dBuV	dB	dB		1	0.18	43.75	-10.58	54.33	34.12	9.62	0.01	Average	2	0.18	55.07	-9.26	64.33	45.44	9.62	0.01	QP	3	0.46	41.80	-4.87	46.67	32.11	9.61	0.08	Average	4	0.46	48.06	-8.61	56.67	38.37	9.61	0.08	QP	5	0.55	42.51	-3.49	46.00	32.83	9.61	0.07	Average	6	0.55	47.35	-8.65	56.00	37.67	9.61	0.07	QP	7	0.58	40.23	-5.77	46.00	30.56	9.61	0.06	Average	8	0.58	48.31	-7.69	56.00	38.64	9.61	0.06	QP	9 MAX	0.63	45.14	-0.86	46.00	35.48	9.61	0.05	Average	10	0.63	52.32	-3.68	56.00	42.66	9.61	0.05	QP	11	0.68	42.42	-3.58	46.00	32.76	9.62	0.04	Average	12	0.68	47.82	-8.18	56.00	38.16	9.62	0.04	QP			
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark																																																																																																																										
	MHz	dBuV	dB	dBuV	dBuV	dB	dB																																																																																																																											
1	0.18	43.75	-10.58	54.33	34.12	9.62	0.01	Average																																																																																																																										
2	0.18	55.07	-9.26	64.33	45.44	9.62	0.01	QP																																																																																																																										
3	0.46	41.80	-4.87	46.67	32.11	9.61	0.08	Average																																																																																																																										
4	0.46	48.06	-8.61	56.67	38.37	9.61	0.08	QP																																																																																																																										
5	0.55	42.51	-3.49	46.00	32.83	9.61	0.07	Average																																																																																																																										
6	0.55	47.35	-8.65	56.00	37.67	9.61	0.07	QP																																																																																																																										
7	0.58	40.23	-5.77	46.00	30.56	9.61	0.06	Average																																																																																																																										
8	0.58	48.31	-7.69	56.00	38.64	9.61	0.06	QP																																																																																																																										
9 MAX	0.63	45.14	-0.86	46.00	35.48	9.61	0.05	Average																																																																																																																										
10	0.63	52.32	-3.68	56.00	42.66	9.61	0.05	QP																																																																																																																										
11	0.68	42.42	-3.58	46.00	32.76	9.62	0.04	Average																																																																																																																										
12	0.68	47.82	-8.18	56.00	38.16	9.62	0.04	QP																																																																																																																										
<p>Note 1: "&gt;20dB" means emission levels that exceed the level of 20 dB below the applicable limit.            Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)</p>																																																																																																																																		





Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	657.5k	1.011M	1M01F1D	643.75k	985.757k




Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;  
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz_TnomVnom	Pass	500k	643.75k	992.004k
2440MHz_TnomVnom	Pass	500k	657.5k	1.011M
2480MHz_TnomVnom	Pass	500k	645k	985.757k

Port X-N dB = Port X 6dB down bandwidth; Port X-OBW = Port X 99% occupied bandwidth;







Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	9.36	0.00863

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz_TnomVnom	Pass	2.00	8.37	30.00
2440MHz_TnomVnom	Pass	2.00	9.36	30.00
2480MHz_TnomVnom	Pass	2.00	3.00	30.00



Summary


Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	3.46

RBW=3kHz.

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz_TnomVnom	Pass	2.00	1.89	8.00
2440MHz_TnomVnom	Pass	2.00	3.46	8.00
2480MHz_TnomVnom	Pass	2.00	-3.89	8.00

RBW=3kHz.






Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.440247G	8.37	-21.63	2.194352G	-61.63	2.399416G	-50.43	2.485088G	-61.29	2.555858G	-47.51	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.440247G	8.37	-21.63	2.194352G	-61.63	2.399416G	-50.43	2.485088G	-61.29	2.555858G	-47.51	1
2440MHz_TnomVnom	Pass	2.440247G	8.37	-21.63	793.68M	-64.21	2.398104G	-63.53	2.484808G	-62.95	2.541786G	-50.41	1
2480MHz_TnomVnom	Pass	2.440247G	8.37	-21.63	2.15528G	-64.34	2.39868G	-63.70	2.483576G	-60.62	2.584001G	-54.05	1





Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-BR(1Mbps)	Pass	PK	142.52M	39.37	43.50	-4.13	-9.77	3	Horizontal	0	2.00	-



**Result**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-BR(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2441MHz	Pass	PK	53.28M	34.68	40.00	-5.32	-14.61	3	Vertical	360	1.00	-
2441MHz	Pass	PK	90.14M	33.62	43.50	-9.88	-12.37	3	Vertical	360	1.00	-
2441MHz	Pass	PK	140.58M	32.38	43.50	-11.12	-9.64	3	Vertical	360	1.00	-
2441MHz	Pass	PK	468.44M	27.38	46.00	-18.62	-2.38	3	Vertical	360	1.00	-
2441MHz	Pass	PK	633.34M	29.89	46.00	-16.11	-0.23	3	Vertical	360	1.00	-
2441MHz	Pass	PK	788.54M	32.42	46.00	-13.58	1.36	3	Vertical	360	1.00	-
2441MHz	Pass	PK	90.14M	32.58	43.50	-10.92	-12.37	3	Horizontal	0	2.00	-
2441MHz	Pass	PK	142.52M	39.37	43.50	-4.13	-9.77	3	Horizontal	0	2.00	-
2441MHz	Pass	PK	225.94M	28.18	46.00	-17.82	-9.81	3	Horizontal	0	2.00	-
2441MHz	Pass	PK	464.56M	28.31	46.00	-17.69	-2.50	3	Horizontal	0	2.00	-
2441MHz	Pass	PK	718.7M	31.34	46.00	-14.66	0.32	3	Horizontal	0	2.00	-
2441MHz	Pass	PK	840.92M	33.43	46.00	-12.57	2.05	3	Horizontal	0	2.00	-






**BT-BR(1Mbps)**

06/11/2018

**2441MHz\_Switching Power Supply**



Lim.PK    
 PK    
 Lim.AV    
 AV


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	53.28M	34.68	40.00	-5.32	-14.61	3	Vertical	360	1.00	-
PK	90.14M	33.62	43.50	-9.88	-12.37	3	Vertical	360	1.00	-
PK	140.58M	32.38	43.50	-11.12	-9.64	3	Vertical	360	1.00	-
PK	468.44M	27.38	46.00	-18.62	-2.38	3	Vertical	360	1.00	-
PK	633.34M	29.89	46.00	-16.11	-0.23	3	Vertical	360	1.00	-
PK	788.54M	32.42	46.00	-13.58	1.36	3	Vertical	360	1.00	-



**BT-BR(1Mbps)**

06/11/2018

**2441MHz\_Switching Power Supply**



Lim.PK    
 PK    
 Lim.AV    
 AV

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	90.14M	32.58	43.50	-10.92	-12.37	3	Horizontal	0	2.00	-
PK	142.52M	39.37	43.50	-4.13	-9.77	3	Horizontal	0	2.00	-
PK	225.94M	28.18	46.00	-17.82	-9.81	3	Horizontal	0	2.00	-
PK	464.56M	28.31	46.00	-17.69	-2.50	3	Horizontal	0	2.00	-
PK	718.7M	31.34	46.00	-14.66	0.32	3	Horizontal	0	2.00	-
PK	840.92M	33.43	46.00	-12.57	2.05	3	Horizontal	0	2.00	-



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.483502G	50.99	54.00	-3.01	30.69	3	Horizontal	318	1.37	-



Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.375G	44.17	54.00	-9.83	30.33	3	Vertical	225	1.51	-
2402MHz	Pass	AV	2.4022G	94.31	Inf	-Inf	30.42	3	Vertical	225	1.51	-
2402MHz	Pass	PK	2.383G	55.25	74.00	-18.75	30.35	3	Vertical	225	1.51	-
2402MHz	Pass	PK	2.4026G	96.35	Inf	-Inf	30.42	3	Vertical	225	1.51	-
2402MHz	Pass	AV	2.389998G	44.08	54.00	-9.92	30.38	3	Horizontal	306	1.22	-
2402MHz	Pass	AV	2.4022G	101.14	Inf	-Inf	30.42	3	Horizontal	306	1.22	-
2402MHz	Pass	PK	2.3804G	54.56	74.00	-19.44	30.34	3	Horizontal	306	1.22	-
2402MHz	Pass	PK	2.4026G	103.12	Inf	-Inf	30.42	3	Horizontal	306	1.22	-
2402MHz	Pass	AV	4.8048G	34.24	54.00	-19.76	5.79	3	Vertical	53	2.71	-
2402MHz	Pass	PK	4.80404G	47.21	74.00	-26.79	5.79	3	Vertical	53	2.71	-
2402MHz	Pass	AV	4.80448G	34.76	54.00	-19.24	5.79	3	Horizontal	66	2.12	-
2402MHz	Pass	PK	4.8046G	48.11	74.00	-25.89	5.79	3	Horizontal	66	2.12	-
2440MHz	Pass	AV	2.375G	44.16	54.00	-9.84	30.33	3	Vertical	265	2.31	-
2440MHz	Pass	AV	2.4402G	96.91	Inf	-Inf	30.55	3	Vertical	265	2.31	-
2440MHz	Pass	AV	2.4998G	46.28	54.00	-7.72	30.75	3	Vertical	265	2.31	-
2440MHz	Pass	PK	2.3806G	56.16	74.00	-17.84	30.34	3	Vertical	265	2.31	-
2440MHz	Pass	PK	2.4398G	99.02	Inf	-Inf	30.55	3	Vertical	265	2.31	-
2440MHz	Pass	PK	2.4998G	55.58	74.00	-18.42	30.75	3	Vertical	265	2.31	-
2440MHz	Pass	AV	2.3622G	44.17	54.00	-9.83	30.29	3	Horizontal	303	1.00	-
2440MHz	Pass	AV	2.4402G	101.89	Inf	-Inf	30.55	3	Horizontal	303	1.00	-
2440MHz	Pass	AV	2.4926G	45.34	54.00	-8.66	30.72	3	Horizontal	303	1.00	-
2440MHz	Pass	PK	2.3898G	54.91	74.00	-19.09	30.38	3	Horizontal	303	1.00	-
2440MHz	Pass	PK	2.4398G	103.76	Inf	-Inf	30.55	3	Horizontal	303	1.00	-
2440MHz	Pass	PK	2.4926G	55.61	74.00	-18.39	30.72	3	Horizontal	303	1.00	-
2440MHz	Pass	AV	4.88752G	42.35	54.00	-11.65	5.96	3	Vertical	305	1.08	-
2440MHz	Pass	AV	7.32144G	37.49	54.00	-16.51	11.15	3	Vertical	158	1.50	-
2440MHz	Pass	PK	4.88756G	48.83	74.00	-25.17	5.96	3	Vertical	305	1.08	-
2440MHz	Pass	PK	7.31996G	50.94	74.00	-23.06	11.15	3	Vertical	158	1.50	-
2440MHz	Pass	AV	4.88752G	37.84	54.00	-16.16	5.96	3	Horizontal	212	1.32	-
2440MHz	Pass	AV	7.32004G	38.30	54.00	-15.70	11.15	3	Horizontal	247	2.24	-
2440MHz	Pass	PK	4.88764G	46.45	74.00	-27.55	5.96	3	Horizontal	212	1.32	-
2440MHz	Pass	PK	7.32G	51.50	74.00	-22.50	11.15	3	Horizontal	247	2.24	-
2480MHz	Pass	AV	2.4802G	92.27	Inf	-Inf	30.68	3	Vertical	267	2.49	-
2480MHz	Pass	AV	2.483502G	47.75	54.00	-6.25	30.69	3	Vertical	267	2.49	-
2480MHz	Pass	PK	2.48G	94.29	Inf	-Inf	30.68	3	Vertical	267	2.49	-
2480MHz	Pass	PK	2.483502G	56.37	74.00	-17.63	30.69	3	Vertical	267	2.49	-
2480MHz	Pass	AV	2.4802G	96.75	Inf	-Inf	30.68	3	Horizontal	318	1.37	-
2480MHz	Pass	AV	2.483502G	50.99	54.00	-3.01	30.69	3	Horizontal	318	1.37	-
2480MHz	Pass	PK	2.48G	98.72	Inf	-Inf	30.68	3	Horizontal	318	1.37	-
2480MHz	Pass	PK	2.483502G	58.68	74.00	-15.32	30.69	3	Horizontal	318	1.37	-
2480MHz	Pass	AV	4.96102G	31.42	54.00	-22.58	6.12	3	Vertical	341	2.84	-
2480MHz	Pass	PK	4.94902G	44.47	74.00	-29.53	6.09	3	Vertical	341	2.84	-
2480MHz	Pass	AV	7.43212G	37.37	54.00	-16.63	11.46	3	Vertical	27	1.49	-
2480MHz	Pass	PK	7.44756G	51.04	74.00	-22.96	11.50	3	Vertical	27	1.49	-
2480MHz	Pass	AV	7.43112G	37.48	54.00	-16.52	11.46	3	Horizontal	318	1.50	-
2480MHz	Pass	PK	7.4334G	51.22	74.00	-22.78	11.47	3	Horizontal	318	1.50	-
2480MHz	Pass	AV	4.96G	31.51	54.00	-22.49	6.11	3	Horizontal	83	1.91	-



## RSE TX above 1GHz Result


## Appendix F.2

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2480MHz	Pass	PK	4.96632G	45.35	74.00	-28.65	6.12	3	Horizontal	83	1.91	-

### BT-LE(1Mbps)

### 2402MHz\_TX

18/07/2018








Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.375G	44.17	54.00	-9.83	30.33	3	Vertical	225	1.51	-
AV	2.4022G	94.31	Inf	-Inf	30.42	3	Vertical	225	1.51	-
PK	2.383G	55.25	74.00	-18.75	30.35	3	Vertical	225	1.51	-
PK	2.4026G	96.35	Inf	-Inf	30.42	3	Vertical	225	1.51	-

**BT-LE(1Mbps)**

**2402MHz\_TX**

18/07/2018




- Lim.PK 
- PK 
- Lim.AV 
- AV 





Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.389998G	44.08	54.00	-9.92	30.38	3	Horizontal	306	1.22	-
AV	2.4022G	101.14	Inf	-Inf	30.42	3	Horizontal	306	1.22	-
PK	2.3804G	54.56	74.00	-19.44	30.34	3	Horizontal	306	1.22	-
PK	2.4026G	103.12	Inf	-Inf	30.42	3	Horizontal	306	1.22	-

### BT-LE(1Mbps)

### 2402MHz\_TX

18/07/2018



Lim.PK	
PK	
Lim.AV	
AV	


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.8048G	34.24	54.00	-19.76	5.79	3	Vertical	53	2.71	-
PK	4.80404G	47.21	74.00	-26.79	5.79	3	Vertical	53	2.71	-



### BT-LE(1Mbps)

### 2402MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.80448G	34.76	54.00	-19.24	5.79	3	Horizontal	66	2.12	-
PK	4.8046G	48.11	74.00	-25.89	5.79	3	Horizontal	66	2.12	-

### BT-LE(1Mbps)

### 2440MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.375G	44.16	54.00	-9.84	30.33	3	Vertical	265	2.31	-
AV	2.4402G	96.91	Inf	-Inf	30.55	3	Vertical	265	2.31	-
AV	2.4998G	46.28	54.00	-7.72	30.75	3	Vertical	265	2.31	-
PK	2.3806G	56.16	74.00	-17.84	30.34	3	Vertical	265	2.31	-
PK	2.4398G	99.02	Inf	-Inf	30.55	3	Vertical	265	2.31	-
PK	2.4998G	55.58	74.00	-18.42	30.75	3	Vertical	265	2.31	-

### BT-LE(1Mbps)

### 2440MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3622G	44.17	54.00	-9.83	30.29	3	Horizontal	303	1.00	-
AV	2.4402G	101.89	Inf	-Inf	30.55	3	Horizontal	303	1.00	-
AV	2.4926G	45.34	54.00	-8.66	30.72	3	Horizontal	303	1.00	-
PK	2.3898G	54.91	74.00	-19.09	30.38	3	Horizontal	303	1.00	-
PK	2.4398G	103.76	Inf	-Inf	30.55	3	Horizontal	303	1.00	-
PK	2.4926G	55.61	74.00	-18.39	30.72	3	Horizontal	303	1.00	-

### BT-LE(1Mbps)

### 2440MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.88752G	42.35	54.00	-11.65	5.96	3	Vertical	305	1.08	-
AV	7.32144G	37.49	54.00	-16.51	11.15	3	Vertical	158	1.50	-
PK	4.88756G	48.83	74.00	-25.17	5.96	3	Vertical	305	1.08	-
PK	7.31996G	50.94	74.00	-23.06	11.15	3	Vertical	158	1.50	-

### BT-LE(1Mbps)

### 2440MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.88752G	37.84	54.00	-16.16	5.96	3	Horizontal	212	1.32	-
AV	7.32004G	38.30	54.00	-15.70	11.15	3	Horizontal	247	2.24	-
PK	4.88764G	46.45	74.00	-27.55	5.96	3	Horizontal	212	1.32	-
PK	7.32G	51.50	74.00	-22.50	11.15	3	Horizontal	247	2.24	-

### BT-LE(1Mbps)

### 2480MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.4802G	92.27	Inf	-Inf	30.68	3	Vertical	267	2.49	-
AV	2.483502G	47.75	54.00	-6.25	30.69	3	Vertical	267	2.49	-
PK	2.48G	94.29	Inf	-Inf	30.68	3	Vertical	267	2.49	-
PK	2.483502G	56.37	74.00	-17.63	30.69	3	Vertical	267	2.49	-

### BT-LE(1Mbps)

### 2480MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.4802G	96.75	Inf	-Inf	30.68	3	Horizontal	318	1.37	-
AV	2.483502G	50.99	54.00	-3.01	30.69	3	Horizontal	318	1.37	-
PK	2.48G	98.72	Inf	-Inf	30.68	3	Horizontal	318	1.37	-
PK	2.483502G	58.68	74.00	-15.32	30.69	3	Horizontal	318	1.37	-

### BT-LE(1Mbps)

### 2480MHz\_TX

18/07/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.96102G	31.42	54.00	-22.58	6.12	3	Vertical	341	2.84	-
PK	4.94902G	44.47	74.00	-29.53	6.09	3	Vertical	341	2.84	-
AV	7.43212G	37.37	54.00	-16.63	11.46	3	Vertical	27	1.49	-
PK	7.44756G	51.04	74.00	-22.96	11.50	3	Vertical	27	1.49	-



### BT-LE(1Mbps)

### 2480MHz\_TX

18/07/2018



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	7.43112G	37.48	54.00	-16.52	11.46	3	Horizontal	318	1.50	-
PK	7.4334G	51.22	74.00	-22.78	11.47	3	Horizontal	318	1.50	-
AV	4.96G	31.51	54.00	-22.49	6.11	3	Horizontal	83	1.91	-
PK	4.96632G	45.35	74.00	-28.65	6.12	3	Horizontal	83	1.91	-