



## 12. Radio Frequency Exposure

### 12.1. Applicable Standards

<input type="checkbox"/> §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																																	
<input type="checkbox"/> §1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance, R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$ .  TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION  <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3">RF Source Frequency</th> <th colspan="3">Minimum Distance</th> <th>Threshold ERP</th> </tr> <tr> <th><math>f_L</math> MHz</th> <th></th> <th><math>f_H</math> MHz</th> <th><math>\lambda_L / 2\pi</math></th> <th></th> <th><math>\lambda_H / 2\pi</math></th> <th>W</th> </tr> </thead> <tbody> <tr> <td>0.3</td> <td>–</td> <td>1.34</td> <td>159 m</td> <td>–</td> <td>35.6 m</td> <td>1,920 R<sup>2</sup></td> </tr> <tr> <td>1.34</td> <td>–</td> <td>30</td> <td>35.6 m</td> <td>–</td> <td>1.6 m</td> <td>3,450 R<sup>2</sup>/f<sup>2</sup></td> </tr> <tr> <td>30</td> <td>–</td> <td>300</td> <td>1.6 m</td> <td>–</td> <td>159 mm</td> <td>3.83 R<sup>2</sup></td> </tr> <tr> <td>300</td> <td>–</td> <td>1,500</td> <td>159 mm</td> <td>–</td> <td>31.8 mm</td> <td>0.0128 R<sup>2</sup>f</td> </tr> <tr> <td>1,500</td> <td>–</td> <td>100,000</td> <td>31.8 mm</td> <td>–</td> <td>0.5 mm</td> <td>19.2R<sup>2</sup></td> </tr> </tbody> </table> <p>Subscripts L and H are low and high; <math>\lambda</math> is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.</p>	RF Source Frequency			Minimum Distance			Threshold ERP	$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W	0.3	–	1.34	159 m	–	35.6 m	1,920 R <sup>2</sup>	1.34	–	30	35.6 m	–	1.6 m	3,450 R <sup>2</sup> /f <sup>2</sup>	30	–	300	1.6 m	–	159 mm	3.83 R <sup>2</sup>	300	–	1,500	159 mm	–	31.8 mm	0.0128 R <sup>2</sup> f	1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R <sup>2</sup>
RF Source Frequency			Minimum Distance			Threshold ERP																																												
$f_L$ MHz		$f_H$ MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W																																												
0.3	–	1.34	159 m	–	35.6 m	1,920 R <sup>2</sup>																																												
1.34	–	30	35.6 m	–	1.6 m	3,450 R <sup>2</sup> /f <sup>2</sup>																																												
30	–	300	1.6 m	–	159 mm	3.83 R <sup>2</sup>																																												
300	–	1,500	159 mm	–	31.8 mm	0.0128 R <sup>2</sup> f																																												
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R <sup>2</sup>																																												
<input checked="" type="checkbox"/> § 1.1307(b)(3)(i)(B)	Device operates between 300MHz and 6GHz and the maximum time-averaged power of effective radiated power (ERP), whichever is greater, $\leq P_{th}$ .  $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>Where</p> $x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ <p>and</p> $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p style="text-align: center;"><math>d = \text{the separation distance (cm);}</math></p>																																																	



### 12.2.EUT Specification

<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2412MHz ~ 2462MHz <input checked="" type="checkbox"/> WLAN: 5150MHz ~ 5250MHz <input checked="" type="checkbox"/> WLAN: 5250MHz ~ 5350MHz <input checked="" type="checkbox"/> WLAN: 5470MHz ~ 5725MHz <input checked="" type="checkbox"/> WLAN: 5725MHz ~ 5850MHz <input type="checkbox"/> Bluetooth: 2402MHz ~ 2480MHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Evaluation applied</b>	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption



12.3. Test Result

Channel Frequency (MHz)	Max. Conducted output (dBm)	Max. Tune up power (dBm)	Antenna Gain (dBi)	Max. Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p. Power (mW)	Limit (mW)
5190-5230	19.76	20.26	7	25.11	323.97	3060
5270-5310	19.87	20.37	7	25.22	332.61	3060
5510-5670	22.58	23.08	7	27.93	620.70	3060
5755-5795	22.96	23.46	7	28.31	678.17	3060

Maximum Permissible Exposure (Co-location)

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Max. Tune up e.r.p. Power(mW)	Limit (mW)	MPE Ratio
GFSK	2402-2480	16.33	16.83	3.00	20.00	58.61	3060.00	0.02
11g	2412-2462	22.67	23.17	3.00	20.00	252.12	3060.00	0.08
Co-location Total								0.10
$\Sigma$ MPE ratios Limit								1.00

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Max. Tune up e.r.p. Power(mW)	Limit (mW)	MPE Ratio
GFSK	2402-2480	16.33	16.83	3.00	20.00	58.61	3060.00	0.02
11ac VHT40	5755-5795	22.96	23.46	7.00	20.00	678.17	3060.00	0.22
Co-location Total								0.24
$\Sigma$ MPE ratios Limit								1.00

-----THE END OF REPORT-----