



# FCC RADIO TEST REPORT

Applicant : Ubiquiti Inc.  
Address : 685 Third Avenue, New York, New York 10017,  
USA  
Equipment : UniFi Talk Phone Touch Max  
Model No. : UTP-TouchMax, UTP-TouchMax-White  
Trade Name : UBIQUITI  
FCC ID : SWX-UTPTM

**I HEREBY CERTIFY THAT :**

The sample was received on May. 27, 2021 and the testing was completed on Mar. 07, 2022 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





## Contents

<b>1. Summary of Test Procedure and Test Results.....</b>	<b>5</b>
1.1 Applicable Standards .....	5
<b>2. Test Configuration of Equipment under Test .....</b>	<b>6</b>
2.1 Feature of Equipment.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software.....	8
2.4 Description of Test System.....	9
2.5 General Information of Test.....	10
2.6 Measurement Uncertainty .....	10
<b>3. Test Equipment and Ancillaries Used for Tests .....</b>	<b>11</b>
<b>4. Antenna Requirements.....</b>	<b>13</b>
4.1 Antenna Construction and Directional Gain.....	13
<b>5. Test of AC Power Line Conducted Emission .....</b>	<b>14</b>
5.1 Test Limit .....	14
5.2 Test Procedures .....	14
5.3 Typical Test Setup .....	15
5.4 Test Result and Data.....	16
5.5 Test Photographs .....	18
<b>6. Test of Radiated Spurious Emission.....</b>	<b>19</b>
6.1 Test Limit .....	19
6.2 Test Procedures .....	20
6.3 Typical Test Setup .....	21
6.4 Test Result and Data (9KHz ~ 30MHz) .....	22
6.5 Test Result and Data (30MHz ~ 1GHz).....	22
6.6 Test Result and Data (1GHz ~ 25GHz).....	24
6.7 Restricted Bands of Operation .....	48
6.8 Test Photographs (30MHz ~ 1GHz).....	49
6.9 Test Photographs (1GHz ~ 25GHz).....	50
<b>7. Test of Conducted Spurious Emission .....</b>	<b>52</b>
7.1 Test Limit .....	52
7.2 Test Procedure .....	52
7.3 Test Setup Layout .....	52
7.4 Test Result and Data.....	52
<b>8. On Time, Duty Cycle and Measurement methods .....</b>	<b>61</b>
8.1 Test Limit .....	61
8.2 Test Procedure .....	61
8.3 Test Setup Layout .....	61
8.4 Test Result and Data.....	61
<b>9. 6dB Bandwidth Measurement Data .....</b>	<b>63</b>
9.1 Test Limit .....	63
9.2 Test Procedures .....	63
9.3 Test Setup Layout .....	63



9.4 Test Result and Data ..... 63

**10. Maximum Peak and Average Output Power ..... 66**

10.1 Test Limit ..... 66

10.2 Test Procedures ..... 66

10.3 Test Setup Layout ..... 66

10.4 Test Result and Data ..... 67

**11. Power Spectral Density ..... 68**

11.1 Test Limit ..... 68

11.2 Test Procedures ..... 68

11.3 Test Setup Layout ..... 68

11.4 Test Result and Data ..... 68

**12. Radio Frequency Exposure ..... 71**

12.1 Applicable Standards ..... 71

12.2 EUT Specification ..... 71

12.3 Test Results ..... 72

12.4 Calculation ..... 72

12.5 Maximum Permissible Exposure ..... 73





# 1. Summary of Test Procedure and Test Results

## 1.1 Applicable Standards

**ANSI C63.10:2013**

**FCC Rules and Regulations Part 15 Subpart C §15.247**

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak and Average Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

\*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.

\*This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report(21050188-TEFV01).

After engineering evaluation, the test results can refer to original report number: TEF1912016.



## 2. Test Configuration of Equipment under Test

### 2.1 Feature of Equipment

Frequency Range	NFC: 13.553MHz~13.567MHz BT / BLE: 2400-2483.5MHz 802.11b/g/n: 2400-2483.5MHz 802.11a/n/ac: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz
Modulation Type	NFC : ASK BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK 802.11b: CCK, DQPSK, DBPSK 802.11g/n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Modulation Technology	DSSS, OFDM, FHSS, DTS
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS7, HT20/40 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	For NFC: Loop Antenna For BT&WLAN: Internal Antenna
Antenna Gain	For NFC: 13.553MHz~13.567MHz: 0dBi For BT/BLE:2400-2480MHz: 0dBi For WLAN: 2400-2483.5MHz: 2dBi 5150-5850MHz: 4.5dBi
Type-C Adapter	Brand: UBIQUITI Model: E015-1G050300VU

Note:

1. EUT supports DFS Client Mode
2. For more details, please refer to the User's manual of the EUT.

Difference description:

Model No.	Remark
UTP-TouchMax	Black enclosure.
UTP-TouchMax-White	White enclosure.



### 2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
<b>*01</b>	<b>2412</b>	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	<b>*11</b>	<b>2462</b>
<b>*06</b>	<b>2437</b>	---	---

802.11n HT40 (2422MHz~2452MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
<b>*03</b>	<b>2422</b>	<b>*09</b>	<b>2452</b>
04	2427	---	---
05	2432	---	---
<b>*06</b>	<b>2437</b>	---	---

Note: Channels remarked \* are selected to perform test.



### 2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- b. The complete test system included Remote workstation and EUT for RF test. The Remote workstation included Notebook.
- c. An executive program, " QRCT ver. 4.0.00129.0" under Windows OS system was executed to transmit and receive data via WLAN.
- d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11n HT40 (13.5Mbps)
caused "Test Mode 3" generated the worst case, it was reported as the final data.	
Radiation Emissions (30MHz ~ 1GHz)	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11n HT40 (13.5Mbps)
caused "Test Mode 3" generated the worst case, they were reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	802.11b (1Mbps)
2	802.11g (6Mbps)
3	802.11n HT20 (6.5Mbps)
4	802.11n HT40 (13.5Mbps)
caused "Test Mode 1~4" generated the worst case, they were reported as the final data.	

Modulation Type	TX CONFIGURATION
802.11b	1TX
802.11g	1TX
802.11n HT20	1TX
802.11n HT40	1TX





### 2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
RJ45 Cable	N/A	N/A	1.2m / NS	N/A
USB TYPE-C	N/A	N/A	1m / NS	N/A
POE	UBIQUITI	GP-H480-050G	N/A	0.6m / NS
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
RJ45 Cable	N/A	N/A	15m / NS	N/A
USB TYPE-C	N/A	N/A	1m / NS	N/A
POE	UBIQUITI	GP-H480-050G	N/A	0.6m / NS
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	ASUS	P2430U	N/A	Adapter / 1.8m / NS
RJ45 Cable	N/A	N/A	1.2m / NS	N/A
USB TYPE-C	N/A	N/A	1m / NS	N/A
POE	UBIQUITI	GP-H480-050G	N/A	0.6m / NS



## 2.5 General Information of Test

Test Site	<b>CerpPASS Technology Corporation Test Laboratory</b> Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881	
	FCC	TW1079, TW1439
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Finish Date	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2019/12/30	22°C / 63%	Nick Guan
Radiated Emissions	3M02-NK	2020/03/27	22°C / 50%	Vic Yeh
AC Power Line Conducted Emission	CON01-NK	2020/03/25	25°C / 49%	Leon Huang

## 2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±1.60dB
Radiated Spurious Emission(9KHz~30MHz)	±3.405dB
Radiated Spurious Emission(30MHz~1GHz)	±5.326dB
Radiated Spurious Emission(1GHz~25GHz)	±5.918dB
Conducted Spurious Emission	±2.156dB
6dB Bandwidth	±4.401%
20dB Bandwidth	±4.40%
Occupied Bandwidth	±4.41%
Peak Output Power(Conducted Power Meter)	±1.31dB
Dwell Time	±0.11%
Power Spectral Density	±2.146dB
Duty Cycle	±0.17%



### 3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	275	2019/09/24	2020/09/23
Bilog Antenna	Schwarzbeck	VULB9168	369	2019/03/29	2020/03/28
Active Loop Antenna	EMCO	6507	40855	2019/05/24	2020/05/23
Horn Antenna	EMCO	3115	31589	2019/04/01	2020/03/31
Horn Antenna	EMCO	3116	31974	2019/09/17	2020/09/16
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2019/05/14	2020/05/13
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100219	2019/07/22	2020/07/21
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2019/08/02	2020/08/01
Preamplifier	EM Electronics corp.	EM330	60660	2020/03/16	2021/03/15
Preamplifier	EMC INSTRUMENTS	EMC051845SE	980333	2019/09/20	2020/09/19
Preamplifier	Agilent	8449B	3008A01954	2020/03/16	2021/03/15
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2019/11/07	2020/11/06
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2019/04/07	2020/04/06
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2019/04/09	2020/04/08
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1316	2019/09/20	2020/09/19
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 100	805443/4	2019/05/20	2020/05/19
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 100	805796/4	2019/05/20	2020/05/19
Cable-8m(1G-40G)	HUBER SUHNER	SUCOFLEX 100	805795/4	2019/05/20	2020/05/19
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100219	2019/07/22	2020/07/21
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2019/08/02	2020/08/01
Bluetooth Tester	ROHDE & SCHWARZ	CBT	101133	2019/04/07	2020/04/06
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2019/11/25	2020/11/24
Attenuator	KEYSIGHT	8491B	MY39250703	2019/09/12	2020/09/11
TEMP & HUMID CHAMBER	T-MACHINE	TMJ-9712	T-12-040111	2019/08/28	2020/08/27
Power Meter	Anritsu	ML2495A	1224005	2019/04/11	2020/04/10
Power Sensor	Anritsu	MA2411B	1207295	2019/04/09	2020/04/08



<b>Test Item</b>	AC Power Line Conducted Emission				
<b>Test Site</b>	CON01-NK				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Serial No</b>	<b>Calibration Date</b>	<b>Valid Date</b>
EMI Receiver	ROHDE & SCHWARZ	ESCI	100821	2019/09/16	2020/09/15
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127-568	2020/03/12	2021/03/11
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	101934	2020/03/11	2021/03/10
Cable-6m(9k~300M)	NA	EMC5D-BM-BM-6	130606	2020/03/11	2021/03/10
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA



## 4. Antenna Requirements

### 4.1 Antenna Construction and Directional Gain

Antenna Type	Internal Antenna
Antenna Gain	2400MHz-2483.5MHz: 2.00 dBi 5150MHz-5850MHz: 4.5 dBi



## 5. Test of AC Power Line Conducted Emission

### 5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


\*Decreases with the logarithm of the frequency.

### 5.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




### 5.3 Typical Test Setup





5.4 Test Result and Data

Power	: AC 120V / 60Hz	Pol/Phase	: LINE
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F
1	0.15	9.92	25.06	34.98	55.93	-20.95	Average	P
2	0.15	9.92	43.33	53.25	65.93	-12.68	QP	P
3	0.16	9.92	23.78	33.70	55.25	-21.55	Average	P
4	0.16	9.92	41.41	51.33	65.25	-13.92	QP	P
5	0.17	9.92	25.22	35.14	54.83	-19.69	Average	P
6	0.17	9.92	40.86	50.78	64.83	-14.05	QP	P
7	0.20	9.92	21.11	31.03	53.44	-22.41	Average	P
8	0.20	9.92	36.15	46.07	63.44	-17.37	QP	P
9	0.23	9.92	19.53	29.45	52.63	-23.18	Average	P
10	0.23	9.92	33.39	43.31	62.63	-19.32	QP	P
11	0.57	9.95	33.51	43.46	46.00	-2.54	Average	P
12	0.57	9.95	40.67	50.62	56.00	-5.38	QP	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=(LISN or ISN or Current Probe)Factor + Cable Loss





Power	: AC 120V / 60Hz	Pol/Phase	: NEUTRAL
Test Mode	: Mode 3, CH06		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.15	9.95	24.76	34.71	55.94	-21.23	Average	P
2	0.15	9.95	42.26	52.21	65.94	-13.73	QP	P
3	0.16	9.95	21.90	31.85	55.62	-23.77	Average	P
4	0.16	9.95	39.92	49.87	65.62	-15.75	QP	P
5	0.17	9.95	23.25	33.20	55.14	-21.94	Average	P
6	0.17	9.95	39.69	49.64	65.14	-15.50	QP	P
7	0.18	9.95	22.63	32.58	54.70	-22.12	Average	P
8	0.18	9.95	38.66	48.61	64.70	-16.09	QP	P
9	0.19	9.95	21.64	31.59	53.93	-22.34	Average	P
10	0.19	9.95	35.78	45.73	63.93	-18.20	QP	P
11	0.56	9.96	32.17	42.13	46.00	-3.87	Average	P
12	0.56	9.96	39.65	49.61	56.00	-6.39	QP	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



## 6. Test of Radiated Spurious Emission

### 6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



## 6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

1. The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.  
(X-AXIS is the worst.)




### 6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






### 6.4 Test Result and Data (9KHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

### 6.5 Test Result and Data (30MHz ~ 1GHz)

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	59.10	-9.42	45.50	36.08	40.00	-3.92	QP	100	336	P
2	179.38	-10.52	44.46	33.94	43.50	-9.56	Peak	100	0	P
3	239.52	-10.46	44.82	34.36	46.00	-11.64	Peak	100	0	P
4	288.02	-8.55	44.65	36.10	46.00	-9.90	Peak	100	0	P
5	383.08	-5.86	39.03	33.17	46.00	-12.83	Peak	100	0	P
6	648.86	-0.37	32.71	32.34	46.00	-13.66	Peak	100	0	P

Note: Level=Reading+Factor  
Margin=Level-Limit  
Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	57.16	-9.19	41.77	32.58	40.00	-7.42	Peak	100	0	P
2	119.24	-11.90	45.64	33.74	43.50	-9.76	Peak	100	0	P
3	165.80	-9.29	41.47	32.18	43.50	-11.32	Peak	100	0	P
4	262.80	-9.51	40.24	30.73	46.00	-15.27	Peak	100	0	P
5	305.48	-8.00	38.74	30.74	46.00	-15.26	Peak	100	0	P
6	743.92	1.25	32.59	33.84	46.00	-12.16	Peak	100	0	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.40	41.76	54.00	-12.24	Average	148	166	P
2	2390.00	-3.64	57.23	53.59	74.00	-20.41	Peak	148	166	P
3	4824.00	3.76	36.49	40.25	54.00	-13.75	Average	333	166	P
4	4824.00	3.76	44.61	48.37	74.00	-25.63	Peak	333	166	P
5	12060.00	13.45	31.24	44.69	54.00	-9.31	Average	100	316	P
6	12060.00	13.45	45.38	58.83	74.00	-15.17	Peak	100	316	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	42.10	38.46	54.00	-15.54	Average	100	303	P
2	2390.00	-3.64	54.92	51.28	74.00	-22.72	Peak	100	303	P
3	4824.00	3.76	33.75	37.51	54.00	-16.49	Average	100	220	P
4	4824.00	3.76	43.87	47.63	74.00	-26.37	Peak	100	220	P
5	12060.00	13.45	31.05	44.50	54.00	-9.50	Average	100	206	P
6	12060.00	13.45	44.48	57.93	74.00	-16.07	Peak	100	206	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor





Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	42.98	39.34	54.00	-14.66	Average	146	170	P
2	2390.00	-3.64	54.70	51.06	74.00	-22.94	Peak	146	170	P
3	2483.50	-3.30	42.30	39.00	54.00	-15.00	Average	146	170	P
4	2483.50	-3.30	55.89	52.59	74.00	-21.41	Peak	146	170	P
5	4874.00	3.95	33.60	37.55	54.00	-16.45	Average	344	170	P
6	4874.00	3.95	43.70	47.65	74.00	-26.35	Peak	344	170	P
7	7311.00	8.84	30.12	38.96	54.00	-15.04	Average	100	212	P
8	7311.00	8.84	43.29	52.13	74.00	-21.87	Peak	100	212	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	41.87	38.23	54.00	-15.77	Average	100	208	P
2	2390.00	-3.64	54.80	51.16	74.00	-22.84	Peak	100	208	P
3	2483.50	-3.30	41.72	38.42	54.00	-15.58	Average	100	208	P
4	2483.50	-3.30	55.10	51.80	74.00	-22.20	Peak	100	208	P
5	4874.00	3.95	30.33	34.28	54.00	-19.72	Average	100	200	P
6	4874.00	3.95	42.98	46.93	74.00	-27.07	Peak	100	200	P
7	7311.00	8.84	29.82	38.66	54.00	-15.34	Average	100	235	P
8	7311.00	8.84	43.34	52.18	74.00	-21.82	Peak	100	235	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	47.99	44.69	54.00	-9.31	Average	146	165	P
2	2483.50	-3.30	59.25	55.95	74.00	-18.05	Peak	146	165	P
3	4924.00	4.10	36.21	40.31	54.00	-13.69	Average	342	170	P
4	4924.00	4.10	46.02	50.12	74.00	-23.88	Peak	342	170	P
5	7386.00	8.94	30.68	39.62	54.00	-14.38	Average	100	216	P
6	7386.00	8.94	43.38	52.32	74.00	-21.68	Peak	100	216	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	44.32	41.02	54.00	-12.98	Average	100	306	P
2	2483.50	-3.30	54.34	51.04	74.00	-22.96	Peak	100	306	P
3	4924.00	4.10	34.43	38.53	54.00	-15.47	Average	100	221	P
4	4924.00	4.10	44.80	48.90	74.00	-25.10	Peak	100	221	P
5	7386.00	8.94	29.75	38.69	54.00	-15.31	Average	100	218	P
6	7386.00	8.94	43.74	52.68	74.00	-21.32	Peak	100	218	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	44.78	41.14	54.00	-12.86	Average	146	161	P
2	2390.00	-3.64	60.31	56.67	74.00	-17.33	Peak	146	161	P
3	4824.00	3.76	29.51	33.27	54.00	-20.73	Average	100	165	P
4	4824.00	3.76	43.59	47.35	74.00	-26.65	Peak	100	165	P
5	12060.00	13.45	30.65	44.10	54.00	-9.90	Average	100	311	P
6	12060.00	13.45	44.60	58.05	74.00	-15.95	Peak	100	311	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	42.99	39.35	54.00	-14.65	Average	100	204	P
2	2390.00	-3.64	57.15	53.51	74.00	-20.49	Peak	100	204	P
3	4824.00	3.76	29.35	33.11	54.00	-20.89	Average	100	232	P
4	4824.00	3.76	42.35	46.11	74.00	-27.89	Peak	100	232	P
5	12060.00	13.45	29.36	42.81	54.00	-11.19	Average	100	212	P
6	12060.00	13.45	43.62	57.07	74.00	-16.93	Peak	100	212	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	47.00	43.36	54.00	-10.64	Average	140	166	P
2	2390.00	-3.64	57.20	53.56	74.00	-20.44	Peak	140	166	P
3	2483.50	-3.30	47.21	43.91	54.00	-10.09	Average	140	166	P
4	2483.50	-3.30	58.59	55.29	74.00	-18.71	Peak	140	166	P
5	4874.00	3.95	29.82	33.77	54.00	-20.23	Average	100	175	P
6	4874.00	3.95	43.60	47.55	74.00	-26.45	Peak	100	175	P
7	7311.00	8.84	30.04	38.88	54.00	-15.12	Average	100	218	P
8	7311.00	8.84	43.77	52.61	74.00	-21.39	Peak	100	218	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	43.98	40.34	54.00	-13.66	Average	100	305	P
2	2390.00	-3.64	56.09	52.45	74.00	-21.55	Peak	100	305	P
3	2483.50	-3.30	44.15	40.85	54.00	-13.15	Average	100	305	P
4	2483.50	-3.30	56.99	53.69	74.00	-20.31	Peak	100	305	P
5	4874.00	3.95	29.32	33.27	54.00	-20.73	Average	100	203	P
6	4874.00	3.95	42.20	46.15	74.00	-27.85	Peak	100	203	P
7	7311.00	8.84	29.94	38.78	54.00	-15.22	Average	100	189	P
8	7311.00	8.84	43.01	51.85	74.00	-22.15	Peak	100	189	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor





Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 2, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	50.99	47.69	54.00	-6.31	Average	150	165	P
2	2483.50	-3.30	69.61	66.31	74.00	-7.69	Peak	150	165	P
3	4924.00	4.10	29.60	33.70	54.00	-20.30	Average	100	178	P
4	4924.00	4.10	43.36	47.46	74.00	-26.54	Peak	100	178	P
5	7386.00	8.94	30.00	38.94	54.00	-15.06	Average	100	225	P
6	7386.00	8.94	43.71	52.65	74.00	-21.35	Peak	100	225	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 2, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	46.69	43.39	54.00	-10.61	Average	100	302	P
2	2483.50	-3.30	64.08	60.78	74.00	-13.22	Peak	100	302	P
3	4924.00	4.10	29.22	33.32	54.00	-20.68	Average	100	209	P
4	4924.00	4.10	42.48	46.58	74.00	-27.42	Peak	100	209	P
5	7386.00	8.94	29.80	38.74	54.00	-15.26	Average	100	212	P
6	7386.00	8.94	43.62	52.56	74.00	-21.44	Peak	100	212	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	47.10	43.46	54.00	-10.54	Average	184	163	P
2	2390.00	-3.64	64.20	60.56	74.00	-13.44	Peak	184	163	P
3	4824.00	3.76	29.75	33.51	54.00	-20.49	Average	100	163	P
4	4824.00	3.76	44.61	48.37	74.00	-25.63	Peak	100	163	P
5	12060.00	13.45	30.82	44.27	54.00	-9.73	Average	100	302	P
6	12060.00	13.45	44.76	58.21	74.00	-15.79	Peak	100	302	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH01		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	43.92	40.28	54.00	-13.72	Average	100	200	P
2	2390.00	-3.64	59.25	55.61	74.00	-18.39	Peak	100	200	P
3	4824.00	3.76	29.54	33.30	54.00	-20.70	Average	100	239	P
4	4824.00	3.76	42.96	46.72	74.00	-27.28	Peak	100	239	P
5	12060.00	13.45	29.71	43.16	54.00	-10.84	Average	100	205	P
6	12060.00	13.45	44.05	57.50	74.00	-16.50	Peak	100	205	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	48.88	45.24	54.00	-8.76	Average	181	156	P
2	2390.00	-3.64	59.13	55.49	74.00	-18.51	Peak	181	156	P
3	2483.50	-3.30	47.44	44.14	54.00	-9.86	Average	181	156	P
4	2483.50	-3.30	60.73	57.43	74.00	-16.57	Peak	181	156	P
5	4874.00	3.95	30.15	34.10	54.00	-19.90	Average	100	182	P
6	4874.00	3.95	44.06	48.01	74.00	-25.99	Peak	100	182	P
7	7311.00	8.84	30.38	39.22	54.00	-14.78	Average	100	205	P
8	7311.00	8.84	44.51	53.35	74.00	-20.65	Peak	100	205	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.06	41.42	54.00	-12.58	Average	100	302	P
2	2390.00	-3.64	58.56	54.92	74.00	-19.08	Peak	100	302	P
3	2483.50	-3.30	46.12	42.82	54.00	-11.18	Average	100	302	P
4	2483.50	-3.30	57.84	54.54	74.00	-19.46	Peak	100	302	P
5	4874.00	3.95	29.66	33.61	54.00	-20.39	Average	100	211	P
6	4874.00	3.95	43.33	47.28	74.00	-26.72	Peak	100	211	P
7	7311.00	8.84	30.15	38.99	54.00	-15.01	Average	100	195	P
8	7311.00	8.84	43.54	52.38	74.00	-21.62	Peak	100	195	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 3, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	50.22	46.92	54.00	-7.08	Average	178	156	P
2	2483.50	-3.30	67.87	64.57	74.00	-9.43	Peak	178	156	P
3	4924.00	4.10	29.86	33.96	54.00	-20.04	Average	100	185	P
4	4924.00	4.10	43.90	48.00	74.00	-26.00	Peak	100	185	P
5	7386.00	8.94	29.87	38.81	54.00	-15.19	Average	100	231	P
6	7386.00	8.94	43.46	52.40	74.00	-21.60	Peak	100	231	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 3, CH11		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	46.09	42.79	54.00	-11.21	Average	100	306	P
2	2483.50	-3.30	63.49	60.19	74.00	-13.81	Peak	100	306	P
3	4924.00	4.10	29.58	33.68	54.00	-20.32	Average	100	215	P
4	4924.00	4.10	43.36	47.46	74.00	-26.54	Peak	100	215	P
5	7386.00	8.94	30.06	39.00	54.00	-15.00	Average	100	198	P
6	7386.00	8.94	44.88	53.82	74.00	-20.18	Peak	100	198	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor





Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4, CH03		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	47.75	44.11	54.00	-9.89	Average	146	159	P
2	2390.00	-3.64	64.89	61.25	74.00	-12.75	Peak	146	159	P
3	4844.00	3.85	29.39	33.24	54.00	-20.76	Average	100	168	P
4	4844.00	3.85	44.39	48.24	74.00	-25.76	Peak	100	168	P
5	7266.00	8.62	29.78	38.40	54.00	-15.60	Average	100	227	P
6	7266.00	8.62	42.75	51.37	74.00	-22.63	Peak	100	227	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4, CH03		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	44.07	40.43	54.00	-13.57	Average	100	214	P
2	2390.00	-3.64	60.17	56.53	74.00	-17.47	Peak	100	214	P
3	4844.00	3.85	28.71	32.56	54.00	-21.44	Average	100	177	P
4	4844.00	3.85	42.85	46.70	74.00	-27.30	Peak	100	177	P
5	7266.00	8.62	29.51	38.13	54.00	-15.87	Average	100	239	P
6	7266.00	8.62	42.91	51.53	74.00	-22.47	Peak	100	239	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	45.08	41.44	54.00	-12.56	Average	180	158	P
2	2390.00	-3.64	60.13	56.49	74.00	-17.51	Peak	180	158	P
3	2483.50	-3.30	47.74	44.44	54.00	-9.56	Average	180	158	P
4	2483.50	-3.30	66.84	63.54	74.00	-10.46	Peak	180	158	P
5	4874.00	3.95	29.42	33.37	54.00	-20.63	Average	100	181	P
6	4874.00	3.95	43.44	47.39	74.00	-26.61	Peak	100	181	P
7	7311.00	8.84	29.58	38.42	54.00	-15.58	Average	100	214	P
8	7311.00	8.84	43.59	52.43	74.00	-21.57	Peak	100	214	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4, CH06		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-3.64	43.75	40.11	54.00	-13.89	Average	100	311	P
2	2390.00	-3.64	58.55	54.91	74.00	-19.09	Peak	100	311	P
3	2483.50	-3.30	44.09	40.79	54.00	-13.21	Average	100	311	P
4	2483.50	-3.30	59.49	56.19	74.00	-17.81	Peak	100	311	P
5	4874.00	3.95	28.68	32.63	54.00	-21.37	Average	100	202	P
6	4874.00	3.95	42.66	46.61	74.00	-27.39	Peak	100	202	P
7	7311.00	8.84	29.59	38.43	54.00	-15.57	Average	100	188	P
8	7311.00	8.84	42.74	51.58	74.00	-22.42	Peak	100	188	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: VERTICAL
Test Mode	: Mode 4, CH09		:




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	55.51	52.21	54.00	-1.79	Average	147	166	P
2	2483.50	-3.30	72.46	69.16	74.00	-4.84	Peak	147	166	P
3	4904.00	4.05	29.24	33.29	54.00	-20.71	Average	100	177	P
4	4904.00	4.05	42.65	46.70	74.00	-27.30	Peak	100	177	P
5	7356.00	8.86	29.69	38.55	54.00	-15.45	Average	100	227	P
6	7356.00	8.86	43.29	52.15	74.00	-21.85	Peak	100	227	P

Note: Level=Reading+Factor  
 Margin=Level-Limit  
 Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V / 60Hz	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 4, CH09		:



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-3.30	51.31	48.01	54.00	-5.99	Average	100	308	P
2	2483.50	-3.30	67.78	64.48	74.00	-9.52	Peak	100	308	P
3	4904.00	4.05	28.55	32.60	54.00	-21.40	Average	100	206	P
4	4904.00	4.05	42.73	46.78	74.00	-27.22	Peak	100	206	P
5	7356.00	8.86	29.67	38.53	54.00	-15.47	Average	100	219	P
6	7356.00	8.86	43.08	51.94	74.00	-22.06	Peak	100	219	P

Note: Level=Reading+Factor  
Margin=Level-Limit  
Factor=Antenna Factor + cable loss - Amplifier Factor



### 6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

\*\* : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



## 7. Test of Conducted Spurious Emission

### 7.1 Test Limit

According to the methods defined in ANSI C63.10-2013 Section 11.11.1


Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

### 7.2 Test Procedure

According to the methods defined in ANSI C63.10-2013 Section 11.11.2 & 11.11.3

- a. The transmitter output was connected to the spectrum analyzer via a low loss cable.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- c. Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- d. The band edges was measured and recorded.

### 7.3 Test Setup Layout




### 7.4 Test Result and Data

Note: Test plots refers to the following pages.










Modulation Type: 802.11b, CH 01






Modulation Type: 802.11b, CH 06






Modulation Type: 802.11b, CH 11










Modulation Type: 802.11g, CH 01






Modulation Type: 802.11g, CH 06






Modulation Type: 802.11g, CH 11










Modulation Type: 802.11n HT20, CH01






Modulation Type: 802.11n HT20, CH06






Modulation Type: 802.11n HT20, CH11










Modulation Type: 802.11n HT40, CH03






Modulation Type: 802.11n HT40, CH06





Modulation Type: 802.11n HT40, CH09







## 8. On Time, Duty Cycle and Measurement methods


### 8.1 Test Limit

None; for reporting purposes only.

### 8.2 Test Procedure

According to the methods defined in ANSI C63.10-2013 Section 11.6  
Zero-Span Spectrum Analyzer Method.

### 8.3 Test Setup Layout



### 8.4 Test Result and Data


Modulation Type	On Time (ms)	Period Time (ms)	Duty Cycle (%)
11b,1M	100.00	100.00	100.00%
11g,6M	1.37	1.37	99.68%
11n HT20	1.28	1.29	99.66%
11n HT40	0.64	0.65	99.10%




Modulation Type: 802.11b (1Mbps)




Modulation Type: 802.11g (6Mbps)



Modulation Type: 802.11n HT20 (6.5Mbps)



Modulation Type: 802.11n HT40 (13.5Mbps)





### 9. 6dB Bandwidth Measurement Data

#### 9.1 Test Limit


The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 9.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.8

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.
- c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- d. The 6dB Bandwidth was measured and recorded.

#### 9.3 Test Setup Layout




#### 9.4 Test Result and Data


Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
			ANT A	
11b	1	2412	<b>8.05</b>	0.5
	6	2437	8.10	0.5
	11	2462	8.55	0.5
11g	1	2412	16.40	0.5
	6	2437	16.40	0.5
	11	2462	16.45	0.5
11n HT20	1	2412	17.65	0.5
	6	2437	17.60	0.5
	11	2462	17.55	0.5
11n HT40	3	2422	35.20	0.5
	6	2437	35.50	0.5
	9	2452	35.30	0.5




6dB Bandwidth:  
Modulation Type: 802.11b  
CH01




Modulation Type: 802.11g  
CH01




CH06




CH06



CH11




CH11







Modulation Type: 802.11n HT20  
CH01




Modulation Type: 802.11n HT40  
CH03




CH06




CH06



CH11



CH09





## 10. Maximum Peak and Average Output Power

### 10.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.


If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

### 10.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.9.2.3.2

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

### 10.3 Test Setup Layout



**10.4 Test Result and Data**

Setting	Modulation Mode	Channel	Frequency (MHz)	Conducted(peak) output power (dBm)	Total PK power (dBm)	Total PK power (mW)	Power Limit (dBm)
				ANT A			
17	11b	1	2412	20.12	20.12	102.802	30.00
16.5		6	2437	19.42	19.42	87.498	30.00
17		11	2462	20.61	20.61	115.080	30.00
13	11g	1	2412	19.58	19.58	90.782	30.00
18.5		6	2437	22.72	22.72	187.068	30.00
15		11	2462	21.64	21.64	145.881	30.00
13.5	11n HT20	1	2412	20.15	20.15	103.514	30.00
18.5		6	2437	22.76	<b>22.76</b>	188.799	30.00
13.5		11	2462	20.31	20.31	107.399	30.00
12	11n HT40	3	2422	17.92	17.92	61.944	30.00
12.5		6	2437	18.59	18.59	72.277	30.00
12		9	2452	19.67	19.67	92.683	30.00

Power Set	Modulation Mode	Channel	Frequency (MHz)	Conducted(average) output power (dBm)	Total AV power (dBm)	Total AV power (mW)	Power Limit (dBm)
				ANT A			
17	11b	1	2412	17.60	17.60	57.544	NA
16.5		6	2437	16.71	16.71	46.881	NA
17		11	2462	17.96	17.96	62.517	NA
13	11g	1	2412	11.96	11.96	15.704	NA
18.5		6	2437	16.36	16.36	43.251	NA
15		11	2462	14.09	14.09	25.645	NA
13.5	11n HT20	1	2412	12.58	12.58	18.113	NA
18.5		6	2437	16.49	16.49	44.566	NA
13.5		11	2462	12.67	12.67	18.493	NA
12	11n HT40	3	2422	10.18	10.18	10.423	NA
12.5		6	2437	11.01	11.01	12.618	NA
12		9	2452	12.03	12.03	15.959	NA

Note: Average power is for reference only.



## 11. Power Spectral Density

### 11.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.


If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

### 11.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 11.10

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer’s resolution bandwidth were set at 3kHz RBW and 10KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- c. The power spectral density was measured and recorded.

### 11.3 Test Setup Layout




### 11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 3KHz Bandwidth(dBm)	Sum chain (dBm)	Duty Cycle CF(dB)	Total PSD (dBm)	Limit (dBm)
			ANT A				
11b	1	2412	-5.67	-5.67	0.00	-5.67	8.00
	6	2437	-6.72	-6.72	0.00	-6.72	8.00
	11	2462	-5.65	-5.65	0.00	-5.65	8.00
11g	1	2412	-13.24	-13.24	0.00	-13.24	8.00
	6	2437	-8.88	-8.88	0.00	-8.88	8.00
	11	2462	-10.18	-10.18	0.00	-10.18	8.00
11n HT20	1	2412	-13.8	-13.80	0.00	-13.80	8.00
	6	2437	-9.79	-9.79	0.00	-9.79	8.00
	11	2462	-13.81	-13.81	0.00	-13.81	8.00
11n HT40	3	2422	-19.21	-19.21	0.00	-19.21	8.00
	6	2437	-17.34	-17.34	0.00	-17.34	8.00
	9	2452	-16.3	-16.30	0.00	-16.30	8.00







Modulation Type: 802.11b  
CH01




Modulation Type: 802.11b  
CH01




CH06




CH06



CH11




CH11




Date: 30.DEC.2019 09:08:00




Modulation Type: 802.11n HT20  
CH01




Modulation Type: 802.11n HT40  
CH03




CH06



CH06



CH11



CH09

