



8. Radio Frequency Exposure

8.1. Applicable Standards

<input checked="" type="checkbox"/> §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																			
<input type="checkbox"/> §1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$. <div style="text-align: center;"> TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION </div> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th colspan="2">RF Source Frequency</th> <th colspan="2">Minimum Distance</th> <th>Threshold ERP</th> </tr> <tr> <th>f_L MHz</th> <th>f_H MHz</th> <th>$\lambda_L / 2\pi$</th> <th>$\lambda_H / 2\pi$</th> <th>W</th> </tr> </thead> <tbody> <tr> <td>0.3</td> <td>—</td> <td>159 m</td> <td>—</td> <td>1,920 R²</td> </tr> <tr> <td>1.34</td> <td>—</td> <td>35.6 m</td> <td>—</td> <td>3,450 R²/f²</td> </tr> <tr> <td>30</td> <td>—</td> <td>1.6 m</td> <td>—</td> <td>3.83 R²</td> </tr> <tr> <td>300</td> <td>—</td> <td>159 mm</td> <td>—</td> <td>0.0128 R²f</td> </tr> <tr> <td>1,500</td> <td>—</td> <td>31.8 mm</td> <td>—</td> <td>19.2R²</td> </tr> </tbody> </table> <p style="font-size: small;">Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.</p>	RF Source Frequency		Minimum Distance		Threshold ERP	f_L MHz	f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W	0.3	—	159 m	—	1,920 R ²	1.34	—	35.6 m	—	3,450 R ² /f ²	30	—	1.6 m	—	3.83 R ²	300	—	159 mm	—	0.0128 R ² f	1,500	—	31.8 mm	—	19.2R ²
RF Source Frequency		Minimum Distance		Threshold ERP																																
f_L MHz	f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W																																
0.3	—	159 m	—	1,920 R ²																																
1.34	—	35.6 m	—	3,450 R ² /f ²																																
30	—	1.6 m	—	3.83 R ²																																
300	—	159 mm	—	0.0128 R ² f																																
1,500	—	31.8 mm	—	19.2R ²																																
<input type="checkbox"/> § 1.1307(b)(3)(i)(B).	Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$ $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p style="text-align: center;">Where</p> $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ <p style="text-align: center;">and</p> $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p style="text-align: center;">$d = \text{the separation distance (cm);}$</p>																																			



8.2. EUT Specification

Frequency band (Operating)	13.553MHz ~ 13.567MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption
Remark:	
1. <i>The maximum Fundamental Emission is <u>66.34dBuV/m</u> at <u>13.56MHz</u> (with <u>0dBi</u> antenna gain.)</i> 2. <i>DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.</i> 3. <i>For mobile or fixed location transmitters, no SAR consideration applied.</i>	

8.3. Test Results

Channel Frequency (MHz)	Fundamental Emission (dBm)	Antenna Gain (dBi)	Conducted Power (dBm)	Max. Tune up power (dBm)	Fundamental Emission (mW)	Limit (mW)
13.56	-28.89	0.00	-28.89	-28.39	0.001449176	1

Antenna Gain (dBi)	Antenna Gain (linear)	Distance (m)	Fundamental Emission (dBuV/m)	Fundamental Emission (V/m)	Fundamental Emission (W)	Fundamental Emission (dBm)
0	1	3	66.34	0.002074914	0.00000129	-28.89

No non-compliance noted.

-----THE END OF REPORT-----