

## RF Exposure Evaluation declaration

Product Name	VOIP Phone
Model No.	UVP-Executive
FCC ID	SWX-UVPEXT

Applicant	Ubiquiti Networks, Inc.
Address	12F, No. 105, Song Ren Rd., Sin Yi District, Taipei 110, Taiwan

Date of Receipt	Sep. 05, 2014
Date of Declaration	Nov. 17, 2014
Report No.	1490231R-RFUSP47V00

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : VOIP Phone  
 Test Item : RF Exposure Evaluation  
 Test Site : No.3 OATS

Operation Frequency	2412-2462MHz, 2402-2480MHz 5745-5825MHz, 5755-5795MHz 5180-5240MHz, 5190-5230MHz 5260-5320MHz, 5270-5310MHz 5500-5700MHz, 5510-5670MHz
---------------------	--

#### (2.4GHz) Output Power Into Antenna & RF Exposure Evaluation Distance:

Target Conducted output power	21dBm
Power Tolerance	±2dB
Maximum Conducted output power	23dBm (note)
Antenna gain	2.27dBi

Note: Maximum Conducted output power = Target Conducted output power + Power Tolerance

Output Power to Antenna (mW)	Power Density at <b>R = 20 cm</b> (mW/cm <sup>2</sup> )
199.5262	0.066947

Power density is lower than the limit (1 mW/cm<sup>2</sup>).

#### (5GHz) Output Power Into Antenna & RF Exposure Evaluation Distance:

Target Conducted output power	14dBm
Power Tolerance	±2dB
Maximum Conducted output power	16dBm (note)
Antenna gain	5.18dBi

Note: Maximum Conducted output power = Target Conducted output power + Power Tolerance

Output Power to Antenna (mW)	Power Density at <b>R = 20 cm</b> (mW/cm <sup>2</sup> )
39.8107	0.026105

Power density is lower than the limit (1 mW/cm<sup>2</sup>).