



FCC Test Report

FCC ID : SWX-UVPT
Equipment : UniFi VoIP Phone Touch
Brand Name : UBIQUITI
Model Name : UVP-Touch
Applicant : Ubiquiti Networks, Inc.
685 Third Avenue, 27th Floor New York,
New York 10017 USA
Manufacturer : Ubiquiti Networks, Inc.
685 Third Avenue, 27th Floor New York,
New York 10017 USA
Standard : 47 CFR FCC Part 15.247

The product was received on Nov. 08, 2018, and testing was started from Nov. 13, 2018 and completed on Dec. 28, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Testing Applied Standards7

1.3 Testing Location Information7

1.4 Measurement Uncertainty7

2 TEST CONFIGURATION OF EUT.....8

2.1 Test Condition8

2.2 Test Channel Mode8

2.3 The Worst Case Measurement Configuration9

2.4 Support Equipment.....10

2.5 Test Setup Diagram11

3 TRANSMITTER TEST RESULT12

3.1 AC Power-line Conducted Emissions12

3.2 DTS Bandwidth.....13

3.3 Maximum Conducted Output Power14

3.4 Power Spectral Density16

3.5 Emissions in Non-restricted Frequency Bands17

3.6 Emissions in Restricted Frequency Bands.....18

4 TEST EQUIPMENT AND CALIBRATION DATA.....21

APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS

APPENDIX B. TEST RESULTS OF DTS BANDWIDTH

APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER

APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY

APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS

APPENDIX G. TEST PHOTOS

PHOTOGRAPHS OF EUT V01



Summary of Test Result

Report Clause	Ref. Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	FCC 15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	FCC 15.207
3.2	15.247(a)	DTS Bandwidth	PASS	≥500kHz
3.3	15.247(b)	Maximum Conducted Output Power	PASS	Power [dBm]:30
3.4	15.247(e)	Power Spectral Density	PASS	PSD [dBm/3kHz]:8
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	Non-Restricted Bands: >30 dBc
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	Restricted Bands: FCC 15.209

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and explanations:
None

Reviewed by: Jackson Tsai

Report Producer: Ann Hou

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- ◆ Bluetooth LE uses a GFSK (1Mbps) modulation for DSSS.
- ◆ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	-	-	internal antenna	Murata

Ant.	Port	Gain (dBi)		
		2.4G	5G	BT
1	1	1	1	1

Note 1: The EUT has one antenna.

For 2.4GHz function:

For IEEE 802.11 b/g/n mode (1TX/1RX)

Ant. 1 (port 1) could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11 a/n/ac mode (1TX/1RX)

Ant. 1 (port 1) could transmit/receive simultaneously.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 1 (port 1) could transmit/receive simultaneously.



1.1.3 EUT Information

Operational Condition	
EUT Power Type	From PoE
EUT Function	<input type="checkbox"/> Point-to-multipoint <input checked="" type="checkbox"/> Point-to-point
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device)	
Combined Equipment - Brand Name / Model No.:	...
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems)	
Host System - Brand Name / Model No.:	...
<input type="checkbox"/> Other:	

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
BT-LE(1Mbps)	0.628	2.02	392.5u	3k

Note. If DC < 0.98, the DCF was added while measuring Output power and PSD.

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2013
- ◆ KDB 558074 D01 v05

1.3 Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
AC Conduction	CO04-HY	Andy	23°C / 61%	13/Nov/2018
RF Conducted	TH01-HY	Streak	23.4°C / 64%	28/Dec/2018
Radiated	03CH02-HY	Lego	23°C / 63%	28/Dec/2018

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.54 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	1.6 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.9 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%
Temperature	0.7 °C	Confidence levels of 95%
Humidity	4 %	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Condition

RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	110V




2.2 Test Channel Mode

Test Software Version	QDART-V 100038
-----------------------	----------------

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	PoE mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	PoE mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT			V




2.4 Support Equipment

Support Equipment – AC Conduction				
No.	Equipment	Brand Name	Model Name	FCC ID
1	PoE	UBNT	GP-C500-120G	N/A

Support Equipment – RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	DoC
2	Adapter for NB	N/A	N/A	DoC

Support Equipment – Radiated Emission				
No.	Equipment	Brand Name	Model Name	FCC ID
1	PoE(Remote)	UBNT	GP-C500-120G	N/A

2.5 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as ANSI C63.10-2013, clause 6.2 foray power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
<ul style="list-style-type: none"> ▪ 6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<ul style="list-style-type: none"> ▪ For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as KDB 558074, clause 8.2 (11.8 of ANSI C63.10) DTS bandwidth measurement.
<input type="checkbox"/> Refer as RSS-Gen, clause 6.7 for for occupied bandwidth testing.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"> ▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	<ul style="list-style-type: none"> ▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	<ul style="list-style-type: none"> ▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> ▪ Smart antenna system (SAS):
	<ul style="list-style-type: none"> - Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
e.i.r.p. Power Limit:	
	<ul style="list-style-type: none"> ▪ 2400-2483.5 MHz Band
	<ul style="list-style-type: none"> ▪ Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	<ul style="list-style-type: none"> ▪ Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
	<ul style="list-style-type: none"> ▪ Smart antenna system (SAS)
	<ul style="list-style-type: none"> - Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<ul style="list-style-type: none"> - Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
<p>P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.</p>	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> ▪ Maximum Peak Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.1 (11.9.1.1 of ANSI C63.10) RBW ≥ EBW method.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.2 (11.9.1.2 of ANSI C63.10) integrated band power method.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.3 (11.9.1.3 of ANSI C63.10) peak power meter.
<ul style="list-style-type: none"> ▪ Maximum Average Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.2.2 (11.9.2.2 of ANSI C63.10) using a spectrum analyzer.
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.3.2.3 (11.9.2.3 of ANSI C63.10) using a power meter.
<ul style="list-style-type: none"> ▪ For conducted measurement. 	
<ul style="list-style-type: none"> ▪ If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. 	
<ul style="list-style-type: none"> ▪ If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$ 	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<ul style="list-style-type: none"> Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
	<ul style="list-style-type: none"> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.4 (11.10 of ANSI C63.10) Method PKPSD.
	<ul style="list-style-type: none"> For conducted measurement. <ul style="list-style-type: none"> If The EUT supports multiple transmit chains using options given below: <ul style="list-style-type: none"> Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as KDB 558074, clause 8.5 (11.11 of ANSI C63.10) for non-restricted frequency bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
	<ul style="list-style-type: none"> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
	<ul style="list-style-type: none"> Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
	<ul style="list-style-type: none"> For the transmitter unwanted emissions shall be measured using following options below: <ul style="list-style-type: none"> Refer as KDB 558074, clause 8.6 (11.12 of ANSI C63.10) for restricted frequency bands.
	<ul style="list-style-type: none"> For the transmitter band-edge emissions shall be measured using following options below: <ul style="list-style-type: none"> Refer as KDB 558074 clause 8.7.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below. Refer as KDB 558074, clause 8.7.2 (6.10.6 of ANSI C63.10) for marker-delta method for band-edge measurements. Refer as KDB 558074, clause 8.7.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	<ul style="list-style-type: none"> Use the following spectrum analyzer settings: <ul style="list-style-type: none"> Set RBW=100 kHz for $f < 1$ GHz; VBW=3 * RBW; Sweep = auto; Detector function = peak; Trace = max hold. Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. For average measurement, refer as 1.1.4.

3.6.4 Test Setup





3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument for AC Conduction

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR	102051	9KHz ~ 3.6GHz	03/May/2018	02/May/2019
LISN	R&S	ENV216	101295	9kHz ~ 30MHz	17/Nov/2017	16/Nov/2018
RF Cable-CON	MTJ	RG142	CB002-CO	9kHz ~ 200MHz	17/Sep/2018	16/Sep/2019
AC POWER	APC	AFC-11005G	F310050055	47Hz~63Hz 5~300V	NCR	NCR
Impuls Begrenzer Pulse Limiter	SCHWARZBECK	VTSD 9561-F	9561-F041	9 kHz ~ 30 MHz	12/Oct/2018	11/Oct/2019

NCR : Non-Calibration Require

Instrument for Conducted Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101013	10Hz~40GHz	05/Feb/2018	04/Feb/2019
Power Sensor	Anritsu	MA2411B	0917017	300MHz ~ 40GHz	05/Feb/2018	04/Feb/2019
Power Meter	Anritsu	ML2495A	0949003	300MHz ~ 40GHz	05/Feb/2018	04/Feb/2019
2Way Divider	Microwave	MVE8546	TH01-DV-01	1MHz~6MHz	23/Jan/2018	22/Jan/2019
Cable 0.2m	HUBER	MY10710/4	RF Cable - 01	30MHz~1G	11/Jan/2018	10/Jan/2019
Cable 0.2m	HUBER	MY10710/4	RF Cable - 01	1G~18G	11/Jan/2018	10/Jan/2019
Cable 0.5m	HUBER	MY10714/4	RF Cable - 05	30MHz~1G	11/Jan/2018	10/Jan/2019
SMB100A Signal Generator	R&S	SMB100A03	181147	100kHz~40GHz	12/Nov/2018	10/Nov/2020

Instrument for Radiated Test


Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	19/Oct/2018	18/Oct/2019
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	1GHz ~ 18GHz 3m	17/Oct/2018	16/Oct/2019
Amplifier	Agilent	8447D	2944A11149	100kHz ~ 1.3GHz	27Jul/2018	02/Jul/2019
Microwave Preamplifier	Agilent	8449B	3008A02373	1GHz ~ 26.5GHz	23/Oct/2018	22/Oct/2019
Signal Analyzer	R&S	FSV40	101500	10Hz ~ 40GHz	18/Jul/2018	17/Jul/2019
RF Cable-R03m	Jye Bao	RG142	CB017	9kHz ~ 1GHz	19/Jan/2018	18/Jan/2019
RF Cable-high	SUHNER	SUCOFLEX104	MY34918/4	1GHz ~ 40GHz	19/Jan/2018	18/Jan/2019
Bilog Antenna & 5dB Attenuator	SCHAFFNER / MTJ	CBL 6112B / MTJ6102-05	2723 / 2	30MHz ~ 1GHz	08/Sep/2018	07/Sep/2019
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA 9170154	18GHz ~ 40GHz	06/Feb/2018	05/Feb/2019
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120D	BBHA 9120 D 1531	1GHz ~ 18GHz	18/Apr/ 2018	17/Apr/2019
Preamplifier	MITEQ	TTA1840-35-HG	1864481	18GHz ~ 40GHz	24/Aug/2018	23/Aug/2019
EMI Test Receiver	R&S	ESR3	102052	9kHz ~ 3.6GHz	10/Apr/2018	09/Apr/2019



AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Neutral
Operating Function	PoE mode		

13/11/2018




Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)
QP	163.205k	41.84	65.29	-23.45	19.66	Neutral	-	22.18	9.63	0.03	10.00
AV	163.205k	31.93	55.29	-23.36	19.66	Neutral	-	12.27	9.63	0.03	10.00
QP	397.221k	48.12	57.91	-9.79	19.71	Neutral	-	28.41	9.61	0.10	10.00
AV	397.221k	39.11	47.91	-8.80	19.71	Neutral	-	19.40	9.61	0.10	10.00
QP	588.888k	36.26	56.00	-19.74	19.67	Neutral	-	16.59	9.61	0.06	10.00
AV	588.888k	27.87	46.00	-18.13	19.67	Neutral	-	8.20	9.61	0.06	10.00
QP	18.207M	44.10	60.00	-15.90	19.85	Neutral	-	24.25	9.71	0.14	10.00
AV	18.207M	42.31	50.00	-7.69	19.85	Neutral	-	22.46	9.71	0.14	10.00
QP	21.518M	45.66	60.00	-14.34	19.84	Neutral	-	25.82	9.71	0.13	10.00
AV	21.518M	43.19	50.00	-6.81	19.84	Neutral	-	23.35	9.71	0.13	10.00
QP	29.322M	46.85	60.00	-13.15	19.95	Neutral	-	26.90	9.69	0.26	10.00
AV	29.322M	45.32	50.00	-4.68	19.95	Neutral	"Worst"	25.37	9.69	0.26	10.00



AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	PoE mode		

13/11/2018



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)
QP	161.469k	41.15	65.39	-24.24	19.65	Line	-	21.50	9.62	0.03	10.00
AV	161.469k	30.28	55.39	-25.11	19.65	Line	-	10.63	9.62	0.03	10.00
QP	399.392k	48.34	57.87	-9.53	19.71	Line	-	28.63	9.61	0.10	10.00
AV	399.392k	39.50	47.87	-8.37	19.71	Line	-	19.79	9.61	0.10	10.00
QP	1.241M	36.90	56.00	-19.10	19.62	Line	-	17.28	9.61	0.01	10.00
AV	1.241M	27.28	46.00	-18.72	19.62	Line	-	7.66	9.61	0.01	10.00
QP	20.098M	46.44	60.00	-13.56	19.82	Line	-	26.62	9.62	0.20	10.00
AV	20.098M	44.14	50.00	-5.86	19.82	Line	-	24.32	9.62	0.20	10.00
QP	26.48M	46.30	60.00	-13.70	19.64	Line	-	26.66	9.54	0.10	10.00
AV	26.48M	44.87	50.00	-5.13	19.64	Line	-	25.23	9.54	0.10	10.00
QP	27.901M	47.31	60.00	-12.69	19.71	Line	-	27.60	9.52	0.19	10.00
AV	27.901M	46.01	50.00	-3.99	19.71	Line	"Worst"	26.30	9.52	0.19	10.00



Summary


Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	675k	1.064M	1M06F1D	666.25k	1.053M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	673.75k	1.058M
2440MHz	Pass	500k	666.25k	1.064M
2480MHz	Pass	500k	675k	1.053M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;





Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	1.41	0.00138

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	1.00	1.41	30.00
2440MHz	Pass	1.00	-5.15	30.00
2480MHz	Pass	1.00	-2.21	30.00



Summary


Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-14.71

RBW=3kHz.

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	1.00	-14.71	8.00
2440MHz	Pass	1.00	-19.72	8.00
2480MHz	Pass	1.00	-16.15	8.00

RBW=3kHz.






Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.402G	1.35	-28.65	1.63669G	-45.10	2.3994G	-45.16	2.4842G	-44.27	17.45764G	-32.38	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.402G	1.35	-28.65	1.63669G	-45.10	2.3994G	-45.16	2.4842G	-44.27	17.45764G	-32.38	1
2440MHz	Pass	2.402G	1.35	-28.65	2.30979G	-46.04	2.39946G	-44.78	2.48419G	-44.10	16.44449G	-33.31	1
2480MHz	Pass	2.402G	1.35	-28.65	2.08809G	-45.31	2.39991G	-44.40	2.48368G	-44.01	16.2306G	-33.05	1





Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	PK	394.72M	38.03	46.00	-7.97	-3.79	3	Horizontal	0	2.00	-




Result




Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2440MHz	Pass	PK	123.12M	30.02	43.50	-13.48	-8.83	3	Vertical	360	1.00	-
2440MHz	Pass	PK	159.98M	30.00	43.50	-13.50	-10.39	3	Vertical	360	1.00	-
2440MHz	Pass	PK	212.36M	27.80	43.50	-15.70	-10.59	3	Vertical	360	1.00	-
2440MHz	Pass	PK	394.72M	36.30	46.00	-9.70	-3.79	3	Vertical	360	1.00	-
2440MHz	Pass	PK	445.16M	32.40	46.00	-13.60	-2.90	3	Vertical	360	1.00	-
2440MHz	Pass	PK	722.58M	37.60	46.00	-8.40	0.44	3	Vertical	360	1.00	-
2440MHz	Pass	PK	123.12M	30.45	43.50	-13.05	-8.83	3	Horizontal	0	2.00	-
2440MHz	Pass	PK	210.42M	31.62	43.50	-11.88	-10.61	3	Horizontal	0	2.00	-
2440MHz	Pass	PK	247.28M	30.92	46.00	-15.08	-7.26	3	Horizontal	0	2.00	-
2440MHz	Pass	PK	394.72M	38.03	46.00	-7.97	-3.79	3	Horizontal	0	2.00	-
2440MHz	Pass	PK	612M	30.87	46.00	-15.13	-0.61	3	Horizontal	0	2.00	-
2440MHz	Pass	PK	771.08M	32.94	46.00	-13.06	1.19	3	Horizontal	0	2.00	-

BT-LE(1Mbps)

28/12/2018

2440MHz_PoE




Lim.PK 
 PK 
 Lim.AV 
 AV 





Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	123.12M	30.02	43.50	-13.48	-8.83	3	Vertical	360	1.00	-
PK	159.98M	30.00	43.50	-13.50	-10.39	3	Vertical	360	1.00	-
PK	212.36M	27.80	43.50	-15.70	-10.59	3	Vertical	360	1.00	-
PK	394.72M	36.30	46.00	-9.70	-3.79	3	Vertical	360	1.00	-
PK	445.16M	32.40	46.00	-13.60	-2.90	3	Vertical	360	1.00	-
PK	722.58M	37.60	46.00	-8.40	0.44	3	Vertical	360	1.00	-

BT-LE(1Mbps)

28/12/2018

2440MHz_PoE



Lim.PK 
 PK 
 Lim.AV 
 AV 

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	123.12M	30.45	43.50	-13.05	-8.83	3	Horizontal	0	2.00	-
PK	210.42M	31.62	43.50	-11.88	-10.61	3	Horizontal	0	2.00	-
PK	247.28M	30.92	46.00	-15.08	-7.26	3	Horizontal	0	2.00	-
PK	394.72M	38.03	46.00	-7.97	-3.79	3	Horizontal	0	2.00	-
PK	612M	30.87	46.00	-15.13	-0.61	3	Horizontal	0	2.00	-
PK	771.08M	32.94	46.00	-13.06	1.19	3	Horizontal	0	2.00	-



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.484G	45.07	54.00	-8.93	32.29	3	Vertical	191	1.50	-




Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.381G	44.97	54.00	-9.03	31.97	3	Vertical	193	1.50	-
2402MHz	Pass	AV	2.402G	90.99	Inf	-Inf	32.04	3	Vertical	193	1.50	-
2402MHz	Pass	PK	2.3602G	56.95	74.00	-17.05	31.90	3	Vertical	193	1.50	-
2402MHz	Pass	PK	2.4022G	92.39	Inf	-Inf	32.05	3	Vertical	193	1.50	-
2402MHz	Pass	AV	2.3776G	44.85	54.00	-9.15	31.97	3	Horizontal	202	1.14	-
2402MHz	Pass	AV	2.402G	90.60	Inf	-Inf	32.04	3	Horizontal	202	1.14	-
2402MHz	Pass	PK	2.3622G	56.09	74.00	-17.91	31.91	3	Horizontal	202	1.14	-
2402MHz	Pass	PK	2.4022G	92.07	Inf	-Inf	32.05	3	Horizontal	202	1.14	-
2402MHz	Pass	AV	4.80216G	32.64	54.00	-21.36	3.33	3	Vertical	151	1.28	-
2402MHz	Pass	PK	4.80389G	45.55	74.00	-28.45	3.34	3	Vertical	151	1.28	-
2402MHz	Pass	AV	4.80399G	32.55	54.00	-21.45	3.34	3	Horizontal	212	1.68	-
2402MHz	Pass	PK	4.80307G	45.21	74.00	-28.79	3.34	3	Horizontal	212	1.68	-
2440MHz	Pass	AV	2.3524G	44.97	54.00	-9.03	31.88	3	Vertical	191	1.50	-
2440MHz	Pass	AV	2.44G	84.12	Inf	-Inf	32.16	3	Vertical	191	1.50	-
2440MHz	Pass	AV	2.484G	45.07	54.00	-8.93	32.29	3	Vertical	191	1.50	-
2440MHz	Pass	PK	2.3724G	56.20	74.00	-17.80	31.94	3	Vertical	191	1.50	-
2440MHz	Pass	PK	2.44G	85.74	Inf	-Inf	32.16	3	Vertical	191	1.50	-
2440MHz	Pass	PK	2.4988G	55.67	74.00	-18.33	32.34	3	Vertical	191	1.50	-
2440MHz	Pass	AV	2.3608G	44.84	54.00	-9.16	31.91	3	Horizontal	87	1.23	-
2440MHz	Pass	AV	2.44G	82.11	Inf	-Inf	32.16	3	Horizontal	87	1.23	-
2440MHz	Pass	AV	2.4928G	45.03	54.00	-8.97	32.32	3	Horizontal	87	1.23	-
2440MHz	Pass	PK	2.3756G	56.34	74.00	-17.66	31.96	3	Horizontal	87	1.23	-
2440MHz	Pass	PK	2.4396G	83.61	Inf	-Inf	32.16	3	Horizontal	87	1.23	-
2440MHz	Pass	PK	2.5G	56.67	74.00	-17.33	32.34	3	Horizontal	87	1.23	-
2440MHz	Pass	AV	4.88001G	32.98	54.00	-21.02	3.52	3	Vertical	85	1.64	-
2440MHz	Pass	PK	4.88094G	45.37	74.00	-28.63	3.53	3	Vertical	85	1.64	-
2440MHz	Pass	AV	4.87802G	33.02	54.00	-20.98	3.52	3	Horizontal	302	1.51	-
2440MHz	Pass	PK	4.87947G	46.72	74.00	-27.28	3.52	3	Horizontal	302	1.51	-
2480MHz	Pass	AV	2.48G	83.15	Inf	-Inf	32.28	3	Vertical	218	1.50	-
2480MHz	Pass	AV	2.4944G	44.96	54.00	-9.04	32.33	3	Vertical	218	1.50	-
2480MHz	Pass	PK	2.4802G	84.66	Inf	-Inf	32.28	3	Vertical	218	1.50	-
2480MHz	Pass	PK	2.4872G	56.62	74.00	-17.38	32.30	3	Vertical	218	1.50	-
2480MHz	Pass	AV	2.48G	80.68	Inf	-Inf	32.28	3	Horizontal	102	1.23	-
2480MHz	Pass	AV	2.4926G	45.01	54.00	-8.99	32.32	3	Horizontal	102	1.23	-
2480MHz	Pass	PK	2.4802G	82.22	Inf	-Inf	32.28	3	Horizontal	102	1.23	-
2480MHz	Pass	PK	2.4924G	56.40	74.00	-17.60	32.32	3	Horizontal	102	1.23	-
2480MHz	Pass	AV	4.95914G	33.39	54.00	-20.61	3.71	3	Vertical	23	1.56	-
2480MHz	Pass	PK	4.95825G	45.83	74.00	-28.17	3.70	3	Vertical	23	1.56	-
2480MHz	Pass	AV	4.95783G	33.50	54.00	-20.50	3.70	3	Horizontal	127	1.74	-
2480MHz	Pass	PK	4.9594G	45.79	74.00	-28.21	3.71	3	Horizontal	127	1.74	-

BT-LE(1Mbps)

2402MHz_TX

28/12/2018








Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.381G	44.97	54.00	-9.03	31.97	3	Vertical	193	1.50	-
AV	2.402G	90.99	Inf	-Inf	32.04	3	Vertical	193	1.50	-
PK	2.3602G	56.95	74.00	-17.05	31.90	3	Vertical	193	1.50	-
PK	2.4022G	92.39	Inf	-Inf	32.05	3	Vertical	193	1.50	-

BT-LE(1Mbps)

2402MHz_TX

28/12/2018



Lim.PK 
 PK 
 Lim.AV 
 AV 


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3776G	44.85	54.00	-9.15	31.97	3	Horizontal	202	1.14	-
AV	2.402G	90.60	Inf	-Inf	32.04	3	Horizontal	202	1.14	-
PK	2.3622G	56.09	74.00	-17.91	31.91	3	Horizontal	202	1.14	-
PK	2.402G	92.07	Inf	-Inf	32.05	3	Horizontal	202	1.14	-



BT-LE(1Mbps)

2402MHz_TX

28/12/2018



Lim.PK
 PK
 Lim.AV
 AV


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.80216G	32.64	54.00	-21.36	3.33	3	Vertical	151	1.28	-
PK	4.80389G	45.55	74.00	-28.45	3.34	3	Vertical	151	1.28	-



BT-LE(1Mbps)

2402MHz_TX

28/12/2018



Legend for plot:


- Lim.PK
- PK
- Lim.AV
- AV




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.80399G	32.55	54.00	-21.45	3.34	3	Horizontal	212	1.68	-
PK	4.80307G	45.21	74.00	-28.79	3.34	3	Horizontal	212	1.68	-

BT-LE(1Mbps)

2440MHz_TX

28/12/2018




Lim.PK 
 PK 
 Lim.AV 
 AV 

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3524G	44.97	54.00	-9.03	31.88	3	Vertical	191	1.50	-
AV	2.44G	84.12	Inf	-Inf	32.16	3	Vertical	191	1.50	-
AV	2.484G	45.07	54.00	-8.93	32.29	3	Vertical	191	1.50	-
PK	2.3724G	56.20	74.00	-17.80	31.94	3	Vertical	191	1.50	-
PK	2.44G	85.74	Inf	-Inf	32.16	3	Vertical	191	1.50	-
PK	2.4988G	55.67	74.00	-18.33	32.34	3	Vertical	191	1.50	-

BT-LE(1Mbps)

2440MHz_TX

28/12/2018



- Lim.PK
- PK
- Lim.AV
- AV


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3608G	44.84	54.00	-9.16	31.91	3	Horizontal	87	1.23	-
AV	2.44G	82.11	Inf	-Inf	32.16	3	Horizontal	87	1.23	-
AV	2.4928G	45.03	54.00	-8.97	32.32	3	Horizontal	87	1.23	-
PK	2.3756G	56.34	74.00	-17.66	31.96	3	Horizontal	87	1.23	-
PK	2.4396G	83.61	Inf	-Inf	32.16	3	Horizontal	87	1.23	-
PK	2.5G	56.67	74.00	-17.33	32.34	3	Horizontal	87	1.23	-



BT-LE(1Mbps)

2440MHz_TX

28/12/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.88001G	32.98	54.00	-21.02	3.52	3	Vertical	85	1.64	-
PK	4.88094G	45.37	74.00	-28.63	3.53	3	Vertical	85	1.64	-



BT-LE(1Mbps)

28/12/2018

2440MHz_TX








Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.87802G	33.02	54.00	-20.98	3.52	3	Horizontal	302	1.51	-
PK	4.87947G	46.72	74.00	-27.28	3.52	3	Horizontal	302	1.51	-

BT-LE(1Mbps)

2480MHz_TX

28/12/2018




Lim.PK 
 PK 
 Lim.AV 
 AV 





Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.48G	83.15	Inf	-Inf	32.28	3	Vertical	218	1.50	-
AV	2.4944G	44.96	54.00	-9.04	32.33	3	Vertical	218	1.50	-
PK	2.4802G	84.66	Inf	-Inf	32.28	3	Vertical	218	1.50	-
PK	2.4872G	56.62	74.00	-17.38	32.30	3	Vertical	218	1.50	-

BT-LE(1Mbps)

2480MHz_TX

28/12/2018



Lim.PK 
 PK 
 Lim.AV 
 AV 


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.48G	80.68	Inf	-Inf	32.28	3	Horizontal	102	1.23	-
AV	2.4926G	45.01	54.00	-8.99	32.32	3	Horizontal	102	1.23	-
PK	2.4802G	82.22	Inf	-Inf	32.28	3	Horizontal	102	1.23	-
PK	2.4924G	56.40	74.00	-17.60	32.32	3	Horizontal	102	1.23	-



BT-LE(1Mbps)

2480MHz_TX

28/12/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.95914G	33.39	54.00	-20.61	3.71	3	Vertical	23	1.56	-
PK	4.95825G	45.83	74.00	-28.17	3.70	3	Vertical	23	1.56	-



BT-LE(1Mbps)

28/12/2018

2480MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.95783G	33.50	54.00	-20.50	3.70	3	Horizontal	127	1.74	-
PK	4.9594G	45.79	74.00	-28.21	3.71	3	Horizontal	127	1.74	-