



RADIO TEST REPORT

Report No:STS1906029W01

Issued for

Bartec USA LLC.

44231 Phoenix Drive Sterling Heights Michigan United States

Product Name:	RITE-SENSOR
Brand Name:	Bartec
Model Name:	RITE-SENSOR
Series Model:	RS-1000
FCC ID:	SX8-RS1000
Test Standard:	FCC Part 15.231

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





TEST REPORT CERTIFICATION

Applicant's Name: Bartec USA LLC.
Address: 44231 Phoenix Drive Sterling Heights Michigan United States

Manufacture's Name: Bartec USA LLC.
Address: 44231 Phoenix Drive Sterling Heights Michigan United States

Product Description

Product Name: RITE-SENSOR
Brand Name: Bartec
Model Name: RITE-SENSOR
Series Model: RS-1000


Test Standards.....: FCC Part 15.231


Test Procedure: ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test:
Date of performance of tests...: 11 June 2019 ~ 12 July 2019
Date of Issue: 12 July 2019
Test Result: **Pass**

Testing Engineer : 
(Chris Chen)

Technical Manager : 
(Sunday Hu)


Authorized Signatory : 
(Vita Li)






TABLE OF CONTENTS	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3. EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.2 TEST PROCEDURE	12
3.3 TEST SETUP	12
3.4 TEST RESULTS	12
4. RADIATED EMISSION MEASUREMENT	13
4.1 RADIATED EMISSION LIMITS	13
4.2 TEST PROCEDURE	14
4.3 DEVIATION FROM TEST STANDARD	15
4.4 TEST SETUP	15
4.5 EUT OPERATING CONDITIONS	16
4.6 TEST RESULTS	16
4.7 FIELD STRENGTH CALCULATION	17
4.8 TEST RESULTS (EMISSION)	17
5. BANDWIDTH TEST	30
5.1 LIMIT	30
5.2 TEST REQUIREMENTS	30
5.3 TEST PROCEDURE	30
5.4 TEST SETUP	30
5.5 EUT OPERATION CONDITIONS	30
5.6 TEST RESULTS	31
6. TRANSMITTER TIMEOUT	35
6.1 LIMIT	35
6.2 TEST PROCEDURE	35
6.3 TEST SETUP	35



TABLE OF CONTENTS	Page
6.4 TEST RESULTS	36
7. PERIODIC OPERATION	40
7.1 TEST PROCEDURE	40
7.2 TEST SETUP	40
7.3 EUT OPERATION CONDITIONS	40
7.4 TEST RESULTS	41
8. ANTENNA REQUIREMENT	45
8.1 STANDARD REQUIREMENT	45
8.2 EUT ANTENNA	45
APPENDIX 1- PHOTOS OF TEST SETUP	46





Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	21 June 2019	STS1906029W01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part 15.231, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	--
15.205(a)/15.209/ 15.231.(e)	Radiated Spurious Emission	PASS	--
15.231	Transmission requirement	PASS	--
15.231(C)	Bandwidth	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE: (1)"N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.4-2014 and ANSI C63.10-2013

1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

FCC test Firm Registration Number: 625569

A2LA Certificate No.: 4338.01;

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	± 0.71 dB
2	Unwanted Emissions, conducted	± 0.63 dB
3	All emissions, radiated 30-200MHz	± 3.43 dB
4	All emissions, radiated 200MHz-1GHz	± 3.57 dB
5	All emissions, radiated >1G	± 4.13 dB
6	Conducted Emission (9KHz-150KHz)	± 3.18 dB
7	Conducted Emission (150KHz-30MHz)	± 2.70 dB



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	RITE-SENSOR	
Trade Name	Bartec	
Model Name	RITE-SENSOR	
Series Model	RS-1000	
Model Difference	Only difference in model name.	
Product Description	The EUT is a RITE-SENSOR	
	Product Type	Low Power Communication Device Transmitter
	Operation Frequency:	315MHz, 433.92MHz
	Modulation Type:	ASK,FSK
	Antenna Designation:	Internal antenna
	Antenna Gain(Peak)	2 dBi
	More details of EUT technical specification, please refer to the User's Manual.	
Battery	Capacity: 345mAh Rated Voltage: DC3V	
Hardware version number	1.0.0	
Software version number	1.0.0	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. The EUT is assembled with three kinds of valves with different materials and structure, not affect the RF characteristics.
3. Table for filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	Bartec	RITE-SENSOR	Internal Ant.	N/A	2	Antenna



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode(315MHz)
Mode 2	TX Mode(433.92MHz)

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode(315MHz)
Mode 2	TX Mode(433.92MHz)

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

E-1
EUT

Note: New battery is used during all test, X, Y, Z axial test all have been done, only worse case is reported.



2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1)The support equipment was authorized by Declaration of Confirmation.
- (2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2018.10.13	2019.10.12
Signal Analyzer	Agilent	N9020A	MY51110105	2019.03.02	2020.03.01
Active loop Antenna	ZHINAN	ZN30900C	16035	2018.03.11	2021.03.10
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.01
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10
Pre-Amplifier(0.1M-3 GHz)	EM	EM330	060665	2018.10.13	2019.10.12
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2018.10.13	2019.10.12
Temperature & Humidity	HH660	Mieo	N/A	2018.10.11	2019.10.10
turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2018.10.13	2019.10.12
Signal Analyzer	Agilent	N9020A	MY49100060	2018.10.13	2019.10.12
Temperature & Humidity	HH660	Mieo	N/A	2018.10.11	2019.10.10



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15. 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



- Note: 1. Support units were connected to second LISN.**
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.4 TEST RESULTS

Temperature:	26 °C	Relative Humidity:	54%
Phase:	L/N	Test Mode:	N/A

Note: EUT is only power by battery, So it is not applicable for this test.



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on Part 15.205(a), then the Part 15.209(a) and Part 15.231(e) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~40.66	100	3
40.66~40.70	100	3
40.70~70	100	3

LIMITS OF RADIATED EMISSION MEASUREMENT

Fundamental Frequency (MHz)	Field Strength of fundamental (microvolts/meter)	Field Strength of Unwanted Emissions (microvolts/meter)
40.66 - 40.70	1,000	100
70 - 130	500	50
130 - 174	500 to 1,500 **	50 to 1,50 **
174 - 260	1,500	1,50
260 - 470	1,500 to 5,000 **	1,50 to 5,00 **
Above 470	5,000	5,00

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

NOTE:** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental

field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = 22.72727(F) - 2454.545;

for the band 260-470 MHz, uV/m at 3 meters = 16.6667(F) - 2833.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in 93 Section 15.209, whichever limit permits a higher field strength.



Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz/9kHz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE

- a. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Below 1GHz)
- b. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Above 1GHz)
- c. The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform (Below 1GHz)
- f. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform. (Above 1GHz)
- g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: Both horizontal and vertical antenna polarities were tested


and performed pretest to three orthogonal axis. The worst case emissions were reported

4.3 DEVIATION FROM TEST STANDARD


No deviation

4.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

INTRODUCTION TO PDCF

Reference: (§15.35 Measurement detector functions and bandwidths.)

- a. Part 15 of the FCC Rules provides for the operation of low power communication devices without an individual license (e.g., intrusion detectors, pulsed water tank level gauges, etc.), subject to certain requirements. Some of these devices use extremely narrow pulses to generate wideband emissions, which are measured to determine compliance with the rules. These measurements are typically performed with a receiver or spectrum analyzer. Depending on a number of factors (e.g., resolution bandwidth, pulsewidth, etc.), the spectrum analyzer may not always display the true peak value of the measured emission. This effect, called “pulse desensitization,” relates to the capabilities of the measuring instrument. For the measurement and reporting of the true peak of pulsed emissions, it may be necessary to apply a “pulse desensitization correction factor” (PDCF) to the measured value, pursuant to 47 CFR 15.35(a).



If using spectrum analyzer to measure pulse signal , it have to make sure the RBW use is at least $2/PW$.

•When RBW is less than $2/PW$, you are able to measure the true peak level of the pulse signal. If this is the case , PDCF is required to compensate to determine true peak value.

Pulse desensitization(ASK):

For 315MHz:

$PW = 28700\text{usec}$, $\text{Period} = 100000\text{usec}$, $\text{Level} = A$; $RBW > 2/PW = 0.07K$, $PRF = 1/T = 0.01K$

For 433.92MHz:

$PW = 16800\text{usec}$, $\text{Period} = 100000\text{usec}$, $\text{Level} = A$; $RBW > 2/PW = 0.12K$, $PRF = 1/T = 0.01K$

Pulse desensitization(FSK):

For 315MHz:

$PW = 28900\text{usec}$, $\text{Period} = 100000\text{usec}$, $\text{Level} = A$; $RBW > 2/PW = 0.07K$, $PRF = 1/T = 0.01K$

For 433.92MHz:

$PW = 17700\text{usec}$, $\text{Period} = 100000\text{usec}$, $\text{Level} = A$; $RBW > 2/PW = 0.11K$, $PRF = 1/T = 0.01K$

NOTE: $2 / PW < RBW$, first don't need

- b. For the actual test, please refer to the ANSI C63.10, Annex C refer to section 7 for more detail



4.7 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

4.8 TEST RESULTS (EMISSION)

(Radiated Emission < 30MHz (9KHz-30MHz, H-field))

Temperature:	26.2 °C	Relative Humidity:	52%
Test Mode:	Mode 1	Polarization:	--

Note: Vertical level have a test this is the worst.

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	PASS
--	--	--	--	PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



Between 30MHz – 5000 MHz

ASK

Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Horizontal	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.1052	29.02	-10.25	-	18.77	40.00	-21.23	QP
2	56.0007	36.11	-23.07	-	13.04	40.00	-26.96	QP
3	118.1860	28.30	-16.85	-	11.45	43.50	-32.05	QP
5	631.6884	36.46	-6.25	-	30.21	67.67	-37.46	Peak
8	631.6884	30.21	-	-10.84	19.37	47.67	-28.3	AV
6	945.4397	41.47	0.03	-	41.50	67.67	-24.17	Peak
9	945.4397	41.50	-	-10.84	30.66	47.67	-17.01	AV


Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4	315.4806	82.22	-13.32	-	68.90	87.67	-18.77	peak
7	315.4806	68.90	-	-10.84	58.06	67.67	-9.61	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit

80.0 dBuV/m





Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Vertical	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.2110	29.39	-11.30	-	18.09	40.00	-21.91	QP
2	53.5052	38.81	-22.48	-	16.33	40.00	-23.67	QP
3	132.2204	27.33	-17.54	-	9.79	43.50	-33.71	QP
5	631.6884	30.80	-6.40	-	24.40	67.67	-43.27	Peak
8	631.6884	24.40	-	-10.84	13.56	47.67	-34.11	AV
6	945.4397	40.86	-0.54	-	40.32	67.67	-27.35	Peak
9	945.4397	40.32	-	-10.84	29.48	47.67	-18.19	AV


Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4	315.4806	80.51	-14.32	-	66.19	87.67	-21.48	peak
7	315.4806	66.19	-	-10.84	55.35	67.67	-12.32	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit

80.0 dBuV/m





Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Horizontal	Test Mode:	Mode 2


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	31.69	-10.19	-	21.50	40.00	-18.50	QP
2	129.4677	32.22	-16.64	-	15.58	43.50	-27.92	QP
3	280.0237	29.15	-14.20	-	14.95	46.00	-31.05	QP
5	640.6110	29.90	-5.96	-	23.94	46.00	-22.06	QP
6	869.1302	42.39	-2.32	-	40.07	72.87	-32.80	peak
8	869.1302	40.07		-15.49	24.58	52.87	-28.29	AV

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4	434.0651	82.26	-10.99	-	71.27	92.87	-21.60	peak
7	434.0651	71.27	-	-15.49	55.78	72.87	-17.09	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit





Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Vertical	Test Mode:	Mode 2

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.1054	32.25	-11.24	-	21.01	40.00	-18.99	QP
2	129.0146	30.25	-17.56	-	12.69	43.50	-30.81	QP
3	285.9778	30.89	-15.57	-	15.32	46.00	-30.68	QP
5	642.8613	29.64	-6.34	-	23.30	46.00	-22.70	QP
6	869.1302	37.26	-2.61	-	34.65	72.87	-38.22	peak
8	869.1302	34.65	-	-15.49	19.16	52.87	-33.71	AV


Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4	434.0651	82.01	-10.99	-	71.02	92.87	-21.85	peak
7	434.0651	71.02	-	-15.49	55.53	72.87	-17.34	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit

80.0 dBuV/m





FSK

Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Horizontal	Test Mode:	Mode 1


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	28.09	-10.19	-	17.90	40.00	-22.10	QP
2	98.1420	27.17	-18.81	-	8.36	43.50	-35.14	QP
3	126.7723	27.18	-16.63	-	10.55	43.50	-32.95	QP
5	631.6884	40.83	-6.25	-	34.58	67.67	-33.09	peak
8	631.6884	34.58	-	-10.78	23.80	47.67	-23.87	AV
6	993.0113	24.46	0.07	-	24.53	67.67	-43.14	peak
9	993.0113	24.53	-	-10.78	13.75	47.67	-33.92	AV

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4	315.4806	86.85	-13.32	-	73.53	87.67	-14.14	peak
7	315.4806	73.53	-	-10.78	62.75	67.67	-4.92	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit





Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Vertical	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.5304	30.63	-11.47	-	19.16	40.00	-20.84	QP
2	109.7960	31.39	-18.36	-	13.03	43.50	-30.47	QP
3	231.7178	33.23	-18.36	-	14.87	46.00	-31.13	QP
5	631.6884	34.14	-6.40	-	27.74	67.67	-39.93	peak
8	631.6884	27.74	-	-10.78	16.96	47.67	-30.71	AV
6	945.4397	41.87	-0.54	-	41.33	67.67	-26.34	peak
9	945.4397	41.33	-	-10.78	30.55	47.67	-17.12	AV


Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4	315.4806	79.47	-14.32	-	65.15	87.67	-22.52	peak
7	315.4806	65.15	-	-10.78	54.37	67.67	-13.30	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor)–Limit

80.0 dBuV/m





Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Horizontal	Test Mode:	Mode 2


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.3173	29.33	-10.36	-	18.97	40.00	-21.03	QP
2	55.2207	41.14	-22.75	-	18.39	40.00	-21.61	QP
3	82.6482	36.13	-21.23	-	14.90	40.00	-25.10	QP
4	145.3505	28.18	-17.01	-	11.17	43.50	-32.33	QP
6	869.1302	40.98	-2.32	-	38.66	72.87	-33.68	peak
8	869.1302	38.66	-	-15.04	23.62	52.87	-29.25	AV

Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
5	434.0651	79.08	-10.99	-	68.09	92.87	-24.78	peak
7	434.0651	68.09	-	-15.04	53.05	72.87	-19.82	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit





Temperature:	26.2 °C	Relative Humidity:	52%
Phase:	Vertical	Test Mode:	Mode 2

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.2110	30.48	-11.30	-	19.18	40.00	-20.82	QP
2	79.8002	35.52	-22.72	-	12.80	40.00	-27.20	QP
3	119.0180	28.90	-17.75	-	11.15	43.50	-32.35	QP
4	224.5192	36.52	-18.83	-	17.69	46.00	-28.31	QP
6	869.1301	33.80	-2.61	-	31.19	72.87	-41.68	peak
8	869.1301	31.19	-	-15.04	16.15	52.87	-36.72	AV


Fundamental Frequency

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Duty cycle Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
5	434.0650	75.97	-10.90	-	65.07	92.87	-27.80	peak
7	434.0650	65.07	-	-15.04	50.03	72.87	-22.84	AV

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit

80.0 dBuV/m





ASK

315MHz:

PEAK TEST RESULTS:

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
								Limit	Margin	Antenna Polar
(MHz)	(dBμV/m)	(PK/QP/AV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
945.06	65.07	PK	45.1	4.0	25.1	-16.00	49.07	74	-24.93	H
945.06	65.76	PK	45.1	4.0	25.1	-16.00	49.76	74	-24.24	V
1260.04	63.10	PK	44.1	5.3	25	-13.80	49.30	74	-24.70	H
1260.04	64.20	PK	44.1	5.3	25	-13.80	50.40	74	-23.60	V
1575.04	61.29	PK	43.8	5.4	25.9	-12.47	48.82	74	-25.18	H
1575.04	62.26	PK	43.8	5.4	25.9	-12.47	49.79	74	-24.21	V
1890.02	57.17	PK	44.4	6.0	27.6	-10.77	46.40	74	-27.60	H
1890.02	57.18	PK	44.4	6.0	27.6	-10.77	46.41	74	-27.59	V

Note: Above 1.5GHz The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

AVG TEST RESULTS:

AV = Peak +20Log10(duty cycle) =PK+(-10.84) [refer to section 7 for more detail]

Frequency	PK Reading	Duty cycle	AV Reading	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
						Limit	Margin	Antenna Polar
(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
945.06	65.07	-10.84	54.23	-16.00	38.23	54	-15.77	H
945.06	65.76	-10.84	54.92	-16.00	38.92	54	-15.08	V
1260.04	63.10	-10.84	52.26	-13.80	38.46	54	-15.54	H
1260.04	64.20	-10.84	53.36	-13.80	39.56	54	-14.44	V
1575.04	61.29	-10.84	50.45	-12.47	37.98	54	-16.02	H
1575.04	62.26	-10.84	51.42	-12.47	38.95	54	-15.05	V
1890.02	57.17	-10.84	46.33	-10.77	35.56	54	-18.44	H
1890.02	57.18	-10.84	46.34	-10.77	35.57	54	-18.43	V



433.92MHz:

PEAK TEST RESULTS:

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
								Limit	Margin	Antenna
(MHz)	(dBμV/m)	(PK/QP/AV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
1301.79	65.27	PK	45.1	4.0	25.1	-16.00	49.27	74	-24.73	H
1301.79	65.57	PK	45.1	4.0	25.1	-16.00	49.57	74	-24.43	V
1735.69	62.97	PK	44.1	5.3	25	-13.80	49.17	74	-24.83	H
1735.69	64.42	PK	44.1	5.3	25	-13.80	50.62	74	-23.38	V
2169.45	61.74	PK	43.8	5.4	25.9	-12.47	49.27	74	-24.73	H
2169.45	62.27	PK	43.8	5.4	25.9	-12.47	49.80	74	-24.20	V
2603.39	57.20	PK	44.4	6.0	27.6	-10.77	46.43	74	-27.57	H
2603.39	57.17	PK	44.4	6.0	27.6	-10.77	46.40	74	-27.60	V

Note: Above 1.5GHz The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

AVG TEST RESULTS:

AV = Peak +20Log10(duty cycle) =PK+(-15.49) [refer to section 7 for more detail]

Frequency	PK Reading	Duty cycle	AV Reading	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
						Limit	Margin	Antenna
(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
1301.79	65.27	-15.49	49.78	-16.00	33.78	54	-20.22	H
1301.79	65.57	-15.49	50.08	-16.00	34.08	54	-19.92	V
1735.69	62.97	-15.49	47.48	-13.80	33.68	54	-20.32	H
1735.69	64.42	-15.49	48.93	-13.80	35.13	54	-18.87	V
2169.45	61.74	-15.49	46.25	-12.47	33.78	54	-20.22	H
2169.45	62.27	-15.49	46.78	-12.47	34.31	54	-19.69	V
2603.39	57.20	-15.49	41.71	-10.77	30.94	54	-23.06	H
2603.39	57.17	-15.49	41.68	-10.77	30.91	54	-23.09	V



FSK

315MHz:

PEAK TEST RESULTS:

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
								Limit	Margin	Antenna Polar
(MHz)	(dBμV/m)	(PK/QP/AV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
945.03	64.96	PK	45.1	4.0	25.1	-16.00	48.96	74	-25.04	H
945.03	65.54	PK	45.1	4.0	25.1	-16.00	49.54	74	-24.46	V
1260.16	62.99	PK	44.1	5.3	25	-13.80	49.19	74	-24.81	H
1260.16	64.23	PK	44.1	5.3	25	-13.80	50.43	74	-23.57	V
1575.14	61.33	PK	43.8	5.4	25.9	-12.47	48.86	74	-25.14	H
1575.14	61.94	PK	43.8	5.4	25.9	-12.47	49.47	74	-24.53	V
1890.01	57.10	PK	44.4	6.0	27.6	-10.77	46.33	74	-27.67	H
1890.01	57.27	PK	44.4	6.0	27.6	-10.77	46.50	74	-27.50	V

Note: Above 1.5GHz The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

AVG TEST RESULTS:

AV = Peak +20Log10(duty cycle) =PK+(-10.78) [refer to section 7 for more detail]

Frequency	PK Reading	Duty cycle	AV Reading	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
						Limit	Margin	Antenna Polar
(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
945.03	64.96	-10.78	54.18	-16.00	38.18	54	-15.82	H
945.03	65.54	-10.78	54.76	-16.00	38.76	54	-15.24	V
1260.16	62.99	-10.78	52.21	-13.80	38.41	54	-15.59	H
1260.16	64.23	-10.78	53.45	-13.80	39.65	54	-14.35	V
1575.14	61.33	-10.78	50.55	-12.47	38.08	54	-15.92	H
1575.14	61.94	-10.78	51.16	-12.47	38.69	54	-15.31	V
1890.01	57.10	-10.78	46.32	-10.77	35.55	54	-18.45	H
1890.01	57.27	-10.78	46.49	-10.77	35.72	54	-18.28	V



433.92MHz:

PEAK TEST RESULTS:

Frequency	Meter Reading	Detector	Amplifier	Loss	Antenna Factor	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
								Limit	Margin	Antenna
(MHz)	(dBμV/m)	(PK/QP/AV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
1301.94	65.18	PK	45.1	4.0	25.1	-16.00	49.18	74	-24.82	H
1301.94	65.64	PK	45.1	4.0	25.1	-16.00	49.64	74	-24.36	V
1735.87	62.97	PK	44.1	5.3	25	-13.80	49.17	74	-24.83	H
1735.87	64.14	PK	44.1	5.3	25	-13.80	50.34	74	-23.66	V
2169.49	61.52	PK	43.8	5.4	25.9	-12.47	49.05	74	-24.95	H
2169.49	61.96	PK	43.8	5.4	25.9	-12.47	49.49	74	-24.51	V
2603.47	56.98	PK	44.4	6.0	27.6	-10.77	46.21	74	-27.79	H
2603.47	57.44	PK	44.4	6.0	27.6	-10.77	46.67	74	-27.33	V

Note: Above 1.5GHz The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

AVG TEST RESULTS:

AV = Peak +20Log10(duty cycle) =PK+(-15.04) [refer to section 7 for more detail]

Frequency	PK Reading	Duty cycle	AV Reading	Orrected Factor	Corrected Amplitude	FCC Part 15.231/15.209/205		RX
						Limit	Margin	Antenna
(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(H/V)
1301.94	65.18	-15.04	50.14	-16.00	34.14	54	-19.86	H
1301.94	65.64	-15.04	50.60	-16.00	34.60	54	-19.40	V
1735.87	62.97	-15.04	47.93	-13.80	34.13	54	-19.87	H
1735.87	64.14	-15.04	49.10	-13.80	35.30	54	-18.70	V
2169.49	61.52	-15.04	46.48	-12.47	34.01	54	-19.99	H
2169.49	61.96	-15.04	46.92	-12.47	34.45	54	-19.55	V
2603.47	56.98	-15.04	41.94	-10.77	31.17	54	-22.83	H
2603.47	57.44	-15.04	42.40	-10.77	31.63	54	-22.37	V

5. BANDWIDTH TEST

5.1 LIMIT

FCC Part 15.231, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.231(C)	20dB Bandwidth	The 20dB bandwidth of the emissions shall not exceed 0.25% of the center frequency	315,433.92	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth
RB	10 kHz (20dB Bandwidth)
VB	30 kHz (20dB Bandwidth)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


5.2 TEST REQUIREMENTS

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

5.3 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting : RBW= 10KHz, VBW=30KHz, Sweep time = Auto.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

TX mode.




5.6 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Mode:	TX Mode		

ASK


Centre Frequency	Measurement		
	20dB Bandwidth	Limit(kHz)	Frequency Range (MHz)
	(KHz)		
315 MHz	49.2	787.5	PASS
433.92 MHz	48.34	1084.8	PASS

315 MHz





433.92 MHz






FSK


Centre Frequency	Measurement		
	20dB Bandwidth (KHz)	Limit(kHz)	Frequency Range (MHz)
315 MHz	125.7	787.5	PASS
433.92 MHz	126.8	1084.8	PASS

315 MHz





433.92 MHz



6. TRANSMITTER TIMEOUT

6.1 LIMIT

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the but in no case less than 10 seconds.

6.2 TEST PROCEDURE

- (1) Put the EUT on the support in its standard position with associated equipment and switched on.
- (2) Set center frequency of spectrum analyzer = operating frequency.
- (3) Set the spectrum analyzer as RBW=100kHz, VBW=100kHz, Span=0Hz, Adjust Sweep=120s.
- (4) record the duration time

6.3 TEST SETUP






6.4 TEST RESULTS

Temperature:	26 °C	Relative Humidity:	53%
Test Mode:	TX Mode1		

ASK

Frequency(MHz)	Each transmission time(s)	silent period between transmissions(s)
315	0.36	15.15
433.92	0.95	30.95
Limit	<1s	>10s and > 30*(duration of transmission)
Result	Pass	

315 MHz





433.92 MHz






FSK

Frequency(MHz)	Each transmission time(s)	silent period between transmissions(s)
315	0.39	15.15
433.92	0.95	31.2
Limit	<1s	>10s and > 30*(duration of transmission)
Result	Pass	

315 MHz





433.92 MHz





7. PERIODIC OPERATION

7.1 TEST PROCEDURE


The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

The Duty Cycle Was Determined By The Following Equation: To Calculate The Actual Field Intensity,The Duty Cycle Correction Factor In Decibel Is Needed For Later Use And Can Be Obtained From Following Conversion

Duty Cycle(%)=Total On Interval In A Complete Pulse Train/ Length Of A Complete Pulse Train * %

Duty Cycle Correction Factor(Db)=20 * Log10(Duty Cycle(%))

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

TX mode.





7.4 TEST RESULTS

ASK
315 MHz

FCC Part15.231(e)	
Total On interval in a complete pulse train(ms)	28.7
Length of a complete pulse train(ms)	100
Duty Cycle(%)	28.70%
Duty Cycle Correction Factor(dB)	-10.84


433.92 MHz

FCC Part15.231(e)	
Total On interval in a complete pulse train(ms)	16.8
Length of a complete pulse train(ms)	100
Duty Cycle(%)	16.80%
Duty Cycle Correction Factor(dB)	-15.49

Refer to the duty cycle plot (as below), This device meets the FCC requirement. Length of a complete pulse train


Remark: FCC part15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

315 MHz





433.92 MHz





FSK

FCC Part15.231(e)	
Total On interval in a complete pulse train(ms)	28.9
Length of a complete pulse train(ms)	100
Duty Cycle(%)	28.90%
Duty Cycle Correction Factor(dB)	-10.78


433.92 MHz

FCC Part15.231(e)	
Total On interval in a complete pulse train(ms)	17.7
Length of a complete pulse train(ms)	100
Duty Cycle(%)	17.70%
Duty Cycle Correction Factor(dB)	-15.04

Refer to the duty cycle plot (as below), This device meets the FCC requirement. Length of a complete pulse train


Remark:FCC part15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

315 MHz





433.92 MHz





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna to the intentional radiator shall be considered sufficient to comply with the provisions of this section. This product use a permanent ceramic printed antenna, fulfill the requirement of this section

8.2 EUT ANTENNA

The EUT antenna is Internal antenna.It conforms to the standard requirements.





APPENDIX 1- PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※END OF THE REPORT※※※※

