



Frequency Hopping on the DLP RFID-UHF1

The DLP RFID-UHF1 uses a 125 frequency, pseudo-random frequency hopping table. The frequency spacing is 200 kHz, and the table covers the UHF ISM band from 902.6 MHz to 927.4 MHz.

The following table lists the pseudo-random order of frequency use:

920.2 MHz	915.8 MHz	917.0 MHz	909.8 MHz	910.0 MHz
921.8 MHz	902.8 MHz	921.6 MHz	922.8 MHz	903.6 MHz
912.8 MHz	924.0 MHz	922.2 MHz	911.8 MHz	926.6 MHz
924.2 MHz	904.0 MHz	926.2 MHz	911.6 MHz	915.6 MHz
903.8 MHz	917.4 MHz	914.2 MHz	918.0 MHz	918.6 MHz
909.0 MHz	909.4 MHz	923.2 MHz	917.2 MHz	927.2 MHz
925.2 MHz	908.2 MHz	919.8 MHz	927.0 MHz	908.6 MHz
905.2 MHz	927.4 MHz	919.4 MHz	916.8 MHz	905.0 MHz
922.4 MHz	909.6 MHz	912.0 MHz	912.6 MHz	906.6 MHz
920.4 MHz	910.6 MHz	918.4 MHz	907.6 MHz	907.2 MHz
904.6 MHz	914.0 MHz	925.4 MHz	918.2 MHz	913.2 MHz
916.6 MHz	923.4 MHz	903.0 MHz	916.0 MHz	915.0 MHz
915.4 MHz	911.4 MHz	909.2 MHz	912.2 MHz	914.8 MHz
906.4 MHz	914.4 MHz	926.0 MHz	918.8 MHz	915.2 MHz
922.0 MHz	921.4 MHz	907.8 MHz	904.4 MHz	910.8 MHz
905.8 MHz	902.6 MHz	919.0 MHz	916.2 MHz	913.8 MHz
906.2 MHz	925.8 MHz	904.8 MHz	906.8 MHz	925.6 MHz
913.6 MHz	924.4 MHz	921.2 MHz	903.2 MHz	908.4 MHz
914.6 MHz	908.8 MHz	911.0 MHz	905.4 MHz	911.2 MHz
908.0 MHz	923.6 MHz	920.6 MHz	907.0 MHz	913.0 MHz
919.6 MHz	924.6 MHz	917.8 MHz	922.6 MHz	926.4 MHz
904.2 MHz	912.4 MHz	925.0 MHz	920.0 MHz	920.8 MHz
913.4 MHz	905.6 MHz	926.8 MHz	906.0 MHz	916.4 MHz
923.8 MHz	921.0 MHz	910.4 MHz	924.8 MHz	907.4 MHz
923.0 MHz	910.2 MHz	919.2 MHz	917.6 MHz	903.4 MHz