

FCC TEST REPORT

Client Information:

Applicant: U2O GLOBAL CO., LTD.
Applicant add.: U2O building, Huanzhu Road 385, Jimei district Xiamen, Fujian China
Manufacturer: U2O GLOBAL CO., LTD.
Manufacturer add.: U2O building, Huanzhu Road 385, Jimei district Xiamen, Fujian China

Product Information:

Product Name: PowerGrip Mag
Model No.: DBL6000M
Brand Name: iWALK
FCC ID: SXQ-DBL6000M

Applicable standards: FCC CFR Title 47 Part 15 Subpart C

Prepared By:

Dongguan Yaxu (AiT) Technology Limited

No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan,
Guangdong, China

Tel.: +86-769-8202 0499 Fax.: +86-769-8202 0495

Date of Receipt: July 27, 2023

Date of Test: July 27~ Aug. 01, 2023

Date of Issue: Aug. 02, 2023

Test Result: Pass

This device described above has been tested by Dongguan Yaxu (AiT) Technology Limited and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Note: This report shall not be reproduced except in full, without the written approval of Dongguan Yaxu (AiT) Technology Limited, this document may be altered or revised by Dongguan Yaxu (AiT) Technology Limited, personal only, and shall be noted in the revision of the document. This test report must not be used by the client to claim product endorsement.

Reviewed by: _____



Simba Huang

Approved by: _____



Seal.chen



1 Contents

	Page
COVER PAGE	
1 CONTENTS	2
2 TEST SUMMARY	5
2.1 STATEMENT OF THE MEASUREMENT UNCERTAINTY	5
2.2 MEASUREMENT UNCERTAINTY	5
3 TEST FACILITY	6
3.1 DEVIATION FROM STANDARD	6
3.2 ABNORMALITIES FROM STANDARD CONDITIONS	6
3.3 TEST LOCATION	6
4 GENERAL INFORMATION	7
4.1 EUT TEST MODE	8
1.1 DESCRIPTION OF TEST SETUP	8
1.2 PERIPHERAL LIST	9
1.3 EUT PERIPHERAL LIST	9
2 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 CONDUCTED EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.2 POWER LINE CONDUCTED EMISSION LIMITS	11
3.3 TEST PROCEDURE	11
3.4 DEVIATION FROM TEST STANDARD	11
3.5 TEST SETUP	12
3.6 EUT OPERATING CONDITIONS	12
3.7 TEST RESULT	13
4 RADIATED EMISSION MEASUREMENT	15
4.1 RADIATED EMISSION LIMITS	15
4.2 ANECHOIC CHAMBER TEST SETUP DIAGRAM	16
4.3 TEST PROCEDURE	16
4.4 DEVIATION FROM TEST STANDARD	16
4.5 TEST RESULT	17
5 BANDWIDTH TEST	20
5.1 TEST PROCEDURE	20
5.2 TEST SETUP	20
6 ANTENNA REQUIREMENT:	22
7 TEST SETUP PHOTOGRAPHS OF EUT	23



8	EXTERNAL PHOTOGRAPHS OF EUT	23
9	INTERNAL PHOTOGRAPHS OF EUT	23



Revision History

Revision	Issue Date	Revisions	Revised By
000	Aug. 02, 2023	Initial Issue	Seal Chen

2 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

Note

1. Test according to ANSI C63.10:2013.
2. The measurement uncertainty is not included in the test result.
3. Test results in other test report (RF Exposure Evaluation Report)

2.1 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the AiT quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

2.2 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	0.009MHz-30MHz	3.10dB	(1)
Radiated Emission	30MHz-1GHz	3.75dB	(1)
Radiated Emission	1GHz-18GHz	3.88dB	(1)
Radiated Emission	18GHz-40GHz	3.88dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	1.20dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

3 Test Facility

The test facility is recognized, certified or accredited by the following organizations:

.CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2017 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on April 18, 2022

FCC-Registration No.: 703111 Designation Number: CN1313

Dongguan Yaxu (AiT) technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 6819A CAB identifier: CN0122

The 3m Semi-anechoic chamber of Dongguan Yaxu (AiT) technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 6819A

A2LA-Lab Cert. No.: 6317.01

Dongguan Yaxu (AiT) technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

3.1 Deviation from standard

None

3.2 Abnormalities from standard conditions

None

3.3 Test Location

Dongguan Yaxu (AiT) Technology Limited

Address: No.22, Jinqianling 3rd Street, Jitigang, Huangjiang,Dongguan, Guangdong, China

Tel.: +86-769-8202 0499

Fax.: +86-769-8202 0495

4 General Information

EUT Name:	PowerGrip Mag
Model No:	DBL6000M
Serial Model:	N/A
Test sample(s) ID:	23072703
Sample(s) Status:	Engineer sample
Serial No.:	N/A
Operation frequency:	113kHz-205kHz
Modulation Technology:	ASK
Test frequency:	127.4KHz
Antenna Type:	loop coil Antenna
Antenna gain:	0dBi
Hardware version.:	N/A
Software version.:	N/A
Power supply:	Capacity:6000mAh(3.85V/22.2Wh) USB-C In/Out:5V3A,9V2A,12V1.5A Wireless Charging:5W,7.5W,10W,15W
Battery:	DC3.85V
Note:	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

4.1 EUT Test Mode


Equipment under test was operated during the measurement under the following conditions:

Test Mode	Description	
Mode 1	AC Adapter : Wireless charging (15W)	Record
Mode 2	AC Adapter : Wireless charging (10W)	Pre-tested
Mode 3	AC Adapter : Wireless charging (7.5W)	Pre-tested
Mode 4	AC Adapter : Wireless charging (5W)	Pre-tested
Mode 5	Battery : Wireless charging(15W)+Load	Pre-tested
Mode 6	Battery : Wireless charging(10W)+Load	Pre-tested
Mode 7	Battery : Wireless charging(7.5W)+Load	Pre-tested
Mode 8	Battery : Wireless charging(5W)+Load	Pre-tested
Mode 9	Test the EUT in idle mode.	Pre-tested

Note: All test modes were pre-tested, but we only recorded the worst case in this report.

1.1 Description of Test setup

EUT was tested in normal configuration (Please See following Block diagram)



1.2 Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	Adapter	HNT	CE	HNT-QC530	N/A	N/A
2	Mobile Iphone	XIAOMI	CE	MI 11	N/A	N/A

1.3 EUT Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A

2 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	R&S	FSV40	101470	2022.09.02	2023.09.01
2	EMI Measuring Receiver	R&S	ESR	101660	2022.09.02	2023.09.01
3	Low Noise Pre Amplifier	HP	HP8447E	1937A01855	2022.09.02	2023.09.01
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2022.09.02	2023.09.01
5	Passive Loop	ETS	6512	00165355	2022.09.04	2024.09.03
6	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2021.08.29	2024.08.28
7	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2021.08.29	2024.08.28
8	SHF-EHF Horn Antenna 15-40GHz	SCHWARZBECK	BBHA9170	BBHA9170367d	2020.11.24	2023.11.23
9	EMI Test Receiver	R&S	ESCI	100124	2022.09.02	2023.09.01
10	LISN	Kyoritsu	KNW-242	8-837-4	2022.09.02	2023.09.01
11	LISN	Schwarzbeck	NNLK 8129	8130179	2022.09.02	2023.09.01
12	Pro.Temp&Humi.chamber	MENTEK	MHP-150-1C	MAA08112501	2022.09.02	2023.09.01
13	RF Automatic Test system	MW	MW100-RFCB	21033016	2022.09.02	2023.09.01
14	Signal Generator	Agilent	N5182A	MY50143009	2022.09.02	2023.09.01
15	Wideband Radio communication tester	R&S	CMW500	1201.0002K50	2022.09.02	2023.09.01
16	RF Automatic Test system	MW	MW100-RFCB	21033016	2022.09.02	2023.09.01
17	DC power supply	ZHAOXIN	RXN-305D-2	28070002559	N/A	N/A
18	RE Software	EZ	EZ-EMC_RE	Ver.AIT-03A	N/A	N/A
19	CE Software	EZ	EZ-EMC_CE	Ver.AIT-03A	N/A	N/A
20	RF Software	MW	MTS 8310	2.0.0.0	N/A	N/A
21	temporary antenna connector(Note)	NTS	R001	N/A	N/A	N/A

3 CONDUCTED EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

3.2 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


3.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.4 DEVIATION FROM TEST STANDARD

No deviation

3.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


3.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.


3.7 Test Result

Temperature:	25.8 °C	Relative Humidity:	52.2%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Mode :	1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1580	44.76	11.75	56.51	65.56	-9.05	QP
2		0.1580	30.98	11.75	42.73	55.56	-12.83	AVG
3		0.2140	40.98	11.03	52.01	63.04	-11.03	QP
4		0.2140	23.71	11.03	34.74	53.04	-18.30	AVG
5		0.5340	28.94	10.00	38.94	56.00	-17.06	QP
6		0.5340	15.63	10.00	25.63	46.00	-20.37	AVG
7		1.2059	19.82	9.95	29.77	56.00	-26.23	QP
8		1.2059	10.95	9.95	20.90	46.00	-25.10	AVG
9		2.2940	22.87	10.00	32.87	56.00	-23.13	QP
10		2.2940	11.40	10.00	21.40	46.00	-24.60	AVG
11		12.2140	37.27	1.33	38.60	60.00	-21.40	QP
12		12.2140	27.82	1.33	29.15	50.00	-20.85	AVG

Temperature:	25.8 °C	Relative Humidity:	52.3%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Mode :	1



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector
1 *	0.1539	44.09	11.84	55.93	65.78	-9.85	QP
2	0.1539	28.49	11.84	40.33	55.78	-15.45	AVG
3	0.2340	37.97	10.94	48.91	62.30	-13.39	QP
4	0.2340	22.52	10.94	33.46	52.30	-18.84	AVG
5	0.5420	26.91	10.00	36.91	56.00	-19.09	QP
6	0.5420	17.05	10.00	27.05	46.00	-18.95	AVG
7	1.5740	25.19	9.97	35.16	56.00	-20.84	QP
8	1.5740	15.87	9.97	25.84	46.00	-20.16	AVG
9	2.7820	27.58	10.03	37.61	56.00	-18.39	QP
10	2.7820	20.17	10.03	30.20	46.00	-15.80	AVG
11	12.2420	38.18	1.33	39.51	60.00	-20.49	QP
12	12.2420	32.43	1.33	33.76	50.00	-16.24	AVG

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor

4 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	

4.1 Radiated Emission Limits

Limits for frequency below 30MHz


Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz


Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value

4.2 Anechoic Chamber Test Setup Diagram

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.

4.3 Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

4.4 DEVIATION FROM TEST STANDARD

No deviation

4.5 Test Result

We pretest AC 120V and AC 230V in full load, half load and no load, the worst voltage was AC 120V in full load and the data recording in the report.

Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

Mode 1:

9 kHz~30 MHz

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
0.0175	-14.06	70.30	56.24	122.5	-66.34	Quasi-Peak
0.1274	38.97	40.68	79.65	105.4	-25.78	Average
0.1274	28.11	40.68	68.79	105.4	-36.64	Quasi-Peak
0.2504	10.39	36.75	47.14	99.60	-52.46	Quasi-Peak
0.4380	15.20	31.54	46.74	94.77	-48.03	Quasi-Peak
3.4394	24.08	17.36	41.44	69.50	-28.06	Quasi-Peak
10.1171	22.27	13.67	35.94	69.50	-33.56	Quasi-Peak

Mode 5:

9 kHz~30 MHz

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
0.0345	-7.96	59.30	51.34	116.7	-65.38	Quasi-Peak
0.1274	38.52	40.68	79.20	105.4	-26.23	Average
0.1274	27.69	40.68	68.37	105.4	-37.06	Quasi-Peak
1.7116	18.69	23.25	41.94	69.50	-27.56	Quasi-Peak
2.4866	21.70	20.14	41.84	69.50	-27.66	Quasi-Peak
7.3733	22.03	14.51	36.54	69.50	-32.96	Quasi-Peak
22.7681	22.09	13.25	35.34	69.50	-34.16	Quasi-Peak

Note:


Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level- Limit.

30MHz-1GHz

Temperature:	25.7°C	Relative Humidity:	52.2%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		41.2765	23.17	3.97	27.14	40.00	-12.86	QP
2		88.6524	25.62	-3.19	22.43	43.50	-21.07	QP
3		199.9856	28.23	-1.32	26.91	43.50	-16.59	QP
4		280.0237	31.40	0.45	31.85	46.00	-14.15	QP
5		528.2458	26.35	9.36	35.71	46.00	-10.29	QP
6	*	790.6188	23.60	12.85	36.45	46.00	-9.55	QP

Temperature:	25.7°C	Relative Humidity:	52.3%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	41.4215	34.98	1.56	36.54	40.00	-3.46	QP
2		75.4464	31.70	-4.44	27.26	40.00	-12.74	QP
3		146.8877	30.02	-1.42	28.60	43.50	-14.90	QP
4		192.4186	32.97	-1.73	31.24	43.50	-12.26	QP
5		501.1790	27.76	4.89	32.65	46.00	-13.35	QP
6		796.1830	23.49	12.89	36.38	46.00	-9.62	QP

Remarks:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

5 BANDWIDTH TEST

5.1 Test Procedure


1. Set RBW = 3 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

5.2 Test setup



Temperature:	20 °C	Relative Humidity:	44%
Pressure:	101kPa		

Frequency (KHz)	20dB bandwidth (KHz)	99% bandwidth (KHz)	Result
127.4	2.663	-	Pass



6 ANTENNA REQUIREMENT:

Standard requirement: FCC Part15 C Section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Inductive loop coil Antenna, the best case gain of the antenna is 0dBi, reference to the appendix for details.

7 Test Setup Photographs of EUT

Please refer to separated files for Test Setup Photos of the EUT.

8 External Photographs of EUT

Please refer to separated files for External Photos of the EUT.

9 Internal Photographs of EUT

Please refer to separated files for Internal Photos of the EUT.

**** End of report ****