



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822  
 Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>



Dates of Tests: Dec 07 ~ Dec 15, 2009  
 Test Report S/N: LR500190912A  
 Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.	<b>SXV-COWON-J3</b>
APPLICANT	<b>COWON SYSTEMS, Inc.</b>

<b>Equipment Class</b>	<b>:</b>	<b>Part 15 Spread Spectrum Transmitter (DSS)</b>
<b>Manufacturing Description</b>	<b>:</b>	<b>Portable Multimedia Player</b>
<b>Manufacturer</b>	<b>:</b>	<b>COWON SYSTEMS, Inc.</b>
<b>Model name</b>	<b>:</b>	<b>COWON J3 DMB, COWON J3</b>
<b>Test Device Serial No.:</b>	<b>:</b>	<b>Identical prototype</b>
<b>Rule Part(s)</b>	<b>:</b>	<b>FCC Part 15.247 Subpart C; ANSI C-63.4-2003</b>
<b>Frequency Range</b>	<b>:</b>	<b>2402 ~ 2480MHz</b>
<b>RF power</b>	<b>:</b>	<b>Maximum -2.56dBm - Conducted</b>
<b>Data of issue</b>	<b>:</b>	<b>December 15, 2009</b>

This test report is issued under the authority of:

The test was supervised by:

\_\_\_\_\_  
 Dong -Min JUNG, Technical Manager

\_\_\_\_\_  
 Kyung-Taek LEE, Test Engineer

**This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.**



NVLAP LAB Code.: 200723-0

---

## TABLE OF CONTENTS

1. GENERAL INFORMATION'S .....	3
2. INFORMATION'S ABOUT TEST ITEM .....	4
3. TEST REPORT .....	6
3.1 SUMMARY OF TESTS .....	6
3.2 TECHNICAL CHARACTERISTICS TEST .....	7
3.2.1 CARRIER FREQUENCY SEPARATION .....	7
3.2.2 NUMBER OF HOPPING FREQUENCIES .....	9
3.2.3 20 dB BANDWIDTH .....	11
3.2.4 TIME OF OCCUPANCY (Dwell Time) .....	15
3.2.5 TRANSMITTER OUTPUT POWER .....	19
3.2.6 BAND – EDGE & SPURIOUS .....	23
3.2.7 FIELD STRENGTH OF HARMONICS .....	29
3.2.8 AC CONDUCTED EMISSIONS .....	34
<b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS .....	37

## 1. General information's

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2010-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2010-05-03	IC filing

## 2. Information's about test item

### 2-1 Applicant & Manufacturer

Company name : COWON SYSTEMS, Inc.  
 Address : COWON Tower, 689-3, Yeoksam-dong, Gangnam-gu, Seoul 135-080, Korea  
 Tel / Fax : +82-2-6900-0102 / +82-2-6900-0022

### 2-2 Equipment Under Test (EUT)

Trade name : Portable Multimedia Player  
 FCC ID : SXV-COWON-J3  
 Model name : COWON J3 DMB, COWON J3  
 → Refer to the Model Description  
 Serial number : Identical prototype  
 Memory size : 4GB / 8GB / 16GB  
 Date of receipt : December 07, 2009  
 EUT condition : Pre-production, not damaged  
 Antenna type : Bluetooth chip antenna with Max. -1.2dBi gain  
 Frequency Range : 2402 ~ 2480MHz  
 RF output power : Maximum -2.56dBm - Conducted  
 Number of channels : 79  
 Channel spacing : 1MHz  
 Channel Access Protocol : Frequency Hopping  
 Type of Modulation : GFSK  
 Power Source for Batt. : Battery: 3.7V (Li-Polymer RECHARGEABLE BATTERY)

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

**2-4 Ancillary Equipment – Bluetooth + Play mode**

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-
-	-	-	-

**2-5 Ancillary Equipment – USB mode**

Equipment	Model No.	Serial No.	Manufacturer
PC(EMI3)	HP Compaq dx7400 Microtower	CNG8330J9R	HP
Monitor 17"	HPL1710	CNC816QHF2	HP
Keyboard	SK-8115	68A-04Q6	DELL
Mouse	MO56UOA	F0J00NOL	DELL
PRINTER	STYLUS C65	FXSY002205	EPSON
-	-	-	-

**2-6 Model Description**

Model	Bluetooth	DMB Module
COWON J3	O	X
COWON J3 DMB	O	O

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)		Radiated
15.109	Field Strength	-	C	
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

#### → Antenna Requirement

The COWON SYSTEMS Inc. FCC ID: SXV-COWON-J3 unit complies with the requirement of §15.203.  
The antenna is Chip antenna.

The sample was tested according to the following specification:  
FCC Parts 15.247; ANSI C-63.4-2003

## 3.2 Transmitter requirements

### 3.2.1 Carrier Frequency Separation

#### Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more)      Sweep = auto

VBW = 10 kHz      Detector function = peak

Trace = max hold

#### Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
0.998	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

#### Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

### Carrier Frequency Separation





### 3.2.2 Number of Hopping Frequencies

#### Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

#### The spectrum analyzer is set to:

Frequency range    1: Start = 2400.0MHz,    Stop = 2441.5 MHz

                          2: Start = 2441.5MHz,    Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more)      Sweep = auto

VBW = 100 kHz (VBW  $\geq$  RBW)              Detector function = peak

Trace = max hold                                  Span > 40MHz

#### Measurement Data: Complies

<b>Total number of Hopping Channels</b>	79
---	----

- See next pages for actual measured spectrum plots.



#### Minimum Standard:

At least 15 hops

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

### Number of Hopping Frequencies



### 3.2.3 20 dB Bandwidth

#### Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

dB/Div = 5dB

#### Measurement Data: Normal Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.877	0.825
2441	39	0.877	0.821
2480	78	0.881	0.825

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

N/A


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

**Channel 1 mode**  
**20 dB Bandwidth**



**99% Bandwidth**



**Channel 2 mode**  
**20 dB Bandwidth**




**99% Bandwidth**



**Channel 3 mode**  
**20 dB Bandwidth**



**99% Bandwidth**



### 3.2.4 Time of Occupancy (Dwell Time)

#### Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW  $\geq$  RBW)

Trace = max hold

Detector function = peak

#### Measurement Data:

Mode	Number of transmission in a 31.6s ( 79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	32(Times/3.16sec) *10= 320	0.523	167.36	400
DH3	16(Times/3.16sec) *10 = 160	1.762	281.92	400
DH5	11(Times/3.16sec) *10 = 110	3.038	334.18	400

- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot ) x duration time per channel} x 0.4 ms



#### Minimum Standard:

0.4 seconds within a 30 second period per any frequency

#### Measurement Setup



Same as the Chapter 3.2.1 (Figure 1)

### DH1 mode







### DH3 mode



### DH5 mode



### 3.2.5 Transmitter Output Power

#### Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW  $\geq$  RBW)

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Normal Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	<b>-4.94</b>	<b>0.32</b>	Complies
2441	39	<b>-3.47</b>	<b>0.45</b>	Complies
2480	78	<b>-2.56</b>	<b>0.55</b>	Complies


- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	< 250 mW
--------------------------	----------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


### Channel 1



**Channel 2**



### Channel 3



### 3.2.6 Band Edge

#### Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

**Band - edge**

**Lower edge**



**Upper edge**





**Band-edges in the restricted band 2310-2390 MHz measurement**


Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
2344.00	40.7	57.5	H	26.0	36.5	8.2	54.0	74.0	38.4	55.2	15.6	18.8

**Band-edges in the restricted band 2483.5-2500 MHz measurement**


Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
2483.50	49.6	56.2	H	26.0	36.5	8.2	54.0	74.0	47.3	53.9	6.7	20.1

**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.**


**Unwanted Emission – Low channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



**Unwanted Emission – Middle channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



**Unwanted Emission – High channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



### 3.2.7 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

#### The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

= 1 MHz ( 1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Trace = max hold

Peak:VBW  $\geq$  RBW

Average:VBW=10Hz

Detector function = Peak and Average

Sweep = auto

#### Measurement Data: **Complies**

→ Refer to the next page.

→ No other emissions were detected at a level greater than 20dB below limit.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data:

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
4804.08	31.2	37.5	H	31.4	34.6	8.7	54.0	74.0	36.7	43.0	17.4	31.1
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
4882.12	31.0	37.2	H	31.4	34.6	8.7	54.0	74.0	36.5	42.7	17.6	31.4
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor			Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp.Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
4960.34	34.5	40.2	H	31.4	34.6	8.7	54.0	74.0	40.0	45.7	14.1	28.4
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-


No other emissions were detected at a level greater than 20dB below limit.

**Field strength at PLAY+BT mode**



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: COWON J3 DMB\_16G TEST MODE: PLAY+BT mode  
Temp Humi : 7 / 31 Tested by: LEE.K.H



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	85.99	50.20	-17.24	32.96	40.00	7.04	100	186 VERTICAL
2	240.00	55.00	-10.65	44.35	46.00	1.65	152	323 HORIZONTAL
3	600.26	41.00	-2.82	38.18	46.00	7.82	260	212 HORIZONTAL
4	713.33	43.20	-0.85	42.35	46.00	3.65	150	214 HORIZONTAL
5	720.00	42.20	-0.73	41.47	46.00	4.53	100	163 VERTICAL
6	723.80	40.10	-0.66	39.44	46.00	6.56	400	160 HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

**Field strength at File up / down mode**



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: COWON J3 DMB\_16G

TEST MODE: File up / down mode


Temp Humi : 7 / 31

Tested by: LEE.K.H

Data: 191

Level (dBuV/m)

Date: 2009-12-14



1	2	3	4	5	6			
Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
85.88	50.30	-17.24	33.06	40.00	6.94	100	202	VERTICAL
240.00	55.00	-10.65	44.35	46.00	1.65	165	23	HORIZONTAL
600.65	41.10	-2.82	38.28	46.00	7.72	265	233	HORIZONTAL
713.69	43.30	-0.84	42.46	46.00	3.54	152	322	HORIZONTAL
720.00	42.30	-0.73	41.57	46.00	4.43	100	32	VERTICAL
723.86	40.20	-0.66	39.54	46.00	6.46	400	165	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




**Field strength at REC mode**



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: COWON J3 DMB\_16G TEST MODE: REC mode  
Temp Humi : 7 / 31 Tested by: LEE.K.H



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	85.35	50.20	-17.21	32.99	40.00	7.01	100	232 VERTICAL
2	240.00	55.00	-10.65	44.35	46.00	1.65	165	323 HORIZONTAL
3	600.80	41.00	-2.82	38.18	46.00	7.82	256	332 HORIZONTAL
4	713.87	43.20	-0.84	42.36	46.00	3.64	150	32 HORIZONTAL
5	720.00	42.20	-0.73	41.47	46.00	4.53	100	189 VERTICAL
6	723.88	40.30	-0.65	39.65	46.00	6.35	400	321 HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.8 AC Conducted Emissions

**Procedure:**

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

**Measurement Data: Complies**

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.

**Minimum Standard: FCC Part 15.207(a)/EN 55022**

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency


**AC Conducted Emissions at File up /down mode – Line**



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-3236008,9  
Fax:+82-31-3236010

EUT / Model No. : COWON J3 DMB\_16G Phase : LINE  
 Test Mode : File up / down mode Test Power : 120 / 60  
 Temp./Humi. : 15 / 34 Test Engineer : LEE.K.H

Data: 342 File: D:\Conducted Data\2009\LTA\_Conduction\_0911\_2.EMI (382) Date: 2009-12-01



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.161	30.60	23.40	9.70	40.29	33.09	65.41	55.41	25.12	22.32
0.210	24.89	17.99	9.62	34.51	27.61	63.21	53.21	28.70	25.60
0.239	27.28	24.88	9.67	36.95	34.55	62.13	52.13	25.18	17.58
12.594	21.59	17.69	10.28	31.87	27.97	60.00	50.00	28.13	22.03
13.637	25.00	20.50	10.35	35.35	30.85	60.00	50.00	24.65	19.15
24.012	22.55	19.55	10.75	33.31	30.31	60.00	50.00	26.69	19.69

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss


**AC Conducted Emissions at File up /down mode – Neutral**



243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-3236008,9  
Fax:+82-31-3236010

EUT / Model No. : COWON J3 DMB\_16G Phase : NEUTRAL  
 Test Mode : File up / down mode Test Power : 120 / 60  
 Temp./Humi. : 15 / 34 Test Engineer : LEE.K.H

Data: 344 File: D:\Conducted Data\2009\LTA\_Conduction\_0911\_2.EMI (382) Date: 2009-12-01



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.171	31.49	27.39	9.72	41.21	37.11	64.91	54.91	23.70	17.80
0.238	34.18	32.88	9.68	43.86	42.56	62.17	52.17	18.31	9.61
0.382	22.46	19.16	9.73	32.19	28.89	58.24	48.24	26.05	19.35
12.007	22.09	15.19	10.20	32.29	25.39	60.00	50.00	27.71	24.61
13.638	25.50	20.70	10.28	35.78	30.98	60.00	50.00	24.22	19.02
24.017	23.65	21.45	10.55	34.20	32.00	60.00	50.00	25.80	18.00

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

## APPENDIX

### TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	Feb-10
2	Spectrum Analyzer	8563E	3425A02505	HP	Apr-10
3	Spectrum Analyzer	8594E	3710A04074	HP	Oct-10
4	Signal Generator	8648C	3623A02597	HP	Apr-10
5	Signal Generator	83711B	US34490456	HP	Apr-10
6	Attenuator (3dB)	8491A	37822	HP	Oct-10
7	Attenuator (10dB)	8491A	63196	HP	Oct-10
8	Attenuator (30dB)	8498A	1801A06689	HP	Oct-10
9	EMI Test Receiver	ESVD	843748/001	R&S	Apr-10
10	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	Nov-10
11	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	Nov-10
12	RF Amplifier	8447D	2949A02670	HP	Oct-10
13	RF Amplifier	8449B	3008A02126	HP	Apr-10
14	Test Receiver	ESHS10	828404/009	R&S	Apr-10
15	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Apr-11
16	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-11
17	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-11
18	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-11
19	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	Dec-11
20	Dipole Antenna	VHA9103	2116	SCHWARZBECK	Nov-10
21	Dipole Antenna	VHA9103	2117	SCHWARZBECK	Nov-10
22	Dipole Antenna	VHA9105	2261	SCHWARZBECK	Nov-10
23	Dipole Antenna	VHA9105	2262	SCHWARZBECK	Nov-10
24	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Apr-10
25	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
26	RF Switch	MP59B	6200414971	ANRITSU	-
27	Power Divider	11636A	6243	HP	Oct-10
28	DC Power Supply	6622A	3448A03079	HP	Oct-10
29	Frequency Counter	5342A	2826A12411	HP	Apr-10
30	Power Meter	EPM-441A	GB32481702	HP	Apr-10
31	Power Sensor	8481A	2702A64048	HP	Apr-10
32	Audio Analyzer	8903B	3729A18901	HP	Oct-10
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-10
34	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	Oct-10
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-11
36	Stop Watch	HS-3	601Q09R	CASIO	Apr-10