

## FCC PART 15.247

## TEST REPORT

For

**Shenzhen KingBoard Technology Co., Ltd.**

Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China

**FCC ID: SXXKTS-691**

|                                                                                                                                                                                                                                                                               |                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                        | <b>Product Name:</b><br>Bluetooth speaker |
| <b>Report Number:</b> RDG170824002-00                                                                                                                                                                                                                                         |                                           |
| <b>Report Date:</b> 2017-08-28                                                                                                                                                                                                                                                |                                           |
| Jerry Zhang                                                                                                                                                                                                                                                                   |                                           |
| <b>Reviewed By:</b>                                                                                                                                                                                                                                                           | EMC Manager                               |
| <b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Dongguan)<br>No.69 Pulongcun, Puxinhu Industry Area,<br>Tangxia, Dongguan, Guangdong, China<br>Tel: +86-769-86858888<br>Fax: +86-769-86858891<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                           |

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

## **TABLE OF CONTENTS**

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                        | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....               | 4         |
| OBJECTIVE .....                                                        | 4         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                     | 4         |
| TEST METHODOLOGY .....                                                 | 4         |
| MEASUREMENT UNCERTAINTY .....                                          | 4         |
| TEST FACILITY .....                                                    | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                  | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                | 6         |
| EUT EXERCISE SOFTWARE .....                                            | 6         |
| EQUIPMENT MODIFICATIONS .....                                          | 6         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                               | 6         |
| EXTERNAL CABLE.....                                                    | 6         |
| BLOCK DIAGRAM OF TEST SETUP .....                                      | 7         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                   | <b>8</b>  |
| <b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1093- RF EXPOSURE .....</b>  | <b>9</b>  |
| APPLICABLE STANDARD .....                                              | 9         |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                          | <b>10</b> |
| APPLICABLE STANDARD .....                                              | 10        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                   | 10        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>             | <b>11</b> |
| APPLICABLE STANDARD .....                                              | 11        |
| EUT SETUP .....                                                        | 11        |
| EMI TEST RECEIVER SETUP.....                                           | 11        |
| TEST PROCEDURE .....                                                   | 11        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                         | 12        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 12        |
| TEST DATA .....                                                        | 12        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b> | <b>15</b> |
| APPLICABLE STANDARD .....                                              | 15        |
| EUT SETUP .....                                                        | 15        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                      | 16        |
| TEST PROCEDURE .....                                                   | 16        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 16        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                         | 17        |
| TEST DATA .....                                                        | 17        |
| <b>FCC §15.247(a) (1) - CHANNEL SEPARATION TEST .....</b>              | <b>23</b> |
| APPLICABLE STANDARD .....                                              | 23        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 23        |
| TEST PROCEDURE .....                                                   | 23        |
| TEST DATA .....                                                        | 23        |
| <b>FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....</b>               | <b>29</b> |
| APPLICABLE STANDARD .....                                              | 29        |
| TEST PROCEDURE .....                                                   | 29        |
| TEST EQUIPMENT LIST AND DETAILS.....                                   | 29        |

|                                                                          |           |
|--------------------------------------------------------------------------|-----------|
| TEST DATA .....                                                          | 29        |
| <b>FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST .....</b> | <b>35</b> |
| APPLICABLE STANDARD .....                                                | 35        |
| TEST PROCEDURE .....                                                     | 35        |
| TEST EQUIPMENT LIST AND DETAILS.....                                     | 35        |
| TEST DATA .....                                                          | 35        |
| <b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b>    | <b>39</b> |
| APPLICABLE STANDARD .....                                                | 39        |
| TEST PROCEDURE .....                                                     | 39        |
| TEST EQUIPMENT LIST AND DETAILS.....                                     | 39        |
| TEST DATA .....                                                          | 39        |
| <b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>          | <b>55</b> |
| APPLICABLE STANDARD .....                                                | 55        |
| TEST PROCEDURE .....                                                     | 55        |
| TEST EQUIPMENT LIST AND DETAILS.....                                     | 55        |
| TEST DATA .....                                                          | 55        |
| <b>FCC §15.247(d) - BAND EDGES TESTING .....</b>                         | <b>61</b> |
| APPLICABLE STANDARD .....                                                | 61        |
| TEST PROCEDURE .....                                                     | 61        |
| TEST EQUIPMENT LIST AND DETAILS.....                                     | 61        |
| TEST DATA .....                                                          | 62        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

The **Shenzhen KingBoard Technology Co., Ltd.**'s product, model number: **KTS-691 (FCC ID: SXXKTS-691)** (the "EUT") in this report was a **Bluetooth speaker**, which was measured approximately: 13.2 cm (L) x 6.3 cm (W) x 7.8 cm (H), rated input voltage: DC3.7V from Battery or DC 5V from USB port.

*\*All measurement and test data in this report was gathered from production sample serial number: 170824002 (Assigned by BACL,Dongguan). The EUT was received on 2017-08-24.*

### Objective

This report is prepared on behalf of **Shenzhen KingBoard Technology Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

N/A

### Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

### Measurement Uncertainty

| Parameter                         | Measurement Uncertainty                                                                                                                                      |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Occupied Channel Bandwidth        | ±5 %                                                                                                                                                         |
| RF output power, conducted        | ±0.61dB                                                                                                                                                      |
| Power Spectral Density, conducted | ±0.61 dB                                                                                                                                                     |
| Unwanted Emissions, radiated      | 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical<br>200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical<br>1G~6GHz: 4.45 dB, 6G~26.5GHz: 5.23 dB |
| Unwanted Emissions, conducted     | ±1.5 dB                                                                                                                                                      |
| Temperature                       | ±1 °C                                                                                                                                                        |
| Humidity                          | ±5%                                                                                                                                                          |
| DC and low frequency voltages     | ±0.4%                                                                                                                                                        |
| Duty Cycle                        | 1%                                                                                                                                                           |
| AC Power Lines Conducted Emission | 3.12 dB (150 kHz to 30 MHz)                                                                                                                                  |

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

Bay Area Compliance Laboratories Corp. (Dongguan) has been accredited to ISO 17025 by CNAS(Lab code: L5662). And accredited to ISO 17025 by NVLAP(Test Laboratory Accreditation Certificate Number 500069-0), the FCC Designation No. CN5002 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Dongguan) was registered with ISED Canada under ISED Canada Registration Number 3062D.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in engineering mode.

### EUT Exercise Software

Test software: ' FCCAssit 1.5.exe ' was used in test, the system configured maximum power level as below setting:

| Test Software Version | FCCAssit 1.5.exe |         |         |
|-----------------------|------------------|---------|---------|
| Test Frequency        | 2402MHz          | 2441MHz | 2480MHz |
| GFSK                  | 10               | 10      | 10      |
| $\pi/4$ -DQPSK        | 10               | 10      | 10      |
| 8DPSK                 | 10               | 10      | 10      |

### Equipment Modifications

No modification was made to the EUT.


### Support Equipment List and Details

| Manufacturer | Description | Model        | Serial Number |
|--------------|-------------|--------------|---------------|
| HUAWEI       | Adapter     | HW-050200C01 | N/A           |

### External Cable

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From    | To  |
|-------------------|----------------|--------------|------------|---------|-----|
| USB Cable         | Yes            | No           | 1          | Adapter | EUT |

## Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                           | Description of Test              | Result     |
|-------------------------------------|----------------------------------|------------|
| FCC §15.247 (i) & §1.1310 & §2.1093 | RF Exposure                      | Compliance |
| §15.203                             | Antenna Requirement              | Compliance |
| §15.207 (a)                         | Conducted Emissions              | Compliance |
| §15.205, §15.209, §15.247(d)        | Spurious Emissions               | Compliance |
| §15.247 (a)(1)                      | 20 dB Bandwidth                  | Compliance |
| §15.247(a)(1)                       | Channel Separation Test          | Compliance |
| §15.247(a)(1)(iii)                  | Time of Occupancy (Dwell Time)   | Compliance |
| §15.247(a)(1)(iii)                  | Quantity of hopping channel Test | Compliance |
| §15.247(b)(1)                       | Peak Output Power Measurement    | Compliance |
| §15.247(d)                          | Band Edges                       | Compliance |

## **FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**

### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$   
 $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### **Measurement Result**

The max conducted power including tune-up tolerance is -2.0 dBm (0.63 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$   
 $= 0.63/5 \cdot (\sqrt{2.480}) = 0.2 < 3.0$

**So the stand-alone SAR evaluation is not necessary.**

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement for BT, and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207(a)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

$V_C$ : corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

| Manufacturer | Description        | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|---------|---------------|------------------|----------------------|
| R&S          | EMI Test Receiver  | ESCS 30 | 830245/006    | 2016-12-08       | 2017-12-08           |
| R&S          | L.I.S.N            | ESH2-Z5 | 892107/021    | 2016-09-01       | 2017-09-01           |
| R&S          | Two-line V-network | ENV 216 | 3560.6550.12  | 2016-12-08       | 2017-12-08           |
| R&S          | Test Software      | EMC32   | Version8.53.0 | N/A              | N/A                  |
| Unknown      | Coaxial Cable      | 2m      | Con-1         | 2016-09-01       | 2017-09-01           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data


#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.8 °C   |
| Relative Humidity: | 49 %      |
| ATM Pressure:      | 100.2 kPa |

*The testing was performed by Ade Xiao on 2017-08-25.*


Test Mode: Transmitting

AC120V, 60 Hz, Line:



| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.768247        | 40.9             | 9.000           | L1   | 9.8        | 15.1        | 56.0         | Compliance |
| 1.279307        | 40.3             | 9.000           | L1   | 9.7        | 15.7        | 56.0         | Compliance |
| 2.047133        | 39.0             | 9.000           | L1   | 9.7        | 17.0        | 56.0         | Compliance |
| 2.558827        | 39.8             | 9.000           | L1   | 9.8        | 16.2        | 56.0         | Compliance |
| 3.575883        | 40.5             | 9.000           | L1   | 9.8        | 15.5        | 56.0         | Compliance |
| 4.541500        | 39.6             | 9.000           | L1   | 9.8        | 16.4        | 56.0         | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.253797        | 38.0           | 9.000           | L1   | 10.3       | 13.6        | 51.6         | Compliance |
| 0.255827        | 36.8           | 9.000           | L1   | 10.3       | 14.8        | 51.6         | Compliance |
| 0.768247        | 37.4           | 9.000           | L1   | 9.8        | 8.6         | 46.0         | Compliance |
| 1.279307        | 34.6           | 9.000           | L1   | 9.7        | 11.4        | 46.0         | Compliance |
| 1.787792        | 33.8           | 9.000           | L1   | 9.7        | 12.2        | 46.0         | Compliance |
| 2.047133        | 30.7           | 9.000           | L1   | 9.7        | 15.3        | 46.0         | Compliance |

**AC120V, 60 Hz, Neutral:**

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.768247        | 36.5             | 9.000           | N    | 9.8        | 19.5        | 56.0         | Compliance |
| 2.047133        | 33.3             | 9.000           | N    | 9.8        | 22.7        | 56.0         | Compliance |
| 2.558827        | 34.6             | 9.000           | N    | 9.8        | 21.4        | 56.0         | Compliance |
| 3.073500        | 28.5             | 9.000           | N    | 9.8        | 27.5        | 56.0         | Compliance |
| 3.575883        | 35.6             | 9.000           | N    | 9.8        | 20.4        | 56.0         | Compliance |
| 4.094608        | 26.9             | 9.000           | N    | 9.8        | 29.1        | 56.0         | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment    |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.768247        | 27.5           | 9.000           | N    | 9.8        | 18.5        | 46.0         | Compliance |
| 1.787792        | 25.0           | 9.000           | N    | 9.7        | 21.0        | 46.0         | Compliance |
| 2.047133        | 18.2           | 9.000           | N    | 9.8        | 27.8        | 46.0         | Compliance |
| 2.558827        | 22.9           | 9.000           | N    | 9.8        | 23.1        | 46.0         | Compliance |
| 3.575883        | 24.3           | 9.000           | N    | 9.8        | 21.7        | 46.0         | Compliance |
| 4.094608        | 15.9           | 9.000           | N    | 9.8        | 30.1        | 46.0         | Compliance |


## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

#### Below 1GHz:



#### Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz   | 120 kHz | QP       |
| Above 1 GHz       | 1MHz    | 3 MHz     | /       | PK       |
|                   | 1MHz    | 10 Hz     | /       | AV       |

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

## Test Equipment List and Details

| Manufacturer          | Description       | Model                  | Serial Number      | Calibration Date | Calibration Due Date |
|-----------------------|-------------------|------------------------|--------------------|------------------|----------------------|
| R&S                   | EMI Test Receiver | ESCI                   | 100224             | 2016-09-01       | 2017-08-31           |
| Sunol Sciences        | Antenna           | JB3                    | A060611-1          | 2014-11-06       | 2017-11-05           |
| HP                    | Amplifier         | 8447E                  | 2434A02181         | 2016-09-01       | 2017-09-01           |
| R&S                   | Spectrum Analyzer | FSU 26                 | 200256             | 2016-12-08       | 2017-12-08           |
| ETS-Lindgren          | Horn Antenna      | 3115                   | 000 527 35         | 2016-01-05       | 2019-01-04           |
| Ducommun Technologies | Horn Antenna      | ARH-4223-02            | 1007726-02<br>1304 | 2017-06-16       | 2020-06-15           |
| MITEQ                 | Amplifier         | AFS42-00101800-25-S-42 | 2001271            | 2016-09-05       | 2017-09-05           |
| Quinstar              | Amplifier         | QLW-18405536-JO        | 15964001001        | 2016-09-06       | 2017-09-06           |
| Unknown               | Coaxial Cable     | Chamber A-1            | 4m                 | 2016-09-01       | 2017-09-01           |
| Unknown               | Coaxial Cable     | Chamber B-1            | 0.75m              | 2016-09-01       | 2017-09-01           |
| Unknown               | Coaxial Cable     | Chamber A-2            | 10m                | 2016-09-01       | 2017-09-01           |
| Unknown               | Coaxial Cable     | Chamber B-2            | 8m                 | 2016-09-01       | 2017-09-01           |
| Farad                 | Test Software     | EZ-EMC                 | V1.1.4.2           | N/A              | N/A                  |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Data

### Environmental Conditions


|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.3 °C   |
| <b>Relative Humidity:</b> | 62 %      |
| <b>ATM Pressure:</b>      | 100.6 kPa |

*\* The testing was performed by Steven Zuo on 2017-08-25.*


*Test Mode: Transmitting*

## 1) 30MHz-1GHz

Horizontal:



| Frequency (MHz) | Receiver Reading (dBuV) | Detector | Correction Factor (dB/m) | Cord. Amp. (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|-------------------------|----------|--------------------------|---------------------|----------------|-------------|
| 30.9700         | 24.85                   | QP       | 0.35                     | 25.20               | 40.00          | 14.80       |
| 65.8900         | 31.37                   | QP       | -11.87                   | 19.50               | 40.00          | 20.50       |
| 119.2400        | 24.21                   | QP       | -4.91                    | 19.30               | 43.50          | 24.20       |
| 270.5600        | 24.18                   | QP       | -4.08                    | 20.10               | 46.00          | 25.90       |
| 384.0500        | 30.95                   | QP       | -2.75                    | 28.20               | 46.00          | 17.80       |
| 576.1100        | 26.86                   | QP       | 0.54                     | 27.40               | 46.00          | 18.60       |

**Vertical:**

| Frequency (MHz) | Receiver Reading (dBuV) | Detector | Correction Factor (dB/m) | Cord. Amp. (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|-----------------|-------------------------|----------|--------------------------|---------------------|----------------|-------------|
| 30.0000         | 24.53                   | QP       | 1.07                     | 25.60               | 40.00          | 14.40       |
| 124.0900        | 24.68                   | QP       | -4.78                    | 19.90               | 43.50          | 23.60       |
| 204.6000        | 25.12                   | QP       | -6.82                    | 18.30               | 43.50          | 25.20       |
| 274.4400        | 24.15                   | QP       | -3.85                    | 20.30               | 46.00          | 25.70       |
| 384.0500        | 28.05                   | QP       | -2.75                    | 25.30               | 46.00          | 20.70       |
| 437.4000        | 24.59                   | QP       | -1.79                    | 22.80               | 46.00          | 23.20       |

**2) 1-25GHz:***BDR Mode (GFSK):*

| Frequency<br>(MHz)       | Receiver          |          | Rx Antenna     |                | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector | Polar<br>(H/V) | Factor<br>(dB) |                       |                           |                                    |                   |                |
| Low Channel: 2402 MHz    |                   |          |                |                |                       |                           |                                    |                   |                |
| 2402                     | 53.85             | PK       | H              | 28.10          | 3.11                  | 0.00                      | 85.06                              | N/A               | N/A            |
| 2402                     | 42.39             | AV       | H              | 28.10          | 3.11                  | 0.00                      | 73.60                              | N/A               | N/A            |
| 2402                     | 49.46             | PK       | V              | 28.10          | 3.11                  | 0.00                      | 80.67                              | N/A               | N/A            |
| 2402                     | 38.24             | AV       | V              | 28.10          | 3.11                  | 0.00                      | 69.45                              | N/A               | N/A            |
| 2390                     | 25.45             | PK       | H              | 28.08          | 3.10                  | 0.00                      | 56.63                              | 74.00             | 17.37          |
| 2390                     | 13.28             | AV       | H              | 28.08          | 3.10                  | 0.00                      | 44.46                              | 54.00             | 9.54           |
| 4804                     | 54.68             | PK       | H              | 32.91          | 4.30                  | 35.48                     | 56.41                              | 74.00             | 17.59          |
| 4804                     | 42.52             | AV       | H              | 32.91          | 4.30                  | 35.48                     | 44.25                              | 54.00             | 9.75           |
| 7206                     | 46.65             | PK       | H              | 35.74          | 5.45                  | 35.97                     | 51.87                              | 74.00             | 22.13          |
| 7206                     | 32.69             | AV       | H              | 35.74          | 5.45                  | 35.97                     | 37.91                              | 54.00             | 16.09          |
| 6359                     | 45.94             | PK       | H              | 34.23          | 5.10                  | 35.77                     | 49.50                              | 74.00             | 24.50          |
| 6359                     | 31.72             | AV       | H              | 34.23          | 5.10                  | 35.77                     | 35.28                              | 54.00             | 18.72          |
| Middle Channel: 2441 MHz |                   |          |                |                |                       |                           |                                    |                   |                |
| 2441                     | 53.67             | PK       | H              | 28.18          | 3.11                  | 0.00                      | 84.96                              | N/A               | N/A            |
| 2441                     | 42.52             | AV       | H              | 28.18          | 3.11                  | 0.00                      | 73.81                              | N/A               | N/A            |
| 2441                     | 49.81             | PK       | V              | 28.18          | 3.11                  | 0.00                      | 81.10                              | N/A               | N/A            |
| 2441                     | 38.36             | AV       | V              | 28.18          | 3.11                  | 0.00                      | 69.65                              | N/A               | N/A            |
| 4882                     | 54.41             | PK       | H              | 33.06          | 4.40                  | 35.54                     | 56.33                              | 74.00             | 17.67          |
| 4882                     | 42.79             | AV       | H              | 33.06          | 4.40                  | 35.54                     | 44.71                              | 54.00             | 9.29           |
| 7323                     | 47.02             | PK       | H              | 36.04          | 5.53                  | 35.98                     | 52.61                              | 74.00             | 21.39          |
| 7323                     | 32.94             | AV       | H              | 36.04          | 5.53                  | 35.98                     | 38.53                              | 54.00             | 15.47          |
| 5965                     | 46.41             | PK       | H              | 34.29          | 4.65                  | 35.85                     | 49.50                              | 74.00             | 24.50          |
| 5965                     | 31.98             | AV       | H              | 34.29          | 4.65                  | 35.85                     | 35.07                              | 54.00             | 18.93          |
| 6322                     | 45.65             | PK       | H              | 34.24          | 5.06                  | 35.78                     | 49.17                              | 74.00             | 24.83          |
| 6322                     | 31.42             | AV       | H              | 34.24          | 5.06                  | 35.78                     | 34.94                              | 54.00             | 19.06          |
| High Channel: 2480 MHz   |                   |          |                |                |                       |                           |                                    |                   |                |
| 2480                     | 53.64             | PK       | H              | 28.26          | 3.10                  | 0.00                      | 85.00                              | N/A               | N/A            |
| 2480                     | 42.68             | AV       | H              | 28.26          | 3.10                  | 0.00                      | 74.04                              | N/A               | N/A            |
| 2480                     | 49.49             | PK       | V              | 28.26          | 3.10                  | 0.00                      | 80.85                              | N/A               | N/A            |
| 2480                     | 38.56             | AV       | V              | 28.26          | 3.10                  | 0.00                      | 69.92                              | N/A               | N/A            |
| 2483.5                   | 25.76             | PK       | H              | 28.27          | 3.10                  | 0.00                      | 57.13                              | 74.00             | 16.87          |
| 2483.5                   | 13.57             | AV       | H              | 28.27          | 3.10                  | 0.00                      | 44.94                              | 54.00             | 9.06           |
| 4960                     | 54.44             | PK       | H              | 33.22          | 4.42                  | 35.60                     | 56.48                              | 74.00             | 17.52          |
| 4960                     | 42.59             | AV       | H              | 33.22          | 4.42                  | 35.60                     | 44.63                              | 54.00             | 9.37           |
| 7440                     | 46.93             | PK       | H              | 36.34          | 5.60                  | 35.99                     | 52.88                              | 74.00             | 21.12          |
| 7440                     | 32.68             | AV       | H              | 36.34          | 5.60                  | 35.99                     | 38.63                              | 54.00             | 15.37          |
| 6115                     | 45.55             | PK       | H              | 34.28          | 4.81                  | 35.82                     | 48.82                              | 74.00             | 25.18          |
| 6115                     | 31.71             | AV       | H              | 34.28          | 4.81                  | 35.82                     | 34.98                              | 54.00             | 19.02          |

EDR Mode ( $\pi/4$ -DQPSK):

| Frequency<br>(MHz)       | Receiver          |          | Rx Antenna     |                | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector | Polar<br>(H/V) | Factor<br>(dB) |                       |                           |                                    |                   |                |
| Low Channel: 2402 MHz    |                   |          |                |                |                       |                           |                                    |                   |                |
| 2402                     | 53.83             | PK       | H              | 28.10          | 3.11                  | 0.00                      | 85.04                              | N/A               | N/A            |
| 2402                     | 40.27             | AV       | H              | 28.10          | 3.11                  | 0.00                      | 71.48                              | N/A               | N/A            |
| 2402                     | 49.96             | PK       | V              | 28.10          | 3.11                  | 0.00                      | 81.17                              | N/A               | N/A            |
| 2402                     | 37.15             | AV       | V              | 28.10          | 3.11                  | 0.00                      | 68.36                              | N/A               | N/A            |
| 2390                     | 25.41             | PK       | H              | 28.08          | 3.10                  | 0.00                      | 56.59                              | 74.00             | 17.41          |
| 2390                     | 13.32             | AV       | H              | 28.08          | 3.10                  | 0.00                      | 44.50                              | 54.00             | 9.50           |
| 4804                     | 54.58             | PK       | H              | 32.91          | 4.30                  | 35.48                     | 56.31                              | 74.00             | 17.69          |
| 4804                     | 41.49             | AV       | H              | 32.91          | 4.30                  | 35.48                     | 43.22                              | 54.00             | 10.78          |
| 7206                     | 46.51             | PK       | H              | 35.74          | 5.45                  | 35.97                     | 51.73                              | 74.00             | 22.27          |
| 7206                     | 32.62             | AV       | H              | 35.74          | 5.45                  | 35.97                     | 37.84                              | 54.00             | 16.16          |
| 5877                     | 45.34             | PK       | H              | 34.25          | 4.64                  | 35.85                     | 48.38                              | 74.00             | 25.62          |
| 5877                     | 31.37             | AV       | H              | 34.25          | 4.64                  | 35.85                     | 34.41                              | 54.00             | 19.59          |
| Middle Channel: 2441 MHz |                   |          |                |                |                       |                           |                                    |                   |                |
| 2441                     | 53.62             | PK       | H              | 28.18          | 3.11                  | 0.00                      | 84.91                              | N/A               | N/A            |
| 2441                     | 40.53             | AV       | H              | 28.18          | 3.11                  | 0.00                      | 71.82                              | N/A               | N/A            |
| 2441                     | 49.97             | PK       | V              | 28.18          | 3.11                  | 0.00                      | 81.26                              | N/A               | N/A            |
| 2441                     | 36.75             | AV       | V              | 28.18          | 3.11                  | 0.00                      | 68.04                              | N/A               | N/A            |
| 4882                     | 54.32             | PK       | H              | 33.06          | 4.40                  | 35.54                     | 56.24                              | 74.00             | 17.76          |
| 4882                     | 41.51             | AV       | H              | 33.06          | 4.40                  | 35.54                     | 43.43                              | 54.00             | 10.57          |
| 7323                     | 46.73             | PK       | H              | 36.04          | 5.53                  | 35.98                     | 52.32                              | 74.00             | 21.68          |
| 7323                     | 32.65             | AV       | H              | 36.04          | 5.53                  | 35.98                     | 38.24                              | 54.00             | 15.76          |
| 5975                     | 45.87             | PK       | H              | 34.29          | 4.66                  | 35.85                     | 48.97                              | 74.00             | 25.03          |
| 5975                     | 31.79             | AV       | H              | 34.29          | 4.66                  | 35.85                     | 34.89                              | 54.00             | 19.11          |
| 6344                     | 45.36             | PK       | H              | 34.23          | 5.08                  | 35.77                     | 48.90                              | 74.00             | 25.10          |
| 6344                     | 31.15             | AV       | H              | 34.23          | 5.08                  | 35.77                     | 34.69                              | 54.00             | 19.31          |
| High Channel: 2480 MHz   |                   |          |                |                |                       |                           |                                    |                   |                |
| 2480                     | 51.78             | PK       | H              | 28.26          | 3.10                  | 0.00                      | 83.14                              | N/A               | N/A            |
| 2480                     | 38.59             | AV       | H              | 28.26          | 3.10                  | 0.00                      | 69.95                              | N/A               | N/A            |
| 2480                     | 47.85             | PK       | V              | 28.26          | 3.10                  | 0.00                      | 79.21                              | N/A               | N/A            |
| 2480                     | 34.63             | AV       | V              | 28.26          | 3.10                  | 0.00                      | 65.99                              | N/A               | N/A            |
| 2483.5                   | 26.25             | PK       | H              | 28.27          | 3.10                  | 0.00                      | 57.62                              | 74.00             | 16.38          |
| 2483.5                   | 13.89             | AV       | H              | 28.27          | 3.10                  | 0.00                      | 45.26                              | 54.00             | 8.74           |
| 4960                     | 53.78             | PK       | H              | 33.22          | 4.42                  | 35.60                     | 55.82                              | 74.00             | 18.18          |
| 4960                     | 41.33             | AV       | H              | 33.22          | 4.42                  | 35.60                     | 43.37                              | 54.00             | 10.63          |
| 7440                     | 46.37             | PK       | H              | 36.34          | 5.60                  | 35.99                     | 52.32                              | 74.00             | 21.68          |
| 7440                     | 32.16             | AV       | H              | 36.34          | 5.60                  | 35.99                     | 38.11                              | 54.00             | 15.89          |
| 5966                     | 45.52             | PK       | H              | 34.29          | 4.65                  | 35.85                     | 48.61                              | 74.00             | 25.39          |
| 5966                     | 31.34             | AV       | H              | 34.29          | 4.65                  | 35.85                     | 34.43                              | 54.00             | 19.57          |

EDR Mode (8DPSK):

| Frequency<br>(MHz)       | Receiver          |          | Rx Antenna     |                | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|----------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector | Polar<br>(H/V) | Factor<br>(dB) |                       |                           |                                    |                   |                |
| Low Channel: 2402 MHz    |                   |          |                |                |                       |                           |                                    |                   |                |
| 2402                     | 53.96             | PK       | H              | 28.10          | 3.11                  | 0.00                      | 85.17                              | N/A               | N/A            |
| 2402                     | 40.34             | AV       | H              | 28.10          | 3.11                  | 0.00                      | 71.55                              | N/A               | N/A            |
| 2402                     | 50.09             | PK       | V              | 28.10          | 3.11                  | 0.00                      | 81.30                              | N/A               | N/A            |
| 2402                     | 37.28             | AV       | V              | 28.10          | 3.11                  | 0.00                      | 68.49                              | N/A               | N/A            |
| 2390                     | 25.54             | PK       | H              | 28.08          | 3.10                  | 0.00                      | 56.72                              | 74.00             | 17.28          |
| 2390                     | 13.45             | AV       | H              | 28.08          | 3.10                  | 0.00                      | 44.63                              | 54.00             | 9.37           |
| 4804                     | 54.71             | PK       | H              | 32.91          | 4.30                  | 35.48                     | 56.44                              | 74.00             | 17.56          |
| 4804                     | 41.62             | AV       | H              | 32.91          | 4.30                  | 35.48                     | 43.35                              | 54.00             | 10.65          |
| 7206                     | 46.64             | PK       | H              | 35.74          | 5.45                  | 35.97                     | 51.86                              | 74.00             | 22.14          |
| 7206                     | 32.75             | AV       | H              | 35.74          | 5.45                  | 35.97                     | 37.97                              | 54.00             | 16.03          |
| 5835                     | 45.47             | PK       | H              | 34.23          | 4.68                  | 35.85                     | 48.53                              | 74.00             | 25.47          |
| 5835                     | 31.34             | AV       | H              | 34.23          | 4.68                  | 35.85                     | 34.40                              | 54.00             | 19.60          |
| Middle Channel: 2441 MHz |                   |          |                |                |                       |                           |                                    |                   |                |
| 2441                     | 53.75             | PK       | H              | 28.18          | 3.11                  | 0.00                      | 85.04                              | N/A               | N/A            |
| 2441                     | 40.66             | AV       | H              | 28.18          | 3.11                  | 0.00                      | 71.95                              | N/A               | N/A            |
| 2441                     | 50.32             | PK       | V              | 28.18          | 3.11                  | 0.00                      | 81.61                              | N/A               | N/A            |
| 2441                     | 36.88             | AV       | V              | 28.18          | 3.11                  | 0.00                      | 68.17                              | N/A               | N/A            |
| 4882                     | 54.45             | PK       | H              | 33.06          | 4.40                  | 35.54                     | 56.37                              | 74.00             | 17.63          |
| 4882                     | 41.64             | AV       | H              | 33.06          | 4.40                  | 35.54                     | 43.56                              | 54.00             | 10.44          |
| 7323                     | 46.86             | PK       | H              | 36.04          | 5.53                  | 35.98                     | 52.45                              | 74.00             | 21.55          |
| 7323                     | 32.78             | AV       | H              | 36.04          | 5.53                  | 35.98                     | 38.37                              | 54.00             | 15.63          |
| 5896                     | 46.27             | PK       | H              | 34.26          | 4.61                  | 35.85                     | 49.29                              | 74.00             | 24.71          |
| 5896                     | 31.92             | AV       | H              | 34.26          | 4.61                  | 35.85                     | 34.94                              | 54.00             | 19.06          |
| 6435                     | 45.49             | PK       | H              | 34.21          | 5.19                  | 35.75                     | 49.14                              | 74.00             | 24.86          |
| 6435                     | 31.28             | AV       | H              | 34.21          | 5.19                  | 35.75                     | 34.93                              | 54.00             | 19.07          |
| High Channel: 2480 MHz   |                   |          |                |                |                       |                           |                                    |                   |                |
| 2480                     | 51.91             | PK       | H              | 28.26          | 3.10                  | 0.00                      | 83.27                              | N/A               | N/A            |
| 2480                     | 38.72             | AV       | H              | 28.26          | 3.10                  | 0.00                      | 70.08                              | N/A               | N/A            |
| 2480                     | 47.98             | PK       | V              | 28.26          | 3.10                  | 0.00                      | 79.34                              | N/A               | N/A            |
| 2480                     | 34.76             | AV       | V              | 28.26          | 3.10                  | 0.00                      | 66.12                              | N/A               | N/A            |
| 2483.5                   | 26.38             | PK       | H              | 28.27          | 3.10                  | 0.00                      | 57.75                              | 74.00             | 16.25          |
| 2483.5                   | 14.02             | AV       | H              | 28.27          | 3.10                  | 0.00                      | 45.39                              | 54.00             | 8.61           |
| 4960                     | 53.91             | PK       | H              | 33.22          | 4.42                  | 35.60                     | 55.95                              | 74.00             | 18.05          |
| 4960                     | 41.46             | AV       | H              | 33.22          | 4.42                  | 35.60                     | 43.50                              | 54.00             | 10.50          |
| 7440                     | 46.48             | PK       | H              | 36.34          | 5.60                  | 35.99                     | 52.43                              | 74.00             | 21.57          |
| 7440                     | 32.29             | AV       | H              | 36.34          | 5.60                  | 35.99                     | 38.24                              | 54.00             | 15.76          |
| 6275                     | 45.65             | PK       | H              | 34.25          | 5.00                  | 35.79                     | 49.11                              | 74.00             | 24.89          |
| 6275                     | 31.47             | AV       | H              | 34.25          | 5.00                  | 35.79                     | 34.93                              | 54.00             | 19.07          |

**FCC §15.247(a) (1) - CHANNEL SEPARATION TEST****Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

**Test Equipment List and Details**

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSP 38  | 100478        | 2016-12-08       | 2017-12-08           |
| Unknown      | RF Cable          | Unknown | C-2           | Each Time        | /                    |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Procedure**

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 25.4 °C   |
| Relative Humidity: | 62 %      |
| ATM Pressure:      | 100.2 kPa |

\* The testing was performed by Mark Pan on 2017-08-27.

**Test Result:** Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

| Mode                     | Channel | Frequency (MHz) | Channel Separation (MHz) | Limit (MHz) |
|--------------------------|---------|-----------------|--------------------------|-------------|
| BDR<br>(GFSK)            | Low     | 2402            | 1.000                    | 0.59        |
|                          | Middle  | 2441            | 1.000                    | 0.59        |
|                          | High    | 2480            | 1.004                    | 0.59        |
| EDR<br>( $\pi/4$ -DQPSK) | Low     | 2402            | 1.004                    | 0.83        |
|                          | Middle  | 2441            | 1.004                    | 0.85        |
|                          | High    | 2480            | 1.000                    | 0.85        |
| EDR<br>(8DPSK)           | Low     | 2402            | 1.004                    | 0.83        |
|                          | Middle  | 2441            | 1.004                    | 0.85        |
|                          | High    | 2480            | 1.000                    | 0.85        |


Note: Limit =  $(2/3) \times 20\text{dB bandwidth}$

BDR Mode (GFSK):




Date: 27.AUG.2017 13:32:14

### Middle Channel



Date: 27.AUG.2017 13:32:57


### High Channel



Date: 27.AUG.2017 13:33:40


EDR Mode ( $\pi/4$ -DQPSK):

### Low Channel




Date: 27.AUG.2017 13:36:52

### Middle Channel



Date: 27.AUG.2017 13:37:47


### High Channel



Date: 27.AUG.2017 13:38:38


EDR Mode (8DPSK):

### Low Channel




Date: 27.AUG.2017 13:39:49

### Middle Channel



Date: 27.AUG.2017 13:40:42

### High Channel



Date: 27.AUG.2017 13:41:30

**FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING****Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Equipment List and Details**

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSP 38  | 100478        | 2016-12-08       | 2017-12-08           |
| Unknown      | RF Cable          | Unknown | C-2           | Each Time        | /                    |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 25.4 °C   |
| Relative Humidity: | 62 %      |
| ATM Pressure:      | 100.2 kPa |

\* The testing was performed by Mark Pan on 2017-08-27.

**Test Result:** Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

| Mode                       | Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |
|----------------------------|---------|-----------------|-----------------------|
| BDR Mode (GFSK)            | Low     | 2402            | 0.88                  |
|                            | Middle  | 2441            | 0.88                  |
|                            | High    | 2480            | 0.88                  |
| EDR Mode ( $\pi/4$ -DQPSK) | Low     | 2402            | 1.25                  |
|                            | Middle  | 2441            | 1.27                  |
|                            | High    | 2480            | 1.27                  |
| EDR Mode (8DPSK)           | Low     | 2402            | 1.24                  |
|                            | Middle  | 2441            | 1.27                  |
|                            | High    | 2480            | 1.27                  |


BDR Mode (GFSK):

### Low Channel




Date: 27.AUG.2017 13:17:57

### Middle Channel




Date: 27.AUG.2017 13:19:27


### High Channel



Date: 27.AUG.2017 13:20:46


*EDR Mode ( $\pi/4$ -DQPSK):***Low Channel**

Date: 27.AUG.2017 13:22:22

**Middle Channel**

Date: 27.AUG.2017 13:23:51


### High Channel



Date: 27.AUG.2017 13:25:01


EDR Mode (8DPSK):

### Low Channel




Date: 27.AUG.2017 13:26:54

### Middle Channel



Date: 27.AUG.2017 13:28:38

### High Channel



Date: 27.AUG.2017 13:29:50

**FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST****Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

**Test Equipment List and Details**

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSP 38  | 100478        | 2016-12-08       | 2017-12-08           |
| Unknown      | RF Cable          | Unknown | C-2           | Each Time        | /                    |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 25.4 °C   |
| Relative Humidity: | 62 %      |
| ATM Pressure:      | 100.2 kPa |

\* The testing was performed by Mark Pan on 2017-08-27.


**Test Result:** Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|-----------------------|---------------------------|-------|
| 2400-2483.5           | 79                        | ≥15   |



Date: 27.AUG.2017 13:45:45

EDR Mode ( $\pi/4$ -DQPSK):


| Frequency Range<br>(MHz) | Number of<br>Hopping Channel | Limit     |
|--------------------------|------------------------------|-----------|
| 2400-2483.5              | 79                           | $\geq 15$ |



Date: 27.AUG.2017 13:50:18

*EDR Mode (8DPSK):*

| Frequency Range<br>(MHz) | Number of<br>Hopping Channel | Limit |
|--------------------------|------------------------------|-------|
| 2400-2483.5              | 79                           | ≥15   |

**Number of Hopping Channels**

Date: 27.AUG.2017 13:53:59

**FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)****Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

**Test Procedure**

The EUT was worked in channel hopping; the time of single pulses was tested.

**Test Equipment List and Details**

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSP 38  | 100478        | 2016-12-08       | 2017-12-08           |
| Unknown      | RF Cable          | Unknown | C-2           | Each Time        | /                    |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 25.4 °C   |
| Relative Humidity: | 62 %      |
| ATM Pressure:      | 100.2 kPa |

\* The testing was performed by Mark Pan on 2017-08-27.

**Test Result:** Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


| Mode       | Channel                                                 | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result     |
|------------|---------------------------------------------------------|------------------|----------------|-----------|------------|
| <b>DH1</b> | Low                                                     | 0.392            | 0.125          | 0.4       | Compliance |
|            | Middle                                                  | 0.392            | 0.125          | 0.4       | Compliance |
|            | High                                                    | 0.392            | 0.125          | 0.4       | Compliance |
|            | Note: Dwell time=Pulse time (ms) × (1600/2/79) × 31.6 s |                  |                |           |            |
| <b>DH3</b> | Low                                                     | 1.662            | 0.266          | 0.4       | Compliance |
|            | Middle                                                  | 1.662            | 0.266          | 0.4       | Compliance |
|            | High                                                    | 1.662            | 0.266          | 0.4       | Compliance |
|            | Note: Dwell time=Pulse time (ms) × (1600/4/79) × 31.6 s |                  |                |           |            |
| <b>DH5</b> | Low                                                     | 2.920            | 0.311          | 0.4       | Compliance |
|            | Middle                                                  | 2.920            | 0.311          | 0.4       | Compliance |
|            | High                                                    | 2.920            | 0.311          | 0.4       | Compliance |
|            | Note: Dwell time=Pulse time (ms) × (1600/6/79) × 31.6 s |                  |                |           |            |

### DH1: Low Channel




Date: 27.AUG.2017 13:54:58

### DH1: Middle Channel




Date: 27.AUG.2017 13:55:08

### DH1: High Channel




Date: 27.AUG.2017 13:55:17

### DH3: Low Channel




Date: 27.AUG.2017 13:56:05

### DH3: Middle Channel




Date: 27.AUG.2017 13:56:15

### DH3: High Channel




Date: 27.AUG.2017 13:56:25

### DH5: Low Channel




Date: 27.AUG.2017 13:57:26

### DH5: Middle Channel



Date: 27.AUG.2017 13:57:36


### DH5: High Channel



Date: 27.AUG.2017 13:57:45


EDR Mode ( $\pi/4$ -DQPSK):

| Mode        | Channel                                                               | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result     |
|-------------|-----------------------------------------------------------------------|------------------|----------------|-----------|------------|
| <b>2DH1</b> | Low                                                                   | 0.402            | 0.129          | 0.4       | Compliance |
|             | Middle                                                                | 0.402            | 0.129          | 0.4       | Compliance |
|             | High                                                                  | 0.402            | 0.129          | 0.4       | Compliance |
|             | Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s |                  |                |           |            |
| <b>2DH3</b> | Low                                                                   | 1.668            | 0.267          | 0.4       | Compliance |
|             | Middle                                                                | 1.668            | 0.267          | 0.4       | Compliance |
|             | High                                                                  | 1.668            | 0.267          | 0.4       | Compliance |
|             | Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s |                  |                |           |            |
| <b>2DH5</b> | Low                                                                   | 2.920            | 0.311          | 0.4       | Compliance |
|             | Middle                                                                | 2.920            | 0.311          | 0.4       | Compliance |
|             | High                                                                  | 2.920            | 0.311          | 0.4       | Compliance |
|             | Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s |                  |                |           |            |

**2DH1: Low Channel**


Date: 27.AUG.2017 13:58:57

### 2DH1: Middle Channel




Date: 27.AUG.2017 13:59:06

### 2DH1: High Channel




Date: 27.AUG.2017 13:59:16

### 2DH3: Low Channel




Date: 27.AUG.2017 14:02:45

### 2DH3: Middle Channel




Date: 27.AUG.2017 14:00:35

### 2DH3: High Channel




Date: 27.AUG.2017 14:03:05

### 2DH5: Low Channel




Date: 27.AUG.2017 14:07:28

### 2DH5: Middle Channel



Date: 27.AUG.2017 14:04:50


### 2DH5: High Channel



Date: 27.AUG.2017 14:09:22


*EDR Mode (8DPSK):*

| Mode        | Channel                                                               | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result     |
|-------------|-----------------------------------------------------------------------|------------------|----------------|-----------|------------|
| <b>3DH1</b> | Low                                                                   | 0.400            | 0.128          | 0.4       | Compliance |
|             | Middle                                                                | 0.402            | 0.129          | 0.4       | Compliance |
|             | High                                                                  | 0.400            | 0.128          | 0.4       | Compliance |
|             | Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s |                  |                |           |            |
| <b>3DH3</b> | Low                                                                   | 1.668            | 0.267          | 0.4       | Compliance |
|             | Middle                                                                | 1.668            | 0.267          | 0.4       | Compliance |
|             | High                                                                  | 1.662            | 0.266          | 0.4       | Compliance |
|             | Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s |                  |                |           |            |
| <b>3DH5</b> | Low                                                                   | 2.930            | 0.313          | 0.4       | Compliance |
|             | Middle                                                                | 2.920            | 0.311          | 0.4       | Compliance |
|             | High                                                                  | 2.920            | 0.311          | 0.4       | Compliance |
|             | Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s |                  |                |           |            |

**3DH1: Low Channel**


Date: 27.AUG.2017 14:10:35

### 3DH1: Middle Channel




Date: 27.AUG.2017 14:10:45

### 3DH1: High Channel




Date: 27.AUG.2017 14:10:55

### 3DH3: Low Channel




Date: 27.AUG.2017 14:11:24

### 3DH3: Middle Channel




Date: 27.AUG.2017 14:11:33

### 3DH3: High Channel




Date: 27.AUG.2017 14:11:43

### 3DH5: Low Channel




Date: 27.AUG.2017 14:12:02

### 3DH5: Middle Channel



Date: 27.AUG.2017 14:12:11

### 3DH5: High Channel



Date: 27.AUG.2017 14:13:41

**FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT****Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

**Test Procedure**

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

**Test Equipment List and Details**

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSP 38  | 100478        | 2016-12-08       | 2017-12-08           |
| Unknown      | RF Cable          | Unknown | C-2           | Each Time        | /                    |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.4 °C   |
| <b>Relative Humidity:</b> | 62 %      |
| <b>ATM Pressure:</b>      | 100.2 kPa |


\* The testing was performed by Mark Pan on 2017-08-27.

**Test Result:** Compliance.

*Test Mode: Transmitting*


| Mode                       | Frequency (MHz) | Peak Conducted Output power (dBm) | Limit (dBm) |
|----------------------------|-----------------|-----------------------------------|-------------|
| BDR Mode (GFSK)            | 2402            | -4.69                             | 30          |
|                            | 2441            | -4.14                             | 30          |
|                            | 2480            | -4.32                             | 30          |
| EDR Mode ( $\pi/4$ -DQPSK) | 2402            | -3.44                             | 30          |
|                            | 2441            | -2.92                             | 30          |
|                            | 2480            | -3.07                             | 30          |
| EDR Mode (8DPSK)           | 2402            | -5.76                             | 30          |
|                            | 2441            | -5.24                             | 30          |
|                            | 2480            | -5.33                             | 30          |

Note: The data above was tested in conducted mode.

***BDR Mode (GFSK):*****Low Channel**


Date: 27.AUG.2017 13:18:25

### Middle Channel



Date: 27.AUG.2017 13:19:58


### High Channel



Date: 27.AUG.2017 13:21:15


**EDR Mode ( $\pi/4$ -DQPSK):**

**Low Channel**




Date: 27.AUG.2017 13:22:51

**Middle Channel**



Date: 27.AUG.2017 13:24:22


### High Channel



Date: 27.AUG.2017 13:25:31


### EDR Mode (8DPSK):

### Low Channel




Date: 27.AUG.2017 13:27:24

### Middle Channel



Date: 27.AUG.2017 13:29:09

### High Channel



Date: 27.AUG.2017 13:30:20

## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | Spectrum Analyzer | FSP 38  | 100478        | 2016-12-08       | 2017-12-08           |
| Unknown      | RF Cable          | Unknown | C-2           | Each Time        | /                    |


\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.4 °C   |
| <b>Relative Humidity:</b> | 62 %      |
| <b>ATM Pressure:</b>      | 100.2 kPa |

*\* The testing was performed by Mark Pan on 2017-08-27.*

**Test Result:** Compliance

*BDR Mode (GFSK):***Band Edge, Left Side**


Date: 27.AUG.2017 13:18:50

**Band Edge, Right Side**

Date: 27.AUG.2017 13:21:40


EDR Mode ( $\pi/4$ -DQPSK):

### Band Edge, Left Side



Date: 27.AUG.2017 13:23:10


### Band Edge, Right Side



Date: 27.AUG.2017 13:25:49


EDR Mode (8DPSK):

### Band Edge, Left Side



Date: 27.AUG.2017 13:27:44

### Band Edge, Right Side



Date: 27.AUG.2017 13:30:51

\*\*\*\*\* END OF REPORT \*\*\*\*\*