



FCC Test Report (Bluetooth)

FCC ID : SXXKTS-88

Applicant : Shenzhen KingBoard Technology Co., Ltd.
Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China

Sample Description

Product Name : Bluetooth Speaker

Model No. : KTS-88

Serial No. : N/A

Trademark : N/A

Receipt Date : 2015-09-25

Test Date : 2015-09-27 to 2015-09-30

Issue Date : 2015-09-30

Test Standard(s) : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Conclusions : PASSED*

*In the configuration tested, the EUT complied with the standards specified above.

Test/Witness Engineer :

Jason Deng

Approved & Authorized :

Frank Zhang

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



Contents

CONTENTS	2
1. GENERAL INFORMATION	4
1.1. Client Information.....	4
1.2. General Description of EUT (Equipment Under Test).....	4
1.3. Block Diagram Showing The Configuration of System Tested.....	6
1.4. Description of Support Units.....	6
1.5. External I/O Cable.....	6
N/A.....	6
1.6. Description of Test Mode.....	6
1.7. Test Instruments List.....	7
1.8. Laboratory Location.....	8
2. TEST SUMMARY	9
3. ANTENNA REQUIREMENT	10
3.1. Standard Requirement.....	10
3.2. Antenna Connected Construction.....	10
4. CONDUCTED EMISSION TEST	11
4.1. Test Standard and Limit.....	11
4.2. Test Setup.....	11
4.3. Test Procedure.....	11
4.4. Test Data.....	12
5. CONDUCTED PEAK OUTPUT POWER TEST	15
5.1. Test Standard and Limit.....	15
5.2. Test Setup.....	15
5.3. Test Procedure.....	15
5.4. Test Data.....	16
6. 20DB OCCUPY BANDWIDTH TEST	22
6.1. Test Standard and Limit.....	22
6.2. Test Setup.....	22
6.3. Test Procedure.....	22
6.4. Test Data.....	22
7. CARRIER FREQUENCY SEPARATION TEST	29
7.1. Test Standard and Limit.....	29
7.2. Test Setup.....	29
7.3. Test Procedure.....	29
7.4. Test Data.....	30
8. NUMBER OF HOPPING CHANNEL	33
8.1. Test Standard and Limit.....	33



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 3 of 57

8.2. Test Setup.....	33
8.3. Test Procedure.....	33
8.4. Test Data.....	33
9. DWELL TIME TEST.....	36
9.1. Test Standard and Limit.....	36
9.2. Test Setup.....	36
9.3. Test Procedure.....	36
9.4. Test Data.....	37
10. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	43
10.1. Standard Requirement.....	43
10.2. EUT Pseudorandom Frequency Hopping Sequence.....	43
11. BAND EDGE REQUIREMENT (CONDUCTED EMISSION METHOD).....	44
11.1. Test Standard and Limit.....	44
11.2. Test Setup.....	44
11.3. Test Procedure.....	44
11.4. Test Data.....	44
12. BAND EDGE REQUIREMENT (RADIATED EMISSION METHOD).....	48
12.1. Test Standard and Limit.....	48
12.2. Test Setup.....	48
12.3. Test Procedure.....	48
12.4. Test Data.....	49
13. SPURIOUS EMISSION (RADIATED EMISSION METHOD).....	51
13.1. Test Standard and Limit.....	51
13.2. Test Setup.....	51
13.3. Test Procedure.....	51
13.4. Test Data.....	52



1. General Information

1.1. Client Information

Applicant	:	Shenzhen KingBoard Technology Co., Ltd.
Address	:	Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China
Manufacturer	:	Shenzhen KingBoard Technology Co., Ltd.
Address	:	Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China

1.2. General Description of EUT (Equipment Under Test)

Product Name	:	Bluetooth Speaker	
Models No.	:	KTS-88	
Difference	:	N/A	
Product Description	:	Operation Frequency:	2402MHz~2480MHz
		Transfer Rate:	1/2/3 Mbits/s
		Number of Channel:	79 Channels
		Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
		Modulation Technology:	FHSS
		Antenna Type:	Integral PCB Antenna
		Antenna Gain:	0 dBi
Power Supply	:	USB DC 5V from USB Port, DC 3.7V from Li-ion battery	

Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 5 of 57


(2) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Remark: Channel 0, 39 & 78 selected for GFSK, $\pi/4$ -DQPSK and 8DPSK.



1.3. Block Diagram Showing The Configuration of System Tested



1.4. Description of Support Units

Name	Model	Serial Number	Manufacturer
Notebook	/	/	ASUS

1.5. External I/O Cable

N/A

1.6. Description of Test Mode

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follows was evaluated respectively.

Test Mode	Description
Charging & Working mode	Keep the EUT in Charging & working mode
Transmitting mode	Keep the EUT in Transmitting mode with worst case data rate
Remark	GFSK(1Mbps) is the worst case mode

Remark: The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.



1.7. Test Instruments List

Item	Test Equipment	Manufacturer	Model No.	Cal. Date	Cal. Due date
1	Bilog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	May 22, 2015	May 21, 2016
2	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	May 27, 2015	May 26, 2016
3	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
4	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
5	Coaxial cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
6	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
7	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
8	Amplifier (10kHz-1.3GHz)	HP	8447D	Mar. 30, 2015	Mar. 29, 2016
9	Amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	Jun. 07, 2015	Jun. 06, 2016
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	Mar. 30, 2015	Mar. 29, 2016
11	Horn Antenna	ETS-LINDGREN	3160	Mar. 30, 2015	Mar. 29, 2016
12	Positioning Controller	UC	UC3000	N/A	N/A
13	Spectrum analyzer 9kHz-30GHz	Rohde & Schwarz	FSP	May 27, 2015	May 26, 2016
14	EMI Test Receiver	Rohde & Schwarz	ESPI	Mar. 30, 2015	Mar. 29, 2016
15	Loop antenna	Laplace instrument	RF300	May 23, 2015	May 22, 2016
16	Universal radio communication tester	Rhode & Schwarz	CMU200	May 27, 2015	May 26, 2016
17	Signal Analyzer	Rohde & Schwarz	FSIQ3	May 27, 2015	May 26, 2016
18	L.I.S.N.#1	Rohde & Schwarz	NSLK8126	May 27, 2015	May 26, 2016
19	L.I.S.N.#2	Rohde & Schwarz	ENV216	May 27, 2015	May 26, 2016



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 8 of 57

1.8. Laboratory Location

Shenzhen TOBY technology Co., Ltd

Address: 1 A/F., Bldg.6, Yusheng Industrial Zone The National Road No.107 Xixiang Section 467,
Xixiang, Bao'an, Shenzhen, Guangdong, 518057, China

At the time of testing, the Laboratory is accredited. It is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562 7.

Tel:0086-755-26509301 Fax: 0086-755-26509195



2. Test Summary

Standard Section	Test Item	Judgment
15.203/15.247(c)	Antenna Requirement	PASSED
15.207	Conducted Emission	PASSED
15.247(b)(1)	Conducted Peak Output Power	PASSED
15.247(a)(1)	20dB Occupied Bandwidth	PASSED
15.247(a)(1)	Carrier Frequencies Separation	PASSED
15.247(a)(1)	Hopping Channel Number	PASSED
15.247(a)(1)	Dwell Time	PASSED
15.247(b)(4)&TCB Exclusion List (7 July 2002)	Pseudorandom Frequency Hopping Sequence	PASSED
15.205/15.209	Spurious Emission	PASSED
15.247(d)	Band Edge	PASSED
Remark: "N/A" is an abbreviation for Not Applicable.		



3. Antenna Requirement

3.1. Standard Requirement

3.1.1 Test standard

FCC Part15 Section 15.203 /247(c)

3.1.2 Requirement

1) 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

2) 15.247(c) (1)(i) requirement:

Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2. Antenna Connected Construction

The bluetooth antenna is an integral antenna which permanently attached, and the best case gain of the antenna is 0dBi. It complies with the standard requirement.

4. Conducted Emission Test

4.1. Test Standard and Limit

4.1.1 Test Standard

FCC Part15 Section 15.207


4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
 (2) The lower limit shall apply at the transition frequencies.

4.2. Test Setup



4.3. Test Procedure

- 1) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50 \Omega / 50\mu\text{H} + 5 \Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.

The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 12 of 57

ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

The Test Receiver setup: RBW=9kHz, VBW=30kHz, Sweep time= auto

4.4. Test Data

Please to see the following pages




ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 13 of 57

Conducted Emission Test Data

EUT: Bluetooth Speaker M/N: KTS-88
 Operating Condition: Charging & Working mode
 Test Site: Shielded room
 Operator: Jason
 Test Specification: AC120V/60Hz
 Polarization: Line
 Note: Tem:25°C Hum:50%



Condition		: FCC PART 15 B QP				POL: LINE		Temp:20.1 °C Hum:45 %	
Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
	MHz	dBuV	Factor	Factor	Loss	dBuV	dBuV	dBuV	
			dB	dB	dB				
1	0.161	34.72	0.03	-9.72	0.10	44.57	65.43	-20.86	QP
2	0.161	21.33	0.03	-9.72	0.10	31.18	55.43	-24.25	Average
3	0.280	29.91	0.03	-9.72	0.10	39.76	60.81	-21.05	QP
4	0.280	18.43	0.03	-9.72	0.10	28.28	50.81	-22.53	Average
5	0.727	25.88	0.04	-9.72	0.10	35.74	56.00	-20.26	QP
6	0.727	15.12	0.04	-9.72	0.10	24.98	46.00	-21.02	Average
7	1.160	23.36	0.04	-9.71	0.10	33.21	56.00	-22.79	QP
8	1.160	12.47	0.04	-9.71	0.10	22.32	46.00	-23.68	Average
9	3.328	17.77	0.08	-9.69	0.12	27.66	56.00	-28.34	QP
10	3.328	6.58	0.08	-9.69	0.12	16.47	46.00	-29.53	Average
11	9.107	24.96	0.16	-9.40	0.18	34.70	60.00	-25.30	QP
12	9.107	15.53	0.16	-9.40	0.18	25.27	50.00	-24.73	Average

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss




ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 14 of 57

Conducted Emission Test Data

EUT: Bluetooth Speaker M/N: KTS-88
 Operating Condition: Charging & Working mode
 Test Site: Shielded room
 Operator: Jason
 Test Specification: AC 120V/60Hz
 Polarization: Neutral
 Note: Tem:25°C Hum:50%



Condition : FCC PART 15 B QP POL: NEUTRAL Temp:20.1 °C Hum:45 %

Item	Freq MHz	Read dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.161	34.65	0.03	-9.72	0.10	44.50	65.43	-20.93	QP
2	0.161	21.40	0.03	-9.72	0.10	31.25	55.43	-24.18	Average
3	0.322	32.99	0.03	-9.72	0.10	42.84	59.66	-16.82	QP
4	0.322	24.07	0.03	-9.72	0.10	33.92	49.66	-15.74	Average
5	0.611	26.78	0.03	-9.72	0.10	36.63	56.00	-19.37	QP
6	0.611	15.85	0.03	-9.72	0.10	25.70	46.00	-20.30	Average
7	1.374	24.24	0.05	-9.71	0.10	34.10	56.00	-21.90	QP
8	1.374	11.20	0.05	-9.71	0.10	21.06	46.00	-24.94	Average
9	4.224	17.52	0.08	-9.69	0.12	27.41	56.00	-28.59	QP
10	4.224	5.24	0.08	-9.69	0.12	15.13	46.00	-30.87	Average
11	9.107	20.24	0.16	-9.40	0.18	29.98	60.00	-30.02	QP
12	9.107	11.85	0.16	-9.40	0.18	21.59	50.00	-28.41	Average

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss



5. Conducted Peak Output Power Test

5.1. Test Standard and Limit


5.1.1 Test Standard

FCC Part15 C Section 15.247 (b)(3)

5.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

5.2. Test Setup



5.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
RBW=1MHz, VBW=1MHz, Detector=Peak (If 20dB BW \leq 1 MHz)
RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.



5.4. Test Data

GFSK mode				
Channel Number	Channel Frequency (MHz)	Test Result (dBm)	Limit (30dBm)	Judgment
CH 00	2402	2.95	21	PASSED
CH 39	2441	3.343	21	PASSED
CH 78	2480	3.085	21	PASSED

$\pi/4$ -DQPSK mode				
Channel Number	Channel Frequency (MHz)	Test Result (dBm)	Limit (30dBm)	Judgment
CH 00	2402	2.22	21	PASSED
CH 39	2441	2.763	21	PASSED
CH 78	2480	2.60	21	PASSED

8DPSK mode				
Channel Number	Channel Frequency (MHz)	Test Result (dBm)	Limit (30dBm)	Judgment
CH 00	2402	2.378	21	PASSED
CH 39	2441	2.888	21	PASSED
CH 78	2480	2.661	21	PASSED


Remark: Test plot as follows



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 17 of 57






ATA Testing Technology Service Co., Ltd.


Report No.: ATA151008001F

Page: 18 of 57



Modulation mode

$\pi/4$ -DQPSK






ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 19 of 57





ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 20 of 57


Modulation mode		8DPSK	
2402MHz			<ul style="list-style-type: none"> Peak Search Next Peak Next Pk Right Next Pk Left Marker Delta Mkr→CF Mkr→Ref Lvl More 1 of 2
2441MHz			<ul style="list-style-type: none"> Peak Search Next Peak Next Pk Right Next Pk Left Marker Delta Mkr→CF Mkr→Ref Lvl More 1 of 2



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 21 of 57





6. 20dB Occupy Bandwidth Test

6.1. Test Standard and Limit


6.1.1 Test Standard

FCC Part15 C Section 15.247 (a)(1)

6.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Bandwidth	20dB bandwidth	2400~2483.5

6.2. Test Setup



6.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Bandwidth: RBW=30 kHz, VBW=100 kHz, detector= Peak

6.4. Test Data

Channel Number	Channel Frequency	20dB Bandwidth (kHz)		
		GFSK	$\pi/4$ -DQPSK	8DPSK
CH 00	2402(MHz)	836.4	1118	1165
CH 39	2441(MHz)	835.0	1117	1163
CH 78	2480(MHz)	836.9	1115	1163



Remark: Test plot as follows



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 23 of 57

Modulation mode	GFSK mode
2402MHz	<div data-bbox="495 352 1372 976"> <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.40200000 GHz</p> <p>Center Freq: 2.40200000 GHz</p> <p>Trig: Free Run</p> <p>#Atten: 20 dB</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p>  <p>10 dB/div Ref 20.00 dBm</p> <p>Center 2.402 GHz</p> <p>#Res BW 30 kHz</p> <p>#VBW 100 kHz</p> <p>Span 3 MHz</p> <p>Sweep 3.2 ms</p> <p>Occupied Bandwidth 841.41 kHz</p> <p>Total Power 9.18 dBm</p> <p>Transmit Freq Error -3.804 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 836.4 kHz</p> <p>x dB -20.00 dB</p> </div>
2441MHz	<div data-bbox="495 997 1372 1617"> <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.44100000 GHz</p> <p>Center Freq: 2.44100000 GHz</p> <p>Trig: Free Run</p> <p>#Atten: 20 dB</p> <p>Radio Std: None</p> <p>Radio Device: BTS</p>  <p>10 dB/div Ref 20.00 dBm</p> <p>Center 2.441 GHz</p> <p>#Res BW 30 kHz</p> <p>#VBW 100 kHz</p> <p>Span 3 MHz</p> <p>Sweep 3.2 ms</p> <p>Occupied Bandwidth 839.50 kHz</p> <p>Total Power 9.54 dBm</p> <p>Transmit Freq Error -4.340 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 835.0 kHz</p> <p>x dB -20.00 dB</p> </div>



ATA Testing Technology Service Co., Ltd.

Report No.: ATA151008001F

Page: 24 of 57

