



FCC TEST REPORT

FCC ID: SY4-A02029

On Behalf of

Shanghai Huace Navigation Technology LTD.

Geodetic GNSS Receiver

Model No.: P5

Prepared for : Shanghai Huace Navigation Technology LTD.
Address : 599 Gaojing Road, Building D, Shanghai 201702, China


Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,
518103, Shenzhen, Guangdong, China

Report Number : A2102016-C01-R06
Date of Receipt : February 20, 2021
Date of Test : February 20, 2021 – March 15, 2021
Date of Report : March 15, 2021
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. General Information	5
1.1. Description of Device (EUT).....	5
1.2. Accessories of Device (EUT)	5
1.3. Tested Supporting System Details	6
1.4. Block Diagram of connection between EUT and simulators.....	6
2. Summary Of Standards And Results	7
2.1. Description of Standards and Results	7
2.2. Test Mode Description.....	7
2.3. Test Equipment List	8
2.4. Test Facility	9
2.5. Measurement Uncertainty	9
3. Power Line Conducted Emission Test.....	10
3.1. Test Limits	10
3.2. Block Diagram of Test Setup.....	10
3.3. Configuration of EUT on Test	11
3.4. Operating Condition of EUT	11
3.5. Test Procedure	11
3.6. Test Results	12
4. Radiated Emission Test.....	15
4.1. Test Limit.....	15
4.2. Block Diagram of Test Setup.....	16
4.3. Configuration of EUT on Test	17
4.4. Operating Condition of EUT	17
4.5. Test Procedure	17
4.6. Test Results	18
5. Photograph.....	24
5.1. Photos of Radiated Emission Test (In Semi Anechoic Chamber)	24
5.2. Photos of Conducted disturbance at mains terminals test.....	25
6. Photos of The EUT	26

TEST REPORT DECLARATION

Applicant : Shanghai Huace Navigation Technology LTD.
 Address : 599 Gaojing Road, Building D, Shanghai 201702, China
 Manufacturer : Shanghai Huace Navigation Technology LTD.
 Address : 599 Gaojing Road, Building D, Shanghai 201702, China
 EUT Description : Geodetic GNSS Receiver
 (A) Model No. : P5
 (B) Trademark : 

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart B Class B, ANSI C63.4:2014

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part15 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Reak Yang 
 Project Engineer

Approved by (name + signature).....: Simple Guan 
 Project Manager

Date of issue..... : March 15, 2021

Revision History

Revision	Issue Date	Revisions	Revised By
V0	March 15, 2021	Initial released Issue	Reak Yang

1. General Information

1.1. Description of Device (EUT)

Product Name : Geodetic GNSS Receiver

Model Number : P5

Diff : N/A

Test Voltage : DC 7.4V From Battery

EUT Information : Input: DC 7.4V, DC 12-36V, DC 12V From Adapter

Highest Frequency : More than 108MHz

Trademark : 

Software version : V1.2.21

Hardware version : V2.0

1.2. Accessories of Device (EUT)


Power Source : N/A

1.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	Notebook PC	Lenovo	ThinkPad E14	N/A	SDOC

1.4. Block Diagram of connection between EUT and simulators

For Test



Signal Cable Description of the above Support Units					
No.	Port Name	Cable	Length	Shielded (Yes or No)	Detachable (Yes or No)
(a)	N/A	N/A	N/A	N/A	N/A

EUT: Geodetic GNSS Receiver

2. Summary Of Standards And Results

2.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

EMISSION			
Description of Test Item	Standard	Limits	Results
Power Line Conducted Emission Test	FCC Part 15 ANSI C63.4:2014	Class B	P
Radiated Emission Test	FCC Part 15 ANSI C63.4:2014	Class B	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.			

2.2. Test Mode Description

For Test		
Mode No.	Test Mode	Test Voltage
※1.	Data Transmitting	DC 7.4V from Battery
2.	GNSS Receive	DC 7.4V from Battery
Note: ※ is worst case mode tests, so this report only reflected the worst mode in each part.		

2.3. Test Equipment List

For Power Line Conducted Emission Test Equipment:						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	101165	2020.09.02	1 Year
2.	L.I.S.N.#1	Schwarz beck	NSLK8126	8126466	2020.09.02	1 Year
3.	L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2020.09.02	1 Year
4.	Pulse Limiter	Schwarz beck	9516F	9618	2020.09.02	1 Year

For Frequency Range 30MHz~1GHz Radiated Emission Test Equipment:						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde&Schwarz	ESR	1316.3003K03-102082-Wa	2020.09.02	1 Year
3	Bilog Antenna	Schwarz beck	VULB 9168	9168-627	2020.09.02	2 Year

For Frequency Range above 1GHz Radiated Emission Test Equipment:						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	ROHDE&SCHWARZ	FSU	1166.1660.26	2020.09.02	1 Year
2	Horn Antenna	Schwarz beck	BBHA 9120 D	BBHA 9120 D(1201)	2020.09.02	2 Year
3	Amplifier	Agilent	8449B	3008A02664	2020.09.02	1 Year

2.4. Test Facility

Shenzhen Alpha Product Testing Co., Ltd.

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

Designation Number: CN1236

2.5. Measurement Uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.74dB
Uncertainty for Radiation Emission test (<1G)	3.77 dB (Distance: 3m Polarize: V)
	3.80 dB (Distance: 3m Polarize: H)
Uncertainty for Radiation Emission test (>1G)	4.13 dB (Distance: 3m Polarize: V)
	4.16 dB (Distance: 3m Polarize: H)
(95% confidence levels, k=2)	


3. Power Line Conducted Emission Test

3.1. Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes:
1. Emission level=Read level + LISN factor-Preamp factor + Cable loss
 2. * Decreasing linearly with logarithm of frequency.
 3. The lower limit shall apply at the transition frequencies.

3.2. Block Diagram of Test Setup



3.3. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 3.2.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode and 15 minutes before taking the test.


3.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4:2014 on conducted Emission test.
- (2) The frequency range from 150kHz to 30MHz is checked, the bandwidth of test receiver (R&S TEST RECEIVER ESCI) is set at 9kHz.

3.6. Test Results

Test Date : 2020.02.25	Temperature : 24°C
Model : P5	Humidity : 56%
Test Mode : Data Transmitting	
Test Results : PASS	Test Engineer : Reak Yang
Note: 1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.	


L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1740	40.80	9.93	50.73	64.77	-14.04	peak	
2		0.2100	34.48	9.93	44.41	63.21	-18.80	peak	
3		0.2910	29.51	9.93	39.44	60.50	-21.06	peak	
4		0.5700	26.54	9.93	36.47	56.00	-19.53	peak	
5		16.2240	23.06	10.36	33.42	60.00	-26.58	peak	
6		22.3470	23.30	10.45	33.75	60.00	-26.25	peak	

*:Maximum data x:Over limit !:over margin (Reference Only)
 Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

N



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1590	42.89	9.94	52.83	65.52	-12.69	peak	
2		0.1720	40.40	9.93	50.33	64.86	-14.53	peak	
3		0.1980	35.78	9.92	45.70	63.69	-17.99	peak	
4		0.2700	30.89	9.95	40.84	61.12	-20.28	peak	
5		0.5790	23.15	9.93	33.08	56.00	-22.92	peak	
6		22.2810	25.54	10.45	35.99	60.00	-24.01	peak	

*:Maximum data x:Over limit !:over margin (Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

4. RADIATED EMISSION TEST

4.1. Test Limit


Frequency MHz			Distance (Meters)	Field Strengths Limits dB(μ V)/m
30	~	88	3	40.0
88	~	216	3	43.5
216	~	960	3	46.0
960	~	1000	3	54.0
Above 1GHz			3	74(Peak) 54(Average)

- Notes:
1. The smaller limit shall apply at the cross point between two frequency bands.
 2. Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
 3. Frequency range of radiated measurements:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

4.2. Block Diagram of Test Setup

In Semi Anechoic Chamber (3m) Test Setup Diagram for 30MHz~1000MHz



In Semi Anechoic Chamber (3m) Test Setup Diagram for Above 1GHz



4.3. Configuration of EUT on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner that tends to maximize its emission characteristics in normal application.

4.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 4.2.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode and 15 minutes before taking the test.


4.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4:2014 on Radiated Emission test.
- (2) For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- (3) The frequency range from 30MHz to 1000MHz is checked, the bandwidth of test receiver (R&S TEST RECEIVER ESR) is set at 120kHz.
- (4) The frequency range from above 1GHz is checked, the bandwidth of spectrum analyzer (Spectrum Analyzer FSU) is set at 1MHz.
- (5) The frequency range from 30MHz to 1000MHz was pre-scanned with a peak detector and all final readings of measurement from Test Receiver are Quasi-Peak values, the frequency range from 1GHz to 6GHz was pre-scanned with a peak detector and all final readings of measurement from Spectrum Analyzer are peak and average values checked, all measurement distance is 3m in 3m semi anechoic chamber.
- (6) The test results are reported on Section 4.7.

4.6. Test Results

Frequency Range : 30MHz~1000MHz	
Test Date : 2021.02.24	Temperature : 24°C
Model : P5	Humidity : 56%
Test Mode : Data Transmitting	Test Engineer : Reak Yang
Test Results : PASS	
Note: 1. The test results are listed in next pages. 2. If the limits for the measurement with the quasi-peak detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.	

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		108.8247	18.63	11.71	30.34	43.50	-13.16			peak
2		134.8425	19.49	13.94	33.43	43.50	-10.07			peak
3		149.9932	18.35	15.06	33.41	43.50	-10.09			peak
4		250.0087	25.44	12.77	38.21	46.00	-7.79			peak
5		314.7072	21.99	14.48	36.47	46.00	-9.53			peak
6	*	750.0203	16.93	22.47	39.40	46.00	-6.60			peak

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		41.1272	16.36	14.34	30.70	40.00	-9.30			peak
2		51.2586	16.13	13.88	30.01	40.00	-9.99			peak
3		107.2590	20.59	11.56	32.15	43.50	-11.35			peak
4		240.0150	20.18	12.55	32.73	46.00	-13.27			peak
5	*	480.0224	21.47	17.95	39.42	46.00	-6.58			peak
6		750.0206	16.04	22.47	38.51	46.00	-7.49			peak

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Frequency Range : Above 1GHz	
Test Date : 2021.02.24	Temperature : 25°C
Model : P5	Humidity : 56%
Test Mode : Data Transmitting	Test Engineer : Reak Yang
Test Results : PASS	
Note: 1. The test results are listed in next pages. 2. If the limits for the measurement with the quasi-peak detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.	

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		1354.577	48.25	-7.15	41.10	74.00	-32.90			peak
2		2194.998	46.12	-3.37	42.75	74.00	-31.25			peak
3		2999.187	45.67	-2.31	43.36	74.00	-30.64			peak
4		3515.957	50.08	-6.36	43.72	74.00	-30.28			peak
5		7762.260	47.24	3.28	50.52	74.00	-23.48			peak
6	*	10514.57	45.92	5.20	51.12	74.00	-22.88			peak

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree degree	Comment
1		2144.825	47.08	-3.77	43.31	74.00	-30.69	peak		
2		4959.307	50.81	-2.58	48.23	74.00	-25.77	peak		
3		7368.741	45.08	3.44	48.52	74.00	-25.48	peak		
4		10393.71	46.16	5.05	51.21	74.00	-22.79	peak		
5		11335.19	45.27	5.76	51.03	74.00	-22.97	peak		
6	*	18000.00	38.85	12.88	51.73	74.00	-22.27	peak		

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.


5. PHOTOGRAPH

5.1.Photos of Radiated Emission Test (In Semi Anechoic Chamber)

30M-1000MHz



Above 1GHz




5.2.Photos of Conducted disturbance at mains terminals test






6. PHOTOS OF THE EUT







































----END OF REPORT----