

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3. Result

Worse case is as below:

Mode	Frequency (MHz)	Prediction distance (cm)	RF output power		MPE (mW/cm ²)	Limit (mW/cm ²)	SAR Test Exclusion
			dBm	mW			
BT EDR	2480	20	4.285	2.682	0.00067	1	Yes
BLE	2480	20	8.379	6.885	0.00172	1	Yes
WIFI	2462	20	13.116	20.493	0.00513	1	Yes
GSM	848.80	20	30.65	1161.449	0.25926	0.5659	Yes
WCDMA	1907.6	20	23.28	212.814	0.04750	1	Yes
LTE	1717.5	20	24.32	270.396	0.06036	1	Yes

Maximum Simultaneous transmission MPE Ratios for BLE+WIFI +GSM:

Max MPE ratio BLE/Limit	Max MPE ratio WIFI/Limit	Max MPE ratio GSM/Limit	Σ MPE ratios	Limit	Result
0.00172	0.00513	0.45814	0.46499	1	PASS

BT&WIFI Antenna Gain: 1dBi, 1.259(numeric)

GSM, WCDMA & LTE Antenna Gain: 0.5dBi, 1.122(numeric)

Then SAR evaluation is not required.