



EMC TEST REPORT

Report No.: 20230717G07543X-W1

Product Name: Communication module

FCC ID: SY4-A02046

Model No. : ALink3

Applicant: Shanghai Huace Navigation Technology.Ltd

Address: 577 Songying Road, Qingpu District, 201706 Shanghai, China

Received Date: 2023.07.04

Dates of Testing: 2023.07.10~2023.07.21

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street,
Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of **19** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name..... Communication module

Model No. ALink3

Trade name..... CHCNAV

Applicant..... Shanghai Huace Navigation Technology.Ltd

Applicant Address..... 577 Songying Road, Qingpu District, 201706 Shanghai, China

Manufacturer Shanghai Huace Navigation Technology.Ltd

Manufacturer Address 577 Songying Road, Qingpu District, 201706 Shanghai, China

Test Standards..... 47 CFR Part 15 Subpart B

Test Result..... PASS

Tested by Ruihong Xie

Ruihong Xie Test Engineer 2023.07.25

Reviewed by Chris You

Chris You Senior Engineer 2023.07.25

Approved by Yang Fan

Yang Fan, Manager 2023.07.25



TABLE OF CONTENTS

1. GENERAL INFORMATION4

1.1 EUT Description4

1.2 Test Standards and Results.....5

Facilities and Accreditations6

1.2.1 Facilities6

1.2.2 Test Environment Conditions.....6

1.2.3 Measurement Uncertainty6

2. TEST CONDITIONS SETTING7

2.1 Test Peripherals7

2.2 Test Mode7

2.3 Test Setup and Equipments List.....8

2.3.1 Conducted Emission8

2.3.2 Radiated Emission.....9

3. 47 CFR PART 15B REQUIREMENTS11

3.1 Conducted Emission11

3.1.1 Requirement11

3.1.2 Test Description11

3.1.3 Test Result.....11

3.2 Radiated Emission14

3.2.1 Requirement14

3.2.2 Test Description15

3.2.3 Test Result.....15

APPENDIX I: PHOTOGRAPHS OF EMC TEST CONFIGURATION..... 错误!未定义书签。

| Change History | | |
|----------------|------------|-------------------|
| Issue | Date | Reason for change |
| 1.0 | 2023.07.25 | First edition |
| | | |
| | | |



1. GENERAL INFORMATION

1.1 EUT Description

EUT Name : Communication module

Trade Name.....: CHCNAV

Brand Name.....: CHCNAV

Hardware Version..... : V1.0.0

Software Version : 3.3.23.6.9

Note1:The EUT is a Communication module;

Note2 :For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

| No. | Identity | Document Title |
|-----|-----------------------------|-------------------------|
| 1 | 47 CFR Part 15 Subpart B | Radio Frequency Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section | Description | Result |
|-----|---------|--------------------|--------|
| 1 | 15.107 | Conducted Emission | PASS |
| 2 | 15.109 | Radiated Emission | PASS |

NOTE:

- (1) The EUT has been tested according to 47 CFR Part 15 Subpart B, Class B. The test procedure is according to ANSI C63.4:2014.



Facilities and Accreditations

1.2.1 Facilities

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Sep.30, 2023.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Sep.30, 2023.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.2.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

| | |
|-----------------------------|---------------|
| Temperature (°C): | 15 °C - 35 °C |
| Relative Humidity (%): | 25% -75% |
| Atmospheric Pressure (kPa): | 86kPa-106kPa |

1.2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

| | |
|---|-------------------|
| Uncertainty of Conducted Emission: | Uc = 3.2 dB (k=2) |
| Uncertainty of Radiated Emission: (30MHz~1GHz) | Uc = 5.8 dB (k=2) |
| Uncertainty of Radiated Emission: (1~6GHz) | Uc = 5.1 dB (k=2) |
| Uncertainty of Radiated Emission: (6~18GHz) | Uc = 5.5 dB (k=2) |



2. TEST CONDITIONS SETTING

2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Support Equipment:

| Description | Brand name | Model | Serial No. | FCCID |
|-------------|------------|--------------|------------|-------|
| Adapter | / | HW-120150E6W | / | / |

Support Cable:

| Description | Shield Type | Ferrite Core | Length |
|-------------|-------------|--------------|--------|
| / | / | / | / |

2.2 Test Mode


The EUT have the following typical setups during the test:

Setup1: EUT+ Charger;

2.3 Test Setup and Equipments List

2.3.1 Conducted Emission

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


B. Equipments List:

| Description | Manufacturer | Model | Serial No. | Calibration Date | Calibration Due. Date |
|---------------|---------------|--------|------------|------------------|-----------------------|
| Test Receiver | KEYSIGHT | N9038A | A141202036 | 2023.06.12 | 2024.06.11 |
| LISN | ROHDE&SCHWARZ | ENV216 | A140701847 | 2023.06.08 | 2024.06.07 |
| Cable | MATCHING PAD | W7 | / | 2022.08.02 | 2023.08.02 |


2.3.2 Radiated Emission

A. Test Setup:

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz



**B. Test Procedure**

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

C. Equipments List:

| Description | Manufacturer | Model | Serial No. | Calibration Date | Calibration Due. Date |
|---------------------|---------------|---------------------------|------------|------------------|-----------------------|
| EMI Test Receiver | ROHDE&SCHWARZ | ESIB7 | A0501375 | 2023.03.16 | 2024.03.15 |
| Broadband Ant. | 2786 | ETC | A150402239 | 2021.09.16 | 2024.03.03 |
| 3M Anechoic Chamber | Albatross | SAC-3MAC 9*6*6m | A0412375 | 2021.03.26 | 2024.03.25 |
| EMI Test Receiver | ROHDE&SCHWARZ | ESW26 | A180502935 | 2023.06.06 | 2024.06.07 |
| 5M Anechoic Chamber | Albatross | SAC-5MAC 12.8x6.8x6.4m | A0304210 | 2022.03.25 | 2025.06.07 |
| EMI Horn Ant. | ROHDE&SCHWARZ | HF906 | A0304225 | 2022.04.12 | 2025.04.11 |



3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

| Frequency range (MHz) | Conducted Limit (dB μ V) | |
|-----------------------|------------------------------|----------|
| | Quasi-peak | Average |
| 0.15 - 0.50 | 66 to 56 | 56 to 46 |
| 0.50 - 5 | 56 | 46 |
| 5 - 30 | 60 | 50 |

Note:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description

See section 2.3.1 of this report.

3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

Note:

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a Nominal 120V AC,50/60Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Test voltage and frequency (120V AC,60Hz)

A. Mains terminal disturbance voltage, L phase,Setup 1




(Plot A: L Phase)

| Frequency (MHz) | QuasiPeak (dB μ V) | CAverage (dB μ V) | Cabel Loss (dB) | Corr. (dB) | Margin - QPK | Limit - QPK | Margin - AV | Limit - AV (dB μ V) |
|-----------------|------------------------|-----------------------|-----------------|------------|--------------|-------------|-------------|-------------------------|
| 0.154500 | 44.22 | 30.65 | 0.1 | 10.4 | 21.53 | 65.8 | 25.10 | 55.8 |
| 0.285000 | 44.88 | 33.62 | 0.1 | 10.5 | 15.79 | 60.7 | 17.05 | 50.7 |
| 0.627000 | 36.41 | 26.10 | 0.1 | 10.4 | 19.59 | 56.0 | 19.90 | 46.0 |
| 1.932000 | 37.53 | 27.52 | 0.2 | 10.4 | 18.47 | 56.0 | 18.48 | 46.0 |
| 2.256000 | 38.76 | 25.79 | 0.2 | 10.4 | 17.24 | 56.0 | 20.21 | 46.0 |
| 2.481000 | 37.98 | 23.39 | 0.3 | 10.4 | 18.02 | 56.0 | 22.61 | 46.0 |



B. Mains terminal disturbance voltage, N phase, Setup 1



(Plot B: N Phase)

| Frequency (MHz) | QuasiPeak (dB μ V) | CAverage (dB μ V) | Cabel Loss (dB) | Corr. (dB) | Margin - QPK | Limit - QPK | Margin - AV | Limit - AV (dB μ V) |
|-----------------|------------------------|-----------------------|-----------------|------------|--------------|-------------|-------------|-------------------------|
| 0.163500 | 43.37 | 27.26 | 0.1 | 10.6 | 21.91 | 65.3 | 28.02 | 55.3 |
| 0.181500 | 42.25 | 27.32 | 0.1 | 10.6 | 22.17 | 64.4 | 27.10 | 54.4 |
| 0.289500 | 43.79 | 33.10 | 0.1 | 10.6 | 16.75 | 60.5 | 17.44 | 50.5 |
| 1.495500 | 34.50 | 24.34 | 0.2 | 10.5 | 21.50 | 56.0 | 21.66 | 46.0 |
| 2.184000 | 34.79 | 21.48 | 0.2 | 10.5 | 21.21 | 56.0 | 24.52 | 46.0 |
| 2.395500 | 34.77 | 24.96 | 0.2 | 10.5 | 21.23 | 56.0 | 21.04 | 46.0 |



3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency range (MHz) | Field Strength | | Field Strength Limitation at 3m Measurement Dist | |
|-----------------------|-----------------|------|--|---------------------|
| | $\mu\text{V/m}$ | Dist | ($\mu\text{V/m}$) | (dBuV/m) |
| 30.0 - 88.0 | 100 | 3m | 100 | 20log 100 |
| 88.0 - 216.0 | 150 | 3m | 150 | 20log 150 |
| 216.0 - 960.0 | 200 | 3m | 200 | 20log 200 |
| Above 960.0 | 500 | 3m | 500 | 20log 500 |

- a) For frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.
- b) Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
- c) For below 1G :QP detector RBW 120kHz ,VBW 300kHz.

For Above 1G: PK detector RBW 1MHz,VBW 3MHz for PK value ;AV detector RBW 1MHz, VBW 10Hz for AV value.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by $20\log \text{Emission Level}(\mu\text{V/m})$.
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$

Example:

F.S Limit at 30m distance is $30\mu\text{V/m}$, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}.$$



3.2.2 Test Description

See section 2.3.2 of this report.

3.2.3 Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.



A.Radiation disturbances, antenna polarization:Vertical,Setup1




(Plot C: Test Antenna Vertical 30M - 1G)

| Frequency (MHz) | QuasiPeak (dBµV/m) | Bandwidth (kHz) | Antenna height (cm) | Limit (dBµV/m) | Margin (dB) | Antenna | Cable Loss(dB) | ANT. Factor(dB) | Verdict |
|-----------------|--------------------|-----------------|---------------------|----------------|-------------|----------|----------------|------------------|---------|
| 43.60 | 27.82 | 120.000 | 104 | 40.00 | 12.18 | Vertical | 0.5 | 13.2 | Pass |
| 59.34 | 30.97 | 120.000 | 104 | 40.00 | 9.03 | Vertical | 0.8 | 5.3 | Pass |
| 177.37 | 23.66 | 120.000 | 102 | 43.50 | 19.84 | Vertical | 1.2 | 10.4 | Pass |
| 193.28 | 28.43 | 120.000 | 101 | 43.50 | 15.07 | Vertical | 1.2 | 8.8 | Pass |
| 645.25 | 36.57 | 120.000 | 101 | 46.00 | 9.43 | Vertical | 1.6 | 20.1 | Pass |
| 857.87 | 38.57 | 120.000 | 102 | 46.00 | 7.43 | Vertical | 2 | 21.6 | Pass |



B.Radiation disturbances, antenna polarization: Horizontal,Setup1




(Plot D: Test Antenna Horizontal 30M - 1G)

| Frequency (MHz) | QuasiPeak (dBµV/m) | Bandwidth (kHz) | Antenna height (cm) | Limit (dBµV/m) | Margin (dB) | Antenna | Cable Loss(dB) | ANT. Factor(dB) | Verdict |
|-----------------|--------------------|-----------------|---------------------|----------------|-------------|------------|----------------|-----------------|---------|
| 31.94 | 20.64 | 120.000 | 104 | 40.00 | 19.36 | Horizontal | 0.5 | 18.8 | Pass |
| 68.87 | 20.34 | 120.000 | 104 | 40.00 | 19.66 | Horizontal | 0.8 | 5.2 | Pass |
| 173.84 | 18.42 | 120.000 | 102 | 43.50 | 25.08 | Horizontal | 1.2 | 10.4 | Pass |
| 195.23 | 20.41 | 120.000 | 101 | 43.50 | 23.09 | Horizontal | 1.2 | 9.1 | Pass |
| 292.42 | 33.93 | 120.000 | 101 | 46.00 | 12.07 | Horizontal | 1.4 | 14.3 | Pass |
| 845.35 | 35.98 | 120.000 | 102 | 46.00 | 10.02 | Horizontal | 2.0 | 21.4 | Pass |



A.Radiation disturbances, antenna polarization: Vertical,Setup1




(Plot M: Test Antenna Horizontal 1G – 18G)

| N O | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin[dB µV/m] | Trace | Height [cm] | Angle [°] | Polarity |
|--------|----------------|-------------------|----------------|-------------------|--------------------|-------|----------------|--------------|----------|
| 1 | 1079.22 | 36.66 | -12.92 | 54.00 | 17.34 | PK | 104 | 12 | Vertical |
| 2 | 1079.22 | 41.03 | -12.92 | 74.00 | 32.97 | AV | 107 | 23 | Vertical |
| 3 | 1319.06 | 40.23 | -13.13 | 74.00 | 33.77 | PK | 107 | 271 | Vertical |
| 4 | 1319.06 | 33.02 | -13.13 | 54.00 | 20.98 | AV | 109 | 270 | Vertical |
| 5 | 1558.91 | 38.08 | -12.34 | 74.00 | 35.92 | PK | 108 | 293 | Vertical |
| 6 | 1560.01 | 29.90 | -12.34 | 54.00 | 24.10 | AV | 103 | 216 | Vertical |
| 7 | 2644.83 | 31.83 | -8.38 | 54.00 | 22.17 | PK | 104 | 132 | Vertical |
| 8 | 2757.05 | 40.87 | -7.88 | 74.00 | 33.13 | AV | 103 | 283 | Vertical |
| 9 | 4825.47 | 40.74 | 0.77 | 54.00 | 13.26 | PK | 103 | 184 | Vertical |
| 1 | 4830.97 | 49.01 | 0.74 | 74.00 | 24.99 | AV | 107 | 250 | Vertical |
| 1 | 14201.94 | 57.27 | 13.44 | 74.00 | 16.73 | PK | 100 | 46 | Vertical |
| 1 | 14293.96 | 48.57 | 13.86 | 54.00 | 5.43 | AV | 106 | 19 | Vertical |



B.Radiation disturbances, antenna polarization: Horizontal,Setup1



(Plot N: Test Antenna Vertical 1G – 18G)

| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin[dB µV/m] | Trace | Height [cm] | Angle [°] | Polarity |
|-----|-------------|----------------|-------------|----------------|-----------------|-------|-------------|-----------|------------|
| 1 | 1079.22 | 29.72 | -12.92 | 54.00 | 24.28 | AV | 104 | 121 | Horizontal |
| 2 | 1079.22 | 37.21 | -12.92 | 74.00 | 36.79 | PK | 104 | 354 | Horizontal |
| 3 | 2030.91 | 29.14 | -10.50 | 54.00 | 24.86 | AV | 102 | 140 | Horizontal |
| 4 | 2039.71 | 38.30 | -10.46 | 74.00 | 35.70 | PK | 103 | 162 | Horizontal |
| 5 | 3302.76 | 33.21 | -6.16 | 54.00 | 20.79 | AV | 101 | 312 | Horizontal |
| 6 | 3369.87 | 42.95 | -5.81 | 74.00 | 31.05 | PK | 106 | 43 | Horizontal |
| 7 | 4768.25 | 48.28 | 0.80 | 74.00 | 25.72 | PK | 103 | 20 | Horizontal |
| 8 | 4832.07 | 39.90 | 0.74 | 54.00 | 14.10 | AV | 104 | 196 | Horizontal |
| 9 | 8710.74 | 54.32 | 7.91 | 74.00 | 19.68 | PK | 102 | 173 | Horizontal |
| 10 | 8903.98 | 44.98 | 7.81 | 54.00 | 9.02 | AV | 100 | 144 | Horizontal |
| 11 | 17247.75 | 48.36 | 16.02 | 54.00 | 5.64 | AV | 105 | 50 | Horizontal |
| 12 | 17284.56 | 58.03 | 16.09 | 74.00 | 15.97 | PK | 104 | 346 | Horizontal |

-----End of Report-----