



RF EXPOSURE REPORT

Report No.: 20230717G07543X-W3

Product Name: Communication module

Model No.: ALink3

FCC ID: SY4-A02046

Applicant: Shanghai Huace Navigation Technology.Ltd

Address: 577 Songying Road, Qingpu District, 201706 Shanghai, China


Dates of Testing: 07/04/2023 - 07/25/2023

Issued by: CCIC Southern Testing Co., Ltd.

Electronic Testing Building, No. 43 Shahe Road, Xili Street,

Lab Location: Nanshan District, Shenzhen, Guangdong, China.

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.





Test Report

Product.....: Communication module

Brand Name....: CHCNAV

Trade Name: CHCNAV

Applicant...... Shanghai Huace Navigation Technology.Ltd

Applicant Address.....: 577 Songying Road, Qingpu District, 201706 Shanghai,

China

Manufacturer...... Shanghai Huace Navigation Technology.Ltd

Manufacturer Address.....: 577 Songying Road, Qingpu District, 201706 Shanghai,

China

Test Standards.....: 47 CFR Part 2.1091

Test Result.....: Pass

Chuiwang Zhang, Test Engineer

Chris You, Senior Engineer

Approved by.....: 2023.07.26

Yang Fan, Manager



Table of Contents

1. GENERAL INFORMATION	.5
1.1. EUT Description	.5
1.2. EUT Description	.6
1.3. Laboratory Facilities	.6
1.4. Laboratory Location	. 6
2. TECHNICAL REQUIREMENTS SPECIFICATION IN CFR TITLE 47 PART 2.1091	7
2.1. Evaluation method	.7
2.2. Predication of MPE limit at a given distance	. 7
2.3. Evaluation Results	. 8
2.4 Conclusion	8



Change History			
Issue	Date	Reason for change	
1.0 2023.07.26		First edition	



1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Communication module		
Device Type	Fixed devices		
Frequency Range	WLAN2.4GHz 802.11b/g/n (HT20/HT40)		
Modulation Type	DSSS (802.11b), OFDM (802.11g/n)		
Antenna Type	Internal Antenna		
Antenna Gain	Antenna 1: 1.24dBi		
	Antenna 2: 1.92dBi		



1.2. EUT Description

EUT has been tested according to the following standards.

No.	Identity	Document Title		
1	47 CFR Part 1	Practice and Procedure		
2	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General		
2	4/ CFR Part 2	Rules and Regulations		
2	KDB 447498 D01 General	RF Exposure Procedures and Equipment Authorization		
3	RF Exposure Guidance v06	Policies for Mobile and Portable Devices		
4	OET Bulletin 65	Evaluating Compliance with FCC Guidelines for Human		
4	Edition 97-01	Exposure to Radiofrequency Electromagnetic Fields		

1.3. Laboratory Facilities

FCC-Registration No.: 406086

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Sep. 30th, 2023.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Sep. 30th, 2023.

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.4. Laboratory Location

Company Name:	CCIC Southern Testing Co., Ltd.
Address:	Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan
Address.	District, Shenzhen, Guangdong, China



2. Technical Requirements Specification in CFR Title 47 Part 2.1091

2.1. Evaluation method

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Averaging Time (minutes)		
	(i) Limits for Occupational/Controlled Exposure					
0.3-3.0	614	1.63	*(100)	< 6		
3.0-30	1824/f	4.89/f	*(900/f ²)	< 6		
30-300	61.4	0.163	1.0	< 6		
300-1500	/	/	f/300	< 6		
1500-100,000	/	/	5	< 6		
(ii) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*(100)	< 30		
1.34-30	824/f	2.19/f	*(180/f ²)	< 30		
30-300	27.5	0.073	0.2	< 30		
300-1500	/	/	f/1500	< 30		
1500-100,000	/	/	1.0	< 30		
Note: f = frequency in MHz. * = Plane-wave equivalent power density.						

2.2. Predication of MPE limit at a given distance

Refer to formulas on page 19 of OET Bulletin 65, Edition 97-01.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units, e.g., cm)



2.3. Evaluation Results

Worst-Case mode Conducted Output Power Results for WLAN

Operation	Frequency	Maximum Output power	Max Tune up power	Max Tune up power
Mode	(MHz)	(dBm)	(dBm)	(mW)
WIFI-ANT1	2412	11.63	11±1	15.85
WIFI-ANT2	2412	11.56	11±1	15.85

Calculation results: Worst-Case mode

Operation	Antenna Gain	Antenna Gain	Distance	Result	Power Density
Mode	(dBi)	(numeric)	(cm)	(mW/cm2)	(mW/cm2)
WIFI-ANT1	1.24	1.33	20	0.004	1.00
WIFI-ANT2	1.92	1.56	20	0.005	1.00

2.4. Conclusion

According to the KDB 447498 D01 General RF Exposure Guidance v06 section 7.2 determine the device is exclusion from SAR test.

** END OF REPORT **