

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3. Result

Mode	Frequency (MHz)	Prediction distance (cm)	Max output power	MPE (mW/cm ²)	Limit (mW/cm ²)	SAR Test Exclusion
			dBm	dBm		
BT EDR	2402	20	6.054	0.00802	1	Yes
BT LE	2402	20	3.429	0.00438	1	Yes
2.4G WiFi	2412	20	16.026	0.07968	1	Yes
5G WIFI	5200	20	15.572	0.07177	1	Yes
5G WIFI	5745	20	15.426	0.06940	1	Yes

Maximum Simultaneous transmission MPE Ratios for BT+WIFI+WWAN:

Max MPE ratio _{BT} /Limit	Max MPE ratio _{WIFI} /Limit	ΣMPE ratios	Limit	Result
0.00802	0.07968	0.0877	1	PASS

BT&WIFI Antenna Gain: 0dBi, 1.0(numeric)

In summary, SAR evaluation is not required.