



Test Mode: Traffic mode


PCS1900 (EGPRS 1 link)



Lowest channel




Middle channel




Highest channel

Test Mode: Traffic mode


WCDMA Band V (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Test Mode: Traffic mode


WCDMA Band II (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Test Mode: Traffic mode


WCDMA Band IV (RMC 12.2Kbps link)



Lowest channel



Middle channel




Highest channel


Band Edge:

Test Mode: Traffic mode

GSM850 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode

GSM850 (EGPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode

PCS1900 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode

PCS1900 (EGPRS 1 link)



Lowest channel




Highest channel

Test Mode: Traffic mode

WCDMA Band V (RMC 12.2Kbps link)




Lowest channel



Highest channel

Test Mode: Traffic mode

WCDMA Band II (RMC 12.2Kbps link)




Lowest channel




Highest channel

Test Mode: Traffic mode

WCDMA Band IV (RMC 12.2Kbps link)






Lowest channel



Highest channel

4.8 ERP, EIRP Measurement

Test Requirement:	FCC part22.913(a) and FCC part24.232(b) , Part 27.54(h) RSS-132(5.5), RSS-133 (6.5), RSS-139 (6.6)
Test Method:	FCC part2.1046
Limit:	GSM850, WCDMA Band V: 7W PCS1900, WCDMA Band II: 2W WCDMA Band IV: 1W
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 

Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated. 3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$ 4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GPRS 1 link)	Lowest	H	V	26.81	38.45	Pass
			H	25.06		
		E1	V	27.08		
			H	25.57		
		E2	V	27.40		
			H	26.13		
	Middle	H	V	28.05	38.45	Pass
			H	25.42		
		E1	V	27.11		
			H	24.96		
		E2	V	26.58		
			H	25.32		
	Highest	H	V	27.30	38.45	Pass
			H	25.92		
		E1	V	27.00		
			H	24.82		
		E2	V	27.99		
			H	25.18		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (EGPRS 1 link)	Lowest	H	V	25.08	38.45	Pass
			H	23.19		
		E1	V	25.71		
			H	23.77		
		E2	V	25.50		
			H	24.05		
	Middle	H	V	25.51	38.45	Pass
			H	23.34		
		E1	V	25.42		
			H	23.64		
		E2	V	25.02		
			H	23.23		
	Highest	H	V	25.69	38.45	Pass
			H	23.86		
		E1	V	25.33		
			H	23.29		
		E2	V	25.94		
			H	23.50		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GPRS 1 link)	Lowest	H	V	29.73	33.01	Pass
			H	25.61		
		E1	V	29.70		
			H	26.63		
		E2	V	29.90		
			H	26.66		
	Middle	H	V	29.94	33.01	Pass
			H	27.01		
		E1	V	29.82		
			H	26.81		
		E2	V	29.19		
			H	27.50		
	Highest	H	V	29.81	33.01	Pass
			H	26.22		
		E1	V	29.14		
			H	26.25		
		E2	V	29.45		
			H	26.71		




EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (EGPRS 1 link)	Lowest	H	V	27.09	33.01	Pass
			H	23.88		
		E1	V	27.19		
			H	24.70		
		E2	V	27.52		
			H	24.29		
	Middle	H	V	27.57	33.01	Pass
			H	24.72		
		E1	V	27.82		
			H	24.76		
		E2	V	27.16		
			H	25.16		
	Highest	H	V	27.58	33.01	Pass
			H	24.23		
		E1	V	27.42		
			H	24.22		
		E2	V	26.90		
			H	24.90		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
WCDMA Band V	Lowest	H	V	20.60	38.45	Pass
			H	20.47		
		E1	V	20.11		
			H	20.62		
		E2	V	20.89		
			H	20.41		
	Middle	H	V	20.76	38.45	Pass
			H	20.59		
		E1	V	21.64		
			H	20.09		
		E2	V	21.03		
			H	20.39		
	Highest	H	V	21.06	38.45	Pass
			H	19.70		
		E1	V	20.87		
			H	20.35		
		E2	V	21.01		
			H	20.30		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band II	Lowest	H	V	21.54	33.01	Pass
			H	20.70		
		E1	V	21.23		
			H	20.26		
		E2	V	21.55		
			H	20.69		
	Middle	H	V	20.52	33.01	Pass
			H	19.94		
		E1	V	20.97		
			H	20.66		
		E2	V	21.14		
			H	20.03		
	Highest	H	V	21.17	33.01	Pass
			H	20.07		
		E1	V	20.84		
			H	20.22		
		E2	V	20.94		
			H	19.66		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band IV	Lowest	H	V	23.49	33.01	Pass
			H	22.13		
		E1	V	21.83		
			H	21.91		
		E2	V	22.01		
			H	22.51		
	Middle	H	V	22.05	33.01	Pass
			H	21.99		
		E1	V	21.87		
			H	21.81		
		E2	V	21.30		
			H	21.16		
	Highest	H	V	21.96	33.01	Pass
			H	21.26		
		E1	V	21.94		
			H	21.58		
		E2	V	21.56		
			H	22.62		

4.9 Field strength of spurious radiation measurement

Test Requirement:	FCC part22.917(a) and FCC part24.238(a), Part 27.54(h) RSS-132(5.5), RSS-133 (6.5), RSS-139 (6.6)
Test Method:	FCC part2.1053
Limit:	-13dBm
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 

Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

Test mode:	GPRS850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.22	V	-44.28	-13.00	Pass
2509.70	V	-42.24		
3346.39	V	-39.46		
4182.74	V	-38.69		
5019.78	V	-37.73		
1672.89	H	-45.39	-13.00	Pass
2509.93	H	-43.64		
3346.11	H	-39.84		
4182.99	H	-38.29		
5019.43	H	-36.16		
Test mode:	EGPRS850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.34	V	-44.27	-13.00	Pass
2545.81	V	-41.40		
3395.27	V	-39.36		
4243.88	V	-37.83		
5092.90	V	-37.44		
1697.61	H	-45.02	-13.00	Pass
2546.29	H	-43.23		
3394.93	H	-41.53		
4244.11	H	-39.34		
5092.55	H	-38.90		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The above table only shows the worst case channel of each mode.
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	GPRS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3759.69	V	-37.29	-13.00	Pass
5639.67	V	-34.48		
7520.29	V	-33.59		
9399.81	V	-31.15		
11279.64	V	-29.75		
3760.07	H	-38.29	-13.00	Pass
5639.96	H	-35.41		
7519.93	H	-33.72		
9400.03	H	-31.20		
11280.02	H	-28.77		
Test mode:	EGPRS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.48	V	-37.27	-13.00	Pass
5729.09	V	-35.27		
7639.49	V	-35.02		
9548.89	V	-30.35		
11458.45	V	-30.61		
3819.63	H	-36.45	-13.00	Pass
5729.42	H	-34.87		
7639.06	H	-34.86		
9548.65	H	-31.21		
11458.63	H	-29.57		

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. The above table only shows the worst case channel of each mode.
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band V		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1652.94	V	-43.92	-13.00	Pass
2478.64	V	-42.76		
3305.48	V	-40.01		
4131.76	V	-40.13		
4958.38	V	-36.92		
1652.48	H	-45.07	-13.00	Pass
2479.14	H	-42.72		
3305.49	H	-41.20		
4131.68	H	-39.59		
4958.13	H	-38.73		
Test mode:	WCDMA Band V		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.07	V	-45.36	-13.00	Pass
2509.31	V	-41.80		
3345.67	V	-39.84		
4182.01	V	-39.85		
5018.20	V	-37.33		
1672.79	H	-44.95	-13.00	Pass
2508.87	H	-43.38		
3345.80	H	-40.76		
4181.81	H	-39.69		
5018.52	H	-38.92		
Test mode:	WCDMA Band V		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1692.69	V	-43.86	-13.00	Pass
2539.70	V	-41.51		
3386.10	V	-41.42		
4232.94	V	-38.59		
5079.40	V	-37.31		
1693.27	H	-43.58	-13.00	Pass
2539.90	H	-42.52		
3385.91	H	-40.06		
4232.63	H	-38.78		
5079.75	H	-39.27		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band II		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3704.80	V	-37.89	-13.00	Pass
5557.43	V	-37.13		
7409.43	V	-34.66		
9262.02	V	-31.74		
11113.84	V	-29.57		
3704.74	H	-38.92	-13.00	Pass
5556.84	H	-36.30		
7409.57	H	-34.50		
9262.17	H	-31.87		
11114.14	H	-30.86		
Test mode:	WCDMA Band II		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3759.60	V	-38.19	-13.00	Pass
5639.85	V	-35.29		
7520.34	V	-34.95		
9399.58	V	-32.04		
11279.45	V	-30.91		
3759.90	H	-39.16	-13.00	Pass
5639.67	H	-36.31		
7519.72	H	-34.63		
9399.66	H	-32.18		
11280.15	H	-29.65		
Test mode:	WCDMA Band II		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3815.43	V	-38.16	-13.00	Pass
5722.90	V	-36.80		
7629.83	V	-34.58		
9538.19	V	-32.64		
11445.90	V	-29.47		
3815.11	H	-39.46	-13.00	Pass
5722.88	H	-35.84		
7629.73	H	-34.58		
9538.02	H	-32.12		
11445.43	H	-28.47		

Remark:


1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band IV		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3424.75	V	-39.18	-13.00	Pass
5137.42	V	-36.09		
10274.00	V	-32.86		
15411.27	V	-29.28		
30823.21	V	--		
3424.92	H	-38.82	-13.00	Pass
5137.28	H	-37.29		
10274.45	H	-31.42		
15411.56	H	-27.91		
30822.83	H	--		
Test mode:	WCDMA Band IV		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3479.94	V	-40.27	-13.00	Pass
5219.83	V	-36.03		
10439.81	V	-30.79		
15660.11	V	-27.67		
31319.93	V	--		
3479.80	H	-38.06	-13.00	Pass
5219.70	H	-35.46		
10439.77	H	-32.04		
15659.82	H	-27.56		
31319.88	H	--		
Test mode:	WCDMA Band IV		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3505.12	V	-39.11	-13.00	Pass
5257.62	V	-35.48		
10515.35	V	-30.61		
15773.57	V	-27.96		
31546.77	V	--		
3504.87	H	-39.49	-13.00	Pass
5257.53	H	-36.43		
10515.61	H	-30.93		
15773.49	H	-27.42		
31546.65	H	--		

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

4.10 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b), RSS-132(5.3), RSS-133 (6.3), RSS-139 (6.4)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to –20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass


Measurement Data

Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	15	0.0179	2.5	Pass
	-10	3	0.0036		
	0	6	0.0072		
	10	12	0.0143		
	20	20	0.0239		
	30	-17	-0.0203		
	40	9	0.0108		
	50	2	0.0024		
	60	8	0.0096		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	16	0.0191	2.5	Pass
	-10	7	0.0084		
	0	2	0.0024		
	10	11	0.0131		
	20	24	0.0287		
	30	-22	-0.0263		
	40	10	0.0120		
	50	2	0.0024		
	60	9	0.0108		

Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.8	-20	13	0.0069	2.5	Pass
	-10	10	0.0053		
	0	4	0.0021		
	10	13	0.0069		
	20	18	0.0096		
	30	-20	-0.0106		
	40	6	0.0032		
	50	-1	-0.0005		
	60	6	0.0032		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
3.8	-20	12	0.0064	2.5	Pass
	-10	4	0.0021		
	0	6	0.0032		
	10	11	0.0059		
	20	21	0.0112		
	30	-19	-0.0101		
	40	9	0.0048		
	50	3	0.0016		
	60	5	0.0027		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	10	0.0120	2.5	Pass
	-10	6	0.0072		
	0	3	0.0036		
	10	14	0.0167		
	20	22	0.0263		
	30	-22	-0.0263		
	40	4	0.0048		
	50	5	0.0060		
	60	8	0.0096		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	10	0.0053	2.5	Pass
	-10	4	0.0021		
	0	2	0.0011		
	10	14	0.0074		
	20	21	0.0112		
	30	-22	-0.0117		
	40	11	0.0059		
	50	0	0.0000		
	60	4	0.0021		
Reference Frequency: WCDMA Band IV Middle channel=1450 channel=1740.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	14	0.0080	2.5	Pass
	-10	7	0.0040		
	0	2	0.0011		
	10	15	0.0086		
	20	24	0.0138		
	30	-20	-0.0115		
	40	11	0.0063		
	50	1	0.0006		
	60	9	0.0052		

4.11 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2), RSS-132(5.3), RSS-133 (6.3), RSS-139 (6.4)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	 Temperature Chamber Spectrum analyzer Att. EUT Variable Power Supply Note : Measurement setup for testing on Antenna connector
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass



Measurement Data

Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	8	0.0046	2.5	Pass
	24	9	0.0052		
	9	15	0.0086		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	-6	-0.0034	2.5	Pass
	24	-4	-0.0023		
	9	10	0.0057		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	-19	-0.0109	2.5	Pass
	24	-6	-0.0034		
	9	-15	-0.0086		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	-13	-0.0075	2.5	Pass
	24	-4	-0.0023		
	9	-8	-0.0046		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	-7	-0.0040	2.5	Pass
	24	0	0.0000		
	9	9	0.0052		
Reference Frequency: WCDMA Band II Middle channel=940 channel=1880.0MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	-13	-0.0075	2.5	Pass
	24	-8	-0.0046		
	9	-15	-0.0086		
Reference Frequency: WCDMA Band IV Middle channel=1450 channel=1740.0MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	24	5	0.0029	2.5	Pass
	24	-2	-0.0011		
	9	7	0.0040		

5 Test Setup Photo

Radiated Emission



-----END OF REPORT-----