



# **FCC TEST REPORT**

**FCC ID: SY4-B01011**

**On Behalf of**

**Shanghai Huace Navigation Technology LTD.**

**Handheld GNSS Data Collector**

**Model No.: LT50**

Prepared for : Shanghai Huace Navigation Technology LTD.  
Address : Building C, 599 Gaojing Road, Qingpu District, Shanghai, China


Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an  
District, 518103, Shenzhen, Guangdong, China

Report Number : T1880174 02  
Date of Receipt : January 25, 2018  
Date of Test : January 25, 2018-June 28, 2018  
Date of Report : June 28, 2018  
Version Number : REV0

# Contents

	Page
<b>1 TEST SUMMARY .....</b>	<b>5</b>
<b>2 GENERAL INFORMATION .....</b>	<b>6</b>
2.1 GENERAL DESCRIPTION OF EUT .....	6
2.2 TEST MODE .....	8
2.3 TEST FACILITY .....	8
2.4 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	8
2.5 DESCRIPTION OF SUPPORT UNITS .....	8
2.6 ADDITIONAL INSTRUCTIONS .....	9
<b>3 TEST INSTRUMENTS LIST .....</b>	<b>10</b>
<b>4 TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>11</b>
4.1 ANTENNA REQUIREMENT .....	11
4.2 CONDUCTED EMISSIONS .....	12
4.3 CONDUCTED PEAK OUTPUT POWER .....	15
4.4 20dB EMISSION BANDWIDTH .....	16
4.5 CARRIER FREQUENCIES SEPARATION .....	20
4.6 HOPPING CHANNEL NUMBER .....	24
4.7 DWELL TIME .....	24
4.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....	28
4.9 BAND EDGE .....	29
4.9.1 <i>Conducted Emission Method</i> .....	29
4.9.2 <i>Radiated Emission Method</i> .....	33
4.10 SPURIOUS EMISSION .....	35
4.10.1 <i>Conducted Emission Method</i> .....	35
4.10.2 <i>Radiated Emission Method</i> .....	37
<b>5 TEST SETUP PHOTO .....</b>	<b>44</b>
<b>6 EUT CONSTRUCTIONAL DETAILS .....</b>	<b>46</b>

## TEST REPORT DECLARATION

Applicant : Shanghai Huace Navigation Technology LTD.  
 Address : Building C, 599 Gaojing Road, Qingpu District, Shanghai, China  
 Manufacturer : Shanghai Huace Navigation Technology LTD.  
 Address : Building C, 599 Gaojing Road, Qingpu District, Shanghai, China  
 EUT Description : Handheld GNSS Data Collector  
 (A) Model No. : LT50  
 (B) Trademark : 


Measurement Standard Used:


**FCC CFR Title 47 Part 15 Subpart C Section 15.247**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Reak Yang  
 Project Engineer 

Approved by (name + signature).....: Simple Guan  
 Project Manager 

Date of issue.....: June 28, 2018

**Revision History**

Revision	Issue Date	Revisions	Revised By
00	June 28, 2018	Initial released Issue	Simple Guan

## 1 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

*Remark: Test according to ANSI C63.10:2013*

### Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 2 General Information

### 2.1 General Description of EUT

Product Name:	Handheld GNSS Data Collector
Model No.:	LT50
Test Model No:	LT50
Quantity of tested samples	1
Serial No.:	N/A
Tested Sample(s) ID:	N/A
Hardware Version:	A5503_MPCB_V4.0_0905
Software Version:	A5502_V1.01
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, Pi/4 QPSK, 8DPSK
Antenna Type:	PIFA Antenna
Antenna gain:	1dBi
Power supply:	DC 3.8V by battery or DC 5V from adapter input AC 120V, 60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

**2.2 Test mode**

Transmitting mode	Turn off the WiFi and keep the Bluetooth in continuously transmitting mode
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

**2.3 Test Facility**

<p>Shenzhen Alpha Product Testing Co., Ltd  Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen,  Guangdong, China</p> <p>June 21, 2018 File on Federal Communication Commission  Registration Number: 293961</p> <p>July 25, 2017 Certificated by IC  Registration Number: 12135A</p>
---

**2.4 Other Information Requested by the Customer**

None.
-------

**2.5 Description of Support Units**

Accessories1	:	AC Adapter
Manufacturer	:	EDAC Power Electronics Co., Ltd.
Model	:	EA1012AVRU-050
Input	:	100-240V~, 50/60Hz, 1.0A
Output	:	DC 5V, 2.4A




## 2.6 Additional instructions

Software (Used for test) from client

Mode	Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

Power level setup in software			
Test Software Name	QRCT—External Licensed		
Test Software Version	2.5.8		
Support Units (Software installation media)	Description	Manufacturer	Model
	Laptop	Apple	A1278
Mode	Channel	Frequency (MHz)	Soft Set
GFSK, Pi/4 QPSK, 8DPSK	CH1	2402	TX LEVEL is built-in set parameters and cannot be changed and selected.
	CH40	2441	
	CH79	2480	

### Run Software



### 3 Test Instruments list

#### Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	2017.09.22	1Year
Spectrum analyzer	Agilent	E4407B	MY46185649	2017.09.22	1Year
Receiver	R&S	ESCI	1166.5950K03-1011	2017.09.22	1Year
Receiver	R&S	ESCI	101202	2017.09.22	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2016.09.30	2Year
Horn Antenna	EMCO	3115	640201028-06	2016.09.30	2Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2016.09.30	2Year
Cable	Resenberger	N/A	No.1	2017.09.22	1Year
Cable	SCHWARZECK	N/A	No.2	2017.09.22	1Year
Cable	SCHWARZECK	N/A	No.3	2017.09.22	1Year
Pre-amplifier	Schwarzbeck	BBV9743	9743-019	2017.09.22	1Year
Pre-amplifier	R&S	AFS33-18002650-30-8P-44	SEL0080	2017.09.22	1Year
Base station	Agilent	E5515C	GB44300243	2017.09.22	1 Year
Temperature controller	Terchy	MHQ	120	2017.09.22	1Year
Power divider	Anritsu	K240C	020346	2017.09.22	1 Year
Signal Generator	HP	83732B	VS3449051	2017.09.22	1 Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2017.09.22	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2017.09.22	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2017.09.22	1 Year
18-40 Horn Antenna	18-40G antenna	Sas-574	571	2018-3-15	2021-03-18
Power Meter	Anritsu	ML2487A	6K00001491	2017.09.22	1 Year

## 4 Test results and Measurement Data

### 4.1 Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
<p><b>15.203 requirement:</b></p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p><b>15.247(c) (1)(i) requirement:</b></p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<p><b>E.U.T Antenna:</b></p> <p><i>The antenna is PIFA antenna, the best case gain of the antenna is 1dBi</i></p>	
 <p>The photograph shows the internal components of a smartphone, including the main board, battery, and back cover. A ruler is used for scale. A red arrow points to a small component on the back cover labeled 'BT Antenna'.</p>	

## 4.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Test Frequency Range:	150KHz to 30MHz														
Class / Severity:	Class B														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	<p><i>Remark:</i>  E.U.T: Equipment Under Test  LISN: Line Impedance Stabilization Network  Test table height=0.8m</p>														
Test procedure:	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>														
Test Instruments:	Refer to section 6.0 for details														
Test mode:	Refer to section 5.2 for details														
Test results:	Pass														

### Measurement data:

Line:


Conducted Emission Measurement

File :LT50 2#

Data :#8

Date: 2018-1-27

Time: 9:00:19



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	44.27	9.73	54.00	66.00	-12.00	QP	
2		0.1500	29.68	9.73	39.41	56.00	-16.59	AVG	
3	*	0.2490	41.67	9.76	51.43	61.79	-10.36	peak	
4		1.1429	34.15	9.84	43.99	56.00	-12.01	peak	
5		2.3069	24.87	9.96	34.83	56.00	-21.17	peak	
6		3.7740	24.89	10.10	34.99	56.00	-21.01	peak	
7		9.9120	22.48	10.35	32.83	60.00	-27.17	peak	

\*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:


Conducted Emission Measurement

File :LT50 2#

Data :#7

Date: 2018-1-27

Time: 8:55:04



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1560	43.37	9.73	53.10	65.67	-12.57	QP	
2		0.1560	30.84	9.73	40.57	55.67	-15.10	AVG	
3		0.2250	39.92	9.75	49.67	62.63	-12.96	QP	
4		0.2250	24.21	9.75	33.96	52.63	-18.67	AVG	
5	*	0.3060	41.12	9.76	50.88	60.08	-9.20	peak	
6		1.1489	33.85	9.84	43.69	56.00	-12.31	peak	
7		5.8500	25.27	10.24	35.51	60.00	-24.49	peak	
8		10.6830	20.04	10.36	30.40	60.00	-29.60	peak	
9		18.4680	18.53	10.48	29.01	60.00	-30.99	peak	


\*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss


### 4.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	30dBm(for GFSK),20.97dBm(for EDR)
Test setup:	 <p>The diagram illustrates the test setup. A Power Meter is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### Measurement Data

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	1.56	30.00	Pass
	Middle	1.78		
	Highest	0.32		
Pi/4QPSK	Lowest	0.97	20.97	Pass
	Middle	1.44		
	Highest	-0.27		
8DPSK	Lowest	1.21	20.97	Pass
	Middle	1.67		
	Highest	0.24		

#### 4.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


#### Measurement Data

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.9319	Pass
	Middle	0.9337	
	Highest	0.9352	
Pi/4QPSK	Lowest	1.260	Pass
	Middle	1.259	
	Highest	1.262	
8DPSK	Lowest	1.225	Pass
	Middle	1.223	
	Highest	1.223	




Test plot as follows:


Test mode: GFSK mode



Lowest channel




Middle channel




Highest channel


Test mode: Pi/4QPSK mode



Lowest channel




Middle channel




Highest channel


Test mode: 8DPSK mode



Lowest channel




Middle channel



Highest channel

#### 4.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=20KHz, VBW=62KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 <p>The diagram shows a Spectrum Analyzer and an E.U.T. connected by a red cable. They are positioned on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### Measurement Data

Mode	Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
GFSK	Lowest	1008	623	Pass
	Middle	1000	623	Pass
	Highest	1014	623	Pass
Pi/4QPSK	Lowest	1006	841	Pass
	Middle	1000	841	Pass
	Highest	1002	841	Pass
8DSK	Lowest	1000	817	Pass
	Middle	1018	817	Pass
	Highest	1012	817	Pass

Note: According to section 7.4

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	935.2	623
Pi/4QPSK	1262.00	841
8DSK	1225.00	817

Test plot as follows:


Modulation mode:	GFSK
------------------	------



Lowest channel




Middle channel




Highest channel


Test mode: Pi/4QPSK mode



Lowest channel




Middle channel




Highest channel


Test mode: 8DPSK mode



Lowest channel




Middle channel




Highest channel

### 4.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an Equipment Under Test (E.U.T.). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data:


Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
Pi/4QPSK	79	15	Pass
8DPSK	79	15	Pass



### 4.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second



Test setup:	 <p>The diagram shows a Spectrum Analyzer on the left and an E.U.T. on the right, connected by a red cable. They are placed on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement Data

Mode	Frequency (MHz)	Burst Type	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	2441	DH1	0.347	111.04	400	PASS
		DH3	1.617	258.72		
		DH5	2.862	305.28		
π/4-DQPSK	2441	DH1	0.373	119.36	400	PASS
		DH3	1.643	262.88		
		DH5	2.879	307.09		
8DPSK	2441	DH1	0.381	121.92	400	PASS
		DH3	1.634	261.44		
		DH5	2.896	308.91		

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2402MHz/2441MHz/2480MHz as blow

DH1 time slot= Pulse time (ms)\*(1600/ (2\*79))\*31.6

DH3 time slot= Pulse time (ms)\*(1600/ (4\*79))\*31.6



DH5 time slot= Pulse time (ms)\*(1600/ (6\*79))\*31.6

Test plot as follows:

Dwell time



GFSK

$\pi/4$ -DQPSK





Channel 39 / 2441 MHz - DH1

Channel 39 / 2441 MHz - 2DH1



Channel 39 / 2441 MHz - DH3

Channel 39 / 2441 MHz - 2DH3




Channel 39 / 2441 MHz - DH5


Channel 39 / 2441 MHz - 2DH5

Dwell time


8DPSK



Channel 39 / 2441 MHz - 3DH1



2 Channel 39 / 2441 MHz - 3DH3



Channel 39 / 2441 MHz - 3DH5

## 4.8 Pseudorandom Frequency Hopping Sequence

**Test Requirement:**

**FCC Part15 C Section 15.247 (a)(1) requirement:**


*Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.*

*Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.*

### EUT Pseudorandom Frequency Hopping Sequence


*The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.*

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



#### Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:




*Each frequency used equally on the average by each transmitter.*

*The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.*

## 4.9 Band Edge


### 4.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Test plot as follows:

GFSK Mode:

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel




No-hopping mode




Hopping mode

Pi/4QPSK Mode:

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel




No-hopping mode




Hopping mode

8DPSK Mode:

Test channel: Lowest channel




No-hopping mode




Hopping mode

Test channel: Highest channel




No-hopping mode



Hopping mode



#### 4.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All restriction band have been tested, and 2.31GHz to 2.5GHz band is the worse case				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

**Remark:**

1. During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.

Test channel:	Lowest
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	45.69	27.59	5.38	30.18	48.48	74.00	-25.52	Horizontal
2400.00	50.85	27.58	5.39	30.18	53.64	74.00	-20.36	Horizontal
2390.00	46.36	27.59	5.38	30.18	49.15	74.00	-24.85	Vertical
2400.00	50.49	27.58	5.39	30.18	53.28	74.00	-20.72	Vertical

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	36.05	27.59	5.38	30.18	38.84	54.00	-15.16	Horizontal
2400.00	36.71	27.58	5.39	30.18	39.50	54.00	-14.50	Horizontal
2390.00	36.07	27.59	5.38	30.18	38.86	54.00	-15.14	Vertical
2400.00	37.82	27.58	5.39	30.18	40.61	54.00	-13.39	Vertical

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.11	27.53	5.47	29.93	51.18	74.00	-22.82	Horizontal
2500.00	47.11	27.55	5.49	29.93	50.22	74.00	-23.78	Horizontal
2483.50	49.70	27.53	5.47	29.93	52.77	74.00	-21.23	Vertical
2500.00	48.39	27.55	5.49	29.93	51.50	74.00	-22.50	Vertical

**Average value:**


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.23	27.53	5.47	29.93	41.30	54.00	-12.70	Horizontal
2500.00	36.52	27.55	5.49	29.93	39.63	54.00	-14.37	Horizontal
2483.50	40.13	27.53	5.47	29.93	43.20	54.00	-10.80	Vertical
2500.00	36.28	27.55	5.49	29.93	39.39	54.00	-14.61	Vertical

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 4.10 Spurious Emission

### 4.10.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Remark:**

During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.

Test channel: Lowest channel




30MHz~25GHz

Test channel: Middle channel



30MHz~25GHz

Test channel: Highest channel



30MHz~25GHz

**4.10.2 Radiated Emission Method**

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
74.0		Peak Value			
Test setup:	Below 1GHz				
Test setup:	Above 1GHz				
Test Procedure:	<p>1. The EUT was placed on the top of a rotating table (0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the</p>				

	<p>highest radiation.</p> <ol style="list-style-type: none"> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


*Remark:*

1. *During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

Measurement data:

Vertical:

Radiated Emission Measurement




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Detector	Comment
1		39.9942	10.84	14.24	25.08	40.00	-14.92			peak	
2		49.0145	10.13	13.64	23.77	40.00	-16.23			peak	
3		78.6888	13.60	9.64	23.24	40.00	-16.76			peak	
4	*	136.9391	19.35	13.65	33.00	43.50	-10.50			peak	
5		193.7728	12.52	10.70	23.22	43.50	-20.28			peak	
6		308.9126	7.33	13.62	20.95	46.00	-25.05			peak	

Note: 1. \*:Maximum data; x:Over limit; !:over margin.  
 2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

Radiated Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		40.4172	7.52	14.18	21.70	40.00	-18.30			peak
2		50.0566	6.91	13.71	20.62	40.00	-19.38			peak
3		78.1389	12.53	9.84	22.37	40.00	-17.63			peak
4		142.3243	8.29	14.00	22.29	43.50	-21.21			peak
5		191.7450	8.15	10.82	18.97	43.50	-24.53			peak
6	*	316.5890	14.66	13.79	28.45	46.00	-17.55			peak

Note:1. \*:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.



■ Above 1GHz

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	38.24	31.78	8.60	32.09	46.53	74.00	-27.47	Vertical
7206.00	32.57	36.15	11.65	32.00	48.37	74.00	-25.63	Vertical
9608.00	31.98	37.95	14.14	31.62	52.45	74.00	-21.55	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	42.66	31.78	8.60	32.09	50.95	74.00	-23.05	Horizontal
7206.00	33.68	36.15	11.65	32.00	49.48	74.00	-24.52	Horizontal
9608.00	31.15	37.95	14.14	31.62	51.62	74.00	-22.38	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	26.99	31.78	8.60	32.09	35.28	54.00	-18.72	Vertical
7206.00	20.84	36.15	11.65	32.00	36.64	54.00	-17.36	Vertical
9608.00	20.45	37.95	14.14	31.62	40.92	54.00	-13.08	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	30.78	31.78	8.60	32.09	39.07	54.00	-14.93	Horizontal
7206.00	23.37	36.15	11.65	32.00	39.17	54.00	-14.83	Horizontal
9608.00	19.52	37.95	14.14	31.62	39.99	54.00	-14.01	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “\*”, means this data is too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Middle
---------------	--------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	37.44	31.85	8.67	32.12	45.84	74.00	-28.16	Vertical
7323.00	32.38	36.37	11.72	31.89	48.58	74.00	-25.42	Vertical
9764.00	31.57	38.35	14.25	31.62	52.55	74.00	-21.45	Vertical
12205.00	*					74.00		Vertical
14646.00	*					74.00		Vertical
4882.00	42.82	31.85	8.67	32.12	51.22	74.00	-22.78	Horizontal
7323.00	33.94	36.37	11.72	31.89	50.14	74.00	-23.86	Horizontal
9764.00	31.75	38.35	14.25	31.62	52.73	74.00	-21.27	Horizontal
12205.00	*					74.00		Horizontal
14646.00	*					74.00		Horizontal

**Average value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	26.27	31.85	8.67	32.12	34.67	54.00	-19.33	Vertical
7323.00	20.37	36.37	11.72	31.89	36.57	54.00	-17.43	Vertical
9764.00	20.29	38.35	14.25	31.62	41.27	54.00	-12.73	Vertical
12205.00	*					54.00		Vertical
14646.00	*					54.00		Vertical
4882.00	31.20	31.85	8.67	32.12	39.60	54.00	-14.40	Horizontal
7323.00	22.60	36.37	11.72	31.89	38.80	54.00	-15.20	Horizontal
9764.00	20.12	38.35	14.25	31.62	41.10	54.00	-12.90	Horizontal
12205.00	*					54.00		Horizontal
14646.00	*					54.00		Horizontal

**Remark:**

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *“\*”, means this data is too weak instrument of signal is unable to test.*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel:	Highest
---------------	---------

**Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	37.66	31.93	8.73	32.16	46.16	74.00	-27.84	Vertical
7440.00	32.59	36.59	11.79	31.78	49.19	74.00	-24.81	Vertical
9920.00	31.81	38.81	14.38	31.88	53.12	74.00	-20.88	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	42.28	31.93	8.73	32.16	50.78	74.00	-23.22	Horizontal
7440.00	33.67	36.59	11.79	31.78	50.27	74.00	-23.73	Horizontal
9920.00	31.96	38.81	14.38	31.88	53.27	74.00	-20.73	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

**Average value:**


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	27.14	31.93	8.73	32.16	35.64	54.00	-18.36	Vertical
7440.00	21.10	36.59	11.79	31.78	37.70	54.00	-16.30	Vertical
9920.00	20.24	38.81	14.38	31.88	41.55	54.00	-12.45	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	31.00	31.93	8.73	32.16	39.50	54.00	-14.50	Horizontal
7440.00	23.40	36.59	11.79	31.78	40.00	54.00	-14.00	Horizontal
9920.00	20.10	38.81	14.38	31.88	41.41	54.00	-12.59	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

**Remark:**

1.  $Final\ Level = Receiver\ Read\ level + Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 5 Test Setup Photo

Radiated Emission



Conducted Emission



## 6 EUT Constructional Details

Please refer to report T1880174 01.

-----End-----