

# TEST REPORT

OF

## FCC Part 15 Subpart C

FCC ID: SY5SVISMKFNA04

Equipment Under Test : Smart Key Fob  
Model Name : SVI-SMKFNA04  
Serial No. : N/A  
Applicant : Siemens Automotive Systems Corporation  
Manufacturer : Siemens Automotive Systems Corporation  
Date of Test(s) : 2006-10-11 ~ 2006-10-25  
Date of Issue : 2006-10-27

In the configuration tested, the EUT complied with the standards specified above.



The above test certificate is the accredited test results by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

**Tested By:**  **Date** **2006-10-27**

**Feel Jeong**

**Approved By**  **Date** **2006-10-27**

**Albert Lim**

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

# INDEX

<u>TABLE OF CONTENTS</u>	<b>Page</b>
<b>1. General Information -----</b>	<b>3</b>
<b>2. Field Strength of the Carrier -----</b>	<b>6</b>
<b>3. Spurious Emission-----</b>	<b>9</b>
<b>4. Bandwidth of Operation Frequency-----</b>	<b>13</b>
<b>5. Transmission Time-----</b>	<b>15</b>
<b>Appendix A. Photo of Field Strength &amp; Spurious Emission Test</b>	
<b>Appendix B. Photos of the EUT</b>	

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 1. General Information

### 1.1. Testing Laboratory

SGS Testing Korea Co., Ltd.  
 Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-Si, Gyeonggi-do, Korea 435-040  
[www.sgstesting.co.kr](http://www.sgstesting.co.kr)  
 Telephone : +82 +31 428 5700  
 FAX : +82 +31 427 2371

### 1.2. Details of Applicant

Applicant : Siemens Automotive Systems Corporation  
 Address : 403-2, Saeum-dong, Ichon-city, Kyungki-do, Korea 467-080  
 Contact Person : Sung Min Jang  
 Phone No. : 82-031-645-4864  
 Fax No. : 82-031-630-0891

### 1.3. Description of EUT

#### Remote Keyless Entry :

The RKE transmitter transmits at 315MHz for NA an FSK modulated data signal to the SRx. The RF system of SRx receives this encrypted RF signal. The SRx send the signal to corresponding the host Body Control Module through single wired K-line bus then the host module broadcasts the requested remote commands to the appropriate control modules in the vehicle through CAN-communication line. In general the following functions are provided:  
 -Lock the car, Unlock the car, Unlock the trunk of the car, Panic

<b>Kind of Product</b>	Smart Key Fob
<b>Model Name</b>	SVI-SMKFNA04
<b>Serial Number</b>	N/A
<b>Power Supply</b>	DC 3 V(Lithium)
<b>Frequency Range</b>	315 MHz
<b>Modulation Technique</b>	FSK
<b>Frequency Generation</b>	X-Tal
<b>Number of Channels</b>	1 CH
<b>Operating Conditions</b>	-20 °C ~ + 60 °C
<b>Antenna Type</b>	Integrated PCB Patten

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 1.4. Details of modification

-N/A

#### 1.5. Test Equipment List

EQUIPMENT	MANUFACTURER	MODEL	CAL DUE.
Spectrum Analyzer	Agilent	E4440A	May 2007
Test Receiver	Rohde & Schwarz	ESU26	Aug. 2007
Ultra-Broadband Antenna	Rohde & Schwarz	HL562	Oct. 2007
Horn Antenna	Schwarzbeck	BBHA9120A	Jul. 2007
Anechoic Chamber	SY Corporation	L x W x H 9.6 x 6.4 x 6.4	Jun. 2008

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD:FCC Part15, Subpart C		
Standard Section	Test Item	Result
15.231(b)	Field Strength of the Carrier, Spurious Emission	PASS
15.231(c)	Bandwidth of Operation frequency	PASS
15.231(a)	Transmission Time	PASS

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2. Field Strength of the Carrier

### 2.1. Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 40 GHz Emissions.




Figure 1 : Frequencies measured below 1 GHz configuration




Figure 2 : Frequencies measured above 1 GHz configuration

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 2.2. Limit

In addition to the provisions of Section 15.205, the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66 – 47.70	2,250	225
70 - 130	1,250	125
130 – 174	1,250 to 3,750 **	125 to 375 **
174 – 260	3,750	375
260 – 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

\*\* linear interpolations

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows : for the band 130-174 MHz, uV/m at 3 meters = 56.81818(F)-6136.3636; for the band 260-470 MHz, uV/m at 3 meters = 41.6667(F)-7083.333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

## 2.3. Test Procedures

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 meter away from the interference-receiving antenna.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

### Note :

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection and frequency above 1 GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2.4. Test Result

Ambient temperature: 23 °C      Relative humidity: 50 %

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	Ant. (dB/m)	Cable (dB)	Actual (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
315	56.5	Peak	H	11.39	2.06	69.95	75.62	5.67

**Remark:**

To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.

**Note:**

A Peak limit is 20 dB above the average limit.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*



### 3. Spurious Emission

#### 3.1. Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 40 GHz Emissions.




Figure 1 : Frequencies measured below 1 GHz configuration




Figure 2 : Frequencies measured above 1 GHz configuration

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

### 3.2. Limit

In addition to the provisions of Section 15.205, the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (micro volts/meter)	Field Strength of Spurious Emissions (micro volts/meter)
40.66 – 47.70	2,250	225
70 - 130	1,250	125
130 – 174	1,250 to 3,750 **	125 to 375 **
174 – 260	3,750	375
260 – 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

\*\* linear interpolations

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows : for the band 130-174 MHz, uV/m at 3 meters =  $56.81818(F)-6136.3636$ ; for the band 260-470 MHz, uV/m at 3 meters =  $41.6667(F)-7083.333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 3.3. Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 meter away from the interference-receiving antenna.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**Note :**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection and frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 3.4. Test Result

Ambient temperature: 23 °C      Relative humidity: 50 %

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical

Radiated Emissions			Ant	Correction Factors		Total	FCC Limit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF/CL (dB/m)/(dB)	Amp Gain (dB)	Actual (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)
630	25.7	Peak	H	17.50 / 2.93	-	46.13	55.62	9.49
945	23.5	Peak	H	20.78 / 3.61	-	47.89	55.62	7.73
Above 1000	Not Detected							

**Remark:**

To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.


**Note:**

A Peak limit is 20 dB above the average limit.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 4. Bandwidth of Operation Frequency

### 4.1. Test Setup



### 4.2. Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Limit of 20 dB bandwidth:  $315 \text{ MHz} * 0.0025 = 787.5 \text{ kHz}$

### 4.3. Test Procedure

Spectrum Analyzer setting:

RBW: 1 kHz

VBW: 1 kHz

Span: 500 kHz

Sweep Time: Auto


Detector Mode: Peak

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 4.4. Test Result

Ambient temperature: 21 °C      Relative humidity: 48 %


Carrier Frequency	Bandwidth of the emission (kHz)	Limit (kHz)	Remark
315	83	787.5	The point 20 dB down from the modulated carrier



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 5. Transmission Time

### 5.1. Test Setup



### 5.2. Limit

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

### 5.3. Test Procedure

Spectrum Analyzer setting:


RBW: 1 kHz  
VBW: 1 kHz  
Span: 0 Hz  
Sweep Time: 5 sec  
Detector Mode: Peak

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 5.4. Test Result

Ambient temperature: 21 °C      Relative humidity: 48 %

Carrier Frequency	Bandwidth of the emission (sec)	Limit (sec)	Remark
315	0.467	5	-



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



**Appendix A. Photo of Field Strength & Spurious Emission Test**

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*