



25#哑银PET+PET+3M(300LSE) 防水耐温大于100度 UL969标准

81*38

MIN. 1.6mm FONT HEIGHT

REPLACE WITH CORRECT
PRODUCTION DATE

			<p>CONFORMS TO UL STD. 1598 CERTIFIED TO CSA STD. C22.2 No. 250.0</p>
<p>Item#: S13CWPK/MM/BZ 120/277V, 50/60Hz, 1.1A, 125W 3000/3500/4000/5000/6500K 4000/8000/12000 Lumens FCC ID: SYW-S13CWPKMM IC: 20416-S13CWPKMM Made in Vietnam Patent: feit.com/patents 146-24-WW</p>	<p>THIS SIDE UP</p>	<p>Intertek 5014385</p>	<p>WALL MOUNT ONLY</p> <p>CAUTION RISK OF FIRE: MIN 90°C SUPPLY CONDUCTORS CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR. SUITABLE FOR WET LOCATIONS.</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p>