

RF EXPOSURE EVALUATION

EUT Specification

| | |
|-----------------------------------|---|
| EUT | OUTDOOR PLUG |
| Model Name | SYNC/WIFI, UNSSB001/WIFIBLE/ONESYNC-WT, UNSSB001/WIFIBLE/ONESYNC-XXX |
| Frequency band (Operating) | <input checked="" type="checkbox"/> 2.402GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz) |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____ |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | -0.6876 dBm (0.854mW) |
| Antenna gain | -3.49dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) |
|----------------------|------------------------------|------------------------------|------------------------------------|
| 300-1500 | -- | -- | F/1500 |
| 1500-100000 | -- | -- | 1 |

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in Mw

G= gain of antenna in linear scale

$\pi=3.1416$

R= distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

$$E = EIRP - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

$$EIRP = E - 104.8 + 20\log D = 94.57 - 104.8 + 20\log 3 = -0.6876 \text{ dBm}$$

| Max Output power (dB μ V/m) | Gain | Channel Frequency (MHz) | Max Output power (dBm) | Tolerance | Max Tune-U P power (mW) | Power density at 20cm (mW/cm ²) | Power density Limits (mW/cm ²) |
|---------------------------------|-------|-------------------------|------------------------|-----------|-------------------------|---|--|
| GFSK | | | | | | | |
| 94.57 | -3.49 | 2402 | -0.6876 | ± 0.5 | 0.958 | 0.00009 | 1 |