



# FCC TEST REPORT

FOR

Feit Electric Company

4 FTLED WRAP UTILITY LIGHTWITH MOTION SENSOR AND REMOTE

Test Model: WRAP/4C/840/IR/MM


Additional Model No.: Please refer to page 6

Prepared for : Feit Electric Company  
Address : 4901 Gregg Road Pico Rivera, CA90660,United States of America

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,  
Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : October 09, 2022  
Number of tested samples : 2  
Sample No. : A091222048-1, A091222048-2  
Sample number : Prototype  
Date of Test : October 09, 2022 ~ October 21, 2022  
Date of Report : October 22, 2022





FCC TEST REPORT

FCC CFR 47 PART 15 C (15.249)

Report Reference No. .... : LCSA091222048EA

Date of Issue..... : October 22, 2022

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Testing Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □

Applicant's Name..... : Feit Electric Company

Address..... : 4901 Gregg Road Pico Rivera, CA90660, United States of America

Test Specification

Standard..... : FCC CFR 47 PART 15 C(15.249) / ANSI C63.10: 2013

Test Report Form No..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : 4 FTLED WRAP UTILITY LIGHTWITH MOTION SENSOR AND REMOTE

Trade Mark..... : [HI-Light logo]

Test Model..... : WRAP/4C/840/IR/MM

Ratings..... : Input: AC 120V, 60Hz, 27W

Result ..... : Positive

Compiled by:

[Signature of Diamond Lu]

Diamond Lu/ Administrator

Supervised by:

[Signature of Cary Luo]


Cary Luo/ Technique principal

Approved by:

[Signature of Gavin Liang]

Gavin Liang/ Manager





### FCC -- TEST REPORT

<b>Test Report No. :</b>	<b>LCSA091222048EA</b>	<u>October 22, 2022</u> Date of issue
--------------------------	------------------------	--

<b>Test Model</b> .....	: WRAP/4C/840/IR/MM
<b>EUT</b> .....	: 4 FTLED WRAP UTILITY LIGHTWITH MOTION SENSOR AND REMOTE
<b>Applicant</b> .....	: <b>Feit Electric Company</b>
<b>Address</b> .....	: 4901 Gregg Road Pico Rivera, CA90660,United States of America
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /
<b>Manufacturer</b> .....	: <b>Feit Electric Company</b>
<b>Address</b> .....	: 4901 Gregg Road Pico Rivera, CA90660,United States of America
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /
<b>Factory</b> .....	: <b>Xiamen Hi-Light Lighting Co., Ltd</b>
<b>Address</b> .....	: NO.398 Jinyuan East Road, Jimei District, Xiamen, 361022, China
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.  
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.






### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	October 22, 2022	Initial Issue	---





# TABLE OF CONTENTS

- 1. GENERAL INFORMATION..... 6**
  - 1.1 Description of Device (EUT)..... 6
  - 1.2. Support Equipment List..... 7
  - 1.3. External I/O..... 7
  - 1.4. Description of Test Facility..... 7
  - 1.5. Statement of the measurement uncertainty..... 7
  - 1.6. Measurement Uncertainty..... 7
  - 1.7. Description of Test Modes..... 8
- 2. TEST METHODOLOGY ..... 9**
  - 2.1. EUT Configuration..... 9
  - 2.2. EUT Exercise..... 9
  - 2.3. General Test Procedures..... 9
- 3. CONNECTION DIAGRAM OF TEST SYSTEM..... 10**
  - 3.1. Justification..... 10
  - 3.2. EUT Exercise Software..... 10
  - 3.3. Special Accessories..... 10
  - 3.4. Block Diagram/Schematics..... 10
  - 3.5. Equipment Modifications..... 10
  - 3.6. Test Setup..... 10
- 4. SUMMARY OF TEST RESULTS..... 11**
- 5. ANTENNA REQUIREMENT ..... 12**
- 6. POWER LINE CONDUCTED EMISSIONS..... 13**
- 7. RADIATED EMISSION MEASUREMENT..... 16**
- 8. RESULTS FOR BAND EDGE TESTING..... 27**
- 9. 99% AND 20DB BANDWIDTH MEASUREMENT..... 33**
- 10. LIST OF MEASURING EQUIPMENT..... 35**
- 11. TEST SETUP PHOTOGRAPHS OF THE EUT..... 37**
- 12. EXTERIOR PHOTOGRAPHS OF THE EUT..... 37**
- 13. INTERIOR PHOTOGRAPHS OF THE EUT..... 37**





# 1. GENERAL INFORMATION


## 1.1 Description of Device (EUT)

EUT : 4 FTLED WRAP UTILITY LIGHTWITH MOTION SENSOR AND REMOTE  
Test Model : WRAP/4C/840/IR/MM  
Additional Model No. : HLLLEDWRAP-55W(Dm)-IR-MM, HLLLEDWRAP-27W(Dm)-IR-MM, WRAP/2C/840/IR/MM  
Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested  
Power Supply : Input: AC 120V, 60Hz, 27W  
Hardware Version : PCB-V3  
Software Version : V0.1

### 5.8G

Frequency Range : 5750MHz ~ 5870MHz  
Modulation Type : CW  
Antenna Description : integral antenna, 5.966dBi(Max.)





## 1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
---	---	---	---	---

## 1.3. External I/O

I/O Port Description	Quantity	Cable
---	---	---

## 1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	±3.10dB	(1)
	30MHz~200MHz	±2.96dB	(1)
	200MHz~1000MHz	±3.10dB	(1)
	1GHz~26.5GHz	±3.80dB	(1)
	26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	±1.63dB	(1)
Power disturbance	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.







### 1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be TX .

Pre-test AC conducted emission at charge from the mode and channel with the highest output power, recorded worst case.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worst case.

All test modes were tested, only the result of the worst case was recorded in the report.

Test mode	Frequency
Transmitting	5750MHz,5800MHz,5870MHz







## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10: 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.





### 3. CONNECTION DIAGRAM OF TEST SYSTEM

#### 3.1. Justification

The system was configured for testing in a continuous transmit condition.

#### 3.2. EUT Exercise Software

Press the corresponding button, and change the channel.

#### 3.3. Special Accessories

N/A

#### 3.4. Block Diagram/Schematics

Please refer to the related document


#### 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6. Test Setup

Please refer to the test setup photo.





### 4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C §15.249		
FCC Rules	Description Of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Power Line Conducted Emissions	Compliant
§15.205(a), §15.209(a), §15.249(a), §15.249(b), §15.249(d)	Radiated Emissions Measurement	Compliant
§15.249 (d)	Band Edges Measurement	Compliant
§2.1049, §15.215(c)	99% and 20 dB Bandwidth	Compliant

Remark:  
 N/A\* - Not Applicable for this device!!!





## 5. ANTENNA REQUIREMENT

### 5.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 5.2. Antenna Connected Construction

The EUT use integral antenna and maximum antenna gain is 5.966dBi, antenna cannot replacement, meets FCC Part §15.203 antenna requirement. Please see EUT photo for details.

### 5.3. Results

Compliance



## 6. POWER LINE CONDUCTED EMISSIONS


### 6.1. Standard Applicable

According to §15.207 (a): for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

\* Decreasing linearly with the logarithm of the frequency

### 6.2. Block Diagram of Test Setup




### 6.3. Test Results

**PASS.**

The test data please refer to following page.


Temperature	23.4°C	Humidity	53.3%
Test Engineer	Taylor Hu	Configurations	TX





### AC Conducted Emission @ AC 120V/60Hz


Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector
1		0.3256	29.60	19.63	49.23	59.56	-10.33	QP
2		0.3256	11.27	19.63	30.90	49.56	-18.66	AVG
3		0.5370	30.16	19.65	49.81	56.00	-6.19	QP
4		0.5370	12.38	19.65	32.03	46.00	-13.97	AVG
5		0.8745	28.89	19.64	48.53	56.00	-7.47	QP
6		0.8745	10.83	19.64	30.47	46.00	-15.53	AVG
7		1.0500	27.64	19.65	47.29	56.00	-8.71	QP
8		1.0500	8.71	19.65	28.36	46.00	-17.64	AVG
9	*	4.9696	31.07	19.70	50.77	56.00	-5.23	QP
10		4.9696	17.66	19.70	37.36	46.00	-8.64	AVG
11		7.5436	31.72	19.75	51.47	60.00	-8.53	QP
12		7.5436	17.84	19.75	37.59	50.00	-12.41	AVG







Neutral



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1		0.3526	23.75	19.63	43.38	58.90	-15.52	QP
2		0.3526	6.69	19.63	26.32	48.90	-22.58	AVG
3		0.5326	26.67	19.65	46.32	56.00	-9.68	QP
4		0.5371	9.89	19.65	29.54	46.00	-16.46	AVG
5		0.8476	26.24	19.64	45.88	56.00	-10.12	QP
6		0.8521	6.60	19.64	26.24	46.00	-19.76	AVG
7		1.0546	25.71	19.65	45.36	56.00	-10.64	QP
8		1.0546	6.89	19.65	26.54	46.00	-19.46	AVG
9	*	4.9876	31.55	19.80	51.35	56.00	-4.65	QP
10		4.9876	18.28	19.80	38.08	46.00	-7.92	AVG
11		7.0576	34.64	19.83	54.47	60.00	-5.53	QP
12		7.0576	20.91	19.83	40.74	50.00	-9.26	AVG

\*\*\*Note:

- 1). Pre-scan all modes and recorded the worst case results in this report.
- 2). Measurement = Reading + Correct, Margin = Measurement – Limit.  
Correct Factor= Lisn Factor+Cable Factor







## 7. RADIATED EMISSION MEASUREMENT

### 7.1. Standard Applicable

According to FCC § 15.249: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) and 15.249 limit in the table below has to be followed.

#### § 15.249(a)Limits:

Fundamental Frequency	Field Strength of fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### § 15.209Limits:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 7.2. Spectrum Analyzer and Receiver Setup

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 <sup>th</sup> carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average





Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

### 7.3. Test Procedure

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





#### 4) Sequence of testing above 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

##### Premeasurement:


- The antenna is moved spherical over the EUT in different polarizations of the antenna.

##### Final measurement:


- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.




### 7.4. Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Above 1GHz


Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

### 7.5 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.







### 7.6. Test Results of Radiated Emissions (9 KHz~30 MHz)

Temperature	23.8°C	Humidity	52.1%
Test Engineer	Taylor Hu	Configurations	TX

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

### 7.7. Test Results of Radiated Emissions (30 MHz – 1000 MHz)


Temperature	23.8°C	Humidity	52.1%
Test Engineer	Taylor Hu	Configurations	TX

**PASS.**


The test data please refer to following page.








Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	54.2609	34.95	-17.81	17.14	40.00	-22.86	QP
2	67.6751	41.93	-19.32	22.61	40.00	-17.39	QP
3	132.2205	33.61	-20.65	12.96	43.50	-30.54	QP
4	178.7584	37.97	-18.79	19.18	43.50	-24.32	QP
5	238.3101	37.61	-16.14	21.47	46.00	-24.53	QP
6	429.5228	31.12	-14.43	16.69	46.00	-29.31	QP





Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	67.6751	44.01	-19.32	24.69	40.00	-15.31	QP
2	87.1116	43.55	-19.17	24.38	40.00	-15.62	QP
3	131.7577	35.47	-20.63	14.84	43.50	-28.66	QP
4	182.5592	43.42	-18.34	25.08	43.50	-18.42	QP
5	279.0436	35.86	-15.41	20.45	46.00	-25.55	QP
6	607.7867	30.58	-10.64	19.94	46.00	-26.06	QP

Note:

- 1). Pre-scan all modes and recorded the worst case(TX-5870MHz) results in this report .
- 2). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3). Level = Reading + Factor, Margin = Level – Limit,  
Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor






### 7.8. Results for Radiated Emissions (1 – 26 GHz)

Temperature	23.5°C	Humidity	52.1%
Test Engineer	Taylor Hu	Configurations	TX


Field Strength of fundamental:

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5870.354	84.73	-3.56	81.17	114.00	-32.83	peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5870.333	77.77	-3.56	74.21	114.00	-39.79	peak

Note: 1. The peak is smaller than AVG limit, so you not need evaluate AVG.

2. Pre-scan all modes and recorded the worst case(TX-5870MHz) results in this report .





5870 MHz

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
11740	56.16	33.16	35.15	3.96	58.13	74.00	-15.87	Peak	Horizontal
11740	40.70	33.16	35.15	3.96	42.67	54.00	-11.33	Average	Horizontal
11740	51.70	33.16	35.15	3.96	53.67	74.00	-20.33	Peak	Vertical
11740	37.28	33.16	35.15	3.96	39.25	54.00	-14.75	Average	Vertical

Notes:

- 1). Measuring frequencies from 9 KHz - 10<sup>th</sup> harmonic, No emission found between lowest internal used/generated frequency to 30 MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz - 10<sup>th</sup> harmonic were made with an instrument using Peak detector mode.
- 3). 18~25 GHz at least have 20dB margin. No recording in the test report.
- 4). Measured Level = Reading Level + Factor, Margin = Measured Level – Limit,  
Factor = Antenna Factor + Cable Loss - Preamp Factor
- 5). Pre-scan all modes and recorded the worst case(TX-5870MHz) results in this report .




## 8. RESULTS FOR BAND EDGE TESTING

### 8.1. Standard Applicable

According to FCC §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### 8.2. Test Setup Layout



### 8.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

### 8.4. Test Procedures

#### 3) Sequence of testing 1 GHz to 18 GHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.







- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

**Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

**8.5. Measuring Instruments and Setting**


Temperature	23.5°C	Humidity	52.1%
Test Engineer	Taylor Hu	Configurations	TX

PASS


**Remark:**

1. *The other emission levels were very low against the limit.*
2. *The average measurement was not performed when the peak measured data under the limit of average detection.*
3. *Please refer to following test plots;*





Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.000	46.30	-3.35	42.95	74.00	-31.05	peak
2	5672.440	47.32	-3.37	43.95	74.00	-30.05	peak
3	5693.010	47.94	-3.40	44.54	74.00	-29.46	peak
4	5715.560	47.07	-3.42	43.65	74.00	-30.35	peak
5	5725.000	46.10	-3.42	42.68	74.00	-31.32	peak
6	5750.430	84.44	-3.45	80.99	114.00	-33.01	peak








Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.000	47.23	-3.35	43.88	74.00	-30.12	peak
2	5674.310	48.35	-3.38	44.97	74.00	-29.03	peak
3	5694.110	48.16	-3.40	44.76	74.00	-29.24	peak
4	5708.630	47.40	-3.41	43.99	74.00	-30.01	peak
5	5725.000	46.37	-3.42	42.95	74.00	-31.05	peak
6	5750.430	84.48	-3.45	81.03	114.00	-32.97	peak






Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5870.340	87.21	-3.56	83.65	114.00	-30.35	peak
2	5875.000	46.49	-3.57	42.92	74.00	-31.08	peak
3	5886.360	47.95	-3.58	44.37	74.00	-29.63	peak
4	5900.520	47.57	-3.59	43.98	74.00	-30.02	peak
5	5913.240	47.64	-3.61	44.03	74.00	-29.97	peak
6	5925.000	47.65	-3.62	44.03	74.00	-29.97	peak





Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5870.280	87.17	-3.56	83.61	114.00	-30.39	peak
2	5875.000	47.02	-3.57	43.45	74.00	-30.55	peak
3	5886.480	48.16	-3.58	44.58	74.00	-29.42	peak
4	5895.900	47.45	-3.59	43.86	74.00	-30.14	peak
5	5906.280	47.83	-3.60	44.23	74.00	-29.77	peak
6	5925.000	46.64	-3.62	43.02	74.00	-30.98	peak

Notes:

Measured Level = Reading Level + Factor, Margin = Measured Level – Limit,  
 Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor




## 9. 99% AND 20DB BANDWIDTH MEASUREMENT

### 9.1. Standard Applicable

§15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 9.2. Block Diagram of Test Setup



### 9.3. Test Procedure

Use the following spectrum analyzer settings:

Span = 4MHz

RBW = 1%~5% OBW

VBW  $\geq 3 \times$  RBW


Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).





### 9.4. Test Results

Temperature	23.8°C	Humidity	52.1%
Test Engineer	Taylor Hu		

Test Result of 20dB Bandwidth Measurement			
Test Frequency (MHz)	99% Bandwidth (kHz)	20dB Bandwidth (kHz)	Limit (kHz)
5800	81.355	82.54	Non-Specified
5750	89.067	83.91	Non-Specified
5870	100.63	82.44	Non-Specified

**Remark:**


1. Test results including cable loss;
2. Please refer following test plots;









### 20dB Bandwidth



### 5800MHz




### 5750MHz



### 5870MHz



**10. LIST OF MEASURING EQUIPMENT**

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2021-11-15	2022-11-14
2	DC Power Supply	Agilent	E3642A	N/A	2021-11-15	2022-11-14
3	Temperature & Humidity Chamber	GUANGZHOU GOGNWEN	GDS-100	70932	2022-10-06	2023-10-05
4	EMI Test Software	AUDIX	E3	/	N/A	N/A
5	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2022-06-16	2023-06-15
6	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2021-08-29	2024-08-28
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
10	EMI Test Receiver	R&S	ESR 7	101181	2022-06-16	2023-06-15
11	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2021-11-16	2022-11-15
12	Broadband Preamplifier	/	BP-01M18G	P190501	2022-06-16	2023-06-15
13	EMI Test Receiver	R&S	ESPI	101940	2022-08-17	2023-08-16
14	Artificial Mains	R&S	ENV216	101288	2022-06-16	2023-06-15
15	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2022-06-16	2023-06-15
16	EMI Test Software	Farad	EZ	/	N/A	N/A







### 11. TEST SETUP PHOTOGRAPHS OF THE EUT

Please refer to separated files for Test Setup Photos of the EUT.

### 12. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

### 13. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----

