

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a Wireless Stereo Headset. The EUT was powered by D.C. 3.7V from internal rechargeable battery or Charge by USB port via USB cable. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0.5dBi.

The nominal conducted output power specified: 0dBm +/-5dB.

The nominal radiated output power (e.i.r.p) specified: 0.5dBm (+/- 5dB)

Modulation Type:  $\pi/4$  -DQPSK.

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 92.3dB $\mu$ V/m at 3m in the frequency 2405.35MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -2.9dBm

which is within the production variation.

The minimum peak radiated emission for the EUT is 90.9dB $\mu$ V/m at 3m in the frequency 2477.35MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -4.3dBm

which is within the production variation.

The maximum conducted output power specified is 5dBm = 3.2mW

The source-based time-averaging conducted output power

=  $3.2 \cdot \text{Duty Cycle}$  mW < 3.2 mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt}(2.477)$  mW

= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Transmitter Duty Cycle Calculation

The Duty Cycle of this product is below 1.

---

This requirement is according to KDB 865664 D02

FCC ID: SZGCECHYA0083