



EnOcean GmbH Kolpingring 18a 82041 Oberhaching/Germany

Federal Communications Commission  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

USA

**Armin Anders**  
VP Product Marketing

Phone +49 89 6734 689 33  
Fax +49 89 6734 689 55  
Mobile +171 228 2856  
Armin.anders@enocean.com

Date: April 28, 2010  
Page: 1

To whom it may concern

For the products stated below,

**Applicant: EnOcean, GmbH**  
**Products: EnOcean PTM330C, PTM332C radio transmitters**  
**Models: PTM330C, PTM332C**  
**FCC ID: SZV-PTM33XC**

**and pursuant to DA 00-1407, EnOcean seeks Limited Modular Approval for the radio transmitter.**

1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with Part 15 limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation.

The modular transmitter has a ground plane and other grounding elements that are designed to provide adequate shielding; it was tested in a stand-alone configuration and the measurements confirmed the effectiveness of the ground plane shield. The modular transmitter complies with Part 15 emissions limits.

2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.

The modular transmitter has buffered modulation/data inputs.

3. The modular transmitter must have its own power supply regulation. This is intended to ensure that the module will comply with Part 15 requirements regardless of the design of the power supplying circuitry in the device into which the module is installed.

The modular transmitter has its own power supply regulation.



Date: February 25, 2010 Page: 2

4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). Any antenna used with the module must be approved with the module, either at the time of initial authorization or through a Class II permissive change. The "professional installation" provision of Section 15.203 may not be applied to modules.

The modular transmitters PTM330C/PTM332C have to be used with the approved whip antenna as described in the user manual of the module.

5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)).

The modular transmitter was tested in a stand-alone configuration and complies with Part 15 emission limits.

6. The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.

The modular transmitter is labeled with its own FCC ID number. Because the modular transmitter may be installed inside another device, rendering its own label invisible, the user manual instructs users of the modular transmitter that they must visibly display the necessary text on the outside of the finished product.

7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for





Date: February 25, 2010 Page: 3

operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.

The modular transmitter complies with all applicable operating requirements and adequate instructions are provided in the user manual explaining the requirements.

8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.

The modular transmitter complies with applicable RF exposure requirements.

Yours sincerely,



Armin Anders  
VP Product Marketing



Matthias Heiden  
VP Engineering