

Nemko-CCL, Inc.
1940 West Alexander Street
Salt Lake City, UT 84119
801-972-6146

Test Report

Certification

Test Of:
TCM 320U

FCC ID: SZV-TCM320U

Test Specifications:
FCC Part 15, Subpart C

Test Report Serial No: 224949-2.3

Applicant:
EnOcean GmbH
Kolpingring 18a
Oberhaching 82041
Germany

Dates of Test: November 19 and 26, 2012

Issue Date: January 3, 2013

Accredited Testing Laboratory By:



NVLAP Lab Code 100272-0

CERTIFICATION OF ENGINEERING REPORT

This report has been prepared by Nemko-CCL, Inc. to document compliance of the device described below with the certification requirements of FCC Part 15, Subpart C. This report may be reproduced in full. Partial reproduction of this report may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested.

- Applicant: EnOcean GmbH
- Manufacturer: EnOcean GmbH
- Brand Name: EnOcean
- Model Number: TCM 320U
- FCC ID: SZV-TCM320U


On this 3rd day of January 2013, I, individually, and for Nemko-CCL, Inc., certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge, and are made in good faith.

Although NVLAP has accredited the Nemko-CCL, Inc. EMC testing facilities, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Nemko-CCL, Inc.



Tested by: Norman P. Hansen
EMC Technician



Reviewed by: Thomas C. Jackson
General Manager

TABLE OF CONTENTS

	PAGE
<u>SECTION 1.0 CLIENT INFORMATION</u>	4
<u>SECTION 2.0 EQUIPMENT UNDER TEST (EUT)</u>	5
<u>SECTION 3.0 TEST SPECIFICATION, METHODS & PROCEDURES</u>	7
<u>SECTION 4.0 OPERATION OF EUT DURING TESTING</u>	11
<u>SECTION 5.0 SUMMARY OF TEST RESULTS</u>	12
<u>SECTION 6.0 MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS</u>	13
<u>APPENDIX 1 TEST PROCEDURES AND TEST EQUIPMENT</u>	21
<u>APPENDIX 2 PHOTOGRAPHS</u>	26

SECTION 1.0 CLIENT INFORMATION

1.1 Applicant:

Company Name: EnOcean GmbH
Kolpingring 18a
Oberhaching 82041
Germany

Contact Name: Armin Anders
Title: Director Product Marketing

1.2 Manufacturer:

Company Name: EnOcean GmbH
Kolpingring 18a
Oberhaching 82041
Germany

Contact Name: Armin Anders
Title: Director Product Marketing

SECTION 2.0 EQUIPMENT UNDER TEST (EUT)**2.1 Identification of EUT:**

Brand Name: EnOcean GmbH
 Model Number: TCM 320U
 Serial Number: None

2.2 Description of EUT:

The TCM 320U is a module with a 902.9 MHz transceiver. The module is designed for incorporation into other devices used in alarm and control applications operating at 902.9 MHz. 3.3 VDC is provided to the TCM 320U by the host system. The TCM 320U uses a wire whip antenna.

This report covers the transmitter circuitry of the device subject to FCC Part 15, Subpart C. The circuitry of the device, subject to FCC Part 15, Subpart B, was tested, found compliant, and is covered in Nemko-CCL, Inc. report #224949-1.

2.3 EUT and Support Equipment:

Brand Name Model Number	FCC ID or Compliance	Description	Name of Interface Ports / Interface Cables
BN: EnOcean MN: TCM 320U SN: None	SZV-TCM320U	Transmitter Module	See Section 2.4

2.4 Interface Ports on EUT:

Name of Ports	No. of Ports Fitted to EUT	Cable Descriptions/Length
Module to System Interface (normally soldered directly to host PCB assembly)	1	Power conductors/ extended to 16.5 cm for testing

2.5 Modification Incorporated/Special Accessories on EUT:

The following modifications were made to the EUT by the Client during testing to comply with the specification. This report is not complete without an accompanying signed attestation, that the product will have all of the documented modifications incorporated into the product when manufactured and placed on the market.

1. The maximum power setting in firmware was changed to 0 dB.

SECTION 3.0 TEST SPECIFICATION, METHODS & PROCEDURES

3.1 Test Specification:

Title: FCC PART 15, Subpart C (47 CFR 15)
Section 15.203
Section 15.231

Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

Purpose of Test: The tests were performed to demonstrate initial compliance.

3.2 Methods & Procedures:

3.2.1 §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

3.2.2 §15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-peak	Average
0.15 – 0.5*	66 to 56*	56 to 46*
0.5 – 5	56	46
5 - 30	60	50

*Decreases with the logarithm of the frequency.

3.2.2 §15.231

(a) The provisions of this section are restricted to periodic operation within the band 40.66-40.70 MHz and above 70 MHz. Except as Shown in paragraph (e) of this section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Radio control of toys is not permitted. Continuous transmissions, such as voice or video, and data transmissions are not permitted. The prohibition against data transmissions does not preclude the use of recognition codes. Those codes are used to identify the sensor that is activated or to identify the particular component as being part of the system. The following conditions shall be met to comply with the provisions for this periodic operation:

(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

(3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmission to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.

(4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

(b) In addition to the provisions of §15.205, the field strength of emission from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66 - 40.70	2,250	225
70 - 130	1,250	125
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3,750	375
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

** Linear interpolations

[Where F is the frequency in MHz, the formula for calculating the maximum permitted field strengths are as follows: for the band 130 – 174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260 – 470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provision in §15.35 for averaging pulsed emission and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(3) The limits on the field strength of the spurious emission in the above table are based on the fundamental frequency of the intentional radiator. Spurious emission shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

(c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

(d) For devices operation within the frequency band 40.66-40.70 MHz, the bandwidth of the emission shall be confined within the band edges and the frequency tolerance of the carrier

shall be $\pm 0.01\%$. This frequency tolerance shall be maintained for a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation on the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

(e) Intentional radiators may operate at a periodic rate exceeding that specified in paragraph (a) of this section and may be employed for any type of operation, including operation prohibited in paragraph (a) of this section, provided that intentional radiator complies with the provisions of paragraphs (b) through (d) of this section except the field strength table in paragraph (b) of this section is replaced by the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66 - 40.70	1,000	100
70 - 130	500	50
130 - 174	500 to 1,500 **	50 to 150 **
174 - 260	1,500	150
260 - 470	1,500 to 5,000 **	150 to 500 **
Above 470	5,000	500

** Linear interpolations

[Where F is the frequency in MHZ, the formula for calculating the maximum permitted field strengths are as follows: for the band 130 - 174 MHz, $\mu\text{V/m}$ at 3 meters = $22.72727(F) - 2454.545$; for the band 260 - 470 MHz, $\mu\text{V/m}$ at 3 meters = $16.6667(F) - 2833.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent periods between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

3.2.3 Test Procedure

The testing was performed according to the procedures in ANSI C63.4: 2003 and 47 CFR Part 15. Testing was performed at the Nemko-CCL, Inc. Wanship open area test site #2, located at 29145 Old Lincoln Highway, Wanship, UT. This site has been registered with the FCC, and was renewed February 15, 2012 (90504). This registration is valid for three years.

Nemko-CCL, Inc. is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Lab Code: 100272-0, which is effective until September 30, 2013.

SECTION 4.0 OPERATION OF EUT DURING TESTING

4.1 Operating Environment:

Power Supply: 3.3 VDC

4.2 Operating Modes:

The EUT was tested on three orthogonal axes while constantly transmitting. A new battery was used for radiated emission testing. 3.3 VDC was supplied to the EUT from a debug card for conducted emission testing.

4.3 EUT Exercise Software:

EnOcean test software was used to control the transmitter.

SECTION 5.0 SUMMARY OF TEST RESULTS**5.1 FCC Part 15, Subpart C****5.1.1 Summary of Tests:**

Part 15, Subpart C Reference	Test Performed	Frequency Range (MHz)	Result
15.203	Antenna Requirement	N/A	Complied
15.207	Conducted Emissions at the AC Mains	0.15 to 30	Complied
15.231 (a)	Periodic Operation	902.9	Complied
15.231 (b)	Radiated Emissions	0.15 to 9029	Complied
15.231 (c)	Bandwidth	902.9	Complied
15.231 (d)	Frequency Stability	40.66 to 40.70	Not Applicable
15.231 (e)	Radiated Emissions	30 to 3450	Not Applicable

5.2 Result

In the configuration tested, the EUT complied with the requirements of the specification.

SECTION 6.0 MEASUREMENTS, EXAMINATIONS AND DERIVED RESULTS**6.1 General Comments:**

This section contains the test results only. Details of the test methods used and a list of the test equipment used during the measurements can be found in Appendix 1 of this report.

6.2 Test Results:**6.2.1 §15.203**

The antenna is a wire soldered to the PCB and cannot be replaced by the user.

RESULT

The EUT complied with the requirements of this section.

6.2.2 §15.207

Frequency (MHz)	Line	Detector	Measured Level (dB μ V)	Class B Limit (dB μ V)	Margin (dB)
0.15	Hot Lead	Peak (Note 1)	51.0	56.0	-5.0
0.20	Hot Lead	Peak (Note 1)	49.0	53.5	-4.5
0.23	Hot Lead	Peak (Note 1)	47.1	52.4	-5.3
0.27	Hot Lead	Peak (Note 1)	46.6	51.2	-4.6
0.39	Hot Lead	Peak (Note 1)	41.0	48.1	-7.1
0.48	Hot Lead	Peak (Note 1)	39.4	46.3	-6.9
0.19	Neutral Lead	Peak (Note 1)	46.7	54.1	-7.4
0.23	Neutral Lead	Peak (Note 1)	41.7	52.5	-10.8
0.27	Neutral Lead	Peak (Note 1)	41.2	51.1	-9.9
0.34	Neutral Lead	Peak (Note 1)	38.4	49.1	-10.7
0.42	Neutral Lead	Peak (Note 1)	37.8	47.4	-9.6

Frequency (MHz)	Line	Detector	Measured Level (dBμV)	Class B Limit (dBμV)	Margin (dB)
0.49	Neutral Lead	Peak (Note 1)	35.3	46.1	-10.8


Note 1: The reference detector used for the measurements was Quasi-Peak or Peak and the data was compared to the average limit; therefore, the EUT was deemed to meet both the average and quasi-peak limits.


RESULT

The EUT complied with the specification limit by a margin of 4.5 dB.

6.2.3 §15.231 (a)

1. The EUT is not manually activated.
2. The TCM 320U is automatically activated when a module interface line is activated. The EUT firmware limits the transmission to 3 pulses in 100 ms no matter how often the interface line is activated. See the plots below.





3. The TCM 320U does not transmit at regular predetermined intervals.
4. The EUT is not used during an emergency that involves fire and safety of life.
5. The EUT does not require set up information transmissions by a professional installer.

RESULT

In the configuration tested, the EUT complied with the requirements of this section.

6.2.4 §15.231 (b) Radiated Emissions

The TCM 320U operates at 902.9 MHz, therefore; the field strength of the fundamental must be less than 12,500 $\mu\text{V/m}$ (81.9 $\text{dB}\mu\text{V/m}$) at 3 meters. The maximum permitted field strength of any unwanted emission must be 20 dB below the maximum allowable fundamental field strength (61.9 $\text{dB}\mu\text{V/m}$).


Emissions in the restricted bands of §15.205 must meet the limits specified in §15.209.


Measurement Data Fundamental and Harmonic Emissions:

The frequency range from 0.15 MHz to the tenth harmonic of the highest fundamental frequency was investigated to measure any radiated emissions.

Pulsed Emission Averaging Factor

The TCM 320U transmitter is a pulsed emission; therefore, the method of §15.35 for averaging a pulsed emission may be used. A timing diagram of the pulsed transmission, plots of the pulse train, and the average factor calculations are shown below:





Average factor calculation

From the plots, there are 3 pulses transmitted in 100 milliseconds. The maximum time for averaging the emission using FCC §15.35(c) is 100 ms. The Average Factor will be calculated using 100 ms as specified in FCC §15.35(c).

The Average Factor is calculated by the equation:

$$\text{Average Factor} = 20 \log (\text{on time/pulse train time})$$

Pulse train time = 100 ms per FCC §15.35(c)

On time = 1.64ms x 3 = 4.92 ms

$$\begin{aligned} \text{Average Factor} &= 20 \log (4.92 / 100) \\ &= -26.2 \text{ dB} \end{aligned}$$

§15.35(b) specifies a 20 dB maximum between the peak and average measurements; therefore, a -20.0 dB averaging factor will be used. The power level of the EUT transmitter was set to 0 dB.

The data in the tables shown below are the worst-case emissions seen at the listed. Emissions were measured from 9 kHz or the lowest frequency used in the device to 9029 MHz, the 10th harmonic of the fundamental frequency. An active loop antenna was used below 30 MHz, a biconilog antenna was used from 30 to 1000 MHz, and a double ridged guide antenna was used above 1000 MHz.

Radiated Interference Measurements – (Vertical Polarity)

Frequency (MHz)	Detector	Receiver Reading (dB μ V)	Correction Factor (dB/m)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Delta (dB)
902.9	Peak	64.1	30.5	-20.0	74.6	81.9	-7.3
1805.8	Peak	14.2	29.3	-20.0	23.5	61.9	-38.4
2708.6*	Peak	8.7	32.6	-20.0	21.3	54.0	-32.7
3611.5*	Peak	10.4	35.7	-20.0	26.1	54.0	-27.9
4514.4*	Peak	10.6	37.1	-20.0	27.7	54.0	-26.3
5417.3*	Peak	6.0	39.3	-20.0	25.3	54.0	-28.7
6320.1	Peak	4.1	40.0	-20.0	24.1	61.9	-37.8
7223.0	Peak	5.0	42.1	-20.0	27.1	61.9	-34.8
8125.9*	Peak	4.7	43.3	-20.0	28.0	54.0	-26.0
9029.0*	Peak	5.1	44.5	-20.0	29.6	54.0	-24.4

* Emissions within restricted bands

Radiated Interference Measurements - (Horizontal Polarity)

Frequency (MHz)	Detector	Receiver Reading (dB μ V)	Correction Factor (dB/m)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Delta (dB)
902.9	Peak	70.5	30.5	-20.0	81.0	81.9	-0.9
1805.8	Peak	16.8	29.3	-20.0	26.1	61.9	-35.8
2708.6*	Peak	9.2	32.6	-20.0	21.8	54.0	-32.2
3611.5*	Peak	10.2	35.7	-20.0	25.9	54.0	-28.1
4514.4*	Peak	7.0	37.1	-20.0	24.1	54.0	-29.9
5417.3*	Peak	5.3	39.3	-20.0	24.6	54.0	-29.4
6320.1	Peak	4.4	40.0	-20.0	24.4	61.9	-37.5
7223.0	Peak	5.3	42.1	-20.0	27.4	61.9	-34.5
8125.9*	Peak	5.0	43.3	-20.0	28.3	54.0	-25.7

Frequency (MHz)	Detector	Receiver Reading (dB μ V)	Correction Factor (dB/m)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Delta (dB)
9029.0*	Peak	5.5	44.5	-20.0	30.0	54.0	-24.0
* Emissions within restricted bands							

Sample Field Strength Calculation:

The field strength is calculated by adding the Correction Factor (Antenna Factor + Cable Factor) and the Average Factor to the measured level of the receiver. The receiver amplitude reading is compensated for any amplifier gain.

The basic equation with a sample calculation is shown below:

$$FS = RA + CF + AV \text{ Where}$$

FS = Field Strength

RA = Receiver Amplitude Reading

CF = Correction Factor (Antenna Factor + Cable Factor)

AV = Averaging Factor

Assume a receiver reading of 44.2 dB μ V is obtained from the receiver, with an average factor of -8.6 dB and a correction factor of 17.5 dB. The field strength is calculated by adding the correction factor and the average factor, giving a field strength of 53.1 dB μ V/m, $FS = 44.2 + 17.5 + (-8.6) = 53.1$ dB μ V/m


RESULT

In the configuration tested, the EUT complied with the requirements of this section.

6.2.5 §15.231 (c) Bandwidth

Demonstration of Compliance:

The bandwidth of the emission must not be wider than 0.25% of the center frequency. The center frequency is 902.9 MHz, therefore the bandwidth must not be wider than 2.25725 MHz. The EUT bandwidth was 308.0 kHz. See spectrum analyzer plot below.



Mkr	X-Axis	Value	Notes
1 ▾	902.817000 MHz	93.6000 dBuV	
2-1 ▾	-75.000000 kHz	-20.0000 dB	
3-2 ▾	271.000000 kHz	-0.5000 dB	band width

RESULT

In the configuration tested, the EUT complied with the requirements of this section.

APPENDIX 1 TEST PROCEDURES AND TEST EQUIPMENT

A1.1 §15.207 Conducted Disturbance at the AC Mains

The conducted disturbance at mains ports from the EUT was measured using a spectrum analyzer with a quasi-peak adapter for peak, quasi-peak and average readings. The quasi-peak adapter uses a bandwidth of 9 kHz, with the spectrum analyzer's resolution bandwidth set at 100 kHz, for readings in the 150 kHz to 30 MHz frequency ranges.

The conducted disturbance at mains ports measurements are performed in a screen room using a (50 Ω /50 μ H) Line Impedance Stabilization Network (LISN).

Where mains flexible power cords are longer than 1 m, the excess cable is folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

Where the EUT is a collection of devices with each device having its own power cord, the point of connection for the LISN is determined from the following rules:

- (a) Each power cord, which is terminated in a mains supply plug, shall be tested separately.
- (b) Power cords, which are not specified by the manufacturer to be connected via a host unit, shall be tested separately.
- (c) Power cords which are specified by the manufacturer to be connected via a host unit or other power supplying equipment shall be connected to that host unit and the power cords of that host unit connected to the LISN and tested.
- (d) Where a special connection is specified, the necessary hardware to effect the connection is supplied by the manufacturer for the testing purpose.
- (e) When testing equipment with multiple mains cords, those cords not under test are connected to an artificial mains network (AMN) different than the AMN used for the mains cord under test.

For AC mains port testing, desktop EUT are placed on a non-conducting table at least 0.8 meters from the metallic floor and placed 40 cm from the vertical coupling plane (copper plating in the wall behind EUT table). Floor standing equipment is placed directly on the earth grounded floor.


Type of Equipment	Manufacturer	Model Number	Serial Number	Date of Last Calibration	Due Date of Calibration
Wanship Open Area Test Site #2 (Note 1)	Nemko-CCL, Inc.	N/A	N/A	11/16/2011	11/16/2012
Test Software	Nemko-CCL, Inc.	Conducted Emissions	Revision 1.2	N/A	N/A
Spectrum Analyzer	Hewlett Packard	8566B	2230A01711	01/17/2012	01/17/2013

Type of Equipment	Manufacturer	Model Number	Serial Number	Date of Last Calibration	Due Date of Calibration
Quasi-Peak Detector	Hewlett Packard	85650A	2043A00137	01/18/2012	01/18/2013
LISN	EMCO	3825/2	9305-2099	03/12/2012	03/12/2013
Conductance Cable Wanship Site #2	Nemko-CCL, Inc.	Cable J	N/A	12/14/2011	12/14/2012
Transient Limiter	Hewlett Packard	11947A	3107A02266	12/14/2011	12/14/2012

Note 1 The Volumetric Normalized site attenuation was performed on 12/7/2012 verifying that the site was still within specification for testing covered in this report.

An independent calibration laboratory or Nemko-CCL Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Conducted Emissions Test Setup



A1.2 §15.231 Radiated Measurements

The radiated emissions from the intentional radiator were measured using a spectrum analyzer with a quasi-peak adapter for peak and quasi-peak readings.

A loop antenna was used to measure emissions below 30 MHz. Emission readings more than 20 dB below the limit at any frequency may not be listed in the reported data. For frequencies between 9 kHz and 30 MHz, or the lowest frequency generated or used in the device greater than 9 kHz, and less than 30 MHz, the spectrum analyzer resolution bandwidth was set to 9 kHz and the video bandwidth was set to 30 kHz. For average measurements, the spectrum analyzer average detector was used.

For frequencies above 30 MHz, an amplifier and preamplifier were used to increase the sensitivity of the measuring instrumentation. The quasi-peak adapter uses a bandwidth of 120 kHz, with the spectrum analyzer's resolution bandwidth set at 1 MHz, for readings in the 30 to 1000 MHz frequency ranges. For peak emissions above 1000 MHz the spectrum analyzer's resolution bandwidth was set to 1 MHz and the video bandwidth was set to 3 MHz. For average measurements above 1000 MHz the spectrum analyzer's resolution bandwidth was set to 1 MHz and the average detector of the analyzer was used.

A biconilog antenna was used to measure the frequency range of 30 to 1000 MHz and a Double Ridge Guide Horn antenna was used to measure the frequency range of 1 GHz to 18 GHz at a distance of 3 meters and/or 1 meter from the EUT. The readings obtained by the antenna are correlated to the levels obtained with a tuned dipole antenna by adding antenna factors.

The configuration of the EUT was varied to find the maximum radiated emission. The EUT was connected to the peripherals listed in Section 2.3 via the interconnecting cables listed in Section 2.4. A technician manually manipulated these interconnecting cables to obtain worst-case radiated disturbance. The EUT was rotated 360 degrees, and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission. Where there were multiple interface ports all of the same type, cables are either placed on all of the ports or cables added to these ports until the emissions do not increase by more than 2 dB.

Desktop EUT are measured on a non-conducting table 0.8 meters above the ground plane. The table is placed on a turntable, which is level with the ground plane. For equipment normally placed on floors, the equipment shall be placed directly on the turntable.


For radiated emission testing at 30 MHz or above that is performed at distances closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

Type of Equipment	Manufacturer	Model Number	Serial Number	Date of Last Calibration	Due Date of Calibration
Wanship Open Area Test Site #2 (Note 1)	Nemko-CCL, Inc.	N/A	N/A	11/16/2011	11/16/2012
Test Software	Nemko-CCL, Inc.	Radiated Emissions	Revision 1.3	N/A	N/A
Spectrum Analyzer/Receiver	Rhode & Schwarz	ESU40	100064	07/28/2012	07/28/2013
Spectrum Analyzer	Hewlett Packard	8566B	2230A01711	01/17/2012	01/17/2013
Quasi-Peak Detector	Hewlett Packard	85650A	2043A00137	01/18/2012	01/18/2013
Loop Antenna	EMCO	6502	2011	03/11/2011	03/13/2013
Biconilog Antenna	EMCO	3142	9601-1009	04/21/2011	04/21/2013
Double Ridged Guide Antenna	EMCO	3115	9604-4779	03/10/2011	03/10/2013
High Frequency Amplifier	Miteq	AFS4-01001800-43-10P-4	1096455	06/26/2012	06/26/2013
6' High Frequency Cable	Microcoax	UFB197C-0-0720-000000	1296	05/14/2012	05/14/2013
20' High Frequency Cable	Microcoax	UFB197C-1-3120-000000	1297	05/14/2012	05/14/2013
3 Meter Radiated Emissions Cable Wanship Site #2	Microcoax	UFB205A-0-4700-000000	1295	05/10/2011	05/10/2013
Pre/Power-Amplifier	Hewlett Packard	8447F	3113A05161	08/27/2012	08/27/2013
6 dB Attenuator	Hewlett Packard	8491A	32835	12/14/2011	12/14/2012

Note 1 The Volumetric Normalized site attenuation was performed on 12/7/2012 verifying that the site was still within specification for testing covered in this report.

An independent calibration laboratory or Nemko-CCL, Inc. personnel calibrates all the equipment listed above at intervals defined in ANSI C63.4:2003 Section 4.4 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to tractability is on file and is available for examination upon request.

Radiated Emissions Test Setup



APPENDIX 2 PHOTOGRAPHS

Photograph 1 – Radiated Disturbance – Flat or Horizontal Configuration



Photograph 2 – View Radiated Disturbance – Vertical Configuration




Photograph 3 –View Radiated Disturbance – On Edge Configuration




Photograph 4 – Front View Conducted Disturbance Worst Case Configuration



Photograph 6 – Front View of the EUT



Photograph 7 – Back View of the EUT



Photograph 8 – Circuitry Under RF Shield

