

SECTION 9

RF EXPOSURE INFORMATION

5.1 RF Safety Requirements to 2.1091 for Mobile Transmitters

Wireless Detection LLC calculated the MPE emission values for the EUT with the 3 dBi gain antenna. They used the formula shown in OET Bulletin 65 and calculated the minimum distance between antenna and unsuspecting user as 20 cm.

The EUT's maximum expected output power as shown in Section 2.7 was

Frequency of Fundamental (MHz)	Measurement (dBm)*	Measurement (mW)*	FCC Limit (Watt)
902.264	18.78	75.5	1.0
914.955	18.98	79.07	1.0
927.304	16.19	41.59	1.0

Power = Antilog (dBm/10) = Antilog (18.78/10) = Antilog 1.878 = 75.5

*** Measurement includes 0.1 dB for cable loss**

Test Date: March 21, 2005

Tester

Signature:  **ne: David Blethen**

The maximum EIRP expected for mobile installations is with a +3 dBi gain antenna. This would yield a maximum EIRP of 21.98 dBm.

RF Safety Requirements to 2.1091 for Mobile Transmitters

The maximum EIRP for mobile installations may be expected to be

$$\text{Antilog}(21.98 \text{ dBm}/10) = 157.8 \text{ mW}$$

MPE Calculations

The limits for this unit (uncontrolled exposure) are $1.0 \text{ mW}/\text{cm}^2$. Taking the RF Density Field Equation:

Mobile Installations

$$S = 157.8 / 4 * \pi * 20^2$$

$$S = 157.8 / 5026.55$$

$$S = 0.03 \text{ mW} / \text{cm}^2$$

This is well below the maximum level of $1.0 \text{ mW} / \text{cm}^2$

All manual instructions will specify 20 cm for mobile installations