



Wireless Detection  
**FCC Part 15, Certification Application**  
**Fire Warning System,**  
**Model SR-002 Rev 02 System Repeater**

April 1, 2005  
UST Project Number: 05-0073



3505 Francis Circle • Alpharetta, GA 30004  
Tel: (770) 740-0717 • Fax: (770) 740-1508 • [www.ustech-lab.com](http://www.ustech-lab.com)





I certify that I am authorized to sign for the manufacturer and that all of the statements in this report and in the Exhibits attached hereto are true and correct to the best of my knowledge and belief:

**UNITED STATES TECHNOLOGIES, INC. (AGENT RESPONSIBLE FOR TEST):**

By:

Name: Louis A. Feudi

Title: Operations Manager

Date: April 1, 2005

**Wireless Detection**  
79 Tyee Drive  
Point Roberts, WA 98281

By:

Name:

Title:

Date:

This report shall not be reproduced except in full. This report may be copied in part only with the prior written approval of U.S. Technologies. The results contained in this report are subject to the adequacy and representative character of the sample provided.



3505 Francis Circle • Alpharetta, GA 30004  
Tel: (770) 740-0717 • Fax: (770) 740-1508 • [www.ustech-lab.com](http://www.ustech-lab.com)



Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

## MEASUREMENT/TECHNICAL REPORT

**COMPANY NAME:** Wireless Detection**MODEL:** SR-002 Rev 02 System Repeater**FCC ID:** SZX-SR002**DATE:** April 1, 2005

This report concerns (check one): Original grant  Class II change \_\_\_\_\_

Equipment type: Spread Spectrum Transceiver

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? yes  No

If yes, defer until: \_\_\_\_\_  
date

N.A. agrees to notify the Commission by N.A.  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Report prepared by:

United States Technologies, Inc.  
3505 Francis Circle  
Alpharetta, GA 30004

Phone Number: (770) 740-0717  
Fax Number: (770) 740-1508

### TABLE OF CONTENTS

### **SECTION 1 GENERAL INFORMATION**

- 1.1 Product Description
- 1.2 Related Submittal(s)

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**SECTION 2  
TESTS AND MEASUREMENTS**

- 2.1 Configuration of Tested EUT
- 2.2 Test Facility
- 2.3 Test Equipment
- 2.4 Modifications
- 2.5 Test Procedure and Results
- 2.6 Antenna Description
- 2.7 Peak Power (Bandedge Antenna Conducted at Antenna Terminal)
- 2.8 Antenna Conducted Spurious Emissions
- 2.9 Peak Radiated Spurious Emissions
- 2.10 Average Radiated Spurious Emissions
- 2.11 Minimum 20 dB Bandwidth
- 2.12 Number of Hopping Channels
- 2.13 Average Time of Occupancy per Channel
- 2.14 Power Line Conducted Emissions for Transmitter
- 2.15 Radiated Emissions for Digital Device & Receiver (47 CFR 15.109a)
- 2.16 Power Line Conducted Emissions for Digital Device and Receiver FCC Section 15.107
- 2.17 Channel Separation

**SECTION 3  
LABELING INFORMATION****SECTION 4  
BLOCK DIAGRAM(S)/ SCHEMATIC(S)****SECTION 5  
PHOTOGRAPHS****SECTION 6  
THEORY OF OPERATION****SECTION 7  
TUNE UP PROCEDURE****SECTION 8  
USER'S MANUAL****SECTION 9  
RF EXPOSURE INFO**

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**LIST OF FIGURES AND TABLES****FIGURES**

- 1) Test Configuration
- 2) Photograph(s) for Spurious and Conducted Emissions
- 3) Peak Output Power
- 4) Conducted Spurious Emissions
- 5) Peak Radiated Spurious Emissions
- 6) 20 dB Bandwidth
- 7) Number of Hopping Channels
- 8) Average Time of Occupancy
- 9) Channel Separation

**TABLES**

- 1) EUT and Peripherals
- 2) Test Instruments
- 3) Peak Power Output
- 4) Peak Radiated Spurious Emissions
- 5) Average Radiated Spurious Emissions
- 6) 20 dB Bandwidth
- 7) Number of Hopping Channels
- 8) Conducted Emissions
- 9) Radiated Emissions for Digital Device and Receiver
- 10) Channel Separation

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

---

Issue Date: April 1, 2005

## SECTION 1

## GENERAL INFORMATION

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

## GENERAL INFORMATION

### 1.1 Product Description

The Equipment Under test (EUT) is the Wireless Detection's Fire Warning System, Model SR-002 Rev 02 System Repeater. Under normal operation the System Repeater (SR-002) is in receive mode. When a data transmission is received and the data is determined to be valid, then the System Repeater re-transmits the data. With each reception only one transmission is sent.

The changing of channels is normally controlled via the Smoke Detector transceiver. When the Smoke Detector sends a status report, the Smoke Detector ends the transmission of data, either after the acknowledgement is received or after a timeout of 7 transmissions. The status is currently sent every 30 minutes; it may be set as low as 15 minutes.

The modes that will put the Smoke Detector in the FHSS mode is as follows:

When the Smoke Detector detects an Alarm condition, which is either the detection of smoke, the temperature rate of rise condition has been met and or the maximum temperature has been exceeded, the unit is being tampered with, or the unit is in test mode via the user push to test button.

During these conditions the Smoke Detector ignores acknowledgement reception and continues to transmit until the alarm condition is no longer present.

When the unit is in FHSS mode, ten transmissions of alarm is sent followed by five transmissions of channel data. When the System Repeater receives the channel data, the unit will change the transceiver channel to the instructed channel as sent by the Smoke Detector. The way this is controlled is by counting the transmissions, after 15 transmissions, the unit is incremented to the next channel. The format of the data transmissions is fixed. The transmit time will never increase or decrease.

When a data transmission is sent the transmit time is 2.84 ms. After a data transmission, the unit is put into the receive mode, the receive time before the next transmit time is 23.8 ms; if no acknowledgement has been received or the acknowledge transmission is inhibited. Each transmit and receive cycle is 26.24 ms. The channel occupancy is 15 transmissions @ 2.84 ms per transmission, which provides channel occupancy of 46.6 ms per channel. With a range of 62 separate channels; the total transmit and receive time is 0.3758 ms per channel. The cycle time of 62 channels is 23.2996 seconds.

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

---

### **1.2 Related Submittal(s)/Grant(s)**

The EUT will be used with part of a system to send/receive data. The transceiver presented in this report will be used with other like transmitters.

The EUT is subject to the following authorizations:

- a) Certification as a transceiver
- b) Verification as a receiver and digital device

The information contained in this report is presented for the certification & verification authorization(s) for the EUT.

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

---

Issue Date: April 1, 2005

## SECTION 2

## TESTS AND MEASUREMENTS

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

## TEST AND MEASUREMENTS

### 2.1 Configuration of Tested System

The sample was tested per ANSI C63.4, Methods of Measurement from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (1992). Conducted and radiated emissions data were taken with the test receiver or spectrum analyzer's resolution bandwidth adjusted to 9 kHz and 120 kHz, respectively. All measurements are peak unless stated otherwise. The video filter associated with the spectrum analyzer was off throughout the evaluation process. Interconnecting cables were manipulated as necessary to maximize emissions. Block diagrams of the tested systems are shown in Figure 1. Test configuration photographs for spurious and fundamental emissions are shown in Figure 2a-b. Test configuration photograph for conducted digital emissions is shown in Figure 2c.

The sample used for testing was received by U.S. Technologies on March 2, 2005 in good condition.

### 2.2 Test Facility

Testing was performed at US Tech's measurement facility at 3505 Francis Circle, Alpharetta, GA. This site has been fully described and submitted to the FCC, and accepted in their letter marked 31040/SIT. Additionally this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number IC2982.

### 2.3 Test Equipment

Table 2 describes test equipment used to evaluate this product.

### 2.4 Modifications


No modifications were made to bring the EUT into compliance with FCC Part 15, Class B Limits for the transmitter portion of the EUT or the Class B Digital Device Requirements:

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**FIGURE 1****TEST CONFIGURATION**

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

**FIGURE 2a****Photograph(s) for Spurious Emissions****Photo represents worst case configuration**

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

**FIGURE 2b****Photograph(s) for Spurious Emissions****Photo represents worst case configuration**

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

**FIGURE 2c****Photograph(s) for Conducted Emissions****Photo represents worst case configuration**

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**TABLE 1**  
**EUT and Peripherals**

PERIPHERAL MANU.	MODEL NUMBER	SERIAL NUMBER	FCC ID:	CABLES P/D
Transmitter (EUT) Wireless Detection	SR-002 Rev 02 System Repeater	None	None	6' U Power Cable
Adapter Cui, Inc.	DV-1230-B11	None	None	120 VAC/ 60 Hz Direct Connect

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Detail of I/O Cables Attached to EUT**

DESCRIPTION OF CABLE	DETAILS OF CABLE			CABLE LENGTH
Power Cable	<u>Manufacturer and Part Number</u>			6'
	Shield Type	Shield Termination	Type of Backshell	
	N/A	N/A	N/A	

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

**TABLE 2**  
**TEST INSTRUMENTS**

EQUIPMENT	MODEL NUMBER	MANUFACTURER	SERIAL NUMBER	DATE OF LAST CALIBRATION
SPECTRUM ANALYZER	8558B	HEWLETT-PACKARD	2332A10055	2/25/05
SPECTRUM ANALYZER	8593E	HEWLETT-PACKARD	3205A00124	3/1/05
SIGNAL GENERATOR	8648B	HEWLETT-PACKARD	3642U01679	4/29/04
RF PREAMP	8447D	HEWLETT-PACKARD	2944A06291	3/1/05
BICONICAL ANTENNA	3110B	EMCO	9307-1431	5/18/04
LOG PERIODIC	3146	EMCO	3110-3236	6/30/04
LISN (x 2) 8028-50-TS24-BNC	8028	SOLAR ELE.	910494 & 910495	1/27/05
HORN ANTENNA	SAS-571	A. H. SYSTEMS	605	04/26/04
PREAMP	8449B	HEWLETT PACKARD	3008A00480	6/23/04
CALCULATION PROGRAM	N/A	N/A	EMCCALC	N/A

Report Number: 05-0073

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

---

Issue Date: April 1, 2005

## **2.6 Antenna Description (Paragraph 15.203)**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The Model Wireless Detection SR-002 Rev 02 System Repeater uses the following antenna:

Linx Technologies

1/4 Wave Whip Antenna

Model ANT-916-JJB-ST

Gain = 3.0 dBi

The antenna mounts on a unique reverse SMA connector.

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**2.7 Peak power within the band 902 – 928 MHz per FCC Section 15.247(b)**

Peak power within the band 902 – 928 MHz has been measured with a spectrum analyzer by connecting the spectrum analyzer directly via a short cable to the antenna output terminals or across the antenna leads on the PCB as specified by the manufacturer. The spectrum analyzer was set for a  $50 \Omega$  impedance with the  $VBW \geq RBW$  6 dB bandwidth. The results of the measurements are given in Table 3 and Figure 3a through Figure 3c.

Fundamental Frequencies were measured at Low Channel, Mid Channel, High Channel.

Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**TABLE 3**  
**PEAK POWER OUTPUT**

Frequency of Fundamental (MHz)	Measurement (dBm)*	Measurement (mW)*	FCC Limit (Watt)
902.277	23.41	219.28	1.0
915.021	23.43	220.3	1.0
927.250	23.06	202.3	1.0

Power = Antilog (dBm/10) = Antilog (23.41/10) = Antilog 2.341 = 219.28

\* Measurement includes 0.1 dB for cable loss

**Test Date:** March 28, 2005

**Tester**

**Signature:** David Blethen **Name:** David Blethen


Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 3a.**  
**Peak Power per FCC Section 15.247(b) (Low Channel)**



Report Number: 05-0073


Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

Figure 3b.

Peak Power per FCC Section 15.247( b) (Mid Channel)




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Figure 3c.  
Peak Power per FCC Section 15.247( b) (High Channel)



Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**2.8 Antenna Conducted Spurious Emission the Frequency Range 30 – 25000 MHz (FCC Section 15.247(c))**

Spurious emissions in the frequency range 30 – 25000 MHz have been measured with a spectrum analyzer by connecting the spectrum analyzer directly via a short cable to the antenna output terminals or across the antenna leads on the PCB as specified by the manufacturer. The spectrum analyzer was set for a  $50 \Omega$  impedance with the  $RBW = 100 \text{ kHz}$  &  $VBW > RBW$ . All spurious emissions were measured to be greater than 20 dB down from the fundamental. The results of conducted spurious emissions are given in Figure 4a through 4l.

Report Number: 05-0073

Customer: Wireless Detection


Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

**Figure 4a**

Antenna Conducted Spurious Emissions 15.247(c) (Low Channel)

NOTE: Due to large span used,  
frequency appears off. Actual Frequency  
of the fundamental is 902.277 MHz.




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 4b**  
Antenna Conducted Spurious Emissions 5.247(c) (Low Channel)




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 4c**  
Antenna Conducted Spurious Emissions 15.247(c) (Low Channel)




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 4d**  
**Antenna Conducted Spurious Emissions 15.247(c) (Low Channel)**



Report Number: 05-0073

Customer: Wireless Detection


Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

Figure 4e

## Antenna Conducted Spurious Emissions 15.247(c) (Mid Channel)

NOTE: Due to large span used,  
frequency appears off. Actual Frequency  
of the fundamental is 915.021 MHz.




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 4f**  
**Antenna Conducted Spurious Emissions 15.247(c) (Mid Channel)**




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 4g**  
**Antenna Conducted Spurious Emissions 15.247(c) (Mid Channel)**




Report Number: 05-0073

Issue Date: April 1, 2005

Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

**Figure 4h**  
Antenna Conducted Spurious Emissions 15.247(c) (Mid Channel)



Report Number: 05-0073


Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

**Figure 4i****Antenna Conducted Spurious Emissions 15.247(c) (High Channel)**

NOTE: Due to large span used,  
frequency appears off. Actual Frequency  
of the fundamental is 927.520 MHz.



Report Number: 05-0073


Customer: Wireless Detection

Model: SR-002 Rev 02 System Repeater

Issue Date: April 1, 2005

Figure 4j


Antenna Conducted Spurious Emissions 15.247(c) (High Channel)



Report Number: 05-0073  
2005  
Customer: Wireless Detection  
Model: SR-002 Rev 02 System Repeater

Rev: 012804  
Issue Date: April 1,

**Figure 4k**  
**Antenna Conducted Spurious Emissions 15.247(c) (High Channel)**



Report Number: 05-0073  
2005  
Customer: Wireless Detection  
Model: SR-002 Rev 02 System Repeater

Rev: 012804  
Issue Date: April 1,

**Figure 4I**  
**Antenna Conducted Spurious Emissions 15.247(c) (High Channel)**

