

# FCC Test Report

**Report No.:** RWAZ202300068B

**Applicant:** YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.

**Address:** No.666 Hu'an Rd. Huli District Xiamen City, Fujian, P.R. China

**Product Name:** Bluetooth Headset

**Product Model:** BHD702

**Multiple Models:** BHM701

**Trade Mark:** 

**FCC ID:** T2C-BHD702

**Standards:** FCC CFR Title 47 Part 15C (§15.247)

**Test Date:** 2023/12/12-2023/12/20

**Test Result:** Complied

**Report Date:** 2024/01/25

**Reviewed by:**

*Abel chen*

**Approved by:**

*Jacob Kong*

Abel Chen

Project Engineer

Jacob Kong

Manager

**Prepared by:**

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen,  
Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

## Announcement

1. This test report shall not be reproduced in full or partial, without the written approval of World Alliance Testing and Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
5. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

## Revision History

Version No.	Issued Date	Description
00	25 Jan, 2024	Original

# Contents

<b>1</b>	<b>General Information .....</b>	<b>4</b>
1.1	Client Information .....	4
1.2	Product Description of EUT .....	4
1.3	Antenna information .....	4
1.4	Related Submittal(s)/Grant(s).....	5
1.5	Measurement Uncertainty .....	5
1.6	Laboratory Location.....	5
1.7	Test Methodology .....	5
<b>2</b>	<b>Description of Measurement.....</b>	<b>6</b>
2.1	Test Configuration.....	6
2.2	Test Auxiliary Equipment .....	6
2.3	Test Setup.....	7
2.4	Test Procedure .....	9
2.5	Measurement Method.....	10
2.6	Measurement Equipment .....	11
<b>3</b>	<b>Test Results .....</b>	<b>12</b>
3.1	Test Summary.....	12
3.2	Limit .....	13
3.3	AC Line Conducted Emissions Test Data.....	14
3.4	Radiated emission Test Data.....	18
3.5	RF Conducted Test Data .....	26
3.5.1	6 dB Emission Bandwidth and 99% Occupied Bandwidth.....	26
3.5.2	Maximum Conducted Peak Output Power.....	26
3.5.3	Power Spectral Density.....	26
3.5.4	100 kHz Bandwidth of Frequency Band Edge .....	26
3.5.5	Duty Cycle .....	27
<b>4</b>	<b>Test Setup Photo.....</b>	<b>33</b>
<b>5</b>	<b>E.U.T Photo.....</b>	<b>34</b>

# 1 General Information

## 1.1 Client Information

Applicant:	YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Address:	No.666 Hu'an Rd. Huli District Xiamen City, Fujian, P.R. China
Manufacturer:	YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Address:	No.666 Hu'an Rd. Huli District Xiamen City, Fujian, P.R. China

## 1.2 Product Description of EUT

The EUT is Bluetooth Headset that contains Classic Bluetooth and BLE radios, this report covers the full testing of the Classic Bluetooth radio.

Sample Serial Number	32-1,32-2 for CE&RE test; 32-3 for RF test conducted test (assigned by WATC)
Sample Received Date	2023-12-08
Sample Status	Good Condition
Frequency Range	2402MHz - 2480MHz(BLE1M)
Maximum Conducted Peak Output Power	-0.27dBm
Modulation Technology	GFSK
Spatial Streams	SISO (1TX, 1RX)
Antenna Gain <sup>#</sup>	0.01dBi
Power Supply	DC 5V from tepy-c port or DC3.8v from battery
Operating temperature <sup>#</sup>	-10 deg.C to +45 deg.C
Adapter Information	N/A
Modification	Sample No Modification by the test lab

## 1.3 Antenna information

<b>15.203 requirement:</b>	
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>Device Antenna information:</b>	
The BLE antenna is an internal antenna which cannot replace by end-user, please see product internal photos for details.	

## 1.4 Related Submittal(s)/Grant(s)

FCC Part 15, Subpart E, Equipment Class: DSS, FCC ID: T2C-BHD702

## 1.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))	
AC Power Lines Conducted Emissions	±3.14dB	
Emissions, Radiated	Below 30MHz	±2.78dB
	Below 1GHz	±4.84dB
	Above 1GHz	±5.44dB
Emissions, Conducted	1.75dB	
Conducted Power	0.74dB	
Frequency Error	150Hz	
Bandwidth	0.34%	
Power Spectral Density	0.74dB	

**Note:** The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor *K* with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

## 1.6 Laboratory Location

World Alliance Testing and Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: [qa@watc.com.cn](mailto:qa@watc.com.cn)

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

## 1.7 Test Methodology

FCC CFR 47 Part 2

FCC CFR 47 Part 15

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

## 2 Description of Measurement

### 2.1 Test Configuration

Operating channels:					
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	19	2440	38	2478
1	2404	20	2442	39	2480
...	...	...	...	/	/
18	2438	...	...	/	/

According to ANSI C63.10-2020 chapter 5.6.1 Table 11 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	19	2440	39	2480

Test Mode:					
Transmitting mode:		Keep the EUT in continuous transmitting with modulation			
Exercise software <sup>#</sup> :		Bus Hound Airoha.Tool.Kitexe			
Mode	Data rate	Power Level Setting <sup>#</sup>			
		Low Channel	Middle Channel	High Channel	
BLE 1M	1Mbps	40	40	40	

The exercise software and the maximum power setting that provided by manufacturer.


Worst-Case Configuration:	
For radiated emissions, EUT was investigated in three orthogonal orientation, the worst-case orientation was recorded in report	
For AC power line conducted emission and radiated emission 9kHz-1GHz and above 18GHz were performed with the EUT transmits at the channel with highest output power as worst-case scenario.	

### 2.2 Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number
/	Adapter	/	/

## 2.3 Test Setup


### 1) Conducted emission measurement:




**Note:** The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.


### 2) Radiated emission measurement:

Below 30MHz (3m SAC)



30MHz-1GHz (3m SAC)







## 2.4 Test Procedure

### Conducted emission:

1. The E.U.T is placed on a non-conducting table 40cm from the vertical ground plane and 80cm above the horizontal ground plane (Please refer to the block diagram of the test setup and photographs).
2. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
3. Line conducted data is recorded for both Line and Neutral

### Radiated Emission Procedure:

#### a) For below 30MHz

1. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz- 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were  $40 \cdot \log(\text{test distance} / \text{specification distance})$ .
2. Loop antenna use, investigation was done on the three antenna orientations (parallel, perpendicular, ground-parallel)

#### b) For 30MHz-1GHz:

1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

#### c) For above 1GHz:

1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m (1-18GHz) and 1.5 m (above 18GHz).
2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
4. Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

### RF Conducted Test:

1. The antenna port of EUT was connected to the RF port of the test equipment (Power Meter or

Spectrum analyzer) through Attenuator and RF cable.

2. The cable assembly insertion loss of 7.0dB (including 6.0 dB Attenuator and 0.5dB cable) was entered as an offset in the power meter. Note: Actual cable loss was unavailable at the time of testing, therefore a loss of 0.5dB was assumed as worst case. This was later verified to be true by laboratory. ( if the RF cable provided by client, the cable loss declared by client)
3. The EUT is keeping in continuous transmission mode and tested in all modulation modes.

## 2.5 Measurement Method

Description of Test	Measurement Method
AC Line Conducted Emissions	ANSI C63.10-2020 Section 6.2
Maximum Conducted Output Power	ANSI C63.10-2020 Section 11.9.1.1
Power Spectral Density	ANSI C63.10-2020 Section 11.10.2
6 dB Emission Bandwidth	ANSI C63.10-2020 Section 11.8.1
99% Occupied Bandwidth	ANSI C63.10-2020 Section 6.9.3
100kHz Bandwidth of Frequency Band Edge	ANSI C63.10-2020 Section 6.10
Radiated emission	ANSI C63.10-2020 Section 11.11&11.12.1
Duty Cycle	ANSI C63.10-2020 Section 11.6

## 2.6 Measurement Equipment

Manufacturer	Description	Model	Management No.	Calibration Date	Calibration Due Date
<b>AC Line Conducted Emission Test</b>					
ROHDE& SCHWARZ	EMI TEST RECEIVER	ESR	101817	2023/7/3	2024/7/2
R&S	LISN	ENV216	101748	2023/8/1	2024/7/31
N/A	Coaxial Cable	NO.12	N/A	2023/7/3	2024/7/2
Farad	Test Software	EZ-EMC	Ver. EMEC-3A1	/	/
<b>Radiated Emission Test</b>					
R&S	EMI test receiver	ESR3	102758	2023/7/3	2024/7/2
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40-N	101608	2023/7/3	2024/7/2
SONOMA INSTRUMENT	Low frequency amplifier	310	186014	2023/7/12	2024/7/11
COM-POWER	preamplifier	PAM-118A	18040152	2023/8/21	2024/8/20
COM-POWER	Amplifier	PAM-840A	461306	2023/8/8	2024/8/7
ETS	Passive Loop Antenna	6512	29604	2023/7/7	2024/7/6
SCHWARZBECK	Log - periodic wideband antenna	VULB 9163	9163-872	2023/7/7	2024/7/6
Astro Antenna Ltd	Horn antenna	AHA-118S	3015	2023/7/6	2024/7/5
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2023/7/10	2024/7/9
Oulitong	Band Reject Filter	OBSF-2400-248 3.5-50N	OE02103119	2023/9/15	2024/9/14
N/A	Coaxial Cable	N/A	NO.9	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.10	2023/8/8	2024/8/7
N/A	Coaxial Cable	N/A	NO.11	2023/8/8	2024/8/7
<b>RF Conducted Test</b>					
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSU-40	101419	2023/9/12	2024/9/11
MARCONI	10dB Attenuator	1692595	2942	2023/10/25	2024/10/24

Note: All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or International standards.

### 3 Test Results

#### 3.1 Test Summary

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
-	99% Occupied Bandwidth	Compliance
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.205, §15.209, §15.247(d)	Radiated emission	Compliance
-	Duty Cycle	Compliance


### 3.2 Limit


Test items	Limit
AC Line Conducted Emissions	See details §15.207 (a)
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Spurious Emissions, 100kHz Bandwidth of Frequency Band Edge	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 3.3 AC Line Conducted Emissions Test Data


<b>Test Date:</b>	2023-12-15	<b>Test By:</b>	Lirou Li
<b>Environment condition:</b>	Temperature: 23.4 C; Relative Humidity:42%; ATM Pressure: 101.5kPa		

Model BHM701






Model BHD702







Limit: QP	Phase: <b>N</b>	Temperature: 23.4
Mode: transmitting	Power: AC 120V/60Hz	Humidity: 42 %
Note: BLE		Air Pressure: 1015 hpa

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over Limit		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	32.45	10.61	43.06	66.00	-22.94	QP	
2		0.1500	14.38	10.61	24.99	56.00	-31.01	AVG	
3		0.1700	31.66	10.53	42.19	64.96	-22.77	QP	
4		0.1700	14.67	10.53	25.20	54.96	-29.76	AVG	
5		0.1940	29.96	10.43	40.39	63.86	-23.47	QP	
6		0.1940	11.08	10.43	21.51	53.86	-32.35	AVG	
7	*	0.5180	30.25	10.70	40.95	56.00	-15.05	QP	
8		0.5180	17.81	10.70	28.51	46.00	-17.49	AVG	
9		0.2260	26.07	10.45	36.52	62.60	-26.08	QP	
10		0.2260	7.69	10.45	18.14	52.60	-34.46	AVG	
11		18.1299	17.30	10.72	28.02	60.00	-31.98	QP	
12		18.1299	7.17	10.72	17.89	50.00	-32.11	AVG	

**Remark:**

Measurement (dBuV)= Reading Level (dBuV) + Correct Factor(dB)

Correct Factor(dB)= LISN Voltage Division Factor (dB)+ Cable loss(dB)

Over Limit = Measurement – Limit

### 3.4 Radiated emission Test Data

9 kHz-30MHz:


<b>Test Date:</b>	2023-12-12	<b>Test By:</b>	Bard Huang
<b>Environment condition:</b>	Temperature: 24.2 C; Relative Humidity:37%; ATM Pressure: 101.6kPa		


For radiated emissions below 30MHz, there were no emissions found within 20dB of limit.

**30MHz-1GHz:**

<b>Test Date:</b>	2023-12-12	<b>Test By:</b>	Bard Huang
<b>Environment condition:</b>	Temperature: 24.9 C; Relative Humidity:49%; ATM Pressure: 100.9kPa		

**Model BHM701**







Project No. : RWAZ202300068  
 Test Mode : Transmitting  
 Test Voltage : AC 120V/60Hz  
 Environment : 24.9°C/49%R.H./100.9kPa  
 Tested by : Bard Huang  
 Polarization : vertical  
 Remark : BHD701 BLE

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	41.277	36.49	-12.73	23.76	40.00	-16.24	Peak
2	46.442	34.96	-12.18	22.78	40.00	-17.22	Peak
3	99.572	28.76	-14.28	14.48	43.50	-29.02	Peak
4	168.857	42.45	-16.36	26.09	43.50	-17.41	Peak
5	182.160	38.83	-15.47	23.36	43.50	-20.14	Peak
6	710.427	29.09	-3.51	25.58	46.00	-20.42	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain

**Model BHD702**





Project No. : RWAZ202300068  
 Test Mode : Transmitting  
 Test Voltage : AC 120V/60Hz  
 Environment : 24.9°C/49%R.H./100.9kPa  
 Tested by : Bard Huang  
 Polarization : vertical  
 Remark : BHD702 BLE

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	42.469	38.28	-12.45	25.83	40.00	-14.17	Peak
2	52.783	33.69	-12.28	21.41	40.00	-18.59	Peak
3	133.795	34.45	-17.47	16.98	43.50	-26.52	Peak
4	183.442	40.48	-15.35	25.13	43.50	-18.37	Peak
5	415.815	28.83	-8.39	20.44	46.00	-25.56	Peak
6	775.517	29.60	-2.26	27.34	46.00	-18.66	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain

**Remark:**

*Result = Reading + Factor*

*Factor = Antenna factor + Cable loss – Amplifier gain*

*Over Limit = Result – Limit*

**Above 1GHz:**

<b>Test Date:</b>	2023-12-20	<b>Test By:</b>	Luke Li
<b>Environment condition:</b>	Temperature: 24.6 C; Relative Humidity:45%; ATM Pressure: 101.4kPa		

Frequency (MHz)	Reading level (dBµV)	Polar	Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
BLE 1M							
Low Channel							
2390.000	49.01	horizontal	8.25	57.26	74	-16.74	Peak
2390.000	36.67	horizontal	8.25	44.92	54	-9.08	Average
2390.000	49.7	vertical	8.25	57.95	74	-16.05	Peak
2390.000	36.94	vertical	8.25	45.19	54	-8.81	Average
4804.000	53.55	horizontal	0.21	53.76	74	-20.24	Peak
4804.000	46.04	horizontal	0.21	46.61	54	-7.39	Average
4804.000	52.71	vertical	0.21	52.92	74	-21.08	Peak
4804.000	45.5	vertical	0.21	45.71	54	-8.29	Average
Middle Channel							
4880.000	52.48	horizontal	0.44	52.92	74	-21.08	Peak
4880.000	45.54	horizontal	0.44	45.98	54	-8.02	Average
4880.000	51.58	vertical	0.44	52.02	74	-21.98	Peak
4880.000	43.88	vertical	0.44	44.32	54	-9.68	Average
High Channel							
2483.500	48.96	horizontal	8.25	57.21	74	-16.79	Peak
2483.500	36.58	horizontal	8.25	44.83	54	-9.17	Average
2483.500	49.54	vertical	8.25	57.79	74	-16.21	Peak
2483.500	35.76	vertical	8.25	44.01	54	-9.99	Average
4960.000	52.41	horizontal	0.93	53.34	74	-20.66	Peak
4960.000	43.36	horizontal	0.93	44.29	54	-9.71	Average
4960.000	51.9	vertical	0.93	52.83	74	-21.17	Peak
4960.000	42.28	vertical	0.93	43.21	54	-10.79	Average

Remark:

Corrected Amplitude= Reading level + corrected Factor


Corrected Factor = Antenna factor + Cable loss – Amplifier gain

Margin = Corrected Amplitude – Limit


The emission levels of other frequencies that were lower than the limit 20dB, not show in test report.

For emissions in 18GHz-25GHz range, all emissions were investigated and in the noise floor level.

**Test plot for example as below:**







### 3.5 RF Conducted Test Data

<b>Test Date:</b>	2023-12-18	<b>Test By:</b>	Ryan Zhang
<b>Environment condition:</b>	Temperature: 24.9~25.5°C; Relative Humidity: 58~65%; ATM Pressure: 99~102.3kPa		

#### 3.5.1 6 dB Emission Bandwidth and 99% Occupied Bandwidth

Test Mode	Channel	6dB BW [MHz]	99% OBW[MHz]	6dB BW Limit[MHz]	Verdict
BLE 1M	2402	0.724	1.034	0.5	pass
	2440	0.724	1.038	0.5	pass
	2480	0.720	1.038	0.5	pass

#### 3.5.2 Maximum Conducted Peak Output Power

Test Mode	Channel [MHz]	Result [dBm]	Limit [dBm]	Verdict
BLE 1M	2402	-0.36	30	Pass
	2440	-0.27	30	Pass
	2480	-0.34	30	Pass

#### 3.5.3 Power Spectral Density

Test Mode	Channel [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE 1M	2402	-16.01	8	Pass
	2440	-15.99	8	Pass
	2480	-16.01	8	Pass

#### 3.5.4 100 kHz Bandwidth of Frequency Band Edge




Test Mode	Channel	Result	Limit	Verdict
BLE 1M	2402	Refer test plot	Refer test plot	Pass
	2440	Refer test plot	Refer test plot	Pass

### 3.5.5 Duty Cycle

Test Mode	Channel	Ton (ms)	Ton+off (ms)	Duty Cycle [%]	1/T[kHz]	VBW setting [kHz]
BLE 1M	2440	0.38	0.63	60.32	2.632	3

## Test Plots:

### 6 dB Emission Bandwidth:

BLE 1M	/
<p style="text-align: center;"><b>Lowest channel</b></p>  <p>CF 2.402 GHz      501 pts      Span 2.0 MHz</p> <p>Date: 18_DEC_2023 14:13:07</p>	/
<p style="text-align: center;"><b>Middle channel</b></p>  <p>CF 2.44 GHz      501 pts      Span 2.0 MHz</p> <p>Date: 18_DEC_2023 14:14:38</p>	/
<p style="text-align: center;"><b>High channel</b></p>  <p>CF 2.48 GHz      501 pts      Span 2.0 MHz</p> <p>Date: 18_DEC_2023 14:15:51</p>	/

**99% Occupied Bandwidth:**

BLE 1M	/
<p style="text-align: center;">Lowest channel</p>	/
<p style="font-size: small;">Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT IPK Max M1[1] -4.52 dBm 2.40195610 GHz Occ Bw 1.039932136 MHz CF 2.402 GHz 501 pts Span 2.0 MHz Date: 18_DEC.2023 14:13:22</p>	/
<p style="text-align: center;">Middle channel</p>	/
<p style="font-size: small;">Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT IPK Max M1[1] -4.48 dBm 2.43995610 GHz Occ Bw 1.037924152 MHz CF 2.44 GHz 501 pts Span 2.0 MHz Date: 18_DEC.2023 14:14:52</p>	/
<p style="text-align: center;">High channel</p>	/
<p style="font-size: small;">Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 63.1 μs VBW 100 kHz Mode Auto FFT IPK Max M1[1] -4.62 dBm 2.47995610 GHz Occ Bw 1.037924152 MHz CF 2.48 GHz 501 pts Span 2.0 MHz Date: 18_DEC.2023 14:16:02</p>	/


**Maximum Conducted Peak Output Power:**

BLE 1M	/
<p style="text-align: center;">Lowest channel</p>	/
<p>Spectrum          Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz          Att 30 dB SWT 1.3 μs VBW 10 MHz Mode Auto FFT          IPk Max M1[1] -0.36 dBm 2.4022400 GHz          CF 2.402 GHz 501 pts Span 10.0 MHz          Date: 18_DEC_2023 14:13:35</p>	/
<p style="text-align: center;">Middle channel</p>	/
<p>Spectrum          Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz          Att 30 dB SWT 1.3 μs VBW 10 MHz Mode Auto FFT          IPk Max M1[1] -0.27 dBm 2.4298600 GHz          CF 2.424 GHz 501 pts Span 10.0 MHz          Date: 18_DEC_2023 14:15:06</p>	/
<p style="text-align: center;">High channel</p>	/
<p>Spectrum          Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz          Att 30 dB SWT 1.3 μs VBW 10 MHz Mode Auto FFT          IPk Max M1[1] -0.34 dBm 2.4802590 GHz          CF 2.48 GHz 501 pts Span 10.0 MHz          Date: 18_DEC_2023 14:16:15</p>	/


**Power Spectral Density:**

BLE 1M	/
<p style="text-align: center;">Lowest channel</p>	/
	/
<p style="text-align: center;">Middle channel</p>	/
	/
<p style="text-align: center;">High channel</p>	/
	/

**100kHz Bandwidth of Frequency Band Edge:**



**Duty cycle:**





## 4 Test Setup Photo

Please refer to the attachment RWAZ202300068 Test Setup photo.

## 5 E.U.T Photo

Please refer to the attachment RWAZ202300068 External photo and RWAZ202300068 Internal photo.

**---End of Report---**