



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.

Address: No.666 Hu'an Rd. Huli District Xiamen City, Fujian, P.R. China

FCC ID: T2C-BHD762

IC: 10741A-BHD762

HVIN: BHD762

Product Name: Bluetooth Headset

**Standard(s): 47 CFR Part 15, Subpart C(15.247)
RSS-247 Issue 2, February 2017
RSS-Gen, Issue 5, February 2021 Amendment 2
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02**

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230844524-00B

Date Of Issue: 2023/8/15

Reviewed By: Julie Tan

Title: RF Engineer

Julie Tan

Approved By: Sun Zhong

Title: Manager

Sun Zhong

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

| | |
|---|-----------|
| TEST FACILITY | 2 |
| DECLARATIONS..... | 2 |
| DOCUMENT REVISION HISTORY | 5 |
| 1. GENERAL INFORMATION..... | 6 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 6 |
| 1.2 DESCRIPTION OF TEST CONFIGURATION..... | 7 |
| 1.2.2 Support Equipment List and Details | 7 |
| 1.2.3 Support Cable List and Details | 7 |
| 1.2.4 Block Diagram of Test Setup..... | 8 |
| 1.3 MEASUREMENT UNCERTAINTY | 9 |
| 2. SUMMARY OF TEST RESULTS | 10 |
| 3. REQUIREMENTS AND TEST PROCEDURES | 11 |
| 3.1 AC LINE CONDUCTED EMISSIONS..... | 11 |
| 3.1.1 Applicable Standard..... | 11 |
| 3.1.2 EUT Setup..... | 13 |
| 3.1.3 EMI Test Receiver Setup | 13 |
| 3.1.4 Test Procedure | 14 |
| 3.1.5 Corrected Amplitude & Margin Calculation..... | 14 |
| 3.2 RADIATION SPURIOUS EMISSIONS..... | 15 |
| 3.2.1 Applicable Standard..... | 15 |
| 3.2.2 EUT Setup..... | 15 |
| 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup | 16 |
| 3.2.4 Test Procedure | 16 |
| 3.2.5 Corrected Amplitude & Margin Calculation..... | 17 |
| 3.3 6 DB EMISSION BANDWIDTH:..... | 18 |
| 3.3.1 Applicable Standard..... | 18 |
| 3.3.2 EUT Setup..... | 18 |
| 3.3.3 Test Procedure | 18 |
| 3.4 99% OCCUPIED BANDWIDTH: | 19 |
| 3.4.1 Applicable Standard..... | 19 |
| 3.4.2 EUT Setup..... | 20 |
| 3.4.3 Test Procedure | 20 |
| 3.5 MAXIMUM CONDUCTED OUTPUT POWER: | 21 |
| 3.5.1 Applicable Standard..... | 21 |
| 3.5.2 EUT Setup..... | 21 |
| 3.5.3 Test Procedure | 21 |
| 3.6 MAXIMUM POWER SPECTRAL DENSITY: | 22 |
| 3.6.1 Applicable Standard..... | 22 |
| 3.6.2 EUT Setup..... | 22 |
| 3.6.3 Test Procedure | 22 |
| 3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE: | 23 |

| | |
|--|-----------|
| 3.7.1 Applicable Standard..... | 23 |
| 3.7.2 EUT Setup..... | 23 |
| 3.7.3 Test Procedure | 23 |
| 3.8 DUTY CYCLE:..... | 24 |
| 3.8.1 EUT Setup..... | 24 |
| 3.8.2 Test Procedure | 24 |
| 3.9 ANTENNA REQUIREMENT..... | 25 |
| 3.9.1 Applicable Standard..... | 25 |
| 3.9.2 Judgment..... | 25 |
| 4. Test DATA AND RESULTS..... | 26 |
| 4.1 AC LINE CONDUCTED EMISSIONS..... | 26 |
| 4.2 RADIATION SPURIOUS EMISSIONS..... | 29 |
| 4.3 MINIMUM 6 DB BANDWIDTH: | 36 |
| 4.4 99% OCCUPIED BANDWIDTH: | 39 |
| 4.5 MAXIMUM CONDUCTED OUTPUT POWER: | 42 |
| 4.6 MAXIMUM POWER SPECTRAL DENSITY: | 45 |
| 4.7 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE: | 48 |
| 4.8 DUTY CYCLE:..... | 51 |
| 5. RF EXPOSURE EVALUATION | 53 |
| 5.1 FCC SAR TEST EXCLUSION | 53 |
| 5.1.1 Applicable Standard..... | 53 |
| 5.1.2 Measurement Result..... | 53 |
| 5.2 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION..... | 54 |
| 5.2.1 Applicable Standard..... | 54 |
| 5.2.2 Measurement Result: | 54 |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number | Description of Revision | Date of Revision |
|-----------------|-----------------|-------------------------|------------------|
| 1.0 | CR230844524-00B | Original Report | 2023/8/15 |

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

| | |
|---|--|
| EUT Name: | Bluetooth Headset |
| Trade Name: | Yealink |
| EUT Model: | BHD762 |
| Multiple Models: | BH76 Plus |
| Operation Frequency: | 2402-2480MHz |
| Maximum Peak Output Power (Conducted): | 0.62 dBm |
| Modulation Type: | GFSK |
| Rated Input Voltage: | DC 3.8V from battery or DC 5V from adapter |
| Serial Number: | 2982-4 |
| EUT Received Date: | 2023/8/3 |
| EUT Received Status: | Good |
| Note: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer. | |

Operation Frequency Detail: For BLE:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0 | 2402 | 20 | 2442 |
| 1 | 2404 | 21 | 2444 |
| ... | ... | ... | ... |
| ... | ... | ... | ... |
| 18 | 2438 | 38 | 2478 |
| 19 | 2440 | 39 | 2480 |

Per section 15.31(m) /RSS-Gen, the below frequencies were performed the test as below:

| Test Channel | Frequency (MHz) |
|--------------|-----------------|
| Lowest | 2402 |
| Middle | 2440 |
| Highest | 2480 |

Antenna Information Detail▲:

| Antenna Type | input impedance (Ohm) | Frequency Range | Antenna Gain |
|--------------|-----------------------|-----------------|--------------|
| FPC | 50 | 2.4~2.5GHz | 0.82 dBi |

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
 Antenna must use a unique type of connector to attach to the EUT.
 Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

| Accessory Description | Manufacturer | Model | Parameters |
|-----------------------|--------------|-------|------------|
| / | / | / | / |

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For BLE:

| | | | |
|--|--|----------------|-----------------|
| EUT Operation Mode: | The system was configured for testing in Engineering Mode, which was provided by the manufacturer. | | |
| Equipment Modifications: | No | | |
| EUT Exercise Software: | Lab Test Tool | | |
| The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲: | | | |
| Test Modes | Power Level Setting | | |
| | Lowest Channel | Middle Channel | Highest Channel |
| 1Mbps | 38 | 38 | 38 |
| 2Mbps | 38 | 38 | 38 |

1.2.2 Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|---------|---------------|
| infinix | Adapter | U680XSA | KX0716722C27 |

1.2.3 Support Cable List and Details


| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To |
|-------------------|----------------|--------------|------------|-----------|-----|
| USB Cable | No | No | 1.5 | Adapter | EUT |

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

| Parameter | Measurement Uncertainty |
|-----------------------------------|---|
| Occupied Channel Bandwidth | ±5 % |
| RF output power, conducted | ±0.61dB |
| Power Spectral Density, conducted | ±0.61 dB |
| Unwanted Emissions, radiated | 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB |
| Unwanted Emissions, conducted | ±1.26 dB |
| Temperature | ±1 °C |
| Humidity | ±5% |
| DC and low frequency voltages | ±0.4% |
| Duty Cycle | 1% |
| AC Power Lines Conducted Emission | 2.8 dB (150 kHz to 30 MHz) |

2. SUMMARY OF TEST RESULTS

| Standard(s) Section | Test Items | Result |
|--|---|-----------|
| §15.207(a) RSS-Gen Clause 8.8 | AC line conducted emissions | Compliant |
| §15.205, §15.209, §15.247(d) RSS-Gen Clause 8.10 | Radiated Spurious Emissions | Compliant |
| §15.247 (a)(2) RSS-247 Clause 5.2 a) | Minimum 6 dB Bandwidth | Compliant |
| RSS-Gen Clause 6.7 | 99% Occupied Bandwidth | Compliant |
| §15.247(b)(3) RSS-247 Clause 5.4 d) | Maximum Conducted Output Power | Compliant |
| §15.247(d) RSS-247 Clause5.5 | 100 kHz Bandwidth Of Frequency Band Edge | Compliant |
| §15.247(e) RSS-247 Clause5.2 b) | Power Spectral Density | Compliant |
| §15.203 RSS-GEN Clause 6.8 | Antenna Requirement | Compliant |
| FCC§15.247 (i) & §1.1307 & §2.1093 | RF Exposure Evaluation | Compliant |
| RSS-102 Clause 2.5.1 | Exemption Limits For Routine Evaluation-SAR Evaluation | Compliant |

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (MHz) | Conducted limit (dB μ V) | |
|-----------------------------|------------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits

| Frequency (MHz) | Conducted limit (dB μ V) | |
|--------------------|------------------------------|-----------------------|
| | Quasi-peak | Average |
| 0.15 - 0.5 | 66 to 56 ¹ | 56 to 46 ¹ |
| 0.5 – 5 | 56 | 46 |
| 5 – 30 | 60 | 50 |

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207,RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions

3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247, RSS-247, RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

| Detector | RBW | Video B/W | IF B/W |
|----------|---------|-----------|--------|
| QP | 120 kHz | 300 kHz | 120kHz |

1GHz- 25GHz:

| Measurement | Duty cycle | RBW | Video B/W |
|-------------|------------|------|------------|
| PK | Any | 1MHz | 3 MHz |
| AV | >98% | 1MHz | 10 Hz |
| | <98% | 1MHz | $\geq 1/T$ |

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$\text{Result} = \text{Reading} + \text{Factor}$$

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Result}$$

3.3 6 dB Emission Bandwidth:

3.3.1 Applicable Standard


FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

RSS-247 Clause 5.2 a

The minimum 6 dB bandwidth shall be 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4 99% Occupied Bandwidth:

3.4.1 Applicable Standard

RSS-Gen Clause 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.


The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.5 Maximum Conducted Output Power:

3.5.1 Applicable Standard


FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

RSS-247 Clause 5.4 d

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW \geq $[3 \times \text{RBW}]$.
- c) Set span \geq $[3 \times \text{RBW}]$.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

3.6 Maximum power spectral density:

3.6.1 Applicable Standard


FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

RSS-247 Clause 5.2 b

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

3.6.2 EUT Setup



3.6.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

3.7 100 kHz Bandwidth of Frequency Band Edge:

3.7.1 Applicable Standard


FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle:

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-GEN Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

| | | | |
|----------------|-------------|--------------|---|
| Serial Number: | 2982-4 | Test Date: | 2023/8/4 |
| Test Site: | CE | Test Mode: | Transmitting (BLE 2Mbps Middle channel) |
| Tester: | David Huang | Test Result: | Pass |

Environmental Conditions:

| | | | | | |
|----------------------|----|------------------------------|----|------------------------|-------|
| Temperature: (°C) | 26 | Relative Humidity: (%) | 57 | ATM Pressure: (kPa) | 100.5 |
|----------------------|----|------------------------------|----|------------------------|-------|

Test Equipment List and Details:


| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | LISN | ENV216 | 101134 | 2023/03/31 | 2024/03/30 |
| R&S | EMI Test Receiver | ESR3 | 102726 | 2023/03/31 | 2024/03/30 |
| MICRO-COAX | Coaxial Cable | UTIFLEX | C-0200-01 | 2023/08/06 | 2024/08/05 |
| Audix | Test Software | E3 | 190306 (V9) | N/A | N/A |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Mode: Transmitting
 Port: Line
 Note:


Date: 2023-08-04



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|----------|
| 1 | 0.152 | 9.84 | 9.61 | 19.45 | 55.91 | 36.46 | Average |
| 2 | 0.152 | 21.44 | 9.61 | 31.05 | 65.91 | 34.86 | QP |
| 3 | 0.473 | 27.43 | 9.61 | 37.04 | 46.47 | 9.43 | Average |
| 4 | 0.473 | 28.95 | 9.61 | 38.56 | 56.47 | 17.91 | QP |
| 5 | 1.170 | 18.60 | 9.62 | 28.22 | 46.00 | 17.78 | Average |
| 6 | 1.170 | 26.15 | 9.62 | 35.77 | 56.00 | 20.23 | QP |
| 7 | 1.541 | 14.20 | 9.63 | 23.83 | 46.00 | 22.17 | Average |
| 8 | 1.541 | 26.23 | 9.63 | 35.86 | 56.00 | 20.14 | QP |
| 9 | 1.746 | 14.15 | 9.63 | 23.78 | 46.00 | 22.22 | Average |
| 10 | 1.746 | 24.29 | 9.63 | 33.92 | 56.00 | 22.08 | QP |
| 11 | 16.352 | 15.09 | 9.72 | 24.81 | 50.00 | 25.19 | Average |
| 12 | 16.352 | 24.68 | 9.72 | 34.40 | 60.00 | 25.60 | QP |

Test Mode: Transmitting
 Port: neutral
 Note:

Date: 2023-08-04



| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB) | Result (dBμV) | Limit (dBμV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|----------|
| 1 | 0.157 | 11.48 | 9.61 | 21.09 | 55.63 | 34.54 | Average |
| 2 | 0.157 | 22.52 | 9.61 | 32.13 | 65.63 | 33.50 | QP |
| 3 | 0.472 | 28.18 | 9.61 | 37.79 | 46.48 | 8.69 | Average |
| 4 | 0.472 | 29.68 | 9.61 | 39.29 | 56.48 | 17.19 | QP |
| 5 | 1.133 | 20.14 | 9.62 | 29.76 | 46.00 | 16.24 | Average |
| 6 | 1.133 | 27.74 | 9.62 | 37.36 | 56.00 | 18.64 | QP |
| 7 | 1.566 | 15.67 | 9.63 | 25.30 | 46.00 | 20.70 | Average |
| 8 | 1.566 | 28.36 | 9.63 | 37.99 | 56.00 | 18.01 | QP |
| 9 | 1.747 | 13.63 | 9.63 | 23.26 | 46.00 | 22.74 | Average |
| 10 | 1.747 | 24.09 | 9.63 | 33.72 | 56.00 | 22.28 | QP |
| 11 | 16.664 | 15.27 | 9.69 | 24.96 | 50.00 | 25.04 | Average |
| 12 | 16.664 | 25.01 | 9.69 | 34.70 | 60.00 | 25.30 | QP |

4.2 Radiation Spurious Emissions

| | | | |
|----------------|-------------------|--------------|--------------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/9~2023/8/11 |
| Test Site: | 966-2,966-1 | Test Mode: | Transmitting |
| Tester: | Carl Xue, Tao Zhu | Test Result: | Pass |

Environmental Conditions:

| | | | | | |
|----------------------|-----------|---------------------------|-------|------------------------|-----------|
| Temperature: (°C) | 26.8~27.9 | Relative Humidity: (%) | 49~64 | ATM Pressure: (kPa) | 99.7~99.9 |
|----------------------|-----------|---------------------------|-------|------------------------|-----------|

Test Equipment List and Details:

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------------|-----------------------|---------------|------------------|----------------------|
| Sunol Sciences | Antenna | JB6 | A082520-5 | 2020/10/19 | 2023/10/18 |
| R&S | EMI Test Receiver | ESR3 | 102724 | 2023/03/31 | 2024/03/30 |
| TIMES MICROWAVE | Coaxial Cable | LMR-600-UltraFlex | C-0470-02 | 2023/07/16 | 2024/07/15 |
| TIMES MICROWAVE | Coaxial Cable | LMR-600-UltraFlex | C-0780-01 | 2023/07/16 | 2024/07/15 |
| Sonoma | Amplifier | 310N | 186165 | 2023/07/16 | 2024/07/15 |
| Audix | Test Software | E3 | 201021 (V9) | N/A | N/A |
| ETS-Lindgren | Horn Antenna | 3115 | 9912-5985 | 2020/10/13 | 2023/10/12 |
| R&S | Spectrum Analyzer | FSV40 | 101591 | 2023/03/31 | 2024/03/30 |
| MICRO-COAX | Coaxial Cable | UFA210A-1-1200-70U300 | 217423-008 | 2023/08/06 | 2024/08/05 |
| MICRO-COAX | Coaxial Cable | UFA210A-1-2362-300300 | 235780-001 | 2023/08/06 | 2024/08/05 |
| Mini | Pre-amplifier | ZVA-183-S+ | 5969001149 | 2022/11/09 | 2023/11/08 |
| PASTERNAK | Horn Antenna | PE9852/2F-20 | 112002 | 2021/02/05 | 2024/02/04 |
| Quinstar | Preamplifier | QLW-18405536-JO | 15964001005 | 2022/09/16 | 2023/09/15 |
| MICRO-COAX | Coaxial Cable | UFB142A-1-2362-200200 | 235772-001 | 2023/08/06 | 2024/08/05 |
| E-Microwave | Band Rejection Filter | 2400-2483.5MHz | OE01902424 | 2023/08/06 | 2024/08/05 |
| Mini Circuits | High Pass Filter | VHF-6010+ | 31119 | 2023/08/06 | 2024/08/05 |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

1) 30MHz-1GHz(Transmitting with BLE 2Mbps Middle channel)


Test Mode: Transmitting
 Polarization: horizontal
 Note:



| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|----------|
| 1 | 31.731 | 28.64 | -4.92 | 23.72 | 40.00 | 16.28 | Peak |
| 2 | 131.297 | 39.97 | -11.36 | 28.61 | 43.50 | 14.89 | Peak |
| 3 | 146.374 | 35.96 | -11.98 | 23.98 | 43.50 | 19.52 | Peak |
| 4 | 218.309 | 37.06 | -12.75 | 24.31 | 46.00 | 21.69 | Peak |
| 5 | 275.157 | 34.67 | -11.89 | 22.78 | 46.00 | 23.22 | Peak |
| 6 | 317.701 | 36.93 | -10.58 | 26.35 | 46.00 | 19.65 | Peak |

Test Mode: Transmitting
 Polarization: vertical
 Note:

Date: 2023-08-09



| No. | Frequency (MHz) | Reading (dB μ V) | Factor (dB/m) | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Detector |
|-----|-----------------|----------------------|---------------|-----------------------|----------------------|-------------|----------|
| 1 | 30.211 | 29.25 | -3.76 | 25.49 | 40.00 | 14.51 | Peak |
| 2 | 37.416 | 33.03 | -9.31 | 23.72 | 40.00 | 16.28 | Peak |
| 3 | 43.659 | 40.97 | -13.46 | 27.51 | 40.00 | 12.49 | Peak |
| 4 | 60.069 | 43.92 | -17.40 | 26.52 | 40.00 | 13.48 | Peak |
| 5 | 131.297 | 37.71 | -11.36 | 26.35 | 43.50 | 17.15 | Peak |
| 6 | 299.316 | 34.23 | -10.65 | 23.58 | 46.00 | 22.42 | Peak |


**1) 1-25GHz:
BLE 1Mbps:**

| Frequency (MHz) | Receiver | | Polar (H/V) | Factor (dB/m) | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|--------------------------|----------------------|----------|-------------|---------------|-----------------------|----------------------|-------------|
| | Reading (dB μ V) | Detector | | | | | |
| Low Channel: 2402 MHz | | | | | | | |
| 2402.000 | 62.83 | PK | H | 31.51 | 94.34 | N/A | N/A |
| 2402.000 | 55.93 | AV | H | 31.51 | 87.44 | N/A | N/A |
| 2402.000 | 56.54 | PK | V | 31.51 | 88.05 | N/A | N/A |
| 2402.000 | 49.94 | AV | V | 31.51 | 81.45 | N/A | N/A |
| 2390.000 | 26.24 | PK | H | 31.46 | 57.70 | 74.00 | 16.30 |
| 2390.000 | 13.66 | AV | H | 31.46 | 45.12 | 54.00 | 8.88 |
| 4804.000 | 35.25 | PK | H | 10.91 | 46.16 | 74.00 | 27.84 |
| 4804.000 | 22.69 | AV | H | 10.91 | 33.60 | 54.00 | 20.40 |
| 7206.000 | 33.38 | PK | H | 14.22 | 47.60 | 74.00 | 26.40 |
| 7206.000 | 20.47 | AV | H | 14.22 | 34.69 | 54.00 | 19.31 |
| Middle Channel: 2440 MHz | | | | | | | |
| 2440.000 | 62.55 | PK | H | 31.60 | 94.15 | N/A | N/A |
| 2440.000 | 56.18 | AV | H | 31.60 | 87.78 | N/A | N/A |
| 2440.000 | 56.33 | PK | V | 31.60 | 87.93 | N/A | N/A |
| 2440.000 | 50.34 | AV | V | 31.60 | 81.94 | N/A | N/A |
| 4880.000 | 33.93 | PK | H | 11.07 | 45.00 | 74.00 | 29.00 |
| 4880.000 | 20.38 | AV | H | 11.07 | 31.45 | 54.00 | 22.55 |
| 7320.000 | 33.47 | PK | H | 14.80 | 48.27 | 74.00 | 25.73 |
| 7320.000 | 20.56 | AV | H | 14.80 | 35.36 | 54.00 | 18.64 |
| High Channel: 2480 MHz | | | | | | | |
| 2480.000 | 63.74 | PK | H | 31.64 | 95.38 | N/A | N/A |
| 2480.000 | 57.28 | AV | H | 31.64 | 88.92 | N/A | N/A |
| 2480.000 | 57.66 | PK | V | 31.64 | 89.30 | N/A | N/A |
| 2480.000 | 51.49 | AV | V | 31.64 | 83.13 | N/A | N/A |
| 2483.500 | 26.48 | PK | H | 31.64 | 58.12 | 74.00 | 15.88 |
| 2483.500 | 13.73 | AV | H | 31.64 | 45.37 | 54.00 | 8.63 |
| 4960.000 | 33.96 | PK | H | 11.23 | 45.19 | 74.00 | 28.81 |
| 4960.000 | 20.55 | AV | H | 11.23 | 31.78 | 54.00 | 22.22 |
| 7440.000 | 33.27 | PK | H | 15.26 | 48.53 | 74.00 | 25.47 |
| 7440.000 | 20.43 | AV | H | 15.26 | 35.69 | 54.00 | 18.31 |


BLE 2Mbps:

| Frequency (MHz) | Receiver | | Polar (H/V) | Factor (dB/m) | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|--------------------------|----------------------|----------|-------------|---------------|-----------------------|----------------------|--------------|
| | Reading (dB μ V) | Detector | | | | | |
| Low Channel: 2402 MHz | | | | | | | |
| 2402.000 | 63.68 | PK | H | 31.51 | 95.19 | N/A | N/A |
| 2402.000 | 51.20 | AV | H | 31.51 | 82.71 | N/A | N/A |
| 2402.000 | 58.66 | PK | V | 31.51 | 90.17 | N/A | N/A |
| 2402.000 | 46.57 | AV | V | 31.51 | 78.08 | N/A | N/A |
| 2390.000 | 26.78 | PK | H | 31.46 | 58.24 | 74.00 | 15.76 |
| 2390.000 | 13.79 | AV | H | 31.46 | 45.25 | 54.00 | 8.75 |
| 4804.000 | 34.25 | PK | H | 10.91 | 45.16 | 74.00 | 28.84 |
| 4804.000 | 21.64 | AV | H | 10.91 | 32.55 | 54.00 | 21.45 |
| 7206.000 | 33.70 | PK | H | 14.22 | 47.92 | 74.00 | 26.08 |
| 7206.000 | 20.58 | AV | H | 14.22 | 34.80 | 54.00 | 19.20 |
| Middle Channel: 2440 MHz | | | | | | | |
| 2440.000 | 62.38 | PK | H | 31.60 | 93.98 | N/A | N/A |
| 2440.000 | 50.37 | AV | H | 31.60 | 81.97 | N/A | N/A |
| 2440.000 | 57.68 | PK | V | 31.60 | 89.28 | N/A | N/A |
| 2440.000 | 45.38 | AV | V | 31.60 | 76.98 | N/A | N/A |
| 4880.000 | 35.47 | PK | H | 11.07 | 46.54 | 74.00 | 27.46 |
| 4880.000 | 22.51 | AV | H | 11.07 | 33.58 | 54.00 | 20.42 |
| 7320.000 | 33.81 | PK | H | 14.80 | 48.61 | 74.00 | 25.39 |
| 7320.000 | 20.68 | AV | H | 14.80 | 35.48 | 54.00 | 18.52 |
| High Channel: 2480 MHz | | | | | | | |
| 2480.000 | 62.75 | PK | H | 31.64 | 94.39 | N/A | N/A |
| 2480.000 | 49.69 | AV | H | 31.64 | 81.33 | N/A | N/A |
| 2480.000 | 57.25 | PK | V | 31.64 | 88.89 | N/A | N/A |
| 2480.000 | 44.02 | AV | V | 31.64 | 75.66 | N/A | N/A |
| 2483.500 | 26.76 | PK | H | 31.64 | 58.40 | 74.00 | 15.60 |
| 2483.500 | 13.66 | AV | H | 31.64 | 45.30 | 54.00 | 8.70 |
| 4960.000 | 34.23 | PK | H | 11.23 | 45.46 | 74.00 | 28.54 |
| 4960.000 | 21.47 | AV | H | 11.23 | 32.70 | 54.00 | 21.30 |
| 7440.000 | 33.86 | PK | H | 15.26 | 49.12 | 74.00 | 24.88 |
| 7440.000 | 20.55 | AV | H | 15.26 | 35.81 | 54.00 | 18.19 |

Test plots(BLE 2Mbps High channel)



Vertical



4.3 Minimum 6 dB Bandwidth:

| | | | |
|----------------|-------------|--------------|--------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/8 |
| Test Site: | RF | Test Mode: | Transmitting |
| Tester: | LingLing Li | Test Result: | Pass |

Environmental Conditions:

| | | | | | |
|----------------------|------|---------------------------|----|------------------------|-------|
| Temperature: (°C) | 27.4 | Relative Humidity: (%) | 64 | ATM Pressure: (kPa) | 100.4 |
|----------------------|------|---------------------------|----|------------------------|-------|


Test Equipment List and Details:

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSU26 | 100147 | 2023/03/31 | 2024/03/30 |
| zhuoxiang | Coaxial Cable | SMA-178 | 211001 | Each time | N/A |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

| Test Modes | Test Frequency (MHz) | 6 dB Bandwidth (MHz) | Limit (MHz) |
|------------|----------------------|----------------------|-------------|
| BLE 1Mbps | 2402 | 0.712 | ≥ 0.5 |
| | 2440 | 0.716 | ≥ 0.5 |
| | 2480 | 0.726 | ≥ 0.5 |
| BLE 2Mbps | 2402 | 1.269 | ≥ 0.5 |
| | 2440 | 1.269 | ≥ 0.5 |
| | 2480 | 1.269 | ≥ 0.5 |



6dB Emission Bandwidth

| | |
|--------------------------------------|--|
| <p>BLE 2Mbps Lowest Channel</p> | <p>Ref 30 dBm *Att 35 dB</p> <p>RBW 100 kHz Delta 1 [T1] -0.37 dB VBW 300 kHz SWT 2.5 ms 1.269230769 MHz</p> <p>Offset 0.4 dB</p> <p>Marker 1 [T1] -1.21 dBm 2.401338538 GHz</p> <p>D1 -0.37 dBm D2 -5.76 dBm</p> <p>Center 2.402 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 8 AUG 2023 18:13:48</p> |
| <p>BLE 2Mbps Middle Channel</p> | <p>Ref 30 dBm *Att 35 dB</p> <p>RBW 100 kHz Delta 1 [T1] -0.54 dB VBW 300 kHz SWT 2.5 ms 1.269230769 MHz</p> <p>Offset 0.4 dB</p> <p>Marker 1 [T1] -1.06 dBm 2.439341346 GHz</p> <p>D1 -0.54 dBm D2 -5.76 dBm</p> <p>Center 2.44 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 8 AUG 2023 18:12:06</p> |
| <p>BLE 2Mbps Highest Channel</p> | <p>Ref 30 dBm *Att 35 dB</p> <p>RBW 100 kHz Delta 1 [T1] -0.49 dB VBW 300 kHz SWT 2.5 ms 1.269230769 MHz</p> <p>Offset 0.4 dB</p> <p>Marker 1 [T1] -1.21 dBm 2.479341346 GHz</p> <p>D1 -0.49 dBm D2 -5.77 dBm</p> <p>Center 2.48 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 8 AUG 2023 18:10:08</p> |

4.4 99% Occupied Bandwidth:

| | | | |
|----------------|-------------|--------------|--------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/8 |
| Test Site: | RF | Test Mode: | Transmitting |
| Tester: | LingLing Li | Test Result: | N/A |

Environmental Conditions:

| | | | | | |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature: (°C) | 27.4 | Relative Humidity: (%) | 64 | ATM Pressure: (kPa) | 100.4 |
|----------------------|------|------------------------------|----|------------------------|-------|


Test Equipment List and Details:


| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSU26 | 100147 | 2023/03/31 | 2024/03/30 |
| zhuoxiang | Coaxial Cable | SMA-178 | 211001 | Each time | N/A |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

| Test Mode | Test Channel | Test Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|-----------|--------------|----------------------|------------------------------|
| BLE 1Mbps | Lowest | 2402 | 1.035 |
| | Middle | 2440 | 1.032 |
| | Highest | 2480 | 1.035 |
| BLE 2Mbps | Lowest | 2402 | 2.064 |
| | Middle | 2440 | 2.064 |
| | Highest | 2480 | 2.064 |





4.5 Maximum Conducted Output Power:

| | | | |
|----------------|-------------|--------------|--------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/8 |
| Test Site: | RF | Test Mode: | Transmitting |
| Tester: | LingLing Li | Test Result: | Pass |

Environmental Conditions:

| | | | | | |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature: (°C) | 27.4 | Relative Humidity: (%) | 64 | ATM Pressure: (kPa) | 100.4 |
|----------------------|------|------------------------------|----|------------------------|-------|

Test Equipment List and Details:




| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSU26 | 100147 | 2023/03/31 | 2024/03/30 |
| zhuoxiang | Coaxial Cable | SMA-178 | 211001 | Each time | N/A |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




Test Data:

| Test Modes | Test Frequency (MHz) | Maximum Conducted Peak Output Power (dBm) | Limit (dBm) |
|-------------------------------|----------------------|---|-------------|
| BLE 1Mbps | 2402 | 0.5 | ≤30 |
| | 2440 | 0.59 | ≤30 |
| | 2480 | 0.56 | ≤30 |
| BLE 2Mbps | 2402 | 0.56 | ≤30 |
| | 2440 | 0.62 | ≤30 |
| | 2480 | 0.6 | ≤30 |
| Max.EIRP: | 1.44 | dBm | |
| EIRP Limit for RSS-247:36 dBm | | | |

Maximum Conducted Peak Output Power

| | |
|--------------------------------------|--|
| <p>BLE 1Mbps Lowest Channel</p> |  <p>Ref 30 dBm *Att 35 dB RBW 3 MHz Marker 1 [T1] 0.50 dBm VBW 10 MHz SWT 2.5 ms 2.401759615 GHz</p> <p>30 Offset 0.4 dB</p> <p>1 PK MAXH</p> <p>1</p> <p>EVL</p> <p>Center 2.402 GHz 1 MHz/ Span 10 MHz</p> <p>Date: 8 AUG 2023 18:22:30</p> |
| <p>BLE 1Mbps Middle Channel</p> |  <p>Ref 30 dBm *Att 35 dB RBW 3 MHz Marker 1 [T1] 0.59 dBm VBW 10 MHz SWT 2.5 ms 2.439919872 GHz</p> <p>30 Offset 0.4 dB</p> <p>1 PK MAXH</p> <p>1</p> <p>EVL</p> <p>Center 2.44 GHz 1 MHz/ Span 10 MHz</p> <p>Date: 8 AUG 2023 18:23:40</p> |
| <p>BLE 1Mbps Highest Channel</p> |  <p>Ref 30 dBm *Att 35 dB RBW 3 MHz Marker 1 [T1] 0.56 dBm VBW 10 MHz SWT 2.5 ms 2.479935897 GHz</p> <p>30 Offset 0.4 dB</p> <p>1 PK MAXH</p> <p>1</p> <p>EVL</p> <p>Center 2.48 GHz 1 MHz/ Span 10 MHz</p> <p>Date: 8 AUG 2023 18:24:25</p> |

Maximum Conducted Peak Output Power

| | |
|--------------------------------------|---|
| <p>BLE 2Mbps Lowest Channel</p> |  <p>Date: 8 AUG 2023 18:27:27</p> |
| <p>BLE 2Mbps Middle Channel</p> |  <p>Date: 8 AUG 2023 18:26:34</p> |
| <p>BLE 2Mbps Highest Channel</p> |  <p>Date: 8 AUG 2023 18:25:32</p> |

4.6 Maximum power spectral density:

| | | | |
|----------------|-------------|--------------|--------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/8 |
| Test Site: | RF | Test Mode: | Transmitting |
| Tester: | LingLing Li | Test Result: | Pass |

Environmental Conditions:

| | | | | | |
|----------------------|------|---------------------------|----|------------------------|-------|
| Temperature: (°C) | 27.4 | Relative Humidity: (%) | 64 | ATM Pressure: (kPa) | 100.4 |
|----------------------|------|---------------------------|----|------------------------|-------|

Test Equipment List and Details:

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSU26 | 100147 | 2023/03/31 | 2024/03/30 |
| zhuoxiang | Coaxial Cable | SMA-178 | 211001 | Each time | N/A |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

| Test Channel | Test Frequency (MHz) | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) |
|--------------|----------------------|-----------------------------------|------------------|
| BLE 1Mbps | 2402 | -15.32 | ≤8.00 |
| | 2440 | -15.23 | ≤8.00 |
| | 2480 | -15.29 | ≤8.00 |
| BLE 2Mbps | 2402 | -17.59 | ≤8.00 |
| | 2440 | -17.46 | ≤8.00 |
| | 2480 | -17.5 | ≤8.00 |

Maximum power spectral density

| | |
|--------------------------------------|--|
| <p>BLE 1Mbps Lowest Channel</p> | <p>Ref 30 dBm * Att 35 dB RBW 3 kHz VBW 10 kHz SWT 120 ms Marker 1 [T1] -15.32 dBm 2.401976038 GHz</p> <p>30 Offset 0.4 dB</p> <p>1 PK MAXH</p> <p>Center 2.402 GHz 106.8 kHz/ Span 1.068 MHz</p> <p>Date: 8 AUG 2023 18:22:41</p> |
| <p>BLE 1Mbps Middle Channel</p> | <p>Ref 30 dBm * Att 35 dB RBW 3 kHz VBW 10 kHz SWT 120 ms Marker 1 [T1] -15.23 dBm 2.439977625 GHz</p> <p>30 Offset 0.4 dB</p> <p>1 PK MAXH</p> <p>Center 2.44 GHz 107.4 kHz/ Span 1.074 MHz</p> <p>Date: 8 AUG 2023 18:23:48</p> |
| <p>BLE 1Mbps Highest Channel</p> | <p>Ref 30 dBm * Att 35 dB RBW 3 kHz VBW 10 kHz SWT 125 ms Marker 1 [T1] -15.29 dBm 2.479975567 GHz</p> <p>30 Offset 0.4 dB</p> <p>1 PK MAXH</p> <p>Center 2.48 GHz 108.9 kHz/ Span 1.089 MHz</p> <p>Date: 8 AUG 2023 18:24:34</p> |

Maximum power spectral density

| | |
|--------------------------------------|----------------------------------|
| <p>BLE 2Mbps Lowest Channel</p> | <p>Date: 8 AUG 2023 18:27:35</p> |
| <p>BLE 2Mbps Middle Channel</p> | <p>Date: 8 AUG 2023 18:26:45</p> |
| <p>BLE 2Mbps Highest Channel</p> | <p>Date: 8 AUG 2023 18:25:40</p> |

4.7 100 kHz Bandwidth of Frequency Band Edge:

| | | | |
|----------------|-------------|--------------|--------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/8 |
| Test Site: | RF | Test Mode: | Transmitting |
| Tester: | LingLing Li | Test Result: | Pass |

Environmental Conditions:

| | | | | | |
|----------------------|------|------------------------------|----|------------------------|-------|
| Temperature: (°C) | 27.4 | Relative Humidity: (%) | 64 | ATM Pressure: (kPa) | 100.4 |
|----------------------|------|------------------------------|----|------------------------|-------|

Test Equipment List and Details:


| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSU26 | 100147 | 2023/03/31 | 2024/03/30 |
| zhuoxiang | Coaxial Cable | SMA-178 | 211001 | Each time | N/A |

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


100 kHz Bandwidth of Frequency Band Edge

BLE 1Mbps
Lowest Band edge



Date: 8.AUG.2023 18:22:54


BLE 1Mbps
Highest Band edge



Date: 8.AUG.2023 18:24:46


100 kHz Bandwidth of Frequency Band Edge

BLE 2Mbps
Lowest Band edge



Date: 8.AUG.2023 18:27:48

BLE 2Mbps
Highest Band edge



Date: 8.AUG.2023 18:25:56

4.8 Duty Cycle:

| | | | |
|----------------|-------------|--------------|--------------|
| Serial Number: | 2982-4 | Test Date: | 2023/8/8 |
| Test Site: | RF | Test Mode: | Transmitting |
| Tester: | LingLing Li | Test Result: | N/A |

Environmental Conditions:

| | | | | | |
|----------------------|------|---------------------------|----|------------------------|-------|
| Temperature: (°C) | 27.4 | Relative Humidity: (%) | 64 | ATM Pressure: (kPa) | 100.4 |
|----------------------|------|---------------------------|----|------------------------|-------|

Test Equipment List and Details:

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSU26 | 100147 | 2023/03/31 | 2024/03/30 |
| zhuoxiang | Coaxial Cable | SMA-178 | 211001 | Each time | N/A |


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

| Test Modes | Ton (ms) | Ton+off (ms) | Duty cycle (%) | 1/T (Hz) | VBW Setting (kHz) |
|------------|-------------|-----------------|-------------------|-------------|----------------------|
| BLE 1Mbps | 0.405 | 0.633 | 63.98 | 2469 | 3 |
| BLE 2Mbps | 0.204 | 0.625 | 32.64 | 4902 | 10 |


Duty Cycle

BLE 1Mbps



Date: 8.AUG.2023 18:18:11

BLE 2Mbps



Date: 8.AUG.2023 18:17:25

5. RF EXPOSURE EVALUATION

5.1 FCC SAR test exclusion

5.1.1 Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

5.1.2 Measurement Result

For BLE:

The max conducted power including tune-up tolerance is 1.0 dBm (1.26mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 1.26/5 * (\sqrt{2.480}) = 0.4 < 3.0$

Result: Compliant. The stand-alone SAR evaluation is not necessary.

5.2 Exemption limits for Routine Evaluation – SAR Evaluation

5.2.1 Applicable Standard

According to RSS-102 § (2.5.1):

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance⁴⁵

| Frequency (MHz) | Exemption Limits (mW) | | | | |
|-----------------|---------------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| | At separation distance of ≤ 5 mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| ≤ 300 | 71 mW | 101 mW | 132 mW | 162 mW | 193 mW |
| 450 | 52 mW | 70 mW | 88 mW | 106 mW | 123 mW |
| 835 | 17 mW | 30 mW | 42 mW | 55 mW | 67 mW |
| 1900 | 7 mW | 10 mW | 18 mW | 34 mW | 60 mW |
| 2450 | 4 mW | 7 mW | 15 mW | 30 mW | 52 mW |
| 3500 | 2 mW | 6 mW | 16 mW | 32 mW | 55 mW |
| 5800 | 1 mW | 6 mW | 15 mW | 27 mW | 41 mW |

| Frequency (MHz) | Exemption Limits (mW) | | | | |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--|
| | At separation distance of 30 mm | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of ≥ 50 mm |
| ≤ 300 | 223 mW | 254 mW | 284 mW | 315 mW | 345 mW |
| 450 | 141 mW | 159 mW | 177 mW | 195 mW | 213 mW |
| 835 | 80 mW | 92 mW | 105 mW | 117 mW | 130 mW |
| 1900 | 99 mW | 153 mW | 225 mW | 316 mW | 431 mW |
| 2450 | 83 mW | 123 mW | 173 mW | 235 mW | 309 mW |
| 3500 | 86 mW | 124 mW | 170 mW | 225 mW | 290 mW |
| 5800 | 56 mW | 71 mW | 85 mW | 97 mW | 106 mW |

5.2.2 Measurement Result:

For BLE:

The max tune-up conducted power is 1.0 dBm, Antenna Gain: 0.82 dBi,

EIRP: 1.82 dBm(1.52 mW)

The exemption power(P) limits for routine evaluation in 2402-2480MHz is:

$$(2480-2450)/(3500-2450)=(P-4)/(2-4)$$

$$\Rightarrow P=3.94 \text{ mW}@2480 \text{ MHz}$$

$$> 1.52 \text{ mW}$$

So the stand-alone SAR evaluation can be exempted.

===== END OF REPORT =====