

## FCC §1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

### Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R <sup>2</sup> .
1.34-30	3,450 R <sup>2</sup> /f <sup>2</sup> .
30-300	3.83 R <sup>2</sup> .
300-1,500	0.0128 R <sup>2</sup> f.
1,500-100,000	19.2R <sup>2</sup> .

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

**Result**

Mode	Frequency (MHz)	Tune up conducted power <sup>#</sup>	Antenna Gain <sup>#</sup>		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	8.0	2.52	0.37	8.37	6.87	0.2	768
BLE	2402-2480	6.0	2.52	0.37	6.37	4.34	0.2	768
2.4G Wi-Fi	2412-2462	24.0	2.52	0.37	24.37	273.53	0.2	768
5.2G Wi-Fi	5180-5240	17.0	3.73	1.58	18.58	72.11	0.2	768
5.3G Wi-Fi	5260-5320	16.5	3.73	1.58	18.08	64.27	0.2	768
5.6G Wi-Fi	5500-5700	15.0	3.73	1.58	16.58	45.50	0.2	768
5.8G Wi-Fi	5745-5825	15.0	3.73	1.58	16.58	45.50	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.  
 2. The BT, 2.4G Wi-Fi and 5G Wi-Fi cannot transmit at same time.  
 3. 0dBd=2.15dBi

**NFC:**

Mode	Frequency (MHz)	Maximum E-Field (dBuV/m@3m)	Maximum EIRP (dBm)	ERP		Evaluation Distance (m)	ERP Limit (mW)
				(dBm)	(mW)		
NFC	13.56	67.73	-27.47	-29.62	0.0011	0.2	751

Note: EIRP = E-Field – 95.2 @3m, ERP = EIRP-2.15

Simultaneous transmitting consideration (worst case):

The ratio=  $ERP_{2.4G\ Wi-Fi}/limit + ERP_{NFC}/limit = 273.53/768 + 0.0011/751 = 0.356 < 1.0$

So simultaneous exposure is compliant.

To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant**