FCC ID : T2C-VC200

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency | Electric Field | Magnetic Field | Power | Average Time | | |
|---|---|----------------|------------------------------|--------------|--|--|
| Range(MHz) | Strength(V/m) | Strength(A/m) | Density(mW/cm ²) | • | | |
| | (A) Limits for Occupational/Control Exposures | | | | | |
| 300-1500 | | | F/300 | 6 | | |
| 1500-100000 | | | 5 | 6 | | |
| (B) Limits for General Population/Uncontrol Exposures | | | | | | |
| 300-1500 | | | F/1500 | 6 | | |
| 1500-100000 | | | 1 | 30 | | |

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in 20cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

BLE:

| Max. conducted power (dBm) | Max. Tune-up power (dBm) | antenna gain (dBi) | Evaluation result (mW/cm2) | Power density Limits (mW/cm2) |
|----------------------------|-----------------------------|-----------------------|----------------------------------|-------------------------------------|
| -1.66 dBm | -1 | 3.31 | 0.00034 | <1 |

WIFI 2.4G:

| Max. condu power (dBm) | Max. Tune-up power (dBm) | er Max. Tune-up antenna gair | Evaluation result (mW/cm2) | Power density Limits (mW/cm2) |
|------------------------------|--------------------------|------------------------------|----------------------------|-------------------------------------|
| 19.09 | 20 | 9 20 3.31 | 0.043 | <1 |

WIFI 5G:

| Band | Max. conducted power (dBm) | Max. Tune-up power (dBm) | antenna gain (dBi) | Evaluation result (mW/cm2) | Power density Limits (mW/cm2) |
|---------|----------------------------|-----------------------------|-----------------------|----------------------------------|-------------------------------------|
| U-NII-1 | 11.18 | 12 | 3.42 | 0.007 | <1 |
| U-NII-3 | 13.68 | 14 | 3.42 | 0.011 | <1 |