Shenzhen Accurate Technology Co., Ltd.

FCC §15.247 (i) &§1.1307 (b) (3) - RF EXPOSURE EVALUATION

Applicable Standard

According to subpart 15.247 (i) and \$1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

SAR-Based Exemption:

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum timeaveraged power or maximum time-averaged ERP, whichever is greater.

Per § 1.1307(b)(3)(i)(B), for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} (mW) = \begin{cases} ERP_{20 \ cm} (d/20 \ cm)^x & d \le 20 \ cm \\ ERP_{20 \ cm} & 20 \ cm < d \le 40 \ cm \end{cases}$$

Where

 $x = -\log_{10}\left(\frac{60}{ERP_{20\ cm}\sqrt{f}}\right)$ and f is in GHz;

and

$$ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$$

d = the separation distance (cm);

Result

Mode	Frequency (MHz)	P _{th}		Maximum tune-up conducted power	Maximum ERP	Exemption
		(mW)	(dBm)	(dBm)	(dBm)	I
5.2G Wi-Fi	5180-5240	3060	34.86	13.0	13.85	Compliant
5.3G Wi-Fi	5260-5320	3060	34.86	13.0	13.85	Compliant
5.6G Wi-Fi	5500-5720	3060	34.86	15.0	15.85	Compliant
5.8G Wi-Fi	5745-5825	3060	34.86	15.5	16.35	Compliant

Note: 1. The tune up conducted power was declared by the applicant.

2. The antenna gain is 3dBi(0.85dBd), so the ERP was used for evaluation.

3. The Wi-Fi and Bluetooth can't transmit simultaneously.

4. To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.