FCC §1.1307 (b) (3) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: SZNS220511-19727E-RF-00

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

RF Source frequency (MHz)	Threshold ERP (watts)			
0.3-1.34	1,920 R ² .			
1.34-30	3,450 R ² /f ² .			
30-300	3.83 R ² .			
300-1,500	0.0128 R ² f.			
1,500-100,000	19.2R ² .			

Ris the minimum separation distance in meters f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

Version 10: 2021-11-09 Page 14 of 292 FCC-5G Wi-Fi

Result

For worst case:

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance	ERP Limit
	()	(dBm)	(dBi)	(dBd)	(dBm)	(W)	(m)	(W)
BT	2402-2480	8.5	3.32	1.17	9.67	0.009	0.2	0.768
BLE	2402-2480	8.0	3.32	1.17	9.17	0.008	0.2	0.768
2.4G Wi-Fi	2412-2462	18.5	3.32	1.17	19.67	0.093	0.2	0.768
	5180-5240	12.0	4.18	2.03	14.03	0.025	0.2	0.768
5G Wi-Fi	5260-5280	13.0	4.18	2.03	15.03	0.032	0.2	0.768
SG WI-FI	5500-5700	12.0	4.18	2.03	14.03	0.025	0.2	0.768
	5745-5825	14.5	4.18	2.03	16.53	0.045	0.2	0.768

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{BT}/limit+ERP_{Wi-Fi}/limit=0.009/0.768+0.093/0.768=0.133 \le 1.0$, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
2. The BT can transmit at the same time with the Wi-Fi, the 2.4G Wi-Fi and 5G Wi-Fi cannot Simultaneous transmitting